



Swing Barrier AV-SB-01 Metallic (L)

Key Specification :

- Sleek and magnificent design used to control the pedestrian flow smoothly.
- Housing and barrier arm is made up of splash proof SS 304.
- Recommended for heavy passage flow & gateway for outsider entry.
- With in – built sensors crawling can be avoided.
- Smooth finishing without exposure to screws.
- The barrier gate can be set to delay closing in 1 – 60 sec after a valid card closing.
- Double anti clipping function, photocell anti clipping and mechanical anti clipping.
- The metallic flaps are specially design to prevent the passengers getting harmed passing cross.
- Auto reset function: if no passage during identified card reading time, the system reset automatically the passenger are prohibited to pass until their second identified reading.
- Arrows for direction indication are provided at the top for easy access.

Technical Specification

- Power Supply : 100–240Vac
- Operating Voltage : 24 V
- Frequency : 50Hz
- Power Consumption : 30W
- Unlock Time : 0.2 sec
- Transaction Rate : 35 Person/min
- Passage Width : ≤1100mm
- Operating Temperature : -25 to 70°C
- Working Environment : Indoor/Outdoor (If Roofed)
- Protection Level : IP55
- Dimensions(L*W*H) : 1200*280*960mm
- Packaging Dimensions(L*W*H) : 1260*340*1070mm
- Net Weight : 50kg
- Gross Weight : 71Kg