FRONT

PICTURE 1

September 1990

This pamphlet contains procedures for isolating problems to a FRU, a Symptom-To-FRU Index, and a parts listing for the IBM Personal System/2 Model 30 286.

This pamphlet is intended to be used with the IBM Personal System/2 <code>Hardware Maintenance Reference</code> manual (part number 15F2190, form number S15F-2190) and the IBM Personal System/2 <code>Hardware Maintenance Service</code> manual (part number 15F2200, form number S15F-2200).

Part Number 91F9232

Form Number S15F-2192-01

IBM PS/2 Model 30 286 HMS Safety Information

FRONT_1 Safety Information

Refe	fer to the Hardware Maintenance Servi	ce General	Information	pamphlet	for
the	e following information:				
	General Safety				
	Electrical Safety				
	Safety Inspection Guide.				

Second Edition (September 1990)

The following paragraph does not apply to the United Kingdom or any country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This publication could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time.

It is possible that this publication may contain reference to, or information about, IBM products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that IBM intends to announce such IBM products, programming, or services in your country.

Requests for technical information about IBM products should be made to your IBM Authorized Dealer or your IBM Marketing Representative.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the IBM Director of Commercial Relations, IBM Corporation, Armonk NY 10504.

| Copyright International Business Machines Corporation 1990. All rights reserved.

Note to US Government users-Documentation related to Restricted rights-Use, duplication, or disclosure is subject to restrictions set forth in GSA ADP Schedule Contract with IBM Corp.

IBM PS/2 Model 30 286 HMS Special Notices

FRONT_2 Special Notices

References in this publication to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates. Any reference to an IBM product, program or service is not intended to state or imply that only IBM's product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any of IBM's intellectual property rights or other legally protectible rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, programs, or services, except those expressly designated by IBM, are the user's responsibility.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the IBM Director of Commercial Relations, IBM Corporation, Purchase, NY 10577.

The following terms, denoted by an asterisk (*) in this publication, are trademarks of the IBM Corporation in the United States and/or other countries:

IBM
Personal System/2.

IBM PS/2 Model 30 286 HMS Table of Contents

FRONT_1 FRONT_2 CONTENTS 1.0 2.0 3.0 4.0 5.0 6.0 7.0 8.0	Table of Contents Safety Information Special Notices Table of Contents General Checkout Undetermined Problem Memory Printer Installed Devices Display Self-Test Symptom-to-FRU Index How To Use This Parts Catalog
8.0 9.0 10.0	How To Use This Parts Catalog System Overview Parts
TU.U	Parts

IBM PS/2 Model 30 286 HMS General Checkout

1.0 General Checkout

The advanced diagnostic tests are intended to test $only\ {\tt IBM}\ ({\tt ^*})$ products. Non-IBM products, prototype cards, or modified options can give false errors and invalid system responses.

IMPORTANT:

- If more than one error code is displayed, diagnose the first error code first. The cause of the first error code can cause false error codes to be displayed.
- If an adapter or device consists of more than one FRU, an error code may be caused by any of the FRUs. Before replacing the adapter or device, remove the FRUs, one by one, to see if the symptoms change.

To disable the power-on password, move the J13 jumper on the system board to the unused position.

```
1001
- Check all signal cables and power cords.
- If you cannot load a diagnostics diskette, go to "Symptom-to-FRU Index."
- Load the Advanced Diagnostics diskette, and check for the following
 responses:
 1. Memory test

    One or two short beeps (press the F1 key if prompted)
    First diagnostic menu.

ARE ALL THREE RESPONSES CORRECT?
Yes No
    - 1
     +---+
    002
    Go to "Symptom-to-FRU Index."
-
1003
IS THE INSTALLED DEVICES LIST CORRECT?
Yes No
     - 1
    |004|
     Go to "Installed Devices."
 -
005
+---+
- Run the diagnostic tests.
ARE THE TESTS SUCCESSFUL?
Yes No
     - 1
    006
     Go to "Symptom-to-FRU Index."
 -
1007
+---+
You may have an intermittent problem.

    Check for damaged cables and connectors.
    Reseat all adapters, drives, and modules.

3. Start an error log, and run the tests multiple times.
```

(*) Trademark of the International Business Machines Corporation.

IBM PS/2 Model 30 286 HMS

Undetermined Problem

- 2.0 Undetermined Problem
- Power-off the system.
 Remove or disconnect one of the following devices or adapters:
 - a. Non-IBM devices
 - b. External devices (modem, printer, or mouse)
 - c. Math coprocessor d. Any adapter

 - e. Bus adapter

 - f. Diskette drive cable g. Fixed disk drive cable.
- Power-on the system.
 Repeat the previous steps until you find the failing adapter or device.

If all devices and adapters have been removed and the problem continues, check the power supply output voltages. If the output voltages are good, replace the system board; otherwise replace the power supply.

If the power supply fan is not running, replace the power supply.

PICTURE 2

V dc Minimum	Maximum		Pin
+ 4.8	+ 5.2	P7-5	P7-10
+ 4.5	+ 5.4	P7-9	P7-5
+11.5	+12.6	P7-5	· ·
+10.8	+12.9	P7-4	· ·

IBM PS/2 Model 30 286 HMS Memory

3.0 Memory 001 - Power-off the system and wait 5 seconds. - Insert the Advanced Diagnostics diskette into drive A. - Power-on the system. - Make a note of any POST errors you receive. - Disregard 164-Memory Size Errors. Press the ${\bf F1}$ key and continue with these steps. DID YOU RECEIVE A XXXXXX XXXX 201 POST ERROR? Yes No - | +---+ 002 - Run the memory tests. Use the RUN TESTS ONE TIME option. DID THE MEMORY TESTS COMPLETE WITHOUT AN ERROR? Yes No | | |003| Follow the instructions on the screen. +---+ 004 +---+ Your system memory is now functioning correctly. If you suspect an intermittent problem, start an error log. 005 - Replace pack A with a known good pack of the same size that is installed in the system (256KB and 1MB packs are not interchangeable). - If the problem remains, swap the pack removed from A with pack B.

- If the problem remains, swap the pack removed from B with pack C. If the problem remains, swap the pack removed from C with pack D.
- If all memory packs have been swapped and the problem remains, replace the system board.

IBM PS/2 Model 30 286 HMS Printer

4.0 Printer

- 1. Make sure the printer is properly connected and powered-on. 2. Run the printer self-test.

If the printer self-test does not run correctly, the problem is in the printer. Refer to the printer service manual.

If the printer self-test runs correctly, install a wrap plug on the parallel port and run the advanced diagnostic tests to determine which of the following FRUs is failing:

- $\ \square$ System board
- Parallel adapterPrinter cable.

IBM PS/2 Model 30 286 HMS Installed Devices

5.0 Installed Devices

If a device or adapter is not on the installed devices list, replace the device, adapter or cable. If the error remains, replace the bus adapter.

If an adapter is shown on the installed-devices list but is not in the system, remove the bus adapter. If the error remains, replace the system

IBM PS/2 Model 30 286 HMS Display Self-Test

- 6.0 Display Self-Test
- 1. Power-off the system unit and display.
- Disconnect the display signal cable.
 Power-on the display.
- 4. Turn the contrast to its maximum position.
- 5. Turn the brightness control to the center detent position.

The screen should be white with a black margin, as described below (some shading may occur near the edges). If the screen differs, replace the display. If the display passes the test, replace the system board or display adapter that the display is attached to.

- **8503, 8512, 8513, 8514, 8515:** 2-20 mm (0.08-0.79 in.) wide on one or both sides.
- 8506: 2-35 mm (0.08-1.38 in.) wide on the top, or bottom, or both.
- **8507, 8508:** 2-20 mm (0.08-0.79 in.) wide on the top, or bottom, or both.
- **8604:** 2-20 mm (0.08-0.79 in.) wide, on all four sides.

IBM PS/2 Model 30 286 HMS Symptom-to-FRU Index

7.0 Symptom-to-FRU Index

The Symptom-to-FRU Index lists symptoms and errors and the possible causes. The most likely cause is listed first. Use this index to help you decide which FRUs you should have available when servicing a system.

Note: If you are using the Advanced Diagnostics diskette to determine what is actually failing, always begin with "General Checkout" in topic 1.0.

If the system displays an error message and gives an incorrect audio response, the most likely causes are those listed for the error message. An $\it X$ in an error message can be any number.

Symptom/Error	FRU/Action
No beep during POST	System Board Power Supply Memory Packs Any Adapter Bus Adapter Power Cord
One long and two short beeps during POST	System Board
Continuous beep	System Board
Blank or illegible display See "Display Self-Test" in topic 6.0 before replacing any FRUs.	System Board Display Power Supply System Board Video Cable
Other display problems See "Display Self-Test" in topic 6.0 before replacing any FRUs.	System Board Display Power Supply System Board Video Cable
Insert a Diskette icon	Diskette Drive System Board Diskette Cable Network Adapter
System loads BASIC or loads from fixed disk	Diskette Drive System Board Diskette Cable Network Adapter
Incorrect memory size during POST See "Memory" in topic 3.0 before replacing any FRUs.	System Board
110 ????? See "Memory" in topic 3.0 before replacing any FRUs.	Adapter Memory Bus Adapter System Board
111 ????? See "Memory" in topic 3.0 before replacing any FRUs.	Adapter Memory Bus Adapter System Board
Printer problems	See "Printer" in topic 4.0.
Serial or parallel port device failure	Device Self-Test OK? Device Cable System Board

IBM PS/2 Model 30 286 HMS Symptom-to-FRU Index

	Symptom-to-FRU Index
	Alternate Adapter Bus Adapter
XXXX ROM Error	Any Adapter
Some or all keys on the keyboard don't work.	Keyboard System Board Keyboard Cable
Real-Time Clock inaccurate	Clock Module System Board
161	Run Setup Clock Module System Board
162	Run Setup Clock Module System Board
163	Time and Date Set? Clock Module System Board
164 See "Memory" in topic 3.0 before replacing any FRUs.	Run Setup System Board
199	See "Installed Devices" in topic 5.0.
1XX	System Board
201 See "Memory" in topic 3.0 before replacing any FRUs.	System Board
301	System Board Keyboard Keyboard Cable
3XX	Keyboard System Board Keyboard Cable
6XX	Diskette Drive External Drive Adapter System Board Power Supply Diskette Cable
7XX	Math Coprocessor System Board
9xx	System Board
10XX	Alt. Parallel Adapter Bus Adapter
11XX	System Board
12XX	Alt. Serial Adapter Bus Adapter
13XX	Game Control Adapter Bus Adapter
14XX	See "Printer" in topic 4.0.
17XX	Fixed Disk Drive System Board Fixed Disk Cable Power Supply
24XX	System Board Display System Board Video Cable
28XX	- +

IBM PS/2 Model 30 286 HMS Symptom-to-FRU Index 3278/79 Adapter | Coaxial Cable Bus Adapter 30XX PC Network Adapter LF Translator | Cable Problem | Bus Adapter 31XX Alt. PC Network Adapter | LF Translator | Cable Problem | Bus Adapter GPIB Adapter | 36XX | Bus Adapter DAC Adapter 38XX | Bus Adapter Speech Adapter 84XX | Speech Control Assembly Bus Adapter Mouse | System Board | Music Card | MIDI Adapter Unit

	Problem ren ptom-to-FRU	"Undetermined	Problem."	Supplemental	
. – – -		 			

| Bus Adapter

IBM PS/2 Model 30 286 HMS How To Use This Parts Catalog

8.0 How To Use This Parts Catalog

INDEX REFERENCE NUMBERS: Refer to the illustrations for index reference
numbers listed in the left margin of the parts listing.

SIMILAR ASSEMBLIES: If two assemblies contain a majority of identical parts, they are broken down on the same list. Parts peculiar to one or the other of the assemblies are listed separately and identified by description.

 ${\tt AR\colon}$ (As Required) indicates that the quantity is not the same for all machines.

 ${\bf R}\colon$ (Restricted) indicates that the part has a restricted availability.

INDENTURE the indenture is marked by a series of dots located before the parts description. The indenture indicates the relationship of a part to the next higher assembly. For example:

Indenture Relationship of Parts

(No dot)	Main Assembly
(One dot)	$\ \square$ Detail parts of a main assembly
(One dot)	☐ Subassembly of the main assembly
(Two dot)	\square \square Detail part of a one-dot
	subassembly
(Two dot)	\square \square Subassembly of a one-dot
	subassembly

IBM PS/2 Model 30 286 HMS System Overview

9.0 System Overview

PICTURE 3

10.0 Parts

Index	System Unit	
1	Top Cover	27F4172
2	Rear Cover	27F4174
3	System Base (with rubber feet)	27F4167
4 5	Power Supply, 120/230 V Power Switch Link and Lever	27F4166 27F4168
6	Drive Cradle	27F4170
7	Cover Lock Assembly	27F4169
8	Blank Drive Bezel	72X7534
8	Diskette Drive Bezel (see Diskette Drive / Fixed Disk	Draine
8	Fixed Disk Drive Bezel	Drive)
•	(see Diskette Drive / Fixed Disk	Drive)
	Front Bezel (w/o Logo)	27F4173
9	Front Cover Logo (R)	27F4249
10	Back Panel (I/O Panel) System Board (Model E-21 only)	27F4229 27F4069
10	System Board System Board	34F0046
	System Board Clip	61X8933
	Memory Pack - 256KB	1497256
	Memory Pack - 1MB Clock Module	74X8637
11	Bus Adapter	8509237 27F4164
12	Bus Adapter Support	27F4165
	Support Bracket	61X8914
	Sliding Support Bracket	61X8926
	System Board Video Cable 80287 Math Coprocessor	27F4163 72X8528
	Miscellaneous Parts Kit	27F4171
	☐ Captive Screw (Qty 4)	
	☐ Screw (Qty 5)	
	□ Spring (Qty 4)	
	□ Lock Slide Assembly (Qty 2)	
	_ , , , _, , _, ,	
	te Drive / Fixed Disk Drive te Drive 1.44MB (1/2 high)	72X8523
	te Drive Bezel (1/2 high)	27F4175
	te 1 Drive Cable (1/2 high)	27F4916
	te 2 Drive Cable (1/2 high)	34F0001
	te Drive 1.44MB (1/3 high) te Drive Bezel (1/3 high)	33F8211 27F4230
	te 1 Drive Cable (1/3 high)	27F4230 27F4912
	te 2 Drive Cable (1/3 high)	34F0000
	te Drive Slide (1/3 high)	27F4917
	Disk Drive, 20MB Disk Drive, 30MB	6128285
	Disk Drive, 30MB Disk Drive, 45MB	6128279 92F0016
	Disk Drive Bezel	27F4177
	Disk Drive Cable	27F4178
	nch Diskette Drive:	
	EB External (4869-001) EB External (4869-501)	72X6759 72X6768
	iskette Drive	72X6771
	ower Supply	72X6769
Adap		72X6757
	-Inch External Diskette Drive Cable	27F4211
(L	rom system board to adapter)	
0=+1	and Adoptons	
	: and Adapters .cquisition Adapter	6181768
Data A	cquisition Distribution Panel	6181769
	ed 5250 Emulation Adapter	30F5384
	ontrol Adapter dapter	8529151 6181770
	dapter Unit	81X8624
	ic Adapter	81X8620
	work Adapter	8286171
	work Adapter II work Baseband Adapter	72X8105 72X8101
	work Baseband Adapter Communicator Adapter	72X81U1 33F4846
	Communicator Cable (Black-L)	57F1261
PhoneC	communicator Cable (Black-S)	57F1262
	communicator Cable (Beige-L)	57F1263
	ommunicator Cable (Beige-S)	57F1264
	r Cable Multifunction Adapter	8529214 30F5447
	mory Pack - 256KB	1497256
	mory Pack - 1MB	74X8637
	Reader Adapter	33F4842
screen	Reader Keypad	1393515

IBM PS/2 Model 30 286 HMS

	Parts
Screen Reader Keypad Cable	72X8537
SpeechViewer Adapter	15F8511
☐ Test Plug (for 15F8511)	15F8512
SDLC Adapter	8286099
Communications Adapter Cable	8529274
Serial/Parallel Adapter	8286147
Serial Adapter Cable	8286170
Serial Adapter Connector	8286194
Speech Adapter	61X8921
Speech Control Unit	61X8934
Token Ring Adapter	16F0463
Token Ring 16/4 Adapter	25F8884
Token Ring RPL (Module)	83X7839
3278/3279 Emulation Adapter	8665792
80287 Math Coprocessor	72X8528

Keyboard / Mouse

Arabic	1392014
Belgian	1392012
Canadian French	1392011
Danish	1392005
French	1392000
German	1392001
Hebrew	1392006
Italian	1392002
Norwegian	1392007
Portuguese	1392008
Spanish	1392003
Spanish / Latin	1392015
Swedish	1392009
Swiss / French / German	1392010
U.K. English	1392004
U.S. English	1392090
SolutionPac	1393390
Keyboard Cable (30 286)	27F4984
Mouse	61X8923
Mouse Ball and Pop-Off Retainer	33F8461
Mouse Ball and Twist-Off Retainer	33F8462

8503 Monochrome Display (with Tilt/Swivel Stand)

110/120 V	ac		68X3045
220/240 V	ac (Northern	Hemisphere)	68X3046
220/240 V	ac (Southern	Hemisphere)	72X7878
Tilt/Swive	1 Stand		68X3061

8506 Monochrome Display (with Tilt/Swivel Stand)

110/125 V ac (US/Canada)				39F8087				
	110/125	or	200/240	V	ac	(Northern	Hemisphere)	39F8088
	110/125	or	220/240	V	ac	(Southern	Hemisphere)	39F8089

8507 Monochrome Display (with Tilt/Swivel Stand)

110/120 or 220/240 V ac (Universal Model) 6247808

8508 Monochrome Display (with Tilt/Swivel Stand)

110/125 V ac (US/Canada)						6247838		
	110/125	or	200/240	V	ac	(Northern	Hemisphere)	39F8067
	110/125	or	220/240	V	ac	(Southern	Hemisphere)	39F8068

8512 Color Display (without Tilt/Swivel Stand)

110/120 V ac	61X8924
220/240 V ac (Northern Hemisphere)	61X8928
220/240 V ac (Southern Hemisphere)	61X8927
Tilt/Swivel Stand	61X8925

8513 Color Display (with Tilt/Swivel Stand)

110/120 V ac	68X3088
220/240 V ac (Northern Hemisphere)	72X7870
220/240 V ac (Southern Hemisphere)	72X7877
Tilt/Swivel Stand	68X3061

8514 Color Display (without Tilt/Swivel Stand)

110/120 V ac 75X5945 220/240 V ac (Northern Hemisphere) 75X5946

	IBM PS/2 Model 30 286 HMS Parts						
220/240 V ac (Southern Hemisphere) Tilt/Swivel Stand	75X5947 75X5907						
8515 Color Display (with Tilt/Swivel	Stand)						
90/137 V ac (U.S. and Canada)	38F3911						
90/265 V ac (Northern Hemisphere)	38F3912						
180/265 V ac (Southern Hemisphere)	38F3913						
90/137 V ac (Japan, S.Korea, Taiwan) 38F3914						
	8604 Monochrome Display (with Tilt/Swivel Stand)						
110/120 V ac	6398267						
Power Cords							
PICT	URE 4						
Index Power Cords							
Warning: Use the power core							
certified for your coun	try.						
1 Power Cord, Displays	C0X2071						
(except 8514), for:	68X3071						
Colombia, U.S., Venezuela 2 Power Cord, System Unit, fo							
Colombia, U.S., Venezuela							
3 Power Cord, System Unit, for Hong Kong, Singapore, U.K							
4 Power Cord, System Unit, fe							
France, Germany, Spain 5 Power Cord, System Unit, fo	or: 8529282						
Italy 6 Power Cord, System Unit, for	or: 8529284						
Australia, New Zealand							
Tools and Miscellaneous							
Tri-Connector Wrap Plug	72X8546						
Data Migration Connector Adapter	61X8936						
Supplemental Parts:							

IBM PS/2 Model 30 286 HMS Parts
