



## DUAL INPUT DIFFERENTIAL MANOMETER

386P

### FEATURES

- Most robust differential pressure meter
- 4 switchable units: InWC, mmWC, mBar, psi
- Rubber-boot protection for tough applications
- Dual Display and Dual input
- Main Display: P1, P2
- Second Display: P1 - P2

### APPLICATIONS

- HVAC system troubleshooting
- Gas pressure measurement

### SPECIFICATIONS

Accuracy	:	± 1.5% FS.
Operating Environment	:	0°C to 50° (32°F to 122°F) ambient
Compatible Media	:	Dry, non-corrosive gases
Battery Life	:	200 hours with low battery indication on display
Units of Measure	:	InWC, mmWC, mBar, psi
Pressure Ports	:	Tube connectors for 8mm I.D. flexible tubing
Weight	:	Approx. 195g. including battery
Measurement range	:	InWC : 0.00 to ± 60.0 mmWC : 0.0 to ± 1500 mBar : 0.00 to ± 150.0 psi : 0.000 ± 2.000
Accuracy	:	± 1.5% FS
Battery	:	9V



# Micon Engineers

25, NETAJI SUBHAS ROAD, KOLKATA-700001  
PHONE : 033-2230-9138/8378 • FAX : 033-22308378  
email : miconeng@rediffmail.com