

# Deoxo™ (FTIS/OBIGGS)

## Fuel Tank Inerting System / On-Board Inert Gas Generating System (FTIS/OBIGGS) Catalytic Ozone Converter

The air separation system for FTIS/ OBIGGS is a safety feature for commercial aircraft mandated by the Federal Aviation Administration (FAA).

FTIS/OBIGGS use an Air Separation Module (ASM) to separate nitrogen from the air. The nitrogen is blanketed over the fuel in the tank to lower the risk of explosions. FTIS/OBIGGS require an ozone converter to protect the membrane inside the ASM from decomposition by ozone.

Commercial and military aircraft can be equipped or retrofitted with BASF's Deoxo™ FTIS/OBIGGS catalytic ozone converter.

### **Deoxo™ FTIS/OBIGGS Catalytic Ozone Converters Offer:**

- ✓ The highest protection for air separation membranes inside the FTIS/OBIGGS.
- ✓ Low weight and pressure drop
- ✓ Easy installation and removal.
- ✓ Cost-effective maintenance.

### **A Proven Solution**

After millions of flight hours in-service, BASF Deoxo™ ozone converters have exhibited superior catalyst life, durability, and cost-effective maintenance.

### **World-wide MRO Service**

BASF offers competitive pricing for functional evaluation, maintenance, and repair services. BASF's worldwide service couples industry leading quality with short lead-times. BASF's repair services can increase the life of ozone converters to decrease total cost-per-hour over the service life of an aircraft.



## About Us

BASF's Catalysts division is the world's leading supplier of environmental and process catalysts. The group offers exceptional expertise in the development of technologies that protect the air we breathe, produce the fuels that power our world and ensure efficient production of a wide variety of chemicals, plastics and other products, including advanced battery materials. By leveraging our industry-leading R&D platforms, passion for innovation and deep knowledge of precious and base metals, BASF's Catalysts division develops unique, proprietary solutions that drive customer success.

**BASF - We create chemistry**

## Contact Us Today

### Aircraft OEM Sales

#### **Patrick Monaco**

Global Account Manager, Aircraft Ozone

BASF Corporation

25 Middlesex/Essex Turnpike

Iselin, New Jersey, 08830, USA

Tel: +1-732-205-6236

Email: [pat.monaco@basf-catalystsmetals.com](mailto:pat.monaco@basf-catalystsmetals.com)

### Airline Aftermarket & MRO Sales

#### **Aircraft Ozone Sales**

BASF Corporation

25 Middlesex/Essex Turnpike

Iselin, New Jersey, 08830, USA

Tel: +1-732-205-6078

Email: [aircraft.cleanair@basf-catalystsmetals.com](mailto:aircraft.cleanair@basf-catalystsmetals.com)

#### **Huntsville Facility – OEM & MRO**

BASF Corporation

9800 Kellner Road

Huntsville, Alabama, 35824, USA

In 1980, FAA AC-120-38 was released mandating that aircraft cabin ozone levels cannot exceed 0.25 ppm above FL-320, and 0.10 ppm above FL-270 as a time weighted average for all flight segments longer than 4 hours. Ozone concentrations in excess of these levels can result in serious health issues including pulmonary distress, sinus pain, chest pain, fatigue, and dizziness.

Deoxo is a trademark of BASF.

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2023 BASF

BASF-9369, USL 07/23