Semantic subtyping for non-strict languages

Tommaso Petrucciani

DIBRIS, Università di Genova, Italy & IRIF, Université Paris Diderot, France

Giuseppe Castagna

CNRS, IRIF, Université Paris Diderot, France

Davide Ancona and Elena Zucca

DIBRIS, Università di Genova, Italy

Abstract -

Semantic subtyping is an approach to define subtyping relations for type systems featuring union and intersection type connectives. It has been studied only for strict languages, and it is unsound for non-strict semantics. In this work, we study how to adapt this approach to non-strict languages: in particular, we define a type system using semantic subtyping for a functional language with a call-by-need semantics. We do so by introducing an explicit representation for divergence in the types, so that the type system distinguishes expressions that are results from those which are computations that might diverge.

1 Introduction

Semantic subtyping is a powerful framework which allows language designers to define subtyping relations for rich languages of types – including union and intersection types – that can express precise properties of programs. However, it has been developed for languages with call-by-value semantics and, in its current form, it is unsound for non-strict languages. We show how to design a type system which keeps the advantages of semantic subtyping while being sound for non-strict languages (more specifically, for call-by-need semantics).

1.1 Semantic subtyping

Union and intersection types can be used to type several language constructs – from branching and pattern matching to function overloading – very precisely. However, they make it challenging to define a subtyping relation that behaves precisely and intuitively.

Semantic subtyping is a technique to do so, studied by Frisch, Castagna, and Benzaken [20] for types given by:

$$t \coloneqq b \mid t \to t \mid t \times t \mid t \vee t \mid t \wedge t \mid \neg t \mid 0 \mid 1 \qquad \text{where } b \coloneqq \mathsf{Int} \mid \mathsf{Bool} \mid \cdots$$

Types include constructors – basic types b, arrows, and products – plus union $t \vee t$, intersection $t \wedge t$, negation (or complementation) $\neg t$, and the bottom and top types $\mathbb O$ and $\mathbb I$ (actually, $t_1 \wedge t_2$ and $\mathbb I$ can be defined respectively as $\neg(\neg t_1 \vee \neg t_2)$ and $\neg \mathbb O$). The grammar above is interpreted coinductively rather than inductively, thus allowing infinite terms that correspond to recursive types. Subtyping is defined by giving an interpretation $[\![\cdot]\!]$ of types as sets and defining $t_1 \leq t_2$ as the inclusion of the interpretations, that is, $t_1 \leq t_2$ is defined as $[\![t_1]\!] \subseteq [\![t_2]\!]$. Intuitively, we can see $[\![t]\!]$ as the set of values that inhabit t in the language. By interpreting union, intersection, and negation as the corresponding operations on sets and by giving appropriate interpretations to the other constructors, we ensure that subtyping will satisfy all commutative and distributive laws we expect: for example, $(t_1 \times t_2) \vee (t'_1 \times t'_2) \leq (t_1 \vee t'_1) \times (t_2 \vee t'_2)$ or $(t \to t_1) \wedge (t \to t_2) \leq t \to (t_1 \wedge t_2)$.

This relation is used in [20] to type a call-by-value language featuring higher-order functions, data constructors and destructors (pairs), and a typecase construct which models

A version of this article without the Appendix is being submitted for publication in the post-proceedings of the 24th International Conference on Types for Proofs and Programs (TYPES 2018).

runtime type dispatch and acts as a form of pattern matching. Functions can be recursive and are explicitly typed; their type can be an intersection of arrow types, describing overloaded behaviour. A simple example of an overloaded function is

let
$$f x = if (x is Int) then (x + 1) else not(x)$$

which tests whether its argument \mathbf{x} is of type Int and in this case returns its successor, its negation otherwise. This function can be given the type (Int \rightarrow Int) \land (Bool \rightarrow Bool), which signifies that it has both type Int \rightarrow Int and type Bool \rightarrow Bool: the two types define its two possible behaviours depending on the outcome of the test (and, thus, on the type of the input). This is done in [20] by explicitly annotating the whole function definition. Using notation for typecases from [20]: let $f:(\operatorname{Int} \rightarrow \operatorname{Int}) \land (\operatorname{Bool} \rightarrow \operatorname{Bool}) = \lambda x. \ (x \in \operatorname{Int})? \ (x+1):(\operatorname{not} x)$. The type deduced for this function is $(\operatorname{Int} \rightarrow \operatorname{Int}) \land (\operatorname{Bool} \rightarrow \operatorname{Bool})$, but it can also be given the type (Int \lor Bool) \rightarrow (Int \lor Bool): the latter type states that the function can be applied to both integers and booleans and that its result is either an integer or a boolean. This latter type is less precise than the intersection, since it loses the correlation between the types of the argument and of the result. Accordingly, the semantic definition of subtyping ensures (Int \rightarrow Int) \land (Bool \rightarrow Bool) \le (Int \lor Bool) \rightarrow (Int \lor Bool).

The work of [20] has been extended to treat more language features, including parametric polymorphism [14, 12, 11], type inference [13], and gradual typing [10] and adapted to SMT solvers [6]. It has been used to type object-oriented languages [16, 1], XML queries [8], NoSQL languages [4], and scientific languages [22]. It is also at the basis of the definition of CDuce, an XML-processing functional programming language with union and intersection types [5]. However, only strict evaluation had been considered, until now.

1.2 Semantic subtyping in lazy languages

Our work started as an attempt to design a type system for the Nix Expression Language [17], an untyped, purely functional, and lazily evaluated language for Unix/Linux package management. Since Nix is untyped, some programming idioms it encourages require advanced type system features to be analyzed properly. Notably, the possibility of writing functions that use type tests to have an overloaded-like behaviour made intersection types and semantic subtyping a good fit for the language. However, existing semantic subtyping relations are unsound for non-strict semantics; this was already observed in [20] and no adaptation has been proposed later. Here we describe our solution to define a type system based on semantic subtyping which is sound for a non-strict language. In particular, we consider a call-by-need variant of the language studied in [20].

Current semantic subtyping systems are unsound for non-strict semantics because of the way they deal with the bottom type \mathbb{O} , which corresponds to the empty set of values ($[\![\mathbb{O}]\!] = \varnothing$). The intuition is that a reducible expression e can be safely given a type t only if all results (i.e., values) it can return are of type t. Accordingly, \mathbb{O} can only be assigned to expressions that are statically known to diverge (i.e., that never return a result). For example, the ML expression let rec f x = f x in f () can be given type \mathbb{O} . Let us use \bar{e} to denote any diverging expression that, like this, can be given type \mathbb{O} . Consider the following typing derivations, which are valid in current semantic subtyping systems (π_2 projects the second component of a pair).

Note that both π_2 (\bar{e} , 3) and (λx . 3) \bar{e} diverge in call-by-value semantics (since \bar{e} must be evaluated first), while they both reduce to 3 in call-by-name or call-by-need. The derivations are therefore sound for call-by-value, while they are clearly unsound with non-strict evaluation.

Why are these derivations valid? The crucial steps are those marked with $[\simeq]$, which convert between types that have the same interpretation; \simeq denotes this equivalence relation. With semantic subtyping, $0 \times \text{Int} \simeq 0 \times \text{Bool}$ holds because all types of the form $0 \times t$ are equivalent to 0 itself: none of these types contains any value (indeed, product types are interpreted as Cartesian products and therefore the product with the empty set is itself empty). It can appear more surprising that $0 \to \text{Int} \simeq 0 \to \text{Bool}$ holds. We interpret a type $t_1 \to t_2$ as the set of functions which, on arguments of type t_1 , either diverge or return results in type t_2 . Since there is no argument of type 0 (because, in call-by-value, arguments are always values), all types of the form $0 \to t$ are equivalent (they all contain every well-typed function).

1.3 Our approach

The intuition behind our solution is that, with non-strict semantics, it is not appropriate to see a type as the set of the values that have that type. In a call-by-value language, operations like application or projection occur on values: thus, we can identify two types (and, in some sense, the expressions they type) if they contain (and their expressions may produce) the same values. In non-strict languages, though, operations also occur on partially evaluated results: these, like $(\bar{e},3)$ in our example, can contain diverging sub-expressions below their top-level constructor.

As a result, it is unsound, for example, to type $(\bar{e},3)$ as $\mathbb{O} \times \mathsf{Int}$, since we have that $\mathbb{O} \times \mathsf{Int}$ and $\mathbb{O} \times \mathsf{Bool}$ are equivalent. It is also unsound to have subtyping rules for functions which assume implicitly that every argument will eventually be a value.

One approach to solve this problem would be to change the interpretation of $\mathbb O$ so that it is non-empty. However, the existence of types with an empty interpretation is important for the internal machinery of semantic subtyping. Notably, the decision procedure for subtyping relies on them (checking whether $t_1 \leq t_2$ holds is reduced to checking whether the type $t_1 \wedge \neg t_2$ is empty). Therefore, we keep the interpretation $[\![\mathbb O]\!] = \emptyset$, but we change the type system so that this type is *never* derivable, not even for diverging expressions. We keep it as a purely "internal" type useful to describe subtyping, but never used to type expressions.

We introduce instead a separate type \perp as the type of diverging expressions. This type is non-empty but disjoint from the types of constants, functions, and pairs: [⊥] is a singleton whose unique element represents divergence. Introducing the \perp type means that we track termination in types. In particular, we distinguish two classes of types: those that are disjoint from \perp (for example, Int, Int \rightarrow Bool, or Int \times Bool) and those that include \perp (since the interpretation of \perp is a singleton, no type can contain a proper subset of it). Intuitively, the former correspond to computations that are guaranteed to terminate: for example, Int is the type of terminating expressions producing an integer result. Conversely, the types of diverging expressions must always contain \perp and, as a result, they can always be written in the form $t \vee \bot$, for some type t. Subtyping verifies $t \leq t \vee \bot$ for any t: this ensures that a terminating expression can always be used when a possibly diverging one is expected. This subdivision of types suggests that \perp is used to approximate the set of diverging well-typed expressions: an expression whose type contains \perp is an expression that may diverge. Actually, the type system we propose performs a rather gross approximation. We derive "terminating types" (i.e., subtypes of $\neg \bot$) only for expressions that are already results and cannot be reduced: constants, functions, or pairs. Applications and projections, instead, are always expression e_1 to be possibly diverging: we require it to

typed by assuming that they might diverge. The typing rules are written to handle and propagate the \perp type. For example, we type applications using the rule on the right. This rule allows the

$$\frac{\Gamma \vdash e_1 \colon (t' \to t) \lor \bot \qquad \Gamma \vdash e_2 \colon t'}{\Gamma \vdash e_1 \; e_2 \colon t \lor \bot}$$

have the type $(t' \to t) \lor \bot$ instead of the usual $t' \to t$ (but an expression with the latter type can always be subsumed to have the former type). We type the whole application as $t \vee \bot$ to signify that it can diverge even if the codomain t does not include \perp , since e_1 can diverge.

This system avoids the problems we have seen with semantic subtyping: no expression can be assigned the empty type, which was the type on which subtyping had incorrect behaviour. The new type \perp does not cause the same problems because $[\![\perp]\!]$ is non-empty. For example, the type of expressions like $(\bar{e},3)$ – where \bar{e} is diverging – is now $\perp \times$ Int. This type is not equivalent to $\perp \times \mathsf{Bool}$: indeed, the two interpretations are different because the interpretation of types includes an element ($[\![\bot]\!]$) to represent divergence.

Typing all applications as possibly diverging – even very simple ones like $(\lambda x. 3) e$ – is a very coarse approximation which can seem unsatisfactory. We could try to amend the rule to say that if e_1 has type $t' \to t$, then $e_1 e_2$ has type t instead of $t \vee \bot$. However, we prefer to keep the simpler rules since they achieve our goal of giving a sound type system that still enjoys most benefits of semantic subtyping.

An advantage of the simpler system is that it allows us to treat \perp as an internal type that does not need to be written explicitly by programmers. Since the language is explicitly typed, if \perp were to be treated more precisely, programmers would presumably need to include it or exclude it explicitly from function signatures. This would make the type system significantly different from conventional ones where divergence is not explicitly expressed in the types. In the present system, instead, we can assume that programmers annotate programs using standard set-theoretic types and \perp is introduced only behind the scenes and, thus, is transparent to programmers.

We define this type system for a call-by-need variant of the language studied in [20], and we prove its soundness in terms of progress and subject reduction.

The choice of call-by-need rather than call-by-name stems from the behaviour of semantic subtyping on intersections of arrow types. Our type system would actually be unsound for callby-name if the language were extended with constructs that can reduce non-deterministically to different answers. For example, the expression rnd(t) of [20] that returns a random value of type t could not be added while keeping soundness. This is because in call-by-name, if such an expression is duplicated, each occurrence could reduce differently; in call-byneed, instead, its evaluation would be shared. Intersection and union types make the type system precise enough to expose this difference. In the absence of such non-deterministic constructs, call-by-name and call-by-need can be shown to be observationally equivalent, so that soundness should hold for both; however, call-by-need also simplifies the technical work to prove soundness.

We show an example of this, though we will return on this point later. Consider the following derivation, where \bar{e} is an expression of type Int \vee Bool.

$$\underbrace{ \begin{array}{c} x \colon \mathsf{Int} \vdash (x,x) \colon \mathsf{Int} \times \mathsf{Int} & x \colon \mathsf{Bool} \vdash (x,x) \colon \mathsf{Bool} \times \mathsf{Bool} \\ \vdash \lambda x. \, (x,x) \colon (\mathsf{Int} \to \mathsf{Int} \times \mathsf{Int}) \wedge (\mathsf{Bool} \to \mathsf{Bool} \times \mathsf{Bool}) \\ \hline \vdash \lambda x. \, (x,x) \colon \mathsf{Int} \vee \mathsf{Bool} \to (\mathsf{Int} \times \mathsf{Int}) \vee (\mathsf{Bool} \times \mathsf{Bool}) \\ \hline \vdash (\lambda x. \, (x,x)) \, \bar{e} \colon (\mathsf{Int} \times \mathsf{Int}) \vee (\mathsf{Bool} \times \mathsf{Bool}) \\ \end{array} } \vdash \bar{e} \colon \mathsf{Int} \vee \mathsf{Bool}$$

In a system with intersection types, the function $\lambda x.(x,x)$ can be given the type (Int \rightarrow $Int \times Int$) \land (Bool \rightarrow Bool \times Bool) because it has both arrow types (in practice, the function will have to be annotated with the intersection). Then, the step marked with $[\leq]$ is allowed because, in semantic subtyping, $(\operatorname{Int} \times \operatorname{Int}) \wedge (\operatorname{Bool} \to \operatorname{Bool} \times \operatorname{Bool})$ is a subtype of $(\operatorname{Int} \vee \operatorname{Bool}) \to ((\operatorname{Int} \times \operatorname{Int}) \vee (\operatorname{Bool} \times \operatorname{Bool}))$ (in general, $(t_1 \to t_1') \wedge (t_2 \to t_2') \leq t_1 \vee t_2 \to t_1' \vee t_2')$. Therefore, the application $(\lambda x. (x, x))$ \bar{e} is well-typed with type $(\operatorname{Int} \times \operatorname{Int}) \vee (\operatorname{Bool} \times \operatorname{Bool})$. In call-by-name, it reduces to (\bar{e}, \bar{e}) : therefore, for the system to satisfy subject reduction, we must be able to type (\bar{e}, \bar{e}) with the type $(\operatorname{Int} \times \operatorname{Int}) \vee (\operatorname{Bool} \times \operatorname{Bool})$ too. But this type is intuitively unsound for (\bar{e}, \bar{e}) if each occurrence of \bar{e} could reduce independently and non-deterministically either to an integer or to a boolean. Using a typecase we can actually exhibit a term that breaks subject reduction.

There are several ways to approach this problem. We could change the type system or the subtyping relation so that $\lambda x.(x,x)$ cannot be given the type $(\operatorname{Int} \vee \operatorname{Bool}) \to ((\operatorname{Int} \times \operatorname{Int}) \vee (\operatorname{Bool} \times \operatorname{Bool}))$. However, this would curtail the expressive power of intersection types as used in the semantic subtyping approach. We could instead assume explicitly that the semantics is deterministic. In this case, the typing would not be unsound intuitively, but a proof of subject reduction would be difficult: we should give a complex union disjunction rule to type (\bar{e}, \bar{e}) . We choose instead to consider a call-by-need semantics because it solves both problems. With call-by-need, non-determinism poses no difficulty because of sharing. We still need a union disjunction rule, but it is simpler to state since we only need it to type the let bindings which represent shared computations.

1.4 Contributions

The main contribution of this work is the development of a type system for non-strict languages based on semantic subtyping; to our knowledge, this had not been studied before.

Although the idea of our solution is simple – to track divergence – its technical development is far from trivial. Our work highlights how a type system featuring union and intersection types is sensitive to the difference between strict and non-strict semantics and also, in the presence of non-determinism, to that between call-by-name and call-by-need. This shows once more how union and intersection types can express very fine properties of programs. Our main technical contribution is the description of sound typing for let bindings – a construct peculiar to most of the formalizations of call-by-need semantics – in the presence of union types. Finally, our work shows how to integrate the \bot type, which is an explicit representation for divergence, in a semantic subtyping system. It can thus also be seen as a first step towards the definition of a type system based on semantic subtyping that performs a non-trivial form of termination analysis.

1.5 Related work

Previous work on semantic subtyping does not discuss non-strict semantics. Castagna and Frisch [9] describe how to add a type constructor lazy(t) to semantic subtyping systems, but this is meant just to have lazily constructed expressions within a call-by-value language.

Many type systems for functional languages – like the simply-typed λ -calculus or Hindley-Milner typing – are sound for both strict and non-strict semantics. However, difficulties similar to ours are found in work on refinement types. Vazou et al. [23] study how to adapt refinement types for Haskell. Their types contain logical predicates as refinements: e.g., the type of positive integers is $\{v\colon \operatorname{Int} \mid v>0\}$. They observe that the standard approach to typechecking in these systems – checking implication between predicates with an SMT solver – is unsound for non-strict semantics. In their system, a type like $\{v\colon \operatorname{Int} \mid \operatorname{false}\}$ is analogous to \emptyset in our system insofar as it is not inhabited by any value. These types can be given to

XX:6 Semantic subtyping for non-strict languages

diverging expressions, and their introduction into the environment causes unsoundness. To avoid this problem, they stratify types, with types divided in diverging and non-diverging ones. This corresponds in a way to our use of a type \bot in types of possibly diverging expressions. As for ours, their type system can track termination to a certain extent. Partial correctness properties can be verified even without precise termination analysis. However, with their kind of analysis (which goes beyond what is expressible with set-theoretic types) there is a significant practical benefit to tracking termination more precisely. Hence, they also study how to check termination of recursive functions.

The notion of a stratification of types to keep track of divergence can also be found in work of a more theoretical strain. For instance, in [15] it is used to model partial functions in constructive type theory. This stratification can be understood as a monad for partiality, as it is treated in [7]. Our type system can also be seen, intuitively, as following this monadic structure. Notably, the rule for applications in a sense lifts the usual rule for application in this partiality monad. Injection in this monad is performed implicitly by subtyping via the judgment $t \leq t \vee \bot$. However, we have not developed this intuition formally.

The fact that a type system with union and intersection types can require changes to account for non-strict semantics is also remarked in work on refinement types. Dunfield and Pfenning [19, p. 8, footnote 3] notice how a union elimination rule cannot be used to eliminate unions in function arguments if arguments are passed by name: this is analogous to the aforementioned difficulties which led to our choice of call-by-need (their system uses a dedicated typing rule for what our system handles by subtyping). Dunfield [18, Section 8.1.5] proposes as future work to adapt a subset of the type system he considers (of refinement types for a call-by-value effectful language) to call-by-name. He notes some of the difficulties and advocates studying call-by-need as a possible way to face them. In our work we show, indeed, that a call-by-need semantics can be used to have the type system handle union and intersection types expressively without requiring complex rules.

1.6 Outline

Our presentation proceeds as follows. In Section 2, we define the types and the subtyping relation which we use in our type system. In Section 3, we define the language we study, its syntax and its operational semantics. In Section 4, we present the type system; we state the result of soundness for it and outline the main lemmas required to prove it; we also complete the discussion about why we chose a call-by-need semantics. In Section 5, we study the relation between the interpretation of types used to define subtyping and the expressions that are definable in the language; we show how we can look for a more precise interpretation. In Section 6 we conclude and point out more directions for future work.

For space reasons, some auxiliary definitions and results, as well as the proofs of the results we state, are omitted and can all be found in the Appendix.

2 Types and subtyping

We begin by describing in more detail the types and the subtyping relation of our system.

In order to define types, we first fix two countable sets: a set \mathcal{C} of language constants (ranged over by c) and a set \mathcal{B} of basic types (ranged over by b). For example, we can take constants to be booleans and integers: $\mathcal{C} = \{\text{true}, \text{false}, 0, 1, -1, \ldots\}$. \mathcal{B} might then contain Bool and Int; however, we also assume that, for every constant c, there is a "singleton" basic type which corresponds to that constant alone (for example, a type for true, which will be a subtype of Bool). We assume that a function $\mathbb{B} : \mathcal{B} \to \mathcal{P}(\mathcal{C})$ assigns to each basic type the

set of constants of that type and that a function $b_{(\cdot)}: \mathcal{C} \to \mathcal{B}$ assigns to each constant c a basic type b_c such that $\mathbb{B}(b_c) = \{c\}$.

▶ Definition 2.1 (Types). The set \mathcal{T} of *types* is the set of terms t coinductively produced by the following grammar

$$t ::= \bot \mid b \mid t \times t \mid t \to t \mid t \vee t \mid \neg t \mid \mathbb{0}$$

and which satisfy two additional constraints: (1) regularity: the term must have a finite number of different sub-terms; (2) contractivity: every infinite branch must contain an infinite number of occurrences of the product or arrow type constructors.

We introduce the abbreviations $t_1 \wedge t_2 \stackrel{\text{def}}{=} \neg (\neg t_1 \vee \neg t_2)$, $t_1 \setminus t_2 \stackrel{\text{def}}{=} t_1 \wedge (\neg t_2)$, and $\mathbb{1} \stackrel{\text{def}}{=} \neg \mathbb{0}$. We refer to b, \times , and \rightarrow as type constructors, and to \vee, \neg, \wedge , and \setminus as type connectives.

The contractivity condition is crucial since it bars out ill-formed types such as $t = t \lor t$ (which does not carry any information about the set denoted by the type) or $t = \neg t$ (which cannot represent any set). It also ensures that the binary relation $\triangleright \subseteq \mathcal{T}^2$ defined by $t_1 \lor t_2 \triangleright t_i$, $\neg t \triangleright t$ is Noetherian (that is, strongly normalizing). This gives an induction principle on \mathcal{T} that we will use without further reference to the relation. The regularity condition is necessary only to ensure the decidability of the subtyping relation.

In the semantic subtyping approach we give an interpretation of types as sets; this interpretation is used to define the subtyping relation in terms of set containment. We want to see a type as the set of the values of the language that have that type. However, this set of values cannot be used directly to define the interpretation, because of a problem of circularity. Indeed, in a higher-order language, values include well-typed λ -abstractions; hence to know which values inhabit a type we need to have already defined the type system (to type λ -abstractions), which depends on the subtyping relation, which in turn depends on the interpretation of types. To break this circularity, types are actually interpreted as subsets of a set \mathcal{D} , an interpretation domain, which is not the set of values, though it corresponds to it intuitively (in [20], a correspondence is also shown formally: we return to this in Section 5). We use the following domain which includes an explicit representation for divergence.

▶ Definition 2.2 (Interpretation domain). The *interpretation domain* \mathcal{D} is the set of finite terms d produced inductively by the following grammar

$$d := \bot \mid c \mid (d, d) \mid \{(d, d_{\Omega}), \dots, (d, d_{\Omega})\}$$

$$d_{\Omega} := d \mid \Omega$$

where c ranges over the set \mathcal{C} of constants and where Ω is such that $\Omega \notin \mathcal{D}$.

The elements of \mathcal{D} correspond, intuitively, to the results of the evaluation of expressions. The element \bot stands for divergence. Expressions can produce as results constants or pairs of results, so we include both in \mathcal{D} . For example, a result can be a pair of a terminating computation returning true and a diverging computation: we represent this by (true, \bot). Finally, in a higher-order language, the result of a computation can be a function. Functions are represented in this model by finite relations of the form $\{(d^1, d^1_\Omega), \ldots, (d^n, d^n_\Omega)\}$, where Ω (which is not in \mathcal{D}) can appear in second components to signify that the functions fails (i.e., evaluation is stuck) on the corresponding input. The restriction to *finite* relations is standard in semantic subtyping [20]; we say more about it in Section 5.

We define the interpretation $\llbracket t \rrbracket$ of a type t so that it satisfies the following equalities, where $\mathcal{D}_{\Omega} = \mathcal{D} \cup \{\Omega\}$ and where \mathcal{P}_{fin} denotes the restriction of the powerset to finite subsets:

$$\begin{bmatrix} \bot \end{bmatrix} = \{\bot\} \qquad \qquad \begin{bmatrix} \llbracket b \rrbracket = \mathbb{B}(b) & \llbracket t_1 \times t_2 \rrbracket = \llbracket t_1 \rrbracket \times \llbracket t_2 \rrbracket \\ \llbracket t_1 \to t_2 \rrbracket = \left\{ R \in \mathcal{P}_{\text{fin}}(\mathcal{D} \times \mathcal{D}_{\Omega}) \mid \forall (d, d') \in R. \ d \in \llbracket t_1 \rrbracket \implies d' \in \llbracket t_2 \rrbracket \right\} \\
 \llbracket t_1 \vee t_2 \rrbracket = \llbracket t_1 \rrbracket \cup \llbracket t_2 \rrbracket \qquad \qquad \llbracket \neg t \rrbracket = \mathcal{D} \setminus \llbracket t \rrbracket \qquad \qquad \llbracket 0 \rrbracket = \varnothing$$

We cannot take the equations above directly as an inductive definition of $\llbracket \cdot \rrbracket$ because types are not defined inductively but coinductively. Therefore we give the following definition, which validates these equalities and which uses the aforementioned induction principle on types and structural induction on \mathcal{D} .

▶ Definition 2.3 (Set-theoretic interpretation of types). We define a binary predicate $(d_{\Omega}:t)$ ("the element d_{Ω} belongs to the type t"), where $d_{\Omega} \in \mathcal{D} \cup \{\Omega\}$ and $t \in \mathcal{T}$, by induction on the pair (d_{Ω},t) ordered lexicographically. The predicate is defined as follows:

```
(\bot:\bot) = \mathsf{true} \\ (c:b) = c \in \mathbb{B}(b) \\ ((d_1,d_2):t_1 \times t_2) = (d_1:t_1) \ \mathsf{and} \ (d_2:t_2) \\ (\{(d^1,d^1_\Omega),\dots,(d^n,d^n_\Omega)\}:t_1 \to t_2) = \forall i \in \{1,\dots,n\}. \ \mathsf{if} \ (d^i:t_1) \ \mathsf{then} \ (d^i_\Omega:t_2) \\ (d:t_1 \vee t_2) = (d:t_1) \ \mathsf{or} \ (d:t_2) \\ (d:\neg t) = \mathsf{not} \ (d:t) \\ (d_\Omega:t) = \mathsf{false} \qquad \qquad \mathsf{otherwise}
```

We define the set-theoretic interpretation $[\![\cdot]\!]: \mathcal{T} \to \mathcal{P}(\mathcal{D})$ as $[\![t]\!] = \{d \in \mathcal{D} \mid (d:t)\}.$

Finally, we define the subtyping preorder and its associated equivalence relation as follows.

▶ Definition 2.4 (Subtyping relation). We define the *subtyping* relation \leq and the *subtyping* equivalence relation \simeq as $t_1 \leq t_2 \iff [t_1] \subseteq [t_2]$ and $t_1 \simeq t_2 \iff (t_1 \leq t_2)$ and $(t_2 \leq t_1)$.

3 Language syntax and semantics

We consider a language based on that studied in [20]: a λ -calculus with recursive explicitly annotated functions, pair constructors and destructors, and a typecase construct. We actually define two languages: a *source language* in which programs will be written and a slightly different *internal language*, on which we define the semantics. The internal language adds a let construct; this is a form of explicit substitution used to model call-by-need semantics in a small-step operational style, following a standard approach [3, 2, 21]. Typecases are also defined slightly differently in the two languages (to simplify the semantics), so we show how to compile source programs to the internal language.

First, we give some auxiliary definitions on types. We introduce the abbreviations: $\langle t \rangle \stackrel{\text{def}}{=} t \vee \bot$; $t_1 \to t_2 \stackrel{\text{def}}{=} \langle t_1 \rangle \to \langle t_2 \rangle$; and $t_1 \otimes t_2 \stackrel{\text{def}}{=} \langle t_1 \rangle \times \langle t_2 \rangle$. These are compact notations for types including \bot . The first, $\langle t \rangle$, is an abbreviated way to write the type of possibly diverging expressions whose result has type t. The latter two are used in type annotations. The intent is that programmers never write \bot explicitly. Rather, they use the \to and \otimes constructors instead of \to and \times so that \bot is introduced implicitly. The \to and \times constructors are never written directly in program. We define the following restricted grammars of types

$$T \coloneqq b \mid T \otimes T \mid T \to T \mid T \vee T \mid \neg T \mid \mathbb{0} \qquad \quad \tau \coloneqq b \mid \tau \otimes \tau \mid \mathbb{0} \to \mathbb{1} \mid \tau \vee \tau \mid \neg \tau \mid \mathbb{0}$$

both of which are interpreted coinductively, with the same restrictions of regularity and contractivity as in the definition of types. The types defined by these grammars will be the only ones which appear in programs: neither includes \perp explicitly.

In particular, functions will be annotated with T types, where the \otimes and \rightarrow forms are used to ensure that every type below a constructor is of the form $t \vee \bot$.

Typecases, instead, will check τ types. The only arrow type that can appear in them is $\mathbb{O} \to \mathbb{1}$, which is the top type of functions (every well-typed function has this type). This

restriction means that typecases will not be able to test the types of functions, but only, at most, whether a value is a function or not. This restriction is not imposed in [20], and actually it could be lifted here without difficulty. We include it because the purpose of typecases in our language is, to some extent, the modelling of pattern matching, which cannot test the type of functions. Restricting typecases on arrow types also facilitates the extension of the system with polymorphism and type inference.

3.1 Source language

The source language expressions are the terms e produced inductively by the grammar

$$\mathbf{e} \coloneqq x \mid c \mid \mu f \colon \mathcal{I}. \, \lambda x. \, \mathbf{e} \mid \mathbf{e} \, \mathbf{e} \mid (\mathbf{e}, \mathbf{e}) \mid \pi_i \, \mathbf{e} \mid (x = \mathbf{e}) \in \tau \, ? \, \mathbf{e} : \mathbf{e}$$

$$\mathcal{I} \coloneqq \bigwedge_{i \in I} T_i' \to T_i \qquad |I| > 0$$

where f and x range over a set \mathcal{X} of expression variables, c over the set \mathcal{C} of constants, i in π_i \mathbf{e} over $\{1,2\}$, and where τ in $(x=\mathbf{e}) \in \tau$? \mathbf{e} : \mathbf{e} is such that $\tau \not\simeq 0$ and $\tau \not\simeq 1$.

Source language expressions include variables, constants, λ -abstractions, applications, pairs constructors (**e**, **e**) and destructors π_1 **e** and π_2 **e**, plus the typecase ($x = \mathbf{e}$) $\in \tau$? **e** : **e**.

A λ -abstraction $\mu f \colon \mathcal{I}. \lambda x. \mathbf{e}$ is a possibly recursive function, with recursion parameter f and argument x, both of which are bound in the body; the function is explicitly annotated with its type \mathcal{I} , which is a finite intersection of types of the form $T' \to T$.

A typecase expression $(x = \mathbf{e}_0) \in \tau$? $\mathbf{e}_1 : \mathbf{e}_2$ has the following intended semantics: \mathbf{e}_0 is evaluated until it can be determined whether it has type τ or not, then the selected branch (\mathbf{e}_1 if the result of \mathbf{e}_0 has type τ , \mathbf{e}_2 if it has type $\neg \tau$: one of the two cases always occurs) is evaluated in an environment where x is bound to the result of \mathbf{e}_0 . Actually, to simplify the presentation, we will give a non-deterministic semantics in which we allow to evaluate \mathbf{e}_0 more than what is needed to ascertain whether it has type τ .

In the syntax definition above we have restricted the types τ in typecases asking both $\tau \not\simeq \mathbb{1}$ and $\tau \not\simeq \mathbb{0}$. A typecase checking the type $\mathbb{1}$ is useless: since all expressions have type $\mathbb{1}$, it immediately reduces to its first branch. Likewise, a typecase checking the type $\mathbb{0}$ reduces directly to the second branch. Therefore, the two cases are uninteresting to consider. We forbid them because this allows us to give a simpler typing rule for typecases. Allowing them is just a matter of adding two (trivial) typing rules specific to these cases, as we show later.

As customary, we consider expressions up to renaming of bound variables. In $\mu f : \mathcal{I}. \lambda x. \mathbf{e}$, f and x are bound in \mathbf{e} . In $(x = \mathbf{e}_0) \in \tau$? $\mathbf{e}_1 : \mathbf{e}_2$, x is bound in \mathbf{e}_1 and \mathbf{e}_2 .

We do not provide mechanisms to define cyclic data structures. For example, we do not have a direct syntactic construct to define the infinitely nested pair $(1,(1,\ldots))$. We can define it by writing a fixpoint operator (which can be typed in our system since types can be recursive) or by defining and applying a recursive function which constructs the pair. A general letrec construct as in [2] might be useful in practice (for efficiency or to provide greater sharing) but we omit it here since we are only concerned with typing.

3.2 Internal language

The internal language expressions are the terms e produced inductively by the grammar

$$e ::= x \mid c \mid \mu f \colon \mathcal{I}. \ \lambda x. \ e \mid e \ e \mid (e,e) \mid \pi_i \ e \mid (x=\varepsilon) \in \tau \ ? \ e \colon e \mid \mathsf{let} \ x = e \ \mathsf{in} \ e$$

$$\varepsilon ::= x \mid c \mid \mu f \colon \mathcal{I}. \ \lambda x. \ e \mid (\varepsilon,\varepsilon)$$

where metavariables and conventions are as in the source language. There are two differences with respect to the source language. One is the introduction of the construct let $x = e_1$ in e_2 , which is a binder used to model call-by-need semantics (in let $x = e_1$ in e_2 , x is bound in

 e_2). The other difference is that typecases cannot check arbitrary expressions, but only expressions of the restricted form given by ε .

A source language expression \mathbf{e} can be compiled to an internal language expression $\lceil \mathbf{e} \rceil$ as follows. Compilation is straightforward for all expressions apart from typecases:

and for typecases it introduces a let binder to ensure that the checked expression is a variable:

$$\lceil (x = \mathbf{e}_0) \in \tau \ ? \ \mathbf{e}_1 : \mathbf{e}_2 \rceil = \mathsf{let} \ y = \lceil \mathbf{e}_0 \rceil \ \mathsf{in} \ (x = y) \in \tau \ ? \ \lceil \mathbf{e}_1 \rceil : \lceil \mathbf{e}_2 \rceil$$

where y is chosen not free in \mathbf{e}_1 and \mathbf{e}_2 . (The other forms for ε appear during reduction.)

3.3 Semantics

We define the operational semantics of the internal language as a small-step reduction relation using call-by-need. The semantics of the source language is then given indirectly through the translation. The choice of call-by-need rather than call-by-name was briefly motivated in the Introduction and will be discussed more extensively in Section 4.

We first define the sets of answers (ranged over by a) and of values (ranged over by v) as the subsets of expressions produced by the following grammars:

$$a := c \mid \mu f : \mathcal{I}. \lambda x. e \mid (e, e) \mid \text{let } x = e \text{ in } a$$
 $v := c \mid \mu f : \mathcal{I}. \lambda x. e$

Answers are the results of evaluation. They correspond to expressions which are fully evaluated up to their top-level constructor (constant, function, or pair) but which may include arbitrary expressions below that constructor (so we have (e, e) rather than (a, a)). Since they also include let bindings, they represent closures in which variables can be bound to arbitrary expressions. Values are a subset of answers treated specially in a reduction rule.

The semantics uses evaluation contexts to direct the order of evaluation. A context C is an expression with a hole (written []) in it. We write C[e] for the expression obtained by replacing the hole in C with e. We write C[e] for C[e] when the free variables of e are not bound by C: for example, let $x = e_1$ in x is of the form C[x] – with $C \equiv (\text{let } x = e_1 \text{ in } [])$ – but not of the form C[x]; conversely, let $x = e_1$ in y is both of the form C[y] and C[y].

Evaluation contexts E are the subset of contexts generated by the following grammar:

$$E ::= [\] \mid E \ e \mid \pi_i \ E \mid (x = F) \in \tau \ ? \ e : e \mid \mathsf{let} \ x = e \ \mathsf{in} \ E \mid \mathsf{let} \ x = E \ \mathsf{in} \ E \sqsubseteq \Sigma \rfloor$$

$$F ::= [\] \mid (F, \varepsilon) \mid (\varepsilon, F)$$

Evaluation contexts allow reduction to occur on the left of applications and below projections, but not on the right of applications and below pairs. For typecases alone, the contexts allow reduction also below pairs, since this reduction might be necessary to be able to determine whether the expression has type τ or not. This is analogous to the behaviour of pattern matching in lazy languages, which can force evaluation below constructors. The contexts for let are from standard presentations of call-by-need [2, 21]. They allow reduction of the body of the let, while they only allow reductions of the bound expression when it is required to continue evaluating the body: this is enforced by requiring the body to have the form E[x].

Figure 1 presents the reduction rules. They rely on the typeof function, which assigns types to expressions of the form ε . It is defined as follows:

$$\begin{array}{ll} \operatorname{typeof}(x) = \mathbb{1} & \operatorname{typeof}(\mu f \colon \mathcal{I}. \, \lambda x. \, e) = \mathbb{0} \to \mathbb{1} \\ \operatorname{typeof}(c) = b_c & \operatorname{typeof}(\varepsilon_1, \varepsilon_2)) = \operatorname{typeof}(\varepsilon_1) \times \operatorname{typeof}(\varepsilon_2) \end{array}$$

[APPL] is the standard application rule for call-by-need: the application $(\mu f: \mathcal{I}. \lambda x. e) e'$ reduces to e prefixed by two let bindings that bind the recursion variable f to the function

```
(\mu f\colon \mathcal{I}.\,\lambda x.\,e)\;e'\;\leadsto\; \mathsf{let}\; f=(\mu f\colon \mathcal{I}.\,\lambda x.\,e)\;\mathsf{in}\;\mathsf{let}\; x=e'\;\mathsf{in}\; e
   [Appl]
                                                   (\text{let } x = e \text{ in } a) e' \rightsquigarrow \text{let } x = e \text{ in } a e'
[APPLL]
   [Proj]
                                                                   \pi_i (e_1, e_2) \rightsquigarrow e_i
                                                   \pi_i (\text{let } x = e \text{ in } a) \iff \text{let } x = e \text{ in } \pi_i a
[ProjL]
                                                     \mathsf{let}\ x = v\ \mathsf{in}\ E[x] \leadsto (E[x])[v/x]
  [LetV]
  [LetP]
                                        \mathsf{let} \ x = (e_1, e_2) \ \mathsf{in} \ E_1^{ \lceil x \rceil} \leadsto \ \mathsf{let} \ x_1 = e_1 \ \mathsf{in} \ \mathsf{let} \ x_2 = e_2 \ \mathsf{in} \ (E_1^{ \lceil x \rceil})[(x_1, x_2)/x]
                       let x = (\text{let } y = e \text{ in } a) \text{ in } E_1^T x_1^T \rightsquigarrow \text{let } y = e \text{ in let } x = a \text{ in } E_1^T x_1^T
   [Letl]
                                            (x = \varepsilon) \in \tau ? e_1 : e_2 \rightsquigarrow \text{let } x = \varepsilon \text{ in } e_1
 [CASE1]
                                                                                                                                                                if typeof(\varepsilon) \leq \tau
                                            (x = \varepsilon) \in \tau ? e_1 : e_2 \rightsquigarrow \text{let } x = \varepsilon \text{ in } e_2
                                                                                                                                                              if typeof(\varepsilon) \leq \neg \tau
 [Case2]
                                                                                                                                                               if e \leadsto e'
                                                                              E[e] \rightsquigarrow E[e']
     [CTX]
```

Figure 1 Operational semantics.

itself and the parameter x to the argument e'. [APPLL] instead deals with applications with a let expression in function position: it moves the application below the let. The rule is necessary to prevent loss of sharing: substituting the binding of x to e in a would duplicate e. Symmetrically, there are two rules for pair projections, [PROJ] and [PROJL].

There are three rules for let expressions. They rewrite expressions of the form let x = a in E[x]: that is, let bindings where the bound expression is an answer and the body is an expression whose evaluation requires the evaluation of x. If a is a value v, [LetV] applies and the expression is reduced by just replacing v for x in the body. If a is a pair, [LetP] applies: the occurrences of x in the body are replaced with a pair of variables (x_1, x_2) and each x_i is bound to e_i by new let bindings (replacing x directly by (e_1, e_2) would duplicate expressions). Finally, the [LetL] rule just moves a let binding out of another.

There are two rules for typecases, by which a typecase construct $(x = \varepsilon) \in \tau$? $e_1 : e_2$ can be reduced to either branch, introducing a new binding of x to ε . The rules apply only if either of $\mathsf{typeof}(\varepsilon) \leq \tau$ or $\mathsf{typeof}(\varepsilon) \leq \neg \tau$ holds. If neither holds, then the two rules do not apply, but the [CTX] rule can be used to continue the evaluation of ε .

Comparison to other presentations of call-by-need. These reduction rules mirror those from standard presentations of call-by-need [3, 2, 21]. A difference is that, in [LetV] or [LetP], we replace all occurrences of x in E[x] at once, whereas in the cited presentations only the occurrence in the hole is replaced: for example, in [LetV] they reduce to E[v] instead of (E[x])[v/x]. Our [LetV] rule is mentioned as a variant in [21, p. 38]. We use it because it simplifies the proof of subject reduction while maintaining an equivalent semantics.

Non-determinism in the rules. The semantics is not deterministic. There are two sources of non-determinism, both related to typecases. One is that the contexts F include both (F, ε) and (ε, F) and thereby impose no constraint on the order with which pairs are examined.

The second source of non-determinism is that the contexts for typecases allow us to reduce the bindings of variables in the checked expression even when we can already apply [CASE1] or [CASE2]. For example, take let x=e in $(y=(3,x))\in (\operatorname{Int}\otimes 1)$? $e_1:e_2$. It can be immediately reduced to let x=e in let y=(3,x) in e_1 by applying [CTX] and [CASE1], because typeof((3,x)) = $b_3 \times 1 \leq \operatorname{Int}\otimes 1$. However, we can also use [CTX] to reduce e, if it is reducible: we do so by writing the expression as let x=e in E[x], where E is $(y=(3,[])) \in (\operatorname{Int}\otimes 1)$? $e_1:e_2$. To model a lazy implementation more faithfully, we should

$$[\text{S-Subsum}] \ \frac{\Gamma \vdash \mathbf{e} \colon t'}{\Gamma \vdash \mathbf{e} \colon t} \ t' \leq t \qquad [\text{S-Var}] \ \frac{\Gamma \vdash x \colon t}{\Gamma \vdash x \colon t} \ \Gamma(x) = t \qquad [\text{S-Const}] \ \frac{\Gamma \vdash c \colon b_c}{\Gamma \vdash c \colon b_c}$$

$$\frac{[\text{S-Appl}]}{\Gamma \vdash (\mu f \colon \mathcal{I}, \lambda x. \, \mathbf{e}) \colon \mathcal{I}} \ \mathcal{I} = \bigwedge_{i \in I} T_i' \to T_i \qquad \frac{[\text{S-Appl}]}{\Gamma \vdash \mathbf{e}_1 \colon \langle t' \to t \rangle} \ \frac{\Gamma \vdash \mathbf{e}_2 \colon t'}{\Gamma \vdash \mathbf{e}_1 \mathbf{e}_2 \colon \langle t \rangle}$$

$$[\text{S-Pair}] \ \frac{\Gamma \vdash \mathbf{e}_1 \colon t_1 \quad \Gamma \vdash \mathbf{e}_2 \colon t_2}{\Gamma \vdash (\mathbf{e}_1, \mathbf{e}_2) \colon t_1 \times t_2} \qquad [\text{S-Proj}] \ \frac{\Gamma \vdash \mathbf{e} \colon \langle t_1 \times t_2 \rangle}{\Gamma \vdash \pi_i \, \mathbf{e} \colon \langle t_i \rangle}$$

$$[\text{S-Case}] \ \frac{\Gamma \vdash \mathbf{e}_0 \colon \langle t' \rangle \quad \left(\text{if } t' \not \leq \neg \tau \text{ then } \Gamma, x \colon (t' \land \tau) \vdash \mathbf{e}_1 \colon t\right) \quad \left(\text{if } t' \not \leq \tau \text{ then } \Gamma, x \colon (t' \land \tau) \vdash \mathbf{e}_2 \colon t\right)}{\Gamma \vdash \left((x = \mathbf{e}_0) \in \tau ? \, \mathbf{e}_1 \colon \mathbf{e}_2\right) \colon \langle t \rangle}$$

Figure 2 Typing rules for the source language.

forbid this reduction and state that $(x = F) \in \tau$? e : e is a context only if it cannot be reduced by [CASE1] or [CASE2].

In both cases, we have chosen a non-deterministic semantics because it is less restrictive: as a consequence, the soundness result will also hold for semantics which fix an order.

4 Type system

We define two typing relations for the source language and the internal language.

A type environment Γ is a finite mapping of type variables to types. We write \varnothing for the empty environment. We say that a type environment Γ is well-formed if, for all $(x:t) \in \Gamma$, we have $t \not\simeq \mathbb{O}$. Since we want to ensure that the empty type is never derivable, we will only consider well-formed type environments in the soundness proof.

4.1 Type system for the source language

Figure 2 presents the typing rules for source language. The subsumption rule [S-Subsum] is used to apply subtyping. Notably, it allows expressions with surely converging types (like a pair with type Int × Bool) to be used where diverging types are expected: $t \leq \langle t \rangle$ holds for every t (since $\llbracket t \rrbracket \subseteq \llbracket t \rrbracket \cup \{\bot\} = \llbracket t \vee \bot \rrbracket = \llbracket \langle t \rangle \rrbracket$). The rules [S-VAR] and [S-CONST] for variables and constants are standard. The [S-ABSTR] rule for functions is also straightforward. Function interfaces have the form $\bigwedge_{i \in I} T_i' \to T_i$, that is, $\bigwedge_{i \in I} \langle T_i' \rangle \to \langle T_i \rangle$ (expanding the definition of \to). To type a function $\mu f : \mathcal{I} . \lambda x$. **e**, we check that it has all the arrow types in \mathcal{I} . Namely, for every arrow $T_i' \to T_i$ (i.e., $\langle T_i' \rangle \to \langle T_i \rangle$), we assume that x has type $\langle T_i' \rangle$ and that the recursion variable f has type \mathcal{I} , and we check that the body has type $\langle T_i \rangle$.

The [S-APPL] rule is the first one that deals with \bot in a non-trivial way. In call-by-value semantic subtyping systems, to type an application \mathbf{e}_1 \mathbf{e}_2 with a type t, the standard modus ponens rule (e.g., the one from the simply-typed λ -calculus) is used: \mathbf{e}_1 must have type $t' \to t$ and \mathbf{e}_2 must have type t'. Here, instead, we allow the function to have the type $\langle t' \to t \rangle$ (i.e., $(t' \to t) \lor \bot$) to allow the application also when \mathbf{e}_1 might diverge. We use $\langle t \rangle$ as the type of the whole application, signifying that it might diverge. As anticipated, we do not try to predict whether applications will converge. The rule [S-PAIR] for pairs is standard; [S-PROJ] handles \bot as in applications.

[S-CASE] is the most complex one, but it corresponds closely to that of [20]. To type

$$[Subsum] \frac{\Gamma \vdash e : t'}{\Gamma \vdash e : t} \ t' \leq t \qquad [Var] \frac{\Gamma \vdash x : t}{\Gamma \vdash x : t} \ \Gamma(x) = t \qquad [Const] \frac{\Gamma \vdash c : b_c}{\Gamma \vdash c : b_c}$$

$$[Abstr] \frac{\forall i \in I. \quad \Gamma, f : \mathcal{I}, x : \langle T_i' \rangle \vdash e : \langle T_i \rangle}{\Gamma \vdash (\mu f : \mathcal{I}. \lambda x. e) : \mathcal{I} \land t} \qquad \frac{\mathcal{I} = \bigwedge_{i \in I} T_i' \rightarrow T_i}{t = \bigwedge_{j \in J} \neg (t_j' \rightarrow t_j)} \qquad \frac{\Gamma \vdash e_1 : \langle t' \rightarrow t \rangle \qquad \Gamma \vdash e_2 : t'}{\Gamma \vdash e_1 e_2 : \langle t \rangle}$$

$$[Pair] \frac{\Gamma \vdash e_1 : t_1 \qquad \Gamma \vdash e_2 : t_2}{\Gamma \vdash (e_1, e_2) : t_1 \times t_2} \qquad [Proj] \frac{\Gamma \vdash e : \langle t_1 \times t_2 \rangle}{\Gamma \vdash \pi_i e : \langle t_i \rangle}$$

$$[Case] \frac{\Gamma \vdash e : \langle t' \rangle \qquad (\text{if } t' \nleq \neg \tau \text{ then } \Gamma, x : (t' \land \tau) \vdash e_1 : t) \qquad (\text{if } t' \nleq \tau \text{ then } \Gamma, x : (t' \land \tau) \vdash e_2 : t)}{\Gamma \vdash ((x = \varepsilon) \in \tau ? e_1 : e_2) : \langle t \rangle}$$

$$[Let] \frac{\Gamma \vdash e_1 : \bigvee_{i \in I} t_i \qquad \forall i \in I. \ \Gamma, x : t_i \vdash e_2 : t}{\Gamma \vdash \text{let } x = e_1 \text{ in } e_2 : t}$$

Figure 3 Typing rules for the internal language.

 $(x = \mathbf{e}_0) \in \tau$? $\mathbf{e}_1 : \mathbf{e}_2$ we first type \mathbf{e}_0 with some type $\langle t' \rangle$. Then, we type the two branches \mathbf{e}_1 and \mathbf{e}_2 . We do not always have to type both (note the conditions "if ... then") but for now assume that we do. While typing either branch, we extend the environment with a binding for x. For the first branch, the type for x is $t' \wedge \tau$, a subtype of $\langle t' \rangle$: this type is sound because the first branch is only evaluated if \mathbf{e}_0 evaluates to an answer (meaning we can remove the union with \bot in $\langle t' \rangle$) and if this answer has type τ . Conversely, for the second branch, x is given type $t' \setminus \tau$, that is, $t' \wedge \neg \tau$. Finally, if the branches have type t, the whole typecase is given type $t' \setminus \tau$ since its evaluation may diverge in case \mathbf{e}_0 diverges.

Now let us consider the conditions "if ... then". We need to type the first branch only when $t' \not\leq \neg \tau$; if, conversely, $t' \leq \neg \tau$, we know that the first branch can never be selected (an expression of type $\neg \tau$ cannot reduce to a result of type τ) and thus we don't need to type it. The reasoning for the second branch is analogous. The two conditions are pivotal to type overloaded functions defined by typecases. For example, a negation function implemented as $\mu f: \mathcal{I}. \lambda x. \ (y=x) \in b_{\mathsf{true}}$? false: true, with $\mathcal{I} = (b_{\mathsf{true}} \to b_{\mathsf{false}}) \land (b_{\mathsf{false}} \to b_{\mathsf{true}})$, could not be typed without these conditions.

In the syntax we have restricted the type τ in typecases requiring $\tau \not\simeq \mathbb{1}$ and $\tau \not\simeq 0$. Typecases where these conditions do not hold are uninteresting, since they do not actually check anything. The rule [S-CASE] would be unsound for them because these typecases can reduce to one branch even if \mathbf{e}_0 is a diverging expression that does not evaluate to an answer. For instance, if $\bar{\mathbf{e}}$ has type \bot (that is, $\langle 0 \rangle$), then $(x = \bar{\mathbf{e}}) \in \operatorname{Int} ? 1 : 2$ could be given any type, including unsound ones like $\langle \operatorname{Bool} \rangle$. To allow these typecases, we could add the side condition " $\tau \not\simeq 1$ and $\tau \not\simeq 0$ " to [S-CASE] and give two specialized rules as follows:

$$\frac{\Gamma \vdash \mathbf{e}_0 \colon t' \qquad \Gamma, x \colon t' \vdash \mathbf{e}_1 \colon t}{\Gamma \vdash \left((x = \mathbf{e}_0) \in \tau ? \mathbf{e}_1 \colon \mathbf{e}_2 \right) \colon \langle t \rangle} \ \tau \simeq \mathbb{1} \qquad \frac{\Gamma \vdash \mathbf{e}_0 \colon t' \qquad \Gamma, x \colon t' \vdash \mathbf{e}_2 \colon t}{\Gamma \vdash \left((x = \mathbf{e}_0) \in \tau ? \mathbf{e}_1 \colon \mathbf{e}_2 \right) \colon \langle t \rangle} \ \tau \simeq \mathbb{0}$$

4.2 Type system for the internal language

Figure 3 presents the typing rules for the internal language. These include a new rule for let expressions and a modified rule for λ -abstractions; the other rules are the same as those for

the source language (except for the different syntax of typecases).

The [S-ABSTR] rule for the source language derived the type \mathcal{I} for $\mu f \colon \mathcal{I}.\lambda x.\,\mathbf{e}$. The rule for the internal language, instead, allows us to derive a subtype of \mathcal{I} of the form $\mathcal{I} \wedge t$, where t is an intersection of negations of arrow types. The arrows in t can be chosen freely providing that the intersection $\mathcal{I} \wedge t$ remains non-empty. This rule (directly taken from [20]) can look surprising. For example, it allows us to type $\mu f \colon (\operatorname{Int} \to \operatorname{Int}).\lambda x.\,x$ as $(\operatorname{Int} \to \operatorname{Int}) \wedge \neg(\operatorname{Bool} \to \operatorname{Bool})$ even though, disregarding the interface, the function does map booleans to booleans. But the language is explicitly typed, and thus we can't ignore interfaces (indeed, the function does not have type $\operatorname{Bool} \to \operatorname{Bool}$). The purpose of the rule is to ensure that, given any function and any type t, either the function has type t or it has type t. This property matches the intuitive view of types as sets of values that underpins semantic subtyping. While in our system we do not really interpret types as sets of values (since t is non-empty and yet uninhabited by values), the property is still needed to prove subject reduction. A consequence of this property is that a value (i.e., a constant or a t-abstraction) of type $t_1 \vee t_2$ has always either type t_1 or type t_2 . (In the case of constants, this is obtained directly by reasoning on subtyping, so we don't need a rule to assign negation types to them.)

The [LET] rule combines a standard rule for (monomorphic) binders with a union disjunction rule: it lets us decompose the type of e_1 as a union and type the body of the let once for each summand in the union. The purpose of this rule was hinted at in the Introduction and will be discussed again in Section 4.3, where we show that this rule – combined with the property on union types above – is central to this work: it is the key technical feature that ensures the soundness of the system (see in particular Lemma 4.9 later on). For the time being, just note that the type of e_1 can be decomposed in arbitrarily complex ways by applying subsumption. For example, if e_1 is a pair of type (Int \vee Bool) \times (Int \vee Bool), by applying [Subsum] we can type it as (Int \times Int) \vee (Int \times Bool) \vee (Bool \times Int) \vee (Bool \times Bool) and then type e_2 once for each of the four summands.

The [ABSTR] and [LET] rules introduce non-determinism in the choice of the negations to introduce and of how to decompose types as unions. This would not complicate a practical implementation, since a typechecker would only need to check the source language.

4.3 Properties of the type system

Full results about the type system, including proofs, are available in the Appendix. Here we report the main results and describe the technical difficulties we met to obtain them.

First, we can easily show by induction that compilation from the source language to the internal language preserves typing.

▶ Proposition 4.1. If $\Gamma \vdash \mathbf{e} : t$, then $\Gamma \vdash \lceil \mathbf{e} \rceil : t$.

We show the soundness property for our type system ("well-typed programs do not go wrong"), following the well-known syntactic approach of Wright and Felleisen [24], by proving the two properties of *progress* and *subject reduction* for the internal language.

- ▶ Theorem 4.2 (Progress). Let Γ be a well-formed type environment. Let e be an expression that is well-typed in Γ (that is, $\Gamma \vdash e$: t holds for some t). Then e is an answer, or e is of the form $E[\Gamma]$, or $\exists e'$. $e \leadsto e'$.
- ▶ Theorem 4.3 (Subject reduction). Let Γ be a well-formed type environment. If $\Gamma \vdash e : t$ and $e \rightsquigarrow e'$, then $\Gamma \vdash e' : t$.

The statement of progress is adapted to call-by-need: it applies also to expressions that are typed in a non-empty Γ and it allows a well-typed expression to have the form E[x].

As a corollary of these results, we obtain the following statement for soundness.

▶ Corollary 4.4 (Type soundness). Let e be a well-typed, closed expression (that is, $\varnothing \vdash e$: t holds for some t). If $e \leadsto^* e'$ and e' cannot reduce, then e' is an answer and $\varnothing \vdash e'$: t.

The soundness result for the internal language implies soundness for the source language.

▶ Corollary 4.5 (Type soundness for the source language). Let **e** be a well-typed, closed source language expression (that is, $\varnothing \vdash \mathbf{e} : t$ holds for some t). If $\lceil \mathbf{e} \rceil \leadsto^* e'$ and e' cannot reduce, then e' is an answer and $\varnothing \vdash e' : t$.

We summarize here some of the crucial properties required to derive the results above. We also resume the discussion of the motivations behind our choice of call-by-need.

We introduced the \perp type for diverging expressions because assigning the type \mathbb{O} to any expression causes unsoundness. We must hence ensure that no expression can be assigned the type \mathbb{O} . In well-formed type environments, we can prove this easily by induction.

▶ Lemma 4.6. Let Γ be a well-formed type environment. If $\Gamma \vdash e: t$, then $t \not\simeq \emptyset$.

Call-by-name and call-by-need. In the Introduction, we have given two reasons for our choice of call-by-need rather than call-by-name. One is that the system is only sound for call-by-name if we make assumptions on the semantics that might not hold in an extended language: for example, introducing an expression that can reduce non-deterministically either to an integer or to a boolean would break soundness. The other reason is that, even when these assumptions hold (and when presumably call-by-name and call-by-need are observationally equivalent), call-by-need is better suited to the soundness proof.

Let us review the example from the Introduction. Consider the function $\mu f: \mathcal{I}. \lambda x. (x, x)$ in the source language, where $\mathcal{I} = (\mathsf{Int} \to \mathsf{Int} \otimes \mathsf{Int}) \wedge (\mathsf{Bool} \to \mathsf{Bool} \otimes \mathsf{Bool})$. It is well-typed with type \mathcal{I} . By subsumption, it also has the type $(\mathsf{Int} \vee \mathsf{Bool}) \to (\mathsf{Int} \otimes \mathsf{Int}) \vee (\mathsf{Bool} \otimes \mathsf{Bool})$, which is a supertype of \mathcal{I} : in general we have $(t'_1 \to t_1) \wedge (t'_2 \to t_2) \leq (t'_1 \vee t'_2) \to (t_1 \vee t_2)$ and therefore $(t'_1 \to t_1) \wedge (t'_2 \to t_2) \leq (t'_1 \vee t'_2) \to (t_1 \vee t_2)$.

Therefore, if $\bar{\mathbf{e}}$ has type $\operatorname{Int} \vee \operatorname{Bool} \vee \bot$, the application $(\mu f : \mathcal{I}. \lambda x. (x, x)) \bar{\mathbf{e}}$ is well-typed with type $(\operatorname{Int} \otimes \operatorname{Int}) \vee (\operatorname{Bool} \otimes \operatorname{Bool}) \vee \bot$. Assume that $\bar{\mathbf{e}}$ can reduce either to an integer or to a boolean: for instance, assume that both $\bar{\mathbf{e}} \rightsquigarrow 3$ and $\bar{\mathbf{e}} \rightsquigarrow \text{true}$ can occur.

With call-by-name, $(\mu f : \mathcal{I}. \lambda x. (x, x)) \bar{\mathbf{e}}$ reduces to $(\bar{\mathbf{e}}, \bar{\mathbf{e}})$; then, the two occurrences of $\bar{\mathbf{e}}$ reduce independently. It is intuitively unsound to type it as $(\operatorname{Int} \otimes \operatorname{Int}) \vee (\operatorname{Bool} \otimes \operatorname{Bool}) \vee \bot$: there is no guarantee that the two components of the pair will be of the same type once they are reduced. We can find terms that break subject reduction. Assume for example that there exists a boolean "and" operation; then this typecase is well-typed (as $\langle \operatorname{Bool} \rangle$) but unsafe:

```
(y = (\mu f : \mathcal{I}. \lambda x. (x, x)) \bar{\mathbf{e}}) \in (\mathsf{Int} \otimes \mathsf{Int}) ? \mathsf{true} : (\pi_1 \ y \ \mathsf{and} \ \pi_2 \ y) .
```

Since the application has type $\langle (\operatorname{Int} \otimes \operatorname{Int}) \vee (\operatorname{Bool} \otimes \operatorname{Bool}) \rangle$, to type the second branch of the typecase we can assume that y has the type $((\operatorname{Int} \otimes \operatorname{Int}) \vee (\operatorname{Bool} \otimes \operatorname{Bool})) \setminus (\operatorname{Int} \otimes \operatorname{Int})$, which is a subtype of $\operatorname{Bool} \otimes \operatorname{Bool}$ (it is actually equivalent to $(\operatorname{Bool} \otimes \operatorname{Bool}) \setminus (\bot \times \bot)$). Therefore, both $\pi_1 y$ and $\pi_2 y$ have type $\langle \operatorname{Bool} \rangle$. We deduce then that $(\pi_1 y \text{ and } \pi_2 y)$ has type $\langle \operatorname{Bool} \rangle$ as well (we assume that "and" is defined so as to handle arguments of type \bot correctly).

A possible reduction in a call-by-name semantics would be the following:

```
(y = (\mu f \colon \mathcal{I}. \lambda x. (x, x)) \; \bar{\mathbf{e}}) \in (\mathsf{Int} \otimes \mathsf{Int}) \; ? \; \mathsf{true} : (\pi_1 \; y \; \mathsf{and} \; \pi_2 \; y) \rightsquigarrow (y = (\bar{\mathbf{e}}, \bar{\mathbf{e}})) \in (\mathsf{Int} \otimes \mathsf{Int}) \; ? \; \mathsf{true} : (\pi_1 \; y \; \mathsf{and} \; \pi_2 \; y)
```

(the typecase must force the evaluation of $(\bar{\mathbf{e}}, \bar{\mathbf{e}})$ to know which branch should be selected)

```
\rightsquigarrow^* (y = (\mathsf{true}, \bar{\mathbf{e}})) \in (\mathsf{Int} \otimes \mathsf{Int}) ? \mathsf{true} : (\pi_1 \ y \ \mathsf{and} \ \pi_2 \ y)
```

(now we know that the first branch is impossible, so the second is chosen)

```
\rightsquigarrow \pi_1 \ (\mathsf{true}, \bar{\mathbf{e}}) \ \mathsf{and} \ \pi_2 \ (\mathsf{true}, \bar{\mathbf{e}}) \ \leadsto \ \mathsf{true} \ \mathsf{and} \ \bar{\mathbf{e}} \ \leadsto \ \bar{\mathbf{e}} \ \leadsto \ 3
```

The integer 3 is not a Bool: this disproves subject reduction for call-by-name if the language contains expressions like $\bar{\mathbf{e}}$. No such expressions exist in our current language, but they could be introduced if we extended it with non-deterministic constructs like $\operatorname{rnd}(t)$ from [20].

Since we use a call-by-need semantics, instead, expressions such as $\bar{\mathbf{e}}$ do not pose problems for soundness. With call-by-need, $(\mu f : \mathcal{I}. \lambda x. (x, x)) \bar{\mathbf{e}}$ reduces to let $f = \mu f : \mathcal{I}. \lambda x. (x, x)$ in let $x = \bar{\mathbf{e}}$ in (x, x). The occurrences of x in the pair are only substituted when $\bar{\mathbf{e}}$ has been reduced to an answer, so they cannot reduce independently.

To ensure subject reduction, we allow the rule for let bindings to split unions in the type of the bound term. This means that the following derivation is allowed.

```
\frac{\Gamma \vdash \bar{\mathbf{e}} \colon \mathsf{Int} \lor \mathsf{Bool} \qquad \Gamma, x \colon \mathsf{Int} \vdash (x, x) \colon \mathsf{Int} \otimes \mathsf{Int} \qquad \Gamma, x \colon \mathsf{Bool} \vdash (x, x) \colon \mathsf{Bool} \otimes \mathsf{Bool}}{\Gamma \vdash \mathsf{let} \ x = \bar{\mathbf{e}} \ \mathsf{in} \ (x, x) \colon (\mathsf{Int} \otimes \mathsf{Int}) \lor (\mathsf{Bool} \otimes \mathsf{Bool})}
```

Proving subject reduction: main lemmas. While the typing rule for let bindings is simple to describe, proving subject reduction for the reduction rules [LetV] and [LetP] (those that actually perform substitutions) is challenging. For the reduction let x = v in $E[x] \rightsquigarrow (E[x])[v/x]$, we show the following results.

- ▶ Lemma 4.7. Let v be a value that is well-typed in Γ (i.e., $\Gamma \vdash v : t'$ holds for some t'). Then, for every type t, we have either $\Gamma \vdash v : t$ or $\Gamma \vdash v : \neg t$.
- ▶ Corollary 4.8. If $\Gamma \vdash v : \bigvee_{i \in I} t_i$, then there exists an $i_0 \in I$ such that $\Gamma \vdash v : t_{i_0}$.

Consider for example the reduction let x = v in $(x, x) \leadsto (v, v)$. If v has type $\mathsf{Int} \lor \mathsf{Bool}$, then $\mathsf{let} x = v$ in (x, x) has type $(\mathsf{Int} \otimes \mathsf{Int}) \lor (\mathsf{Bool} \otimes \mathsf{Bool})$ as in the derivation above. Without this corollary, for (v, v) we could only derive the type $(\mathsf{Int} \lor \mathsf{Bool}) \times (\mathsf{Int} \lor \mathsf{Bool})$, which is not a subtype of the type deduced for the redex. Applying the corollary, we deduce that v has either type $\mathsf{Int} \lor \mathsf{Bool}$; in both cases (v, v) can be given the type $(\mathsf{Int} \otimes \mathsf{Int}) \lor (\mathsf{Bool} \otimes \mathsf{Bool})$.

These results are also needed in semantic subtyping for strict languages to prove subject reduction for applications. To ensure them, following [20], we have added in the type system for the internal language the possibility of typing functions with negations of arrow types.

The reduction let $x=(e_1,e_2)$ in $E[x] \rightsquigarrow \text{let } x_1=e_1$ in let $x_2=e_2$ in $(E[x])[(x_1,x_2)/x]$, instead, is dealt with by the following lemma.

▶ Lemma 4.9. If $\Gamma \vdash (e_1, e_2)$: $\bigvee_{i \in I} t_i$, then there exist two types $\bigvee_{j \in J} t_j$ and $\bigvee_{k \in K} t_k$ such that $\Gamma \vdash e_1$: $\bigvee_{j \in J} t_j$, $\Gamma \vdash e_2$: $\bigvee_{k \in K} t_k$, and $\forall j \in J$. $\forall k \in K$. $\exists i \in I$. $t_j \times t_k \leq t_i$.

This is the result we need for the proof: let $x = (e_1, e_2)$ in E[x] is typed by assigning a union type to (e_1, e_2) and then typing E[x] once for every t_i in the union, while the reduct let $x_1 = e_1$ in let $x_2 = e_2$ in $(E[x])[(x_1,x_2)/x]$ must be typed by typing e_1 and e_2 with two union types and then typing the substituted expression with every product $t_j \times t_k$. Showing that each $t_j \times t_k$ is a subtype of a t_i ensures that the substituted expression is well-typed. The proof consists in recognizing that the union $\bigvee_{i \in I} t_i$ must be a decomposition into a union of some type $t_1 \times t_2$ and that therefore t_1 and t_2 can be decomposed separately into two unions.

All these results rely on the distinction between types that contain \bot and those that do not: they would not hold if we assumed that every type implicitly contains \bot .

Despite some technical difficulties, call-by-need seems quite suited to the soundness proof. Hence, it would probably be best to use it for the proof even if we assumed explicitly that the language does not include problematic expressions like $\mathsf{rnd}(t)$. Soundness would then also hold for a call-by-name semantics that it is observationally equivalent to call-by-need.

5 A discussion on the interpretation of types

We have shown in the previous sections that a set-theoretic interpretation of types, adapted to take into account divergence (Definition 2.3), can be the basis for designing a sound type system for languages with lazy evaluation. In this section, we analyze the relation between such interpretation and the expressions that are actually definable in the language.

Let us first recap some notions from [20]. The initial intuition which guides semantic subtyping is to see a type as the set of values of that type in the language we consider: for example, to see $\operatorname{Int} \to \operatorname{Bool}$ as the set of λ -abstractions of type $\operatorname{Int} \to \operatorname{Bool}$. However, we cannot directly define the interpretation of a type t as the set $\{v \mid \varnothing \vdash v \colon t\}$, because the typing relation $\varnothing \vdash v \colon t$ depends on the definition of subtyping, which depends in turn on the interpretation of types. Frisch, Castagna and Benzaken [20] avoid this circularity by giving an interpretation $\llbracket \cdot \rrbracket$ of types as subsets of an interpretation domain where finite relations replace λ -abstractions.

This interpretation (like ours except that there is no \perp) is used to define subtyping and the typing relation. Then, the following result is shown:

$$\forall t_1, t_2. \ \llbracket t_1 \rrbracket \subseteq \llbracket t_2 \rrbracket \iff \llbracket t_1 \rrbracket_{\mathcal{V}} \subseteq \llbracket t_2 \rrbracket_{\mathcal{V}} \qquad \text{where } \llbracket t \rrbracket_{\mathcal{V}} \stackrel{\text{def}}{=} \{ v \mid \varnothing \vdash v \colon t \}$$

This result states that a type t_1 is a subtype of a type t_2 ($t_1 \leq t_2$, which is defined as $[\![t_1]\!] \subseteq [\![t_2]\!]$) if and only if every value v that can be assigned the type t_1 can also be assigned the type t_2 . Showing the result above implies that, once the type system is defined, we can indeed reason on subtyping by reasoning on inclusion between sets of values.¹

This result is useful in practice, since, when typechecking fails because a subtyping judgment $t_1 \leq t_2$ does not hold, we know that there exists a value v such that $\varnothing \vdash v \colon t_1$ holds while $\varnothing \vdash v \colon t_2$ does not. This value v can be shown as a witness to the unsoundness of the program while reporting the error. Moreover, at a more foundational level, the result nicely formalizes the intuition that types statically approximate computations, in the sense that a type t corresponds to the set of all possible values of expressions of type t.

In the following we discuss how an analogous result could hold with a non-strict semantics. First of all, clearly the correspondence cannot be between interpretations of types and sets of values as in [20], since then we would identify \bot with 0. Hence we should consider, rather than values, sets of "results" of some kind, including (a representation of) divergence.

However, whichever notion of result we consider, it is hard to define an interpretation domain of types such that the desired correspondence holds, that is, such that a type t corresponds to the set of all possible results of expressions of type t. As the reader can expect, the key challenge is to provide an interpretation where an arrow type $t_1 \to t_2$ corresponds, as it seems sensible, to the set of λ -abstractions $\{(\mu f \colon \mathcal{I}.\lambda x.\,e) \mid \varnothing \vdash (\mu f \colon \mathcal{I}.\lambda x.\,e) \colon t_1 \to t_2\}$. For instance, our proposed definition of $[\![\cdot]\!]$ is sound with respect to this correspondence, but not complete, that is, not precise enough. We devote the rest of this section to explain why and to discuss the possibility of obtaining a complete definition. Consider the type $\mathsf{Int} \to \mathbb{O}$. By Definition 2.3, we have

$$\begin{split} \llbracket \mathsf{Int} \to \mathbb{0} \rrbracket &= \{ \, R \in \mathcal{P}_{\mathrm{fin}}(\mathcal{D} \times \mathcal{D}_{\Omega}) \, | \, \forall (d,d') \in R. \, d \in \llbracket \mathsf{Int} \rrbracket \implies d' \in \llbracket \mathbb{0} \rrbracket \, \} \\ &= \{ \, R \in \mathcal{P}_{\mathrm{fin}}(\mathcal{D} \times \mathcal{D}_{\Omega}) \, | \, \forall (d,d') \in R. \, d \notin \llbracket \mathsf{Int} \rrbracket \, \} \end{split}$$

(since $\llbracket \mathbb{O} \rrbracket = \varnothing$, the implication can only be satisfied if $d \notin \llbracket \mathsf{Int} \rrbracket$). This type is not empty, therefore, if a result similar to that of [20] held, we would expect to be able to find a function

¹ The circularity is avoided since the typing relation in $\{v \mid \varnothing \vdash v : t\}$ is defined using $[\![\cdot]\!]$ and not $[\![\cdot]\!]_{\mathcal{V}}$.

² In case of a type error, the CDuce compiler shows to the programmer a default value for the type $t_1 \setminus t_2$. Some heuristics are used to build a value in which only the part relevant to the error is detailed.

 $\mu f\colon \mathcal{I}. \lambda x. e$ such that $\varnothing \vdash (\mu f\colon \mathcal{I}. \lambda x. e)\colon \mathsf{Int} \to \mathbb{O}$. Alas, no such function can be defined in our language. This is easy to check: interfaces must include \bot in the codomain of every arrow (since they use the \to form), so no interface can be a subtype of $\mathsf{Int} \to \mathbb{O}$. Lifting this syntactic restriction to allow any arrow type in interfaces would not solve the problem: for a function to have type $\mathsf{Int} \to \mathbb{O}$, its body must have type \mathbb{O} , which is impossible, and indeed must be impossible for the system to be sound. It is therefore to be expected that $\mathsf{Int} \to \mathbb{O}$ is uninhabited in the language. This means that our current definition of $[\![\mathsf{Int} \to \mathbb{O}]\!]$ as a non-empty type is imprecise.

Changing $[\![\cdot]\!]$ to make the types of the form $t \to 0$ empty is easy, but it does not solve the problem in general. Using intersection types we can build more challenging examples: for instance, consider the type $(Int \lor Bool \to Int) \land (Int \lor String \to Bool)$. While neither codomain is empty, and neither arrow should be empty, the whole intersection should: no function, when given an Int as argument, can return a result which is both an Int and a Bool.

In the call-by-value case, it makes sense to have $\operatorname{Int} \to \mathbb{O}$ and the intersection type above be non-empty, because they are inhabited by functions that diverge on integers. This is because divergence is not represented in the types (or, to put it differently, because it is represented by the type \mathbb{O}). A type like $t_1 \to t_2$ is interpreted as a specification of partial correctness: a function of this type, when given an argument in t_1 , either diverges or returns a result in t_2 . In our system, we have introduced a separate non-empty type for divergence. Hence, we should see a type as specifying total correctness, where divergence is allowed only for functions whose codomain includes \bot .

Let us look again at the current interpretation of arrow types.

$$\llbracket t_1 \to t_2 \rrbracket = \{ R \in \mathcal{P}_{fin}(\mathcal{D} \times \mathcal{D}_{\Omega}) \mid \forall (d, d') \in R. \ d \in \llbracket t_1 \rrbracket \implies d' \in \llbracket t_2 \rrbracket \}$$

An arrow type is seen as a set of finite relations: we represent functions extensionally and approximate them with all their finite representations. We use relations instead of functions to account for non-determinism. Within a relation, a pair (d, d') means that the function returns the output d' on the input d; a pair (d, Ω) that the function crashes on d; divergence is represented simply by the absence of a pair. In this way, as said above, a function diverging on some element of $[t_1]$ could erroneously belong to the set even if $[t_2]$ does not contain \bot .

To formalize the requirement of totality on the domain, we could modify the definition in this way:

$$\llbracket t_1 \to t_2 \rrbracket = \{ R \in \mathcal{P}_{\text{fin}}(\mathcal{D} \times \mathcal{D}_{\Omega}) \mid \text{dom}(R) \supseteq \llbracket t_1 \rrbracket \text{ and } \forall (d, d') \in R. d \in \llbracket t_1 \rrbracket \implies d' \in \llbracket t_2 \rrbracket \}$$
(where $\text{dom}(R) = \{ d \mid \exists d' \in \mathcal{D}. (d, d') \in R \}$).

However, if we consider only finite relations as above, the definition makes no sense, since $\llbracket t_1 \rrbracket \subseteq \mathsf{dom}(R)$ can hold only when $\llbracket t_1 \rrbracket$ is finite, whereas types can have infinite interpretations. On the contrary, if we allowed relations to be infinite, then the set \mathcal{D} would have to satisfy the equality $\mathcal{D} = \mathcal{C} \uplus (\mathcal{D} \times \mathcal{D}) \uplus \mathcal{P}(\mathcal{D} \times \mathcal{D}_{\Omega})$ (where \uplus denotes disjoint union), but no such set exists: the cardinality of $\mathcal{P}(\mathcal{D} \times \mathcal{D}_{\Omega})$ is always strictly greater than that of \mathcal{D} .

Frisch, Castagna and Benzaken [20] point out this problem and use finite relations in the domain to avoid it. They motivate this choice with the observation that, while finite relations are not really appropriate to describe functions in a language (since these might have an infinite domain), they are suitable to describe types as far as subtyping is concerned. Indeed, we do not really care what the elements in the interpretation of a type are, but only how they are related to those in the interpretations of other types. It can be shown that

$$\forall t_1, t_1', t_2, t_2'. \ \llbracket t_1' \to t_1 \rrbracket \subseteq \llbracket t_2' \to t_2 \rrbracket \iff (\llbracket t_1' \rrbracket \rightharpoonup \llbracket t_1 \rrbracket) \subseteq (\llbracket t_2' \rrbracket \rightharpoonup \llbracket t_2 \rrbracket)$$

where $X \rightharpoonup Y \stackrel{\text{def}}{=} \{ R \in \mathcal{P}(\mathcal{D} \times \mathcal{D}_{\Omega}) \mid \forall (d, d') \in R. \ d \in X \implies d' \in Y \}$ builds the set of possibly infinite relations. This can be generalized to more complex types:

$$\left[\!\left[\bigwedge_{i\in P}t_i'\to t_i\right]\!\right]\subseteq \left[\!\left[\bigvee_{i\in N}t_i'\to t_i\right]\!\right]\iff \bigcap_{i\in P}\left(\left[\!\left[t_i'\right]\!\right]\rightharpoonup \left[\!\left[t_i\right]\!\right]\right)\subseteq \bigcup_{i\in N}\left(\left[\!\left[t_i'\right]\!\right]\rightharpoonup \left[\!\left[t_i\right]\!\right]\right).$$

In [20], the authors argue that the restriction to finite relations does not compromise the precision of subtyping. For reasons of space we do not elaborate further on this, and we direct the interested reader to their work and the notions of *extensional interpretation* and of *model* therein.

Let us try to proceed analogously in our case: that is, find a new interpretation of types that matches the behaviour of possibly infinite relations that are total on their domain, while introducing an approximation to ensure that the domain is definable. The latter point means, notably, that functions must be represented as finite objects. The following definition of a *model* specifies the properties that such an interpretation should satisfy.

- ▶ Definition 5.1 (Model). A function $(\cdot): \mathcal{T} \to \mathcal{P}(\overline{\mathcal{D}})$ is a *model* if the following hold:
- the set $\overline{\mathcal{D}}$ satisfies $\overline{\mathcal{D}} = \{\bot\} \uplus \mathcal{C} \uplus (\overline{\mathcal{D}} \times \overline{\mathcal{D}}) \uplus \overline{\mathcal{D}}^{\mathsf{fun}}$ for some set $\overline{\mathcal{D}}^{\mathsf{fun}}$;
- \blacksquare for all b, t, t_1 , and t_2 ,

• for every finite, non-empty intersection $\bigwedge_{i \in P} t'_i \to t_i$ and every finite union $\bigvee_{i \in N} t'_i \to t_i$,

$$\left(\left(\bigwedge_{i \in P} t_i' \to t_i \right) \subseteq \left(\bigvee_{i \in N} t_i' \to t_i \right) \iff \bigcap_{i \in P} \left(\left(\left(t_i' \right) \to \left(t_i \right) \right) \subseteq \bigcup_{i \in N} \left(\left(\left(t_i' \right) \to \left(t_i \right) \right) \right)$$

where
$$X \to Y \stackrel{\text{def}}{=} \{ R \in \mathcal{P}(\overline{\mathcal{D}} \times \overline{\mathcal{D}}) \mid \text{dom}(R) \supseteq X \text{ and } \forall (d, d') \in R. \ d \in X \implies d' \in Y \}.$$

We set three conditions for an interpretation of types $(\cdot): \mathcal{T} \to \mathcal{P}(\overline{\mathcal{D}})$ to be a model. The first constrains $\overline{\mathcal{D}}$ to have the same structure as \mathcal{D} , except that we do not fix the subset $\overline{\mathcal{D}}^{\text{fun}}$ in which arrow types are interpreted. The second condition fixes the definition of (\cdot) completely except for arrow types. The third condition ensures that subtyping on arrow types behaves as set containment between the sets of relations that are total on the domains of the arrow types.

An interesting result is that, even though we do not know whether an interpretation of types which is a model can be actually found, we can compare such hypothetical model with the interpretation $[\![\cdot]\!]$ defined in Section 2. Indeed $[\![\cdot]\!]$ turns out to be a sound approximation of every model; that is, the subtyping relation \leq defined in Definition 2.4 from $[\![\cdot]\!]$ is contained in every subtyping relation $\leq_{\{\![\cdot]\!]}$ defined from some model $\{\![\cdot]\!]$. We have proven that this holds for non-recursive types:

▶ Proposition 5.2. Let (\cdot) : $\mathcal{T} \to \mathcal{P}(\overline{\mathcal{D}})$ be a model. Let t_1 and t_2 be two finite (i.e., non-recursive) types. If $[t_1]$ ⊆ $[t_2]$, then (t_1) ⊆ (t_2) .

We conjecture that the result holds for recursive types too, but this proof is left for future work.

Showing that (\cdot) exists would be important to understand the connection between our types and the semantics. To use (\cdot) to define subtyping for the use of a typechecker, though, we would also need to show that the resulting definition is decidable. Otherwise, $[\cdot]$ would remain the definition used in a practical implementation since it is sound and decidable, though less precise.

³ We do not use the error element Ω in the definition of $X \to Y$, because the totality requirement makes it unnecessary: errors on a given input can be represented in a relation by the absence of a pair.

6 Conclusion

We have shown how to adapt the framework of semantic subtyping [20] to languages with non-strict semantics. Our type system uses the subtyping relation from [20] unchanged (except for the addition of \perp), while the typing rules are reworked to avoid the pathological behaviour of semantic subtyping on empty types. Notably, typing rules for constructs like application and projection must handle \perp explicitly. This ensures soundness for call-by-need.

This approach ensures that the subtyping relation still behaves set-theoretically: we can still see union, intersection, and negation in types as the corresponding operations on sets. We can still use intersection types to express overloading.

The type \bot we introduce has no analogue in well-known type systems like the simply typed λ -calculus or Hindley-Milner typing. However, \bot never appears explicitly in programs (it does not appear in types of the forms T and τ given at the beginning of Section 3). Hence, programmers do not need to use it and to consider the difference between terminating and non-terminating types while writing function interfaces or typecases. Still, sub-expressions of a program can have types with explicit \bot (e.g., the type $\mathsf{Int} \lor \bot$). Such types are not expressible in the grammar of types visible to the programmer. Accordingly, error reporting is required to be more elaborated, to avoid mentioning internal types that are unknown to the programmer.

A different approach to use semantic subtyping with non-strict languages would be to change the interpretation of types (and, as a result, the definition of subtyping) to avoid the pathological behaviour on \mathbb{O} , and then to use standard typing rules.

We have explored this alternative approach, but we have not found it promising. A modified subtyping relation loses important properties – especially results on the decomposition of product types – that we need to prove soundness via subject reduction. The approach we have adopted here is more suited to this technical work. However, a modified subtyping relation could yield an alternative type system for the source language, provided that we can relate it to the current system for the internal language.

We also plan to study more expressive typing rules that can track termination with some precision. For example, we could change the application rule so that it does not always introduce \bot . In function interfaces, some arrows could include \bot and some could not: then, overloaded function types would express that a function behaves differently on terminating or diverging arguments. For example, the function $\lambda x. x + 1$ could have type $(\text{Int} \to \text{Int}) \land (\bot \to \bot)$, while $\lambda x. 3$ could have type $\mathbbm{1} \to \text{Int}$: the first diverges on diverging arguments, the other always terminates. It would be interesting for future work to explore forms of termination analysis to obtain greater precision. The difficulty is to ensure that the type $\mathbbm{0}$ remains uninhabited and that all diverging expressions still have types that include \bot . This is trivial in the current system, but it is no longer straightforward with more refined typing rules.

A further direction for future work is to extend the language and the type system we have considered with more features. Notably, polymorphism, gradual typing, and record types are needed to be able to type effectively the Nix Expression Language, which was the starting inspiration for our work.

References

1 Davide Ancona and Andrea Corradi. Semantic subtyping for imperative object-oriented languages. In *Proceedings of the 2016 ACM SIGPLAN International Conference on Object-*

- Oriented Programming, Systems, Languages, and Applications, OOPSLA 2016, pages 568–587. ACM, 2016.
- 2 Zena M. Ariola and Matthias Felleisen. The call-by-need lambda calculus. *Journal of functional programming*, 7(3):265–301, 1997.
- 3 Zena M. Ariola, John Maraist, Martin Odersky, Matthias Felleisen, and Philip Wadler. A call-by-need lambda calculus. In *Proceedings of the 22nd ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, pages 233–246. ACM, 1995.
- V. Benzaken, G. Castagna, K. Nguyen, and J. Siméon. Static and dynamic semantics of NoSQL languages. In POPL '13, 40th ACM Symposium on Principles of Programming Languages, pages 101–113, 2013.
- 5 Véronique Benzaken, Giuseppe Castagna, and Alain Frisch. CDuce: an XML-centric general-purpose language. In *ICFP '03*, 8th ACM International Conference on Functional Programming, pages 51–63, Uppsala, Sweden, 2003.
- 6 Gavin M. Bierman, Andrew D. Gordon, Cătălin Hriţcu, and David Langworthy. Semantic subtyping with an SMT solver. In Proceedings of the 15th ACM SIGPLAN International Conference on Functional Programming, ICFP '10, pages 105–116. ACM, 2010.
- 7 Venanzio Capretta. General Recursion via Coinductive Types. Logical Methods in Computer Science, 1(2), July 2005.
- 8 G. Castagna, H. Im, K. Nguyen, and V. Benzaken. A core calculus for XQuery 3.0. In ESOP '15: 24th European Symposium on Programming, number 5710 in Lecture Notes in Computer Science, pages 232–256. Springer, 2015.
- 9 Giuseppe Castagna and Alain Frisch. A gentle introduction to semantic subtyping. In ACM SIGPLAN International Conference on Principles and Practice of Declarative Programming (PPDP), Lisbon, Portugal, pages 198–208, July 2005.
- 10 Giuseppe Castagna and Victor Lanvin. Gradual typing with union and intersection types. PACMPL, 1(ICFP):41:1–28, 2017.
- Giuseppe Castagna, Kim Nguyen, Zhiwu Xu, and Pietro Abate. Polymorphic functions with set-theoretic types. part 2: Local type inference and type reconstruction. In ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL), Mumbai, India, pages 289–302, January 2015.
- 12 Giuseppe Castagna, Kim Nguyen, Zhiwu Xu, Hyeonseung Im, Sergueï Lenglet, and Luca Padovani. Polymorphic functions with set-theoretic types. Part 1: Syntax, semantics, and evaluation. In ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL), San Diego, California, USA, pages 5–17, January 2014.
- Giuseppe Castagna, Tommaso Petrucciani, and Kim Nguyen. Set-theoretic types for polymorphic variants. In ACM SIGPLAN International Conference on Functional Programming (ICFP), Nara, Japan, pages 378–391, September 2016.
- Giuseppe Castagna and Zhiwu Xu. Set-theoretic foundation of parametric polymorphism and subtyping. In ACM SIGPLAN International Conference on Functional Programming (ICFP), Tokyo, Japan, pages 94–106, September 2011.
- 15 Robert L. Constable and Scott Fraser Smith. Partial objects in constructive type theory. Technical report, Cornell University, 1987.
- Ornela Dardha, Daniele Gorla, and Daniele Varacca. Semantic subtyping for objects and classes. In *Formal Techniques for Distributed Systems*, pages 66–82. Springer, 2013.
- 17 Eelco Dolstra and Andres Löh. NixOS: A purely functional Linux distribution. In *ICFP'08*, 13th ACM SIGPLAN International Conference on Functional Programming, 2008.
- 18 Joshua Dunfield. A Unified System of Type Refinements. PhD thesis, Carnegie Mellon University, August 2007.

XX:22 Semantic subtyping for non-strict languages

- 19 Joshua Dunfield and Frank Pfenning. Type assignment for intersections and unions in call-by-value languages. In *Foundations of Software Science and Computation Structures*, pages 250–266. Springer, 2003.
- 20 Alain Frisch, Giuseppe Castagna, and Véronique Benzaken. Semantic subtyping: dealing set-theoretically with function, union, intersection, and negation types. *Journal of the ACM*, 55(4):1–67, September 2008.
- 21 John Maraist, Martin Odersky, and Philip Wadler. The call-by-need lambda calculus. *Journal of functional programming*, 8(03):275–317, 1998.
- 22 Francesco Zappa Nardelli, Julia Belyakova, Artem Pelenitsyn, Benjamin Chung, Jeff Bezanson, and Jan Vitek. Julia subtyping: a rational reconstruction. *Proc. ACM Program. Lang.*, 2(OOPSLA), 2018.
- Niki Vazou, Eric L. Seidel, Ranjit Jhala, Dimitrios Vytiniotis, and Simon Peyton-Jones. Refinement types for Haskell. In *Proceedings of the 19th ACM SIGPLAN International Conference on Functional Programming*, ICFP '14, pages 269–282. ACM, 2014.
- 24 Andrew K. Wright and Matthias Felleisen. A syntactic approach to type soundness. *Information and Computation*, 115(1):38–94, 1994.

A Appendix

A.1 Properties of subtyping and type decompositions

▶ Lemma A.1.

$$\bigwedge_{i \in I} t'_i \to t_i \leq \bigvee_{j \in J} t'_j \to t_j \iff$$

$$\exists j_0 \in J. \left(t'_{j_0} \leq \bigvee_{i \in I} t'_i \right) \land \left(\forall I' \subsetneq I. \left(t'_{j_0} \leq \bigvee_{i \in I'} t'_i \right) \lor \left(\bigwedge_{i \in I \setminus I'} t_i \leq t_{j_0} \right) \right)$$

Proof. Consequence of Lemma 6.8 of [20].

▶ Corollary A.2. Let $\bigwedge_{i \in I} t'_i \to t_i$ (with |I| > 0) be such that $t'_{i_1} \wedge t'_{i_2} \simeq \mathbb{O}$ for $i_1 \neq i_2$. Then:

$$\bigwedge_{i \in I} t'_i \to t_i \le t' \to t \implies \left(t' \le \bigvee_{i \in I} t'_i \right) \land \left(\forall i \in I. \ \left(t'_i \land t' \not\simeq \mathbb{0} \right) \implies \left(t_i \le t \right) \right)$$

Proof. By applying Lemma A.1, we get

$$\left(t' \leq \bigvee_{i \in I} t_i'\right) \wedge \left(\forall I' \subsetneq I. \ \left(t' \leq \bigvee_{i \in I'} t_i'\right) \vee \left(\bigwedge_{i \in I \setminus I'} t_i \leq t\right)\right).$$

Now consider an arbitrary $i_0 \in I$ such that $t'_{i_0} \wedge t' \not\simeq \mathbb{O}$; we must show $t_{i_0} \leq t$. Instantiating the quantifier above with $I' = I \setminus \{i_0\}$ we get $(t' \leq \bigvee_{i \in I \setminus \{i_0\}} t'_i) \vee (\bigwedge_{i \in I \setminus \{i_0\}} t_i \leq t)$. We show $t' \not\leq \bigvee_{i \in I \setminus \{i_0\}} t'_i$, which concludes the proof since the second term of the union is $t_{i_0} \leq t$.

By contradiction, assume $t' \leq \bigvee_{i \in I \setminus \{i_0\}} t'_i$. Note that $t'_{i_0} \wedge \bigvee_{i \in I \setminus \{i_0\}} t'_i \simeq \mathbb{O}$ (because the t'_i are disjoint); therefore we would also have $t'_{i_0} \wedge t \simeq \mathbb{O}$, which is false by hypothesis.

▶ Corollary A.3. Let
$$\bar{t} = (\bigwedge_{i \in I} t'_i \to t_i) \land (\bigwedge_{j \in J} \neg (t'_j \to t_j))$$
. If $\bar{t} \not\simeq 0$ and $\bar{t} \leq t' \to t$, then $(\bigwedge_{i \in I} t'_i \to t_i) \leq t' \to t$.

Proof. By definition of subtyping, we have

$$\bar{t} \not\simeq \mathbb{O} \iff (\bigwedge_{i \in I} t_i' \to t_i) \land (\bigwedge_{j \in J} \neg (t_j' \to t_j)) \not\leq \mathbb{O} \iff \bigwedge_{i \in I} t_i' \to t_i \not\leq \bigvee_{j \in J} t_j' \to t_j$$

$$\bar{t} \leq t' \to t \iff \bigwedge_{i \in I} t_i' \to t_i \leq (\bigvee_{j \in J} t_j' \to t_j) \lor (t' \to t)$$

Let \bar{j} be such that $\bar{j} \notin J$ and let $t'_{\bar{j}} = t'$ and $t_{\bar{j}} = t$. By Lemma A.1, we derive

$$\forall j_0 \in J. \ \neg \Big((t'_{j_0} \leq \bigvee_{i \in I} t'_i) \land \big(\forall I' \subsetneq I. \ (t'_{j_0} \leq \bigvee_{i \in I'} t'_i) \lor (\bigwedge_{i \in I \setminus I'} t_i \leq t_{j_0}) \big) \Big)$$

$$\exists j_0 \in J \cup \{\bar{j}\}. \ (t'_{j_0} \leq \bigvee_{i \in I} t'_i) \land \big(\forall I' \subsetneq I. \ (t'_{j_0} \leq \bigvee_{i \in I'} t'_i) \lor (\bigwedge_{i \in I \setminus I'} t_i \leq t_{j_0}) \big)$$

where clearly the existentially quantified proposition must be true for \bar{j} , which allows us to conclude.

▶ Lemma A.4. For every set J and every set $\{t_i \mid j \in J\}$,

$$\bigvee_{J'\subset J} \left(\bigwedge_{j\in J'} t_j \wedge \bigwedge_{j\in J\setminus J'} \neg t_j\right) \simeq \mathbb{1}$$

(with the convention that an intersection over an empty set is 1).

Proof. We prove this by induction on |J|. If |J| = 0, then the only J' is J itself, and the equivalence holds. If |J| > 0, consider an arbitrary $j_0 \in J$ and let $\bar{J} = J \setminus \{j_0\}$. We have

$$\bigvee_{J'\subseteq J} \left(\bigwedge_{j\in J'} t_{j} \wedge \bigwedge_{j\in J\setminus J'} \neg t_{j} \right) \\
\simeq \bigvee_{J'\subseteq \bar{J}} \left(\bigwedge_{j\in J'} t_{j} \wedge \bigwedge_{j\in \bar{J}\setminus J'} \neg t_{j} \wedge \neg t_{j_{0}} \right) \vee \bigvee_{J'\subseteq \bar{J}} \left(t_{j_{0}} \wedge \bigwedge_{j\in J'} t_{j} \wedge \bigwedge_{j\in \bar{J}\setminus J'} \neg t_{j} \right) \\
\simeq \left(\neg t_{j_{0}} \wedge \bigvee_{J'\subseteq \bar{J}} \left(\bigwedge_{j\in J'} t_{j} \wedge \bigwedge_{j\in \bar{J}\setminus J'} \neg t_{j} \right) \right) \vee \left(t_{j_{0}} \wedge \bigvee_{J'\subseteq \bar{J}} \left(\bigwedge_{j\in J'} t_{j} \wedge \bigwedge_{j\in \bar{J}\setminus J'} \neg t_{j} \right) \right) \\
\simeq \left(\neg t_{j_{0}} \wedge \mathbb{1} \right) \vee \left(t_{j_{0}} \wedge \mathbb{1} \right)$$

(by the induction hypothesis)

$$\simeq 1$$
.

▶ Lemma A.5. Let $\mathcal{I} = \bigwedge_{i \in I} t'_i \to t_i$ (with |I| > 0) be a type. Then:

$$\mathcal{I} \simeq \bigwedge_{\varnothing \subsetneq I' \subseteq I} s_{I'} \to u_{I'} \quad \text{where } s_{I'} \stackrel{\text{def}}{=} \bigwedge_{i \in I'} t'_i \wedge \bigwedge_{i \in I \setminus I'} \neg t'_i \text{ and } u_{I'} \stackrel{\text{def}}{=} \bigwedge_{i \in I'} t_i$$
(with the convention: $\bigwedge_{i \in \varnothing} \neg t'_i = \mathbb{1}$).

(with the convention, $\bigwedge_{i\in\varnothing} u_i = 1$).

Proof. We first show $\mathcal{I} \leq \bigwedge_{\varnothing \subsetneq I' \subseteq I} s_{I'} \to u_{I'}$. To do this, we show that, for every I' such that $\varnothing \subsetneq I' \subseteq I$, we have $\mathcal{I} \leq s_{I'} \to u_{I'}$, that is,

$$\mathcal{I} \leq \left(\bigwedge_{i \in I'} t'_i \wedge \bigwedge_{i \in I \setminus I'} \neg t'_i \right) \rightarrow \left(\bigwedge_{i \in I'} t_i \right).$$

We have

$$\begin{split} \mathcal{I} &= \bigwedge_{i \in I} t_i' \to t_i \\ &\leq \bigwedge_{i \in I'} t_i' \to t_i \\ &\leq \left(\bigwedge_{i \in I'} t_i'\right) \to \left(\bigwedge_{i \in I'} t_i\right) & \text{by definition of subtyping for arrows} \\ &\leq \left(\bigwedge_{i \in I'} t_i' \wedge \bigwedge_{i \in I \setminus I'} \neg t_i'\right) \to \left(\bigwedge_{i \in I'} t_i\right). \end{split}$$

We now consider the opposite direction. To show $\bigwedge_{\varnothing \subsetneq I' \subseteq I} s_{I'} \to u_{I'} \leq \mathcal{I}$, we show that, for every $i \in I$, we have $\bigwedge_{\varnothing \subsetneq I' \subseteq I} s_{I'} \to u_{I'} \leq t'_i \to t_i$. Consider an arbitrary $i_0 \in I$ and let $\overline{I} = I \setminus \{i_0\}$. We have

$$\bigwedge_{\varnothing \subsetneq I' \subseteq I} s_{I'} \to u_{I'} \leq \bigwedge_{\varnothing \subseteq I' \subseteq I} s_{I'} \to u_{I'}$$

$$\simeq \bigwedge_{I' \subseteq \overline{I}} s_{(I' \cup \{i_0\})} \to u_{(I' \cup \{i_0\})}$$

$$\simeq \bigwedge_{I' \subseteq \overline{I}} \left(\left(t'_{i_0} \wedge \bigwedge_{i \in I'} t'_i \wedge \bigwedge_{i \in \overline{I} \setminus I'} \neg t'_i \right) \to \left(t_{i_0} \wedge \bigwedge_{i \in I'} t_i \right) \right)$$

$$\leq \left(\bigvee_{I' \subseteq \overline{I}} \left(t'_{i_0} \wedge \bigwedge_{i \in I'} t'_i \wedge \bigwedge_{i \in \overline{I} \setminus I'} \neg t'_i \right) \to \left(\bigvee_{I' \subseteq \overline{I}} \left(t_{i_0} \wedge \bigwedge_{i \in I'} t_i \right) \right)$$

$$\simeq \left(t'_{i_0} \wedge \bigvee_{I' \subseteq \overline{I}} \left(\bigwedge_{i \in I'} t'_i \wedge \bigwedge_{i \in \overline{I} \setminus I'} \neg t'_i \right) \right) \to \left(t_{i_0} \wedge \bigvee_{I' \subseteq \overline{I}} \left(\bigwedge_{i \in I'} t_i \right) \right)$$

$$\simeq t'_{i_0} \to \left(t_{i_0} \wedge \bigvee_{I' \subseteq \overline{I}} \left(\bigwedge_{i \in I'} t_i \right) \right)$$

(by Lemma A.4)

$$\leq t'_{i_0} \rightarrow t_{i_0}$$
.

▶ Definition A.6 (Product decomposition). A product decomposition Π is a finite set of product atoms, that is, of types of the form $t_1 \times t_2$.

We say that a product decomposition $\Pi = \{t_i^1 \times t_i^2 \mid i \in I\}$ is fully disjoint if $\forall i \in I$. $t_i^1 \times t_i^2 \not\simeq \mathbb{O}$ and if the following conditions hold for all $i_1 \neq i_2 \in I$:

- ▶ Lemma A.7. For every type t such that $t \leq 1 \times 1$, there exists a product decomposition Π such that $t \simeq \bigvee_{t_1 \times t_2 \in \Pi} t_1 \times t_2$.
- ▶ Lemma A.8. For every product decomposition Π , there exists a product decomposition Π' such that Π' is fully disjoint, that $\bigvee_{t\in\Pi}t\simeq\bigvee_{t'\in\Pi'}t'$, and that $\forall t'\in\Pi$. $\exists t\in\Pi$. $t'\leq t$.

Proof. Let $\Pi = \{t_i^1 \times t_i^2 \mid i \in I\}$. When $i \in I$ and $I', I_1, I_2 \subseteq I$, and $k \in \{1, 2\}$, we define

$$\mathbb{T}^k(i,I') = t_i^k \wedge \bigwedge_{j \in I'} t_j^k \wedge \bigwedge_{j \in I \setminus \{i\} \setminus I'} \neg t_j^k \qquad \mathbb{T}(i,I_1,I_2) = \mathbb{T}^1(i,I_1) \times \mathbb{T}^2(i,I_2)$$

and we consider the product decomposition

$$\Pi' = \bigcup_{i \in I} \{ \mathbb{T}(i, I_1, I_2) \mid I_1 \subseteq I \setminus \{i\}, I_2 \subseteq I \setminus \{i\}, \mathbb{T}^1(i, I_1) \not\simeq \emptyset, \mathbb{T}^2(i, I_2) \not\simeq \emptyset \}.$$

We first show that Π' is fully disjoint. First, consider an arbitrary element of Π' , $\mathbb{T}(i, I_1, I_2) = \mathbb{T}^1(i, I_1) \times \mathbb{T}^2(i, I_2)$. We must show $\mathbb{T}(i, I_1, I_2) \not\simeq \emptyset$, which holds because we explicitly require both $\mathbb{T}^k(i, I_k)$ to be non-empty. Now, we consider two arbitrary elements of Π' :

$$\mathbb{T}(i, I_1, I_2) = \mathbb{T}^1(i, I_1) \times \mathbb{T}^2(i, I_2)$$
 $\mathbb{T}(i', I_1', I_2') = \mathbb{T}^1(i', I_1') \times \mathbb{T}^2(i', I_2')$

and we must prove:

We prove the first (the second is proved identically). Note that if $\{i\} \cup I_1 = \{i'\} \cup I'_1$, then $\mathbb{T}^1(i,I_1)$ and $\mathbb{T}^1(i',I'_1)$ are the same up to reordering of the intersections: therefore $\mathbb{T}^1(i,I_1) \simeq \mathbb{T}^1(i',I'_1)$ holds. Otherwise, assume without loss of generality that there exists an i_0 such that $i_0 \in \{i\} \cup I_1$ but $i_0 \notin \{i'\} \cup I'_1$. Then, we have $\mathbb{T}^1(i,I_1) \leq t^1_{i_0}$ and $\mathbb{T}^1(i',I'_1) \leq \neg t^1_{i_0}$. Then, $\mathbb{T}^1(i,I_1) \wedge \mathbb{T}^1(i',I'_1) \leq t^1_{i_0} \wedge \neg t^1_{i_0} \leq \emptyset$.

Now we show that, for every $\mathbb{T}(i, I_1, I_2) = \mathbb{T}^1(i, I_1) \times \mathbb{T}^2(i, I_2)$ in Π' , there exists a $i' \in I$ such that $\mathbb{T}(i, I_1, I_2) \leq t_{i'}^1 \times t_{i'}^2$. We simply take i' = i, since both $\mathbb{T}^1(i, I_1) \leq t_i^1$ and $\mathbb{T}^2(i, I_2) \leq t_i^2$ always hold.

Finally, we show that $\bigvee_{i \in I} t_i^1 \times t_i^2 \simeq \bigvee_{t \in II} t$. We do so by showing that, for every $i \in I$,

$$t_i^1 \times t_i^2 \simeq \bigvee_{i \in I, I_1 \subset I \setminus \{i\}, I_2 \subset I \setminus \{i\}, \mathbb{T}^1(i, I_1) \not\simeq \emptyset, \mathbb{T}^2(i, I_2) \not\simeq \emptyset} \mathbb{T}(i, I_1, I_2) .$$

Note that we can show this by showing

$$t_i^1 \times t_i^2 \simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}, I_2 \subseteq I \setminus \{i\}} \mathbb{T}(i, I_1, I_2)$$

without the conditions of non-emptiness (we have more summands in the union, but they are empty). We have

$$\begin{split} &\bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}, I_2 \subseteq I \setminus \{i\}} \mathbb{T}(i, I_1, I_2) \\ &= \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}, I_2 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times \mathbb{T}^2(i, I_2) \\ &\simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}} \left(\bigvee_{I_2 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times \mathbb{T}^2(i, I_2)\right) \\ &\simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times \left(\bigvee_{I_2 \subseteq I \setminus \{i\}} \mathbb{T}^2(i, I_2)\right) \end{split}$$

(subtyping of product types satisfies $\bigvee_{i \in I} (t \times t_i) \simeq t \times (\bigvee_{i \in I} t_i)$)

$$\simeq \bigvee_{i\in I, I_1\subseteq I\setminus\{i\}} \mathbb{T}^1(i, I_1) \times \left(\bigvee_{I_2\subseteq I\setminus\{i\}} \left(t_i^2 \wedge \bigwedge_{j\in I_2} t_j^2 \wedge \bigwedge_{j\in I\setminus\{i\}\setminus I_2} \neg t_j^2\right)\right)$$

$$\simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times \left(t_i^2 \wedge \bigvee_{I_2 \subseteq I \setminus \{i\}} \left(\bigwedge_{j \in I_2} t_j^2 \wedge \bigwedge_{j \in I \setminus \{i\} \setminus I_2} - t_j^2 \right) \right)$$

$$\simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times (t_i^2 \wedge \mathbb{1})$$

(by Lemma A.4)

$$\simeq \bigvee_{i \in I, I_1 \subseteq I \setminus \{i\}} \mathbb{T}^1(i, I_1) \times t_i^2$$

$$\simeq t_i^1 \times t_i^2$$

(proceeding as above).

▶ Lemma A.9. Let $\Pi = \{t_i^1 \times t_i^2 \mid i \in I\}$ be a fully disjoint product decomposition and let t^1 and t^2 be two types such that $t^1 \times t^2 \simeq \bigvee_{i \in I} t_i^1 \times t_i^2$. Then, $t^1 \simeq \bigvee_{i \in I} t_i^1$, $t^2 \simeq \bigvee_{i \in I} t_i^2$, and $\forall i_1, i_2 \in I. \ \exists i \in I. \ t_{i_1}^1 \times t_{i_2}^2 \le t_i^1 \times t_i^2.$

Proof. We have

$$t^1 \times t^2 \simeq \bigvee_{i \in I} t_i^1 \times t_i^2 \leq \left(\bigvee_{i \in I} t_i^1\right) \times \left(\bigvee_{i \in I} t_i^2\right)$$

and therefore $t^1 \leq \bigvee_{i \in I} t^1_i$ and $t^2 \leq \bigvee_{i \in I} t^2_i$, since all t^1_i and t^2_i are non-empty. Since $\bigvee_{i \in I} t^1_i \times t^2_i \leq t^1 \times t^2$, we have, for all $i \in I$, $t^1_i \times t^2_i \leq t^1 \times t^2$ and hence (by definition of subtyping, since t^1_i and t^2_i are non-empty) $t^1_i \leq t^1$ and $t^2_i \leq t^2$. Hence, we also

have $\bigvee_{i \in I} t_i^1 \leq t^1$ and $\bigvee_{i \in I} t_i^2 \leq t^2$. This yields $t^1 \simeq \bigvee_{i \in I} t_i^1$ and $t^2 \simeq \bigvee_{i \in I} t_i^2$. To prove $\forall i_1, i_2 \in I$. $\exists i \in I$. $t_{i_1}^1 \times t_{i_2}^2 \leq t_i^1 \times t_i^2$, we consider arbitrary i_1 and i_2 in I; we must show $\exists i \in I$. $t_{i_1}^1 \times t_{i_2}^2 \leq t_i^1 \times t_i^2$. Note that $t_{i_1}^1 \times t_{i_2}^2 \leq t^1 \times t^2$. Hence, we have

$$\begin{split} t_{i_1}^1 \times t_{i_2}^2 &\simeq (t_{i_1}^1 \times t_{i_2}^2) \wedge (t^1 \times t^2) \\ &\simeq (t_{i_1}^1 \times t_{i_2}^2) \wedge (\bigvee_{i \in I} t_i^1 \times t_i^2) \\ &\simeq \bigvee_{i \in I} \left((t_{i_1}^1 \times t_{i_2}^2) \wedge (t_i^1 \times t_i^2) \right) \\ &\simeq \bigvee_{i \in I} \left((t_{i_1}^1 \wedge t_i^1) \times (t_{i_2}^2 \wedge t_i^2) \right). \end{split}$$

Since $t^1_{i_1} \times t^2_{i_2}$ is not empty, there must exist an $i_0 \in I$ such that $(t^1_{i_1} \wedge t^1_{i_0}) \times (t^2_{i_2} \wedge t^2_{i_0})$ is not empty, that is, an i_0 such that $t^1_{i_1} \wedge t^1_{i_0} \not\simeq \mathbb{0}$ and $t^2_{i_2} \wedge t^2_{i_0} \not\simeq \mathbb{0}$. Since the decomposition is fully disjoint, we have $t^1_{i_1} \simeq t^1_{i_0}$ and $t^2_{i_2} \simeq t^2_{i_0}$: therefore $t^1_{i_1} \times t^2_{i_2} \simeq t^1_{i_0} \times t^2_{i_0}$.

Syntactic meta-theory of the type system of the internal language

▶ Lemma A.10 (Weakening). Let Γ and Γ' be two type environments such that, whenever $\Gamma(x) = t, x \in \mathsf{dom}(\Gamma') \text{ and } \Gamma'(x) \leq t. \text{ If } \Gamma \vdash e \colon t, \text{ then } \Gamma' \vdash e \colon t.$

Proof. For every Γ and Γ' , we define

$$\Gamma \leq \Gamma' \iff \forall x \in \mathsf{dom}(\Gamma). \ (x \in \mathsf{dom}(\Gamma')) \land (\Gamma'(x) \leq \Gamma(x)) \ .$$

We prove that, if $\Gamma \vdash e : t$ and $\Gamma' \leq \Gamma$, then $\Gamma' \vdash e : t$. We proceed by induction on the derivation of $\Gamma \vdash e$: t and by case on the last rule applied.

If the last rule is [VAR], we show the result by applying [VAR] and [SUBSUM]. For [CONST], the result is straightforward. For [ABSTR], we can assume by α -renaming that f and x do not appear in Γ and Γ' ; then, we have (for all i) $(\Gamma', f: \mathcal{I}, x: \langle T'_i \rangle) \leq (\Gamma, f: \mathcal{I}, x: \langle T'_i \rangle)$ and we apply the induction hypothesis to conclude. We proceed similarly for [Case] and [Let]. For [APPL], [PAIR], [PROJ], and [SUBSUM], we directly apply the induction hypothesis.

▶ Lemma A.11 (Intersection introduction). If $\Gamma \vdash e: t_1 \text{ and } \Gamma \vdash e: t_2, \text{ then } \Gamma \vdash e: t_1 \land t_2.$

Proof. By induction on the derivations of $\Gamma \vdash e : t_1$ and of $\Gamma \vdash e : t_2$. As a measure we use the sum of the depth of the two derivations.

If the last rule applied in the derivation of $\Gamma \vdash e \colon t_1$ is [Subsum], we have $\Gamma \vdash e \colon t_1'$ and $t_1' \le t_1$. We apply the induction hypothesis to $\Gamma \vdash e \colon t_1'$ and $\Gamma \vdash e \colon t_2$ to derive $\Gamma \vdash e \colon t_1' \land t_2$ and then apply [Subsum] since $t_1' \land t_2 \le t_1 \land t_2$. If the last rule applied for e_1 is not [Subsum], and that for e_2 is, we do the reverse.

Having dealt with the cases where the last rule applied in one derivation at least is [SUBSUM], we can assume for the remainder that the derivations end with the same rule: every derivation for e must end with the application of the rule corresponding to the form of e, possibly followed by applications of [SUBSUM].

If the last rule applied is [VAR] or [CONST], we have $t_1 = t_2$ and we can derive $\Gamma \vdash x \colon t_1 \land t_2$ by subsumption.

If the last rule applied is [ABSTR], we have

$$t_1 = \mathcal{I} \wedge (\bigwedge_{i \in J} \neg (t'_i \to t_i))$$
 $t_2 = \mathcal{I} \wedge (\bigwedge_{k \in K} \neg (t'_k \to t_k))$

and we want to derive $t_1 \wedge t_2$. We do so by applying [ABSTR] to derive $\mathcal{I} \wedge (\bigwedge_{j \in J} \neg (t'_j \to t_j)) \wedge (\bigwedge_{k \in K} \neg (t'_k \to t_k))$ (which is non-empty by Corollary A.3 since t_1 and t_2 are both non-empty), followed by [Subsum].

If the last rule applied is [APPL], we have $e = e_1 e_2$ and

$$\Gamma \vdash e_1 \colon \langle t_1' \to t_1'' \rangle \qquad \Gamma \vdash e_2 \colon t_1' \qquad t_1 = \langle t_1'' \rangle$$

$$\Gamma \vdash e_1 \colon \langle t_2' \to t_2'' \rangle \qquad \Gamma \vdash e_2 \colon t_2' \qquad t_2 = \langle t_2'' \rangle$$

and, by induction, we derive

$$\Gamma \vdash e_1 : \langle t'_1 \to t''_1 \rangle \land \langle t'_2 \to t''_2 \rangle \qquad \Gamma \vdash e_2 : t'_1 \land t'_2.$$

We have

$$\begin{split} \langle t_1' \rightarrow t_1'' \rangle \wedge \langle t_2' \rightarrow t_2'' \rangle &= ((t_1' \rightarrow t_1'') \vee \bot) \wedge ((t_2' \rightarrow t_2'') \vee \bot) \\ &\simeq ((t_1' \rightarrow t_1'') \wedge (t_2' \rightarrow t_2'')) \vee \bot \leq \langle (t_1' \wedge t_2') \rightarrow (t_1'' \wedge t_2'') \rangle \end{split}$$

and can therefore conclude by applying [Subsum] and [APPL].

The cases for [Pair] and [Proj] are similar. They rely on the following properties of subtyping:

$$(t_1^1 \wedge t_2^1) \times (t_1^2 \wedge t_2^2) \simeq (t_1^1 \times t_2^1) \wedge (t_1^2 \times t_2^2)$$

$$\langle t_1^1 \times t_1^2 \rangle \wedge \langle t_2^1 \times t_2^2 \rangle \leq \langle (t_1^1 \wedge t_2^1) \times (t_1^2 \wedge t_2^2) \rangle$$

For [CASE], we have

$$\begin{split} \Gamma \vdash \big((x = \varepsilon) \in \tau \ ? \ e_1 : e_2 \big) \colon \langle t_1 \rangle & \Gamma \vdash \varepsilon \colon \langle t_1' \rangle \\ & \big(\text{if } t_1' \nleq \neg \tau \text{ then } \Gamma, x \colon (t_1' \land \tau) \vdash e_1 \colon t_1 \big) & \big(\text{if } t_1' \nleq \tau \text{ then } \Gamma, x \colon (t_1' \setminus \tau) \vdash e_2 \colon t_1 \big) \\ \Gamma \vdash \big((x = \varepsilon) \in \tau \ ? \ e_1 : e_2 \big) \colon \langle t_2 \rangle & \Gamma \vdash \varepsilon \colon \langle t_2' \rangle \\ & \big(\text{if } t_2' \nleq \neg \tau \text{ then } \Gamma, x \colon (t_2' \land \tau) \vdash e_1 \colon t_2 \big) & \big(\text{if } t_2' \nleq \tau \text{ then } \Gamma, x \colon (t_2' \setminus \tau) \vdash e_2 \colon t_2 \big) \end{split}$$

and we derive $\Gamma \vdash ((x = \varepsilon) \in \tau ? e_1 : e_2) : \langle t_1 \land t_2 \rangle$ from the premises

$$\begin{split} \Gamma \vdash \varepsilon \colon \langle t_1' \wedge t_2' \rangle \\ \left(\text{if } t_1' \wedge t_2' \nleq \neg \tau \text{ then } \Gamma, x \colon ((t_1' \wedge t_2') \wedge \tau) \vdash e_1 \colon t_1 \wedge t_2 \right) \\ \left(\text{if } t_1' \wedge t_2' \nleq \tau \text{ then } \Gamma, x \colon ((t_1' \wedge t_2') \setminus \tau) \vdash e_2 \colon t_1 \wedge t_2 \right) \end{split}$$

The first premise can be derived by applying the induction hypothesis and then subsumption, since $\langle t_1' \rangle \wedge \langle t_2' \rangle \simeq \langle t_1' \wedge t_2' \rangle$. For the second premise, note that, when $t_1' \wedge t_2' \nleq \neg \tau$, we have $t_1' \nleq \neg \tau$ and $t_2' \nleq \neg \tau$ and therefore we have

$$\Gamma, x \colon (t_1' \wedge \tau) \vdash e_1 \colon t_1 \qquad \Gamma, x \colon (t_2' \wedge \tau) \vdash e_1 \colon t_2$$

and, by weakening (Lemma A.10),

$$\Gamma, x \colon ((t_1' \wedge t_2') \wedge \tau) \vdash e_1 \colon t_1 \qquad \Gamma, x \colon ((t_1' \wedge t_2') \wedge \tau) \vdash e_1 \colon t_2 .$$

Hence, we derive the premise by the induction hypothesis. The third premise is derived analogously to the second. Finally, we apply subsumption since $\langle t_1 \wedge t_2 \rangle \simeq \langle t_1 \rangle \wedge \langle t_2 \rangle$.

For [Let], we have

```
\begin{split} \Gamma \vdash \mathsf{let} \ x &= e_1 \ \mathsf{in} \ e_2 \colon t_1 \qquad \Gamma \vdash e_1 \colon \bigvee_{i \in I} t_i \qquad \forall i \in I. \ \Gamma, x \colon t_i \vdash e_2 \colon t_1 \\ \Gamma \vdash \mathsf{let} \ x &= e_1 \ \mathsf{in} \ e_2 \colon t_2 \qquad \Gamma \vdash e_1 \colon \bigvee_{j \in J} t_j \qquad \forall j \in J. \ \Gamma, x \colon t_j \vdash e_2 \colon t_2 \end{split}
```

By the induction hypothesis we derive $\Gamma \vdash e_1 \colon (\bigvee_{i \in I} t_i) \land (\bigvee_{j \in J} t_j)$; by subsumption we obtain $\Gamma \vdash e_1 \colon \bigvee_{(i,j) \in I \times J} (t_i \land t_j)$ since the two types are equivalent. Then, for every $(i,j) \in I \times J$, we want to show $\Gamma, x \colon (t_i \land t_j) \vdash e_2 \colon t_1 \land t_2$, which we show by applying Lemma A.10 and the induction hypothesis.

▶ Lemma A.12. Let Γ be a well-formed type environment. If $\Gamma \vdash e : t$, then $t \not\simeq \emptyset$.

- **Proof.** By induction on the derivation of $\Gamma \vdash e : t$ and by case on the last typing rule applied. If the last rule is [VAR], the conclusion follows from the assumption on Γ . If the last rule is [CONST], [ABSTR], [APPL], [PROJ], or [CASE], then t is surely non-empty. For the remaining rules ([PAIR], [LET], and [SUBSUM]) we apply the induction hypothesis. In particular, for [PAIR], we have by definition of subtyping that, if t_1 and t_2 are both non-empty, $t_1 \times t_2$ is non-empty as well. For [LET], by the induction hypothesis we derive that the type $\bigvee_{i \in I} t_i$ of e_1 is non-empty; therefore, there exists an $i_0 \in I$ such that t_{i_0} is non-empty. The corresponding environment $\Gamma, x : t_{i_0}$ is well-formed (whereas other $\Gamma, x : t_i$ might not be) and thus we can apply the induction hypothesis to it to conclude that t is non-empty.
- ▶ Lemma A.13 (Generation). Let Γ be a well-formed type environment and let a be an answer such that $\Gamma \vdash a$: t holds. Then:

```
■ if t = \langle t_1 \to t_2 \rangle, then a is either of the form \mu f : \mathcal{I}. \lambda x. e or of the form let x = e in a';

■ if t = \langle t_1 \times t_2 \rangle, then a is either of the form (e_1, e_2) or of the form let x = e in a'.
```

Proof. The typing derivation $\Gamma \vdash a : t$ must end with the application of the rule corresponding to the form of a (for an answer, one of [Const], [Abstr], [Pair], or [Let]) possibly followed by applications of [Subsum]. Therefore, if a = c, then we must have $b_c \leq t$: by definition of subtyping, this excludes both $t = \langle t_1 \to t_2 \rangle$ and $t = \langle t_1 \times t_2 \rangle$. Similarly, a non-empty intersection of the form $(\bigwedge_{i \in I} t'_i \to t_i) \wedge (\bigwedge_{j \in J} \neg (t'_j \to t_j))$ cannot be a subtype of $\langle t_1 \times t_2 \rangle$, nor can a type $t_1 \times t_2$ be a subtyping of $\langle t_1 \to t_2 \rangle$, except if it is empty (which is impossible by Lemma A.12).

▶ Lemma A.14. If ε is well-typed in an environment Γ (i.e. if $\Gamma \vdash \varepsilon$: t holds for some t), then $\Gamma \vdash \varepsilon$: typeof(ε).

Proof. By induction on ε . If it is a variable, a constant, or a function, the result is straightforward (note that $\mathbb{O} \to \mathbb{1}$ is greater than any functional type). If it is a pair, we apply the induction hypothesis and use rule [PAIR].

▶ Lemma A.15. Let $\bar{\varepsilon}$ be an expression generated by the grammar $\bar{\varepsilon} ::= c \mid \mu f : \mathcal{I}. \lambda x. e \mid (\bar{\varepsilon}, \bar{\varepsilon})$. Then, for every τ , either $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau$ or $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau$.

Proof. By induction on the pair $(\bar{\varepsilon}, \tau)$ and by case on $\bar{\varepsilon}$ and τ .

If $\tau = 0$, we have typeof($\bar{\varepsilon}$) $\leq \neg \tau$.

If $\tau = \tau_1 \vee \tau_2$, we apply the induction hypothesis to both τ_i . If $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau_1$ or $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau_2$, then $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau_1 \vee \tau_2$. Otherwise, we must have $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau_1$ and $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau_2$; hence, $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau_1 \wedge \neg \tau_2 \simeq \neg(\tau_1 \vee \tau_2)$.

If $\tau = \neg \tau'$, we apply the induction hypothesis to τ' . If $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau'$, then $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau$. Conversely, if $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau'$, then $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau$.

If $\tau = b$ and $\bar{\varepsilon} = c$, then $\mathsf{typeof}(\bar{\varepsilon}) = b_c$. Since $[\![b_c]\!] = \{c\}$, either $\mathsf{typeof}(\bar{\varepsilon}) \leq b$ or $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg b$ holds. If instead $\bar{\varepsilon}$ is not a constant, then $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg b$.

If $\tau = \tau_1 \otimes \tau_2$ and $\bar{\varepsilon} = (\bar{\varepsilon}_1, \bar{\varepsilon}_2)$, we apply the induction hypothesis to $(\bar{\varepsilon}_1, \tau_1)$ and $(\bar{\varepsilon}_2, \tau_2)$. If $\mathsf{typeof}(\bar{\varepsilon}_1) \leq \tau_1$ and $\mathsf{typeof}(\bar{\varepsilon}_2) \leq \tau_2$, then $\mathsf{typeof}((\bar{\varepsilon}_1, \bar{\varepsilon}_2)) \leq \tau_1 \otimes \tau_2$. Otherwise, $\mathsf{typeof}((\bar{\varepsilon}_1, \bar{\varepsilon}_2))$ must be subtype of one of the following $\mathsf{types}: \neg \tau_1 \times \tau_2, \tau_1 \times \neg \tau_2, \text{ or } \neg \tau_1 \times \neg \tau_2$. We also have $\mathsf{typeof}((\bar{\varepsilon}_1, \bar{\varepsilon}_2)) \leq \neg \bot \times \neg \bot$. The intersection of any of the three $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg(\tau_1 \otimes \tau_2)$. Finally, if $\bar{\varepsilon}$ is not a pair, then $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg(\tau_1 \otimes \tau_2)$.

If $\tau = \mathbb{O} \to \mathbb{1}$, then if $\bar{\varepsilon} = \mu f \colon \mathcal{I}. \lambda x. e$, we have $\mathsf{typeof}(\bar{\varepsilon}) \leq \tau$; otherwise, we have $\mathsf{typeof}(\bar{\varepsilon}) \leq \neg \tau$.

▶ Lemma A.16. Let v be a value that is well-typed in Γ (i.e. $\Gamma \vdash v : t'$ holds for some t'). Then, for every t, we have either $\Gamma \vdash v : t$ or $\Gamma \vdash v : \neg t$.

Proof. A value v is either a constant c or an abstraction $\mu f: \mathcal{I}. \lambda x. e$. If v = c, then $\Gamma \vdash v : b_c$ holds. By subsumption, we have $\Gamma \vdash v : t$ whenever $b_c \leq t$. By definition, $b_c \leq t$ is equivalent to $c \in \llbracket t \rrbracket$. Since $c \in \mathcal{D}$, for every type t, either $c \in \llbracket t \rrbracket$ or $c \in \llbracket \neg t \rrbracket = \mathcal{D} \setminus \llbracket t \rrbracket$ must hold. Hence, either $\Gamma \vdash v : t$ or $\Gamma \vdash v : \neg t$ is derivable.

Consider now $v = \mu f : \mathcal{I}. \lambda x. e$. Note that, since v is well-typed, we know by inversion of the typing rules that $\Gamma \vdash v : \mathcal{I}$ holds. We prove the result by induction on t.

If $t = \bot$, t = b, $t = t_1 \times t_2$, or t = 0, we have $\mathcal{I} \leq \neg t$ and hence $\Gamma \vdash v : \neg t$ holds.

If $t=t_1\to t_2$, either $\mathcal{I}\leq t_1\to t_2$ holds or not. If it holds, we can derive $\Gamma\vdash v\colon t_1\to t_2$ by subsumption. If it does not hold we have (by definition of subtyping) $\mathcal{I}\wedge\neg(t_1\to t_2)\not\simeq \emptyset$. We can therefore derive $\Gamma\vdash v\colon \mathcal{I}\wedge\neg(t_1\to t_2)$ and, by subsumption, $\Gamma\vdash v\colon \neg(t_1\to t_2)$.

If $t = t_1 \vee t_2$, we apply the induction hypothesis to t_1 and t_2 . If either $\Gamma \vdash v \colon t_1$ or $\Gamma \vdash v \colon t_2$ hold, $\Gamma \vdash v \colon t_1 \vee t_2$ holds by subsumption. Otherwise, we must have both $\Gamma \vdash v \colon \neg t_1$ and $\Gamma \vdash v \colon \neg t_2$. Then, by Lemma A.11, we have $\Gamma \vdash v \colon (\neg t_1) \wedge (\neg t_2)$ and, by subsumption, $\Gamma \vdash v \colon \neg (t_1 \vee t_2)$ since $(\neg t_1) \wedge (\neg t_2) \simeq \neg (t_1 \vee t_2)$.

If $t = \neg t'$, by the induction hypothesis we have either $\Gamma \vdash v : t'$ or $\Gamma \vdash v : \neg t'$. In the former case, we have $\Gamma \vdash v : \neg t$ since $t' \simeq \neg \neg t' = \neg t$; in the latter, we have $\Gamma \vdash v : t$.

▶ Corollary A.17. If $\Gamma \vdash v : \bigvee_{i \in I} t_i$, then there exists an $i_0 \in I$ such that $\Gamma \vdash v : t_{i_0}$.

Proof. By induction on |I|. If |I| = 1, the result is straightforward.

If |I|=2, that is, if $\Gamma \vdash v \colon t_1 \lor t_2$, either $\Gamma \vdash v \colon t_1$ holds or not. In the former case, the result holds. In the latter, by Lemma A.16, we must have $\Gamma \vdash v \colon \neg t_1$. Hence, by Lemma A.11, we have $\Gamma \vdash v \colon (t_1 \lor t_2) \land \neg t_1$, and $(t_1 \lor t_2) \land \neg t_1 \simeq (t_1 \land \neg t_1) \lor (t_2 \land \neg t_1) \leq t_2$, so we can derive $\Gamma \vdash v \colon t_2$ by subsumption.

If |I| = n > 2, we have $\Gamma \vdash v : (t_1 \lor \cdots \lor t_{n-1}) \lor t_n$. We apply the induction hypothesis to conclude.

▶ Lemma A.18. Let $\mathcal{I} = \bigwedge_{i \in I} t'_i \to t_i$ (with |I| > 0) be a type. There exists a type $\mathcal{I}' = \bigwedge_{k \in K} t'_k \to t_k$ (with |K| > 0) such that:

```
=\mathcal{I}\simeq\mathcal{I}';
```

 $\forall k_1 \neq k_2 \in K. \ t_{k_1} \wedge t_{k_2} \simeq 0;$

 \blacksquare if $\Gamma \vdash (\mu f : \mathcal{I}. \lambda x. e) : \mathcal{I}$, then $\forall k \in K$. $\Gamma, f : \mathcal{I}, x : t'_k \vdash e : t_k$.

Proof. Given \mathcal{I} , we take

$$\mathcal{I}' = \bigwedge_{\varnothing \subseteq I' \subseteq I} s_{I'} \to u_{I'} \quad \text{where } s_{I'} \stackrel{\text{def}}{=} \bigwedge_{i \in I'} t'_i \land \bigwedge_{i \in I \setminus I'} \neg t'_i \text{ and } u_{I'} \stackrel{\text{def}}{=} \bigwedge_{i \in I'} t_i$$

(defining $\bigwedge_{i\in\mathcal{O}} \neg t_i'$ to be 1). By Lemma A.5, we have $\mathcal{I}\simeq\mathcal{I}'$. To prove that the domains are pairwise disjoint, let I_1' and I_2' be two non-empty, arbitrary subsets of I; if $I_1'\neq I_2'$, then there exists an $i_0\in I$ which is in one set and not in the other. Assume, without loss of generality, $i_0\in I_1'$ and $i_0\notin I_2'$. Then:

$$\begin{split} s_{I_1'} \wedge s_{I_2'} &= \left(\bigwedge_{i \in I_1'} t_i' \wedge \bigwedge_{i \in I \setminus I_1'} \neg t_i' \right) \wedge \left(\bigwedge_{i \in I_2'} t_i' \wedge \bigwedge_{i \in I \setminus I_2'} \neg t_i' \right) \\ &\simeq \left(t_{i_0}' \wedge \bigwedge_{i \in I_1' \setminus \{i_0\}} t_i' \wedge \bigwedge_{i \in I \setminus I_1'} \neg t_i' \right) \wedge \left(\neg t_{i_0}' \wedge \bigwedge_{i \in I_2'} t_i' \wedge \bigwedge_{i \in I \setminus \{i_0\} \setminus I_2'} \neg t_i' \right) \\ &\simeq t_{i_0}' \wedge \neg t_{i_0}' \wedge \left(\bigwedge_{i \in I_1' \setminus \{i_0\}} t_i' \wedge \bigwedge_{i \in I \setminus I_1'} \neg t_i' \right) \wedge \left(\bigwedge_{i \in I_2'} t_i' \wedge \bigwedge_{i \in I \setminus \{i_0\} \setminus I_2'} \neg t_i' \right) \\ &\simeq \emptyset . \end{split}$$

To prove the third condition, note that $\Gamma \vdash (\mu f \colon \mathcal{I}. \lambda x. e) \colon \mathcal{I}$ implies that, for every $i \in I$, we can derive $\Gamma, f \colon \mathcal{I}, x \colon t'_i \vdash e \colon t_i$. Now consider an arbitrary I' such that $\varnothing \subsetneq I' \subseteq I$. We must show $\Gamma, f \colon \mathcal{I}, x \colon s_{I'} \vdash e \colon u_{I'}$. Note that $s_{I'} \leq t'_i$ for every $i \in I'$. Hence, by Lemma A.10, we have (for all $i \in I'$) $\Gamma, f \colon \mathcal{I}, x \colon s_{I'} \vdash e \colon t_i$. By Lemma A.11, we have $\Gamma, f \colon \mathcal{I}, x \colon s_{I'} \vdash e \colon u_{I'}$ since $u_{I'} = \bigwedge_{i \in I'} t_i$.

▶ Lemma A.19 (Expression substitution). If $\Gamma, x: t' \vdash e: t$ and $\Gamma \vdash e': t'$, then $\Gamma \vdash e[e'/x]: t$.

Proof. By induction on the derivation of $\Gamma, x: t' \vdash e: t$ and by case on the last rule applied.

▶ Lemma A.20. If $\Gamma \vdash (e_1, e_2)$: $\bigvee_{i \in I} t_i$, then there exist two types $\bigvee_{j \in J} t_j$ and $\bigvee_{k \in K} t_k$ such that

$$\Gamma \vdash e_1 \colon \bigvee\nolimits_{i \in J} t_i \qquad \Gamma \vdash e_2 \colon \bigvee\nolimits_{k \in K} t_k \qquad \forall j \in J. \ \forall k \in K. \ \exists i \in I. \ t_j \times t_k \leq t_i \ .$$

Proof. Since $\Gamma \vdash (e_1, e_2) \colon \bigvee_{i \in I} t_i$, by inversion of the typing derivation, we have $\Gamma \vdash e_1 \colon t^1$, $\Gamma \vdash e_2 \colon t^2$, and $t^1 \times t^2 \leq \bigvee_{i \in I} t_i$.

If $t^1 \simeq 0$ or $t^2 \simeq 0$, then we choose $\bigvee_{j \in J} t_j = t^1$ and $\bigvee_{k \in K} t_k = t^2$ (i.e. |J| = |K| = 1), which ensures the result.

Now we assume $t^1 \not\simeq \mathbb{0}$ and $t^2 \not\simeq \mathbb{0}$. We have $t^1 \times t^2 \simeq (\bigvee_{i \in I} t_i) \wedge (t^1 \times t^2) \simeq \bigvee_{i \in I} (t_i \wedge (t^1 \times t^2))$. For every i, we have $t_i \wedge (t^1 \times t^2) \leq \mathbb{1} \times \mathbb{1}$; therefore, by Lemma A.7, we can find a

product decomposition Π_i such that $t_i \wedge (t^1 \times t^2) \simeq \bigvee_{(t_1,t_2) \in \Pi_i} t_1 \times t_2$. Then, $\Pi = \bigcup_{i \in I} \Pi_i$ is itself a product decomposition, such that $\bigvee_{(t_1,t_2) \in \Pi} t_1 \times t_2 \simeq t^1 \times t^2$.

By Lemma A.8, there exists a fully disjoint product decomposition Π' such that

$$\bigvee_{(t_1,t_2)\in\Pi} t_1 \times t_2 \simeq \bigvee_{(t_1,t_2)\in\Pi'} t_1 \times t_2 \qquad \forall (t_1',t_2')\in\Pi'. \ \exists (t_1,t_2)\in\Pi. \ t_1' \times t_2' \leq t_1 \times t_2 \ .$$

Since $t^1 \times t^2 \simeq \bigvee_{(t_1,t_2)\in\Pi'} t_1 \times t_2$, by Lemma A.9 we have

$$\begin{split} t^1 &\simeq \bigvee_{(t_1,t_2) \in \Pi'} t_1 \qquad t^2 \simeq \bigvee_{(t_1,t_2) \in \Pi'} t_2 \\ &\forall (t_1',t_2'), (t_1'',t_2'') \in \Pi' \, . \exists (t_1,t_2) \in \Pi' . \, t_1' \times t_2'' \leq t_1 \times t_2 \; . \end{split}$$

We take the two decompositions above for t^1 and t^2 : by subsumption, we have

$$\Gamma \vdash e_1 \colon \bigvee_{(t_1,t_2) \in \Pi'} t_1 \qquad \Gamma \vdash e_2 \colon \bigvee_{(t_1,t_2) \in \Pi'} t_2$$

It remains to prove that $\forall (t'_1,t'_2), (t''_1,t''_2) \in \Pi'$. $\exists i \in I. \ t'_1 \times t''_2 \leq t_i$. Consider two arbitrary (t'_1,t'_2) and (t''_1,t''_2) in Π' . There exists a $(t_1,t_2) \in \Pi'$ such that $t'_1 \times t''_2 \leq t_1 \times t_2$. Therefore, there exists also a $(t_1,t_2) \in \Pi$ such that $t'_1 \times t''_2 \leq t_1 \times t_2$. This $(t_1,t_2) \in \Pi$ belongs to some Π_i and therefore $t_1 \times t_2 \leq t_i$, implying also $t'_1 \times t''_2 \leq t_i$.

▶ Lemma A.21. If $\Gamma \vdash E[x]$: t, then $x \in dom(\Gamma)$.

Proof. By induction on the derivation of $\Gamma \vdash E[x]$: t and by case on the last rule applied.

- \blacksquare [VAR]: we have E[T] = x and $x \in dom(\Gamma)$.
- [Const], [Abstr], [Pair]: impossible, since E[x] cannot be a constant, a function, or a pair.
- [APPL]: we have $E[x] = e_1 e_2$, therefore $E = E' e_2$ and $e_1 = E'[x]$; we conclude by applying the induction hypothesis to the derivation of $\Gamma \vdash e_1 : \langle t' \to t \rangle$.
- [ProJ]: we have $E[x] = \pi_i e$, therefore $E = \pi_i E'$ and e = E'[x]; we conclude by applying the induction hypothesis to the derivation of $\Gamma \vdash e : \langle t_1 \times t_2 \rangle$.
- [Case]: we have $E[x] = (y = \varepsilon) \in \tau$? $e_1 : e_2$, therefore $E = (y = F) \in \tau$? $e_1 : e_2$ and $\varepsilon = F[x]$ (hence, $x \neq y$); we also have that ε is well-typed in Γ , so we can conclude by showing, by induction on F, that $\Gamma \vdash F[x] : t$ implies $x \in \mathsf{dom}(\Gamma)$.
- [Let]: since $E[x] = (\text{let } y = e_1 \text{ in } e_2)$ we have either $E = (\text{let } y = e_1 \text{ in } E')$ and $e_2 = E'[x]$ or E = (let y = E' in E''[y]) and $e_1 = E'[x]$; in both cases we have a derivation for E'[x] and, by the induction hypothesis, we derive $x \in \text{dom}(\Gamma)$ (in the first case, the derivation is in an environment $(\Gamma, y: t_i)$, but we have $x \neq y$).
- [Subsum]: we conclude by applying the induction hypothesis.

A.3 Type soundness for the internal language

▶ Theorem A.22 (Progress). Let Γ be a well-formed type environment. Let e be an expression that is well-typed in Γ (that is, $\Gamma \vdash e$: t holds for some t). Then e is an answer, or e is of the form E[x], or $\exists e'$. $e \leadsto e'$.

Proof. By induction on the derivation of $\Gamma \vdash e$: t and by case on the last typing rule applied.

Case [Var] In this case e = x, and therefore e has the form E[x]. Cases [Const], [Abstr], and [Pair] In all cases, e is an answer.

Case [Appl] We have

$$e = e_1 e_2 \qquad \Gamma \vdash e \colon \langle t \rangle \qquad \Gamma \vdash e_1 \colon \langle t' \to t \rangle \qquad \Gamma \vdash e_2 \colon t' .$$

We apply the induction hypothesis to e_1 . If e_1 reduces, then e reduces by the rule [CTX]. If e_1 is of the form E[x], then e is of the form E'[x] with $E' = E e_2$.

If e_1 is an answer, then by Lemma A.13 it is either of the form $\mu f: \mathcal{I}. \lambda x. e'$ or of the form let x = e'' in a. Therefore, e reduces by [APPL] or [APPLL].

Case [Proj] We have

$$e = \pi_i e'$$
 $\Gamma \vdash e : \langle t_i \rangle$ $\Gamma \vdash e' : \langle t_1 \times t_2 \rangle$.

We apply the induction hypothesis to e'. If e' reduces, then e reduces by the rule [CTX]. If it is of the form E[x], then e is of the form E'[x] with $E' = \pi_i E$.

If e' is an answer, then by Lemma A.13 it is either of the form (e_1, e_2) or of the form $\det x = e''$ in a. Then e reduces by [ProjL].

Case [Case] We have

$$e = ((x = \varepsilon) \in \tau ? e_1 : e_2)$$
 $\Gamma \vdash e : \langle t \rangle$ $\Gamma \vdash \varepsilon : \langle t' \rangle$
 $t' \leq \neg \tau \text{ or } \Gamma, x : (t' \land \tau) \vdash e_1 : t$ $t' \leq \tau \text{ or } \Gamma, x : (t' \setminus \tau) \vdash e_2 : t$.

We apply the induction hypothesis to ε . If it reduces, then e reduces by [CTX]. If it is of the form E[y], then we must have $\varepsilon = y$ and E = [] because all other productions in the grammar for E do not appear in the grammar for ε . Then, we have $\varepsilon = F[y]$ (with F = []), and hence e is of the form E[y] with $E = ((x = []) \in \tau ? e_1 : e_2)$.

If ε is an answer, it is either generated by the restricted grammar $\bar{\varepsilon} ::= c \mid \mu f \colon \mathcal{I}. \lambda x. e \mid (\bar{\varepsilon}, \bar{\varepsilon})$ (i.e. it does not contain variables except under abstractions) or not. In the latter case, ε is of the form F[y] for some F and y, and hence e is of the form E[y]. In the former case, by Lemma A.15, either $\exp(\varepsilon) \leq \tau$ or $\exp(\varepsilon) \leq \neg \tau$. Then e reduces by [CASE1] or [CASE2].

Case [Let] We have

$$e = (\mathsf{let}\, x = e_1 \;\mathsf{in}\; e_2) \qquad \Gamma \vdash e \colon t \qquad \Gamma \vdash e_1 \colon \bigvee\nolimits_{i \in I} t_i \qquad \forall i \in I. \; \Gamma, x \colon t_i \vdash e_2 \colon t \;.$$

Since Γ is well-formed, by Lemma A.12, we know that $\bigvee_{i\in I} t_i$ is not empty. As a consequence, at least one of the t_i is non-empty, and hence at least one of the environments $(\Gamma, x: t_i)$ is well-formed, and we can apply the induction hypothesis to it.

We derive that e_2 is an answer, or it has the form E[y], or it reduces. If e_2 is an answer, then e is an answer as well. If e_2 reduces, then e reduces by [CTX]. If e_2 is of the form E[y] for some context E and variable y, then either x = y or not. In the latter case, e is of the form E'[y] too.

If x = y, we apply the induction hypothesis to e_1 . If e_1 is of the form E''[z] for some context E'' and variable z, then e is of such form as well. If e_1 reduces, then e reduces by [CTX]. If e_1 is an answer, then e reduces by [LETV], [LETP], or [LETL].

Case [Subsum] We apply the induction hypothesis to the premise and conclude.

▶ Theorem A.23 (Subject reduction). Let Γ be a well-formed type environment. If $\Gamma \vdash e : t$ and $e \leadsto e'$, then $\Gamma \vdash e' : t$.

Proof. By induction on the derivation of $\Gamma \vdash e$: t and by case on the last typing rule applied.

Cases [Var], [Const], [Abstr], and [Pair] These cases do not occur, because $e \leadsto e'$ cannot hold when e is a variable, a constant, an abstraction, or a pair.

Case [Appl] We have

$$e = e_1 e_2 \qquad \Gamma \vdash e \colon \langle t \rangle \qquad \Gamma \vdash e_1 \colon \langle t' \to t \rangle \qquad \Gamma \vdash e_2 \colon t'$$
.

If $e_1 e_2 \leadsto e'$ occurs by the rule [CTX], then $e' = e'_1 e_2$ and, by the induction hypothesis, $\Gamma \vdash e'_1 : \langle t' \to t \rangle$: we apply [APPL] again to type e'.

If the reduction occurs by [APPL], we have

$$e = (\mu f: \mathcal{I}. \lambda x. e_3) e_2$$
 $e' = (\text{let } f = (\mu f: \mathcal{I}. \lambda x. e_3) \text{ in let } x = e_2 \text{ in } e_3)$

and we must show $\Gamma \vdash e' : \langle t \rangle$. Let $\mathcal{I} = \bigwedge_{i \in I} T'_i \to T_i$. The typing derivation for e is

$$[Appl] \frac{ [Abstr] \frac{\forall i \in I. \ \Gamma, f \colon \mathcal{I}, x \colon \langle T_i' \rangle \vdash e_3 \colon \langle T_i \rangle}{\Gamma \vdash (\mu f \colon \mathcal{I}. \ \lambda x. \ e_3) \colon \mathcal{I} \land \bigwedge_{j \in J} \neg (t_j' \to t_j)}{\Gamma \vdash (\mu f \colon \mathcal{I}. \ \lambda x. \ e_3) \colon \langle t' \to t \rangle} \frac{}{\Gamma \vdash e_2 \colon t'}$$

The side conditions of [ABSTR] and [SUBSUM] ensure

$$\mathcal{I} \wedge \bigwedge_{j \in J} \neg (t'_j \to t_j) \not\simeq \mathbb{0}$$
 $\mathcal{I} \wedge \bigwedge_{j \in J} \neg (t'_j \to t_j) \leq \langle t' \to t \rangle$

from which we have (by definition of subtyping) $\mathcal{I} \wedge \bigwedge_{j \in J} \neg (t'_j \to t_j) \leq t' \to t$ and, by Corollary A.3, $\mathcal{I} \leq t' \to t$.

By Lemma A.18, we find a type $\mathcal{I}' = \bigwedge_{k \in K} t'_k \to t_k$ such that $\mathcal{I} \simeq \mathcal{I}'$, that $t'_{k_1} \wedge t'_{k_2} \simeq \mathbb{O}$ when $k_1 \neq k_2$, and that, for all $k \in K$, $\Gamma, f \colon \mathcal{I}, x \colon t'_k \vdash e_3 \colon t_k$. Since $\mathcal{I} \leq t' \to t$, we also have $\mathcal{I}' \leq t' \to t$. By Corollary A.2, we have $t' \leq \bigvee_{k \in K} t'_k$. Let $\bar{K} = \{k \in K \mid t' \wedge t'_k \not \simeq \emptyset\}$. We have $t' \leq \bigvee_{k \in \bar{K}} t'_k$. By Corollary A.2, we also have $\bigvee_{k \in \bar{K}} t_k \leq t$ and therefore $\bigvee_{k \in \bar{K}} t_k \leq \langle t \rangle$.

We build the typing derivation for e' as follows:

$$\frac{\Gamma, f \colon \mathcal{I} \vdash e_2 \colon t'}{\Gamma, f \colon \mathcal{I} \vdash e_2 \colon \bigvee_{k \in \bar{K}} t'_k} \quad \forall k \in \bar{K}. \quad \frac{\Gamma, f \colon \mathcal{I}, x \colon t'_k \vdash e_3 \colon t_k}{\Gamma, f \colon \mathcal{I}, x \colon t'_k \vdash e_3 \colon \bigvee_{k \in \bar{K}} t_k}}{\Gamma, f \colon \mathcal{I}, x \colon t'_k \vdash e_3 \colon \langle t \rangle}$$

$$\frac{\Gamma \vdash (\mu f \colon \mathcal{I}.\ \lambda x.\ e_3) \colon \mathcal{I} \qquad \Gamma, f \colon \mathcal{I} \vdash (\mathsf{let}\ x = e_2 \mathsf{\ in\ } e_3) \colon \langle t \rangle}{\Gamma \vdash (\mathsf{let}\ f = (\mu f \colon \mathcal{I}.\ \lambda x.\ e_3) \mathsf{\ in\ } \mathsf{let}\ x = e_2 \mathsf{\ in\ } e_3) \colon \langle t \rangle}$$

If the reduction occurs by the rule [APPLL], we have

$$e = (\text{let } x = e'_1 \text{ in } a) e_2 \qquad e' = (\text{let } x = e'_1 \text{ in } a e_2)$$

and we must show $\Gamma \vdash e' : \langle t \rangle$. The typing derivation for e (collapsing the use of [Subsum]) is

$$\frac{\Gamma \vdash e_1' \colon \bigvee_{i \in I} t_i \quad \forall i \in I. \ \Gamma, x \colon t_i \vdash a \colon t''}{\Gamma \vdash (\mathsf{let} \ x = e_1' \ \mathsf{in} \ a) \colon \langle t' \to t \rangle} \ t'' \le \langle t' \to t \rangle \qquad \Gamma \vdash e_2 \colon t'}{\Gamma \vdash (\mathsf{let} \ x = e_1' \ \mathsf{in} \ a) \ e_2 \colon \langle t \rangle}$$

from which we build the needed derivation as follows:

$$\frac{\Gamma, x \colon t_i \vdash a \colon t^{\prime\prime}}{\Gamma, x \colon t_i \vdash a \colon \langle t^\prime \to t \rangle} \ t^{\prime\prime} \le \langle t^\prime \to t \rangle \qquad \Gamma \vdash e_2 \colon t^\prime}{\Gamma, x \colon t_i \vdash a \colon \langle t^\prime \to t \rangle} \\ \frac{\Gamma \vdash e_1^\prime \colon \bigvee_{i \in I} t_i \qquad \forall i \in I.}{\Gamma, x \colon t_i \vdash a \: e_2 \colon \langle t \rangle} \\ \Gamma \vdash (\mathsf{let} \ x = e_1^\prime \ \mathsf{in} \ a \: e_2) \colon \langle t \rangle$$

Case [Proj] We have

$$e = \pi_i e''$$
 $\Gamma \vdash e : \langle t_i \rangle$ $\Gamma \vdash e'' : \langle t_1 \times t_2 \rangle$.

If e reduces by rule [CTX], we obtain the result from the induction hypothesis. Otherwise, the reduction must occur by rule [PROJ] or rule [PROJL].

If [ProJ] applies, we have $e = \pi_i \ (e_1, e_2)$ and $e' = e_i$. We must show $\Gamma \vdash e_i \colon \langle t_i \rangle$. Note that we have $\Gamma \vdash (e_1, e_2) \colon \langle t_1 \times t_2 \rangle$: by inversion of the typing derivation, we have $\Gamma \vdash e_1 \colon t'_1, \ \Gamma \vdash e_2 \colon t'_2, \ \text{and} \ t'_1 \times t'_2 \le \langle t_1 \times t_2 \rangle$. By Lemma A.12, we know $t'_1 \not = \emptyset$ and $t'_2 \not = \emptyset$; hence, by definition of subtyping we have $t'_1 \le t_1$ and $t'_2 \le t_2$. Therefore we can derive $\Gamma \vdash e_i \colon \langle t_i \rangle$ by [Subsum].

If [ProjL] applies, we have $e = \pi_i$ (let x = e''' in a) and e' = (let <math>x = e''' in $\pi_i a$). The typing derivation for e (collapsing the use of [Subsum]) is

$$\frac{\Gamma \vdash e''' \colon \bigvee_{i \in I} t_i \qquad \forall i \in I. \ \Gamma, x \colon t_i \vdash a \colon t}{\Gamma \vdash (\mathsf{let} \ x = e''' \ \mathsf{in} \ a) \colon t} \underbrace{\Gamma \vdash (\mathsf{let} \ x = e''' \ \mathsf{in} \ a) \colon t}_{\Gamma \vdash \pi_i \ (\mathsf{let} \ x = e''' \ \mathsf{in} \ a) \colon \langle t_i \rangle}$$

from which we build the derivation for $\Gamma \vdash e' : \langle t_i \rangle$ as follows:

$$\frac{\Gamma \vdash e''' \colon \bigvee_{i \in I} t_i \quad \forall i \in I. \quad \frac{\Gamma, x \colon t_i \vdash a \colon t}{\Gamma, x \colon t_i \vdash \pi_i \ a \colon \langle t_i \rangle} \ t \leq \langle t_1 \times t_2 \rangle}{\Gamma \vdash (\mathsf{let} \ x = e''' \ \mathsf{in} \ \pi_i \ a) \colon \langle t_i \rangle}$$

Case [Case] We have

$$e = ((x = \varepsilon) \in \tau ? e_1 : e_2) \qquad \Gamma \vdash e : \langle t \rangle \qquad \Gamma \vdash \varepsilon : \langle t' \rangle$$

$$t' \leq \neg \tau \text{ or } \Gamma, x : (t' \land \tau) \vdash e_1 : t \qquad t' \leq \tau \text{ or } \Gamma, x : (t' \setminus \tau) \vdash e_2 : t.$$

If e reduces by rule [CTX], we obtain the result from the induction hypothesis. Otherwise, it reduces by either [CASE1] or [CASE2].

If [CASE2] applies, we proceed similarly. We have $e' = (\text{let } x = \varepsilon \text{ in } e_2)$ and $\text{typeof}(\varepsilon) \leq \neg \tau$. We have $\text{typeof}(\varepsilon) \leq \neg \bot$ because ε cannot be a variable (since in that case we would

have $\tau \simeq 0$, which is forbidden by the syntax). We can derive $\Gamma \vdash \varepsilon : t' \land \neg \tau$, and, if $\Gamma, x : (t' \setminus \tau) \vdash e_2 : t$ holds, $\Gamma \vdash e' : \langle t \rangle$. As before, we can show that $\Gamma, x : (t' \setminus \tau) \vdash e_2 : t$ must always hold by showing that the alternative, $t' \leq \tau$, cannot occur: if we had $t' \leq \tau$, we would have $\Gamma \vdash \varepsilon : \tau \land \neg \tau$, which is impossible.

Case [Let] We have

$$e = (\text{let } x = e_1 \text{ in } e_2)$$
 $\Gamma \vdash e : t$ $\Gamma \vdash e_1 : \bigvee_{i \in I} t_i$ $\forall i \in I. \ \Gamma, x : t_i \vdash e_2 : t$.

If e reduces by rule [CTX], we obtain the result from the induction hypothesis. Otherwise, e reduces by [LETV], [LETP], or [LETL].

If [Let V] applies, we have e = (let x = v in E[x]) and e' = (E[x])[v/x]. We must show $\Gamma \vdash e' \colon t$. Since $\Gamma \vdash v \colon \bigvee_{i \in I} t_i$, by Corollary A.17 we have $\Gamma \vdash v \colon t_{i_0}$ for some $i_0 \in I$. We also have $\Gamma, x \colon t_{i_0} \vdash E[x] \colon t$. By Lemma A.19, we derive $\Gamma \vdash (E[x])[v/x] \colon t$. If [Let P] applies, we have

$$e = (\text{let } x = (e'_1, e''_1) \text{ in } E_1^T \bar{x}_1^T)$$
 $e' = (\text{let } x' = e'_1 \text{ in let } x'' = e''_1 \text{ in } (E_1^T \bar{x}_1^T)[(x', x'')/x])$

and must show $\Gamma \vdash e' : t$. Since $\Gamma \vdash (e'_1, e''_1) : \bigvee_{i \in I} t_i$, by Lemma A.20 we can find two types $\bigvee_{j \in J} t_j$ and $\bigvee_{k \in K} t_k$ such that

$$\Gamma \vdash e'_1 \colon \bigvee_{i \in I} t_i \qquad \Gamma \vdash e''_1 \colon \bigvee_{k \in K} t_k \qquad \forall j \in J. \ \forall k \in K. \ \exists i \in I. \ t_j \times t_k \leq t_i.$$

We show $\Gamma \vdash e' : t$ by showing

$$\forall j \in J. \ \forall k \in K. \quad \Gamma, x' : t_j, x'' : t_k \vdash (E[x])[(x',x'')/x] : t$$

which can be derived by Lemma A.19 from

$$\forall j \in J. \ \forall k \in K. \ \begin{cases} \Gamma, x' \colon t_j, x'' \colon t_k \vdash (x', x'') \colon t_j \times t_k \\ \Gamma, x' \colon t_j, x'' \colon t_k, x \colon t_j \times t_k \vdash E[x] \colon t_k \end{cases}$$

For every j and k, the second derivation is obtained from

$$\forall i \in I. \ \Gamma, x \colon t_i \vdash E_{\scriptscriptstyle \parallel}^{\scriptscriptstyle \sqcap} x_{\scriptscriptstyle \parallel}^{\scriptscriptstyle \sqcap} \colon t$$

by weakening (Lemma A.10), because $t_i \times t_k \leq t_i$ for some $i \in I$.

If [Letl] applies, we have

$$e = (\operatorname{let} x = (\operatorname{let} y = e'' \operatorname{in} a) \operatorname{in} E_{\downarrow} x_{\downarrow})$$
 $e' = (\operatorname{let} y = e'' \operatorname{in} \operatorname{let} x = a \operatorname{in} E_{\downarrow} x_{\downarrow})$.

The typing derivation for e (collapsing the use of [Subsum]) is

$$\frac{\Gamma \vdash e'' \colon \bigvee_{j \in J} t_j \qquad \forall j \in J. \ \Gamma, y \colon t_j \vdash a \colon t'}{\Gamma \vdash (\mathsf{let} \ y = e'' \ \mathsf{in} \ a) \colon \bigvee_{i \in I} t_i} \quad \forall i \in I. \ \Gamma, x \colon t_i \vdash E[x] \colon t}$$

$$\Gamma \vdash (\mathsf{let} \ x = (\mathsf{let} \ y = e'' \ \mathsf{in} \ a) \ \mathsf{in} \ E[x]) \colon t$$

We show $\Gamma \vdash e' : t$ as follows:

$$\frac{\Gamma \vdash e'' \colon \bigvee_{j \in J} t_j \qquad \forall j \in J. \quad \frac{\Gamma, y \colon t_j \vdash a \colon \bigvee_{i \in I} t_i \qquad \forall i \in I. \ \Gamma, y \colon t_j, x \colon t_i \vdash E[x] \colon t}{\Gamma, y \colon t_j \vdash (\mathsf{let} \ x = a \ \mathsf{in} \ E[x]) \colon t}}{\Gamma \vdash \left(\mathsf{let} \ y = e'' \ \mathsf{in} \ \mathsf{let} \ x = a \ \mathsf{in} \ E[x]\right) \colon t}$$

The premise for the typing of $E[\Gamma]$ is derived by weakening (Lemma A.10): we can assume $y \notin dom(\Gamma)$ by α -renaming.

Case [Subsum] We have $\Gamma \vdash e : t'$ for some $t' \leq t$. By the induction hypothesis, we derive $\Gamma \vdash e' : t'$, and we apply [Subsum] to conclude.

▶ Corollary A.24 (Type soundness). Let e be a well-typed, closed expression (that is, $\varnothing \vdash e : t$ holds for some t). If $e \leadsto^* e'$ and e' cannot reduce, then e' is an answer and $\varnothing \vdash e' : t$.

A.4 Results on the source language

- ▶ Proposition A.25. If $\Gamma \vdash \mathbf{e} : t$, then $\Gamma \vdash [\mathbf{e}] : t$.
- ▶ Corollary A.26 (Type soundness for the source language). Let \mathbf{e} be a well-typed, closed source language expression (that is, $\varnothing \vdash \mathbf{e}$: t holds for some t). If $\lceil \mathbf{e} \rceil \leadsto^* e'$ and e' cannot reduce, then e' is an answer and $\varnothing \vdash e'$: t.

A.5 Interpreting types as sets of values

▶ Lemma A.27. Let $(\cdot): \mathcal{T} \to \mathcal{P}(\overline{\mathcal{D}})$ be a model. Let P and N be finite sets of types of the form $t_1 \to t_2$, with $P \neq \emptyset$. Then:

$$\begin{split} \exists t_1' \to t_2' \in N. & \ (\!\!| t_1' \setminus \bigvee_{t_1 \to t_2 \in P} t_1 \!\!|) = \varnothing \text{ and} \\ & \ (\forall P' \subsetneq P. & \ (\!\!| t_1' \setminus \bigvee_{t_1 \to t_2 \in P'} t_1 \!\!|) = \varnothing \text{ or } \ (\!\!| \bigwedge_{t_1 \to t_2 \in P \setminus P'} t_2 \setminus t_2' \!\!|) = \varnothing \big) \\ & \Longrightarrow \bigcap_{t_1 \to t_2 \in P} (\!\!| t_1 \to t_2 \!\!|) \subseteq \bigcup_{t_1 \to t_2 \in N} (\!\!| t_1 \to t_2 \!\!|) \end{split}$$

Proof. We define

$$\begin{split} &\operatorname{Tot}(X) \stackrel{\operatorname{def}}{=} \big\{\, R \in \mathcal{P}(\overline{\mathcal{D}} \times \overline{\mathcal{D}}) \mid \operatorname{dom}(R) \supseteq X \,\big\} \\ & X \rightharpoonup Y \stackrel{\operatorname{def}}{=} \big\{\, R \in \mathcal{P}(\overline{\mathcal{D}} \times \overline{\mathcal{D}}) \mid \forall (d,d') \in R. \, d \in X \implies d' \in \big\} \\ & X \rightharpoonup Y \stackrel{\operatorname{def}}{=} \big\{\, R \in \mathcal{P}(\overline{\mathcal{D}} \times \overline{\mathcal{D}}) \mid \operatorname{dom}(R) \supseteq X \text{ and } \forall (d,d') \in R. \, d \in X \implies d' \in Y \,\big\} \end{split}$$

and therefore we have $X \to Y = \mathsf{Tot}(X) \cap (X \rightharpoonup Y)$. We also have $X \rightharpoonup Y = \mathcal{P}(X \times \overline{Y}^{\overline{\mathcal{D}}})$, using the notation \overline{A}^B for $B \setminus A$.

To show $\bigcap_{t_1 \to t_2 \in P} (t_1 \to t_2) \subseteq \bigcup_{t_1 \to t_2 \in N} (t_1 \to t_2)$, by the definition of model, it suffices to show $\bigcap_{t_1 \to t_2 \in P} (t_1) \to (t_2) \subseteq \bigcup_{t_1 \to t_2 \in N} (t_1) \to (t_2)$. We will actually show $\bigcap_{t_1 \to t_2 \in P} (t_1) \to (t_2) \subseteq (t_1') \to (t_2')$, which is enough to conclude.

To show it, we first show $\bigcap_{t_1 \to t_2 \in P} (t_1) \rightharpoonup (t_2) \subseteq (t_1') \rightharpoonup (t_2')$, without the requirement of totality.

The premise

$$(\!\!|t_1'\setminus\bigvee_{t_1\to t_2\in P}t_1\!\!|)=\varnothing \text{ and } \big(\forall P'\subsetneq P. \ (\!\!|t_1'\setminus\bigvee_{t_1\to t_2\in P'}t_1\!\!|)=\varnothing \text{ or } (\!\!|\bigwedge_{t_1\to t_2\in P\setminus P'}t_2\setminus t_2'\!\!|)=\varnothing\big)$$

can be rewritten as

$$(\!\!|t_1'|\!\!|)\subseteq (\!\!|\bigvee_{t_1\to t_2\in P}t_1\!\!|) \text{ and } \big(\forall P'\subsetneq P. \ (\!\!|t_1'|\!\!|)\subseteq (\!\!|\bigvee_{t_1\to t_2\in P'}t_1\!\!|) \text{ or } (\!\!|\bigwedge_{t_1\to t_2\in P\setminus P'}t_2\!\!|)\subseteq (\!\!|t_2'\!\!|)\big)$$

and implies

$$(\!\!|t_1'|\!\!|)\subseteq\bigcup_{t_1\to t_2\in P}(\!\!|t_1|\!\!|) \text{ and } \big(\forall P'\subsetneq P. \ (\!\!|t_1'|\!\!|)\subseteq\bigcup_{t_1\to t_2\in P'}(\!\!|t_1|\!\!|) \text{ or } \overline{(\!\!|t_2'\!\!|)}^{\overline{D}}\subseteq\bigcup_{t_1\to t_2\in P\setminus P'}\overline{(\!\!|t_2|\!\!|)}^{\overline{D}}\big)$$

and therefore implies

$$\forall P' \subseteq P. \ \ (\![t_1']\!] \subseteq \bigcup_{t_1 \to t_2 \in P'} (\![t_1]\!] \ \text{or} \ \overline{(\![t_2']\!]}^{\overline{D}} \subseteq \bigcup_{t_1 \to t_2 \in P \backslash P'} \overline{(\![t_2]\!]}^{\overline{D}}$$

as well. We can apply Lemma 6.4 of [20] to obtain

$$(t_1') \times \overline{(t_2')}^{\overline{D}} \subseteq \bigcup_{t_1 \to t_2 \in P} (t_1) \times \overline{(t_2)}^{\overline{D}}$$

whence

$$\frac{\overline{\bigcup_{t_1 \to t_2 \in P} (t_1) \times \overline{(t_2)}} \overline{\mathcal{D}} \overline{\mathcal{D}} \times \overline{\mathcal{D}}}{\subseteq (t_1') \times \overline{(t_2')} \overline{\mathcal{D}}} \overline{\mathcal{D}} \times \overline{\mathcal{D}}$$

and

$$\bigcap_{t_1 \to t_2 \in P} \overline{(t_1) \times \overline{(t_2)}^{\overline{\mathcal{D}}}}^{\overline{\mathcal{D}} \times \overline{\mathcal{D}}} \subseteq \overline{(t_1') \times \overline{(t_2')}^{\overline{\mathcal{D}}}}^{\overline{\mathcal{D}} \times \overline{\mathcal{D}}}$$

and finally

$$\bigcap_{t_1 \to t_2 \in P} \mathcal{P} \Big(\overline{\|t_1\| \times \overline{\|t_2\|}^{\overline{\mathcal{D}}}} \overline{\mathcal{D}} \times \overline{\mathcal{D}} \Big) \subseteq \mathcal{P} \Big(\overline{\|t_1'\| \times \overline{\|t_2'\|}^{\overline{\mathcal{D}}}} \overline{\mathcal{D}} \times \overline{\mathcal{D}} \Big)$$

where note that the power set construction obtained is equivalent to the definition of \rightarrow . Now we have

$$\bigcap_{t_1 \to t_2 \in P} (t_1) \rightharpoonup (t_2) \subseteq (t_1') \rightharpoonup (t_2')$$

and we want

$$\bigcap_{t_1 \to t_2 \in P} (|t_1|) \to (|t_2|) \subseteq (|t_1'|) \to (|t_2'|),$$

that is,

$$\bigcap_{t_1 \to t_2 \in P} \left(\mathsf{Tot}(\langle\!\langle t_1 \rangle\!\rangle) \cap (\langle\!\langle t_1 \rangle\!\rangle \rightharpoonup \langle\!\langle t_2 \rangle\!\rangle) \right) \subseteq \mathsf{Tot}(\langle\!\langle t_1' \rangle\!\rangle) \cap (\langle\!\langle t_1' \rangle\!\rangle \rightharpoonup \langle\!\langle t_2' \rangle\!\rangle) .$$

The latter is further equivalent to

$$\operatorname{Tot}((\!\![\bigvee_{t_1 \to t_2 \in P} t_1 \!\!])) \cap \bigcap_{t_1 \to t_2 \in P} ((\!\![t_1]\!\!]) \rightharpoonup (\!\![t_2]\!\!]) \subseteq \operatorname{Tot}((\!\![t_1'\!\!])) \cap ((\!\![t_1'\!\!]) \rightharpoonup (\!\![t_2'\!\!])) \,.$$

Note that $(t_1' \setminus \bigvee_{t_1 \to t_2 \in P} t_1) = \emptyset$ implies $(t_1') \subseteq (\bigvee_{t_1 \to t_2 \in P} t_1)$. Therefore, we have $\mathsf{Tot}((t_1')) \supseteq \mathsf{Tot}((\bigvee_{t_1 \to t_2 \in P} t_1))$. This allows us to conclude that the containment above holds.

▶ Proposition A.28. Let (\cdot) : $\mathcal{T} \to \mathcal{P}(\overline{\mathcal{D}})$ be a model. Let t_1 and t_2 be two finite (that is, non-recursive) types. If $[t_1] \subseteq [t_2]$, then $(t_1) \subseteq (t_2)$.

Proof. First, note that $[t_1] \subseteq [t_2] \iff [t_1 \setminus t_2] = \emptyset$ and that $(t_1) \subseteq (t_2) \iff (t_1 \setminus t_2) = \emptyset$. We therefore show this equivalent proposition: for all finite t, if $[t] = \emptyset$, then $(t) = \emptyset$.

We define the function $h(\cdot)$ on finite types by structural induction as follows:

$$h(\perp) = h(b) = h(0) = 0$$
 $h(t_1 \times t_2) = h(t_1 \to t_2) = \max(h(t_1), h(t_2)) + 1$
 $h(t_1 \vee t_2) = \max(h(t_1), h(t_2))$ $h(\neg t) = h(t)$

That is, h(t) is the maximum number of \times and \to constructors found on paths from the root of t to the leaves. We use $h(\cdot)$ as the measure for induction.

Now, let us consider an arbitrary finite type t such that $[\![t]\!] = \varnothing$. We want to show $(\![t]\!] = \varnothing$.

In the following, we refer to a type of the form \bot , b, $t_1 \times t_2$, or $t_1 \to t_2$ as an atom. We refer to a finite set of pairs of finite sets of atoms (that is, to a set $\{(P_i, N_i) \mid i \in I\}$ where I is finite and where each P_i and N_i is a finite set of atoms) as a disjunctive normal form.

We define the $dnf(\cdot)$ and $dnf^-(\cdot)$ functions as follows (by mutual induction):

$$\begin{split} \operatorname{dnf}(t) &= \{(\{t\},\varnothing)\} & \text{if } t \text{ is an atom} \\ \operatorname{dnf}(t_1 \vee t_2) &= \operatorname{dnf}(t_1) \cup \operatorname{dnf}(t_2) \\ \operatorname{dnf}(\neg t) &= \operatorname{dnf}^-(t) \\ \operatorname{dnf}(\mathbb{O}) &= \varnothing \\ \operatorname{dnf}^-(t) &= \{(\varnothing, \{t\})\} & \text{if } t \text{ is an atom} \\ \operatorname{dnf}^-(t_1 \vee t_2) &= \{(P_1 \cup P_2, N_1 \cup N_2) \mid (P_1, N_1) \in \operatorname{dnf}^-(t_1), (P_2, N_2) \in \operatorname{dnf}^-(t_2)\} \\ \operatorname{dnf}^-(\neg t) &= \operatorname{dnf}(t) \\ \operatorname{dnf}^-(\mathbb{O}) &= \{(\varnothing, \varnothing)\} \end{split}$$

We extend $[\cdot]$ to disjunctive normal forms by defining

$$\llbracket \{ (P_i, N_i) \mid i \in I \} \rrbracket = \bigcup_{i \in I} \left(\bigcap_{t \in P_i} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) \right)$$

where by convention $\bigcap_{t\in\varnothing} \llbracket t \rrbracket = \mathcal{D}$. We can check by induction that, for all types t, $\llbracket t \rrbracket = \llbracket \mathsf{dnf}(t) \rrbracket = \mathcal{D} \setminus \llbracket \mathsf{dnf}^-(t) \rrbracket$.

We extend (\cdot) to disjunctive normal forms likewise; it holds that $(t) = (dnf(t)) = \overline{D} \setminus (dnf^-(t))$.

Let
$$\{(P_i, N_i) \mid i \in I\} = \mathsf{dnf}(t)$$
. Since $[t] = \emptyset$, we have

$$\forall i \in I. \bigcap_{t \in P_i} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing.$$

We want to show

$$\forall i \in I. \bigcap_{t \in P_i} (t) \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus (t)) = \emptyset.$$

which would conclude our proof.

Let us partition atoms into four kinds, according to their form: \bot , b, $t_1 \times t_2$, or $t_1 \to t_2$. Note that if t_1 and t_2 are two atoms of different kind, then $(t_1) \cap (t_2) = \emptyset$ (the same holds for $\llbracket \cdot \rrbracket$).

Now, let us consider an arbitrary $i \in I$. Either P_i is empty or it contains at least one atom. First we show that if P_i contains atoms of at least two different kinds, then $\bigcap_{t \in P_i} (t) \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus (t))$ is empty. This holds because the intersection is a subset of $(t_1) \cap (t_2)$, where t_1 and t_2 are two atoms of different kind in P_i , and we have remarked that atoms of different kinds have disjoint interpretations.

There remain two cases to consider: $P_i = \emptyset$ or P_i non-empty and composed of atoms of a single kind. We consider the case $P_i = \emptyset$ first. Note that in that case

$$\begin{split} \bigcap_{t \in P_i} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) &= \mathcal{D} \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) \\ &= (\{\bot\} \cup \mathcal{C} \cup \llbracket \mathbb{1} \times \mathbb{1} \rrbracket \cup \llbracket \mathbb{0} \to \mathbb{1} \rrbracket) \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) \end{split}$$

because the domain \mathcal{D} can be decomposed as a union of four sets corresponding to the four kinds of atoms. Since the intersection is empty, we have

$$\{\bot\} \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing \qquad \qquad \mathcal{C} \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$
$$\llbracket \mathbb{1} \times \mathbb{1} \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing \qquad \qquad \llbracket \mathbb{0} \to \mathbb{1} \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$

Setting aside the intersection with $\mathcal C$ for a moment, observe that the others are equivalent to

$$\bigcap_{t \in \{\bot\}} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$

$$\bigcap_{t \in \{\mathbb{1} \times \mathbb{1}\}} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$

$$\bigcap_{t \in \{\mathbb{0} \to \mathbb{1}\}} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$

so they can be treated together with the case of non-empty P_i .

As for the intersection with \mathcal{C} , if $\mathcal{C} \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$, then $\mathcal{C} \subseteq \bigcup_{b \in N_i} \mathbb{B}(b)$ (we can ignore atoms of different kind in N_i). But then $\mathcal{C} \subseteq \bigcup_{b \in N_i} (b)$, and therefore $\mathcal{C} \subseteq \bigcup_{t \in N_i} (t)$, which shows that $\mathcal{C} \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus (t)) = \varnothing$.

Now, assuming

$$\{\bot\} \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus \{t\}) = \varnothing \qquad \qquad \mathcal{C} \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus \{t\}) = \varnothing$$
$$(\mathbb{1} \times \mathbb{1}) \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus \{t\}) = \varnothing \qquad \qquad (\mathbb{0} \to \mathbb{1}) \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus \{t\}) = \varnothing$$

we have

$$(\{\bot\} \cup \mathcal{C} \cup (\mathbb{1} \times \mathbb{1}) \cup (\mathbb{0} \to \mathbb{1})) \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus (t)) = \varnothing$$

which is

$$\overline{\mathcal{D}} \cap \bigcap_{t \in N_i} (\overline{\mathcal{D}} \setminus (t)) = \varnothing$$
.

We now consider the remaining case. That is, we assume

$$\bigcap_{t \in P_i} \llbracket t \rrbracket \cap \bigcap_{t \in N_i} (\mathcal{D} \setminus \llbracket t \rrbracket) = \varnothing$$

with P_i non-empty and formed of atoms of a single kind, and we show

$$\bigcap_{t\in P_i} \langle\!\!\langle t \rangle\!\!\rangle \cap \bigcap_{t\in N_i} (\overline{\mathcal{D}} \setminus \langle\!\!\langle t \rangle\!\!\rangle) = \varnothing \ .$$

Equivalently, we assume $\bigcap_{t \in P_i} \llbracket t \rrbracket \subseteq \bigcup_{t \in N_i} \llbracket t \rrbracket$ and we show $\bigcap_{t \in P_i} (\!\![t]\!\!] \subseteq \bigcup_{t \in N_i} (\!\![t]\!\!]$. In doing so, we can disregard the atoms in N_i that are not of the same kind as those in P_i . Therefore, we consider that N_i only contains atoms of that same kind.

If the atoms of P_i are of the kind of \bot (that is, if $P_i = \{\bot\}$) or if they are basic types, the result is immediate because the two interpretations are defined identically on these kinds of atoms.

If the atoms of P_i are all products, then we have (by Lemmas 6.4 and 6.5 of [20]):

$$\bigcap_{t \in P_i} \llbracket t \rrbracket \subseteq \bigcup_{t \in N_i} \llbracket t \rrbracket \iff \\ \forall N \subseteq N_i. \ \left[\bigwedge_{t_1 \times t_2 \in P_i} t_1 \wedge \bigwedge_{t_1 \times t_2 \in N} \neg t_1 \right] = \varnothing \text{ or } \left[\bigwedge_{t_1 \times t_2 \in P_i} t_2 \wedge \bigwedge_{t_1 \times t_2 \in N_i \backslash N} \neg t_2 \right] = \varnothing$$

(with the convention $\bigwedge_{t_1 \times t_2 \in \varnothing} \neg t_i = \mathcal{D}$). Since (\cdot) also satisfies $(t_1 \times t_2) = (t_1) \times (t_2)$, we also have

$$\bigcap_{t \in P_i} \langle t \rangle \subseteq \bigcup_{t \in N_i} \langle t \rangle \iff$$

$$\forall N \subseteq N_i. \ (\bigwedge_{t_1 \times t_2 \in P_i} t_1 \wedge \bigwedge_{t_1 \times t_2 \in N} \neg t_1 \rangle = \varnothing \text{ or } (\bigwedge_{t_1 \times t_2 \in P_i} t_2 \wedge \bigwedge_{t_1 \times t_2 \in N_i \setminus N} \neg t_2 \rangle = \varnothing$$

(with the convention $\bigwedge_{t_1 \times t_2 \in \varnothing} \neg t_i = \mathcal{D}^{\text{tot}}$). This allows us to conclude $\bigcap_{t \in P_i} (t) \subseteq \bigcup_{t \in N_i} (t)$, because we can apply the induction hypothesis to all the types $\bigwedge_{t_1 \times t_2 \in P_i} t_1 \wedge \bigwedge_{t_1 \times t_2 \in N} \neg t_1$

XX:40 Semantic subtyping for non-strict languages

and $\bigwedge_{t_1 \times t_2 \in P_i} t_2 \wedge \bigwedge_{t_1 \times t_2 \in N_i \setminus N} \neg t_2$. Indeed, note that $h(\cdot)$ on these types is always strictly less than $\max\{h(t_1 \times t_2) \mid t_1 \times t_2 \in P_i \cup N_i\}$, because the \times constructor has been eliminated. Also, $h(t) \ge \max\{h(t_1 \times t_2) \mid t_1 \times t_2 \in P_i \cup N_i\}$ because any atom $t_1 \times t_2$ appeared under t.

The last case to examine is that of P_i composed only of arrow types. In that case, by Lemma A.1, we have

$$\begin{split} \bigcap_{t_1 \to t_2 \in P_i} \llbracket t_1 \to t_2 \rrbracket \subseteq \bigcup_{t_1 \to t_2 \in N_i} \llbracket t_1 \to t_2 \rrbracket \iff \\ \exists t_1' \to t_2' \in N_i. \ \llbracket t_1' \setminus \bigvee_{t_1 \to t_2 \in P_i} t_1 \rrbracket = \varnothing \text{ and} \\ \left(\forall P \subsetneq P_i. \ \llbracket t_1' \setminus \bigvee_{t_1 \to t_2 \in P} t_1 \rrbracket = \varnothing \text{ or } \llbracket \bigwedge_{t_1 \to t_2 \in P_i \setminus P} t_2 \setminus t_2' \rrbracket = \varnothing \right) \end{split}$$

and, by Lemma A.27,

$$\begin{split} \exists t_1' \to t_2' \in N_i. \ \, (\!\!\mid\! t_1' \setminus \bigvee_{t_1 \to t_2 \in P_i} t_1 \!\!\mid) &= \varnothing \text{ and } \\ \big(\forall P \subsetneq P_i. \ \, (\!\!\mid\! t_1' \setminus \bigvee_{t_1 \to t_2 \in P} t_1 \!\!\mid) &= \varnothing \text{ or } (\!\!\mid\! \bigwedge_{t_1 \to t_2 \in P_i \setminus P} t_2 \setminus t_2' \!\!\mid) &= \varnothing \big) \\ &\Longrightarrow \bigcap_{t_1 \to t_2 \in P_i} (\!\!\mid\! t_1 \to t_2 \!\!\mid) \subseteq \bigcup_{t_1 \to t_2 \in N_i} (\!\!\mid\! t_1 \to t_2 \!\!\mid) \end{split}$$

and we can therefore conclude by applying the induction hypothesis (with the same argument as before to show that $h(\cdot)$ decreases).