BioSentVec: creating sentence embeddings for biomedical texts

Qingyu Chen¹, Yifan Peng¹, and Zhiyong Lu²

National Center for Biotechnology Information (NCBI)
National Library of Medicine (NLM)
National Institutes of Health (NIH)
8600 Rockville Pike, Bethesda, MD 20894, USA

Abstract

Sentence embeddings have become an essential part of today's natural language processing (NLP) systems, especially together advanced deep learning methods. Although pre-trained sentence encoders are available in the general domain, none exists for biomedical texts to date. In this work, we introduce BioSentVec: the first open set of sentence embeddings trained with over 30 million documents from both scholarly articles in PubMed and clinical notes in the MIMIC-III Clinical Database. We evaluate BioSentVec embeddings in two sentence pair similarity tasks in different text genres. Our benchmarking results demonstrate that the BioSentVec embeddings can better capture sentence semantics compared to the other competitive alternatives and achieve state-of-the-art performance in both tasks. We expect BioSentVec to facilitate the research and development in biomedical text mining and to complement the existing resources in biomedical word embeddings.

BioSentVec is publicly available at https://github.com/ncbi-nlp/BioSentVec.

1 Introduction

Capturing sentence semantics plays a critical role in biomedical text and data mining research. Traditional methods that rely on bag-of-words may not model such information accurately due to language richness ambiguity. For instance, different sentences can be used to describe similar findings (e.g., 'It has recently been shown that Craf is essential for Kras^{G12D}-induced NSCLC.' versus 'It has recently become evident that Craf is essential for the onset of Kras-driven non-small cell lung cancer.') [1]. In response, embedding-based approaches have shown promising results recently as the semantic is represented by high dimensional vectors regardless whether the same set of words are used. Such vector-based representations are commonly learnt from large text corpora [2] have becoming increasingly important in today's text mining research, especially when used as input in advanced deep learning techniques [3,4].

Representative sentence embeddings are doc2vec [5], Universal Sentence Encoder [6], and sent2vec [7]. However, to the best of our knowledge, there is no publicly available sentence embeddings in biomedicine, in spite of many biomedical use cases and sentence-based applications, such as finding relevant or evident sentences for information retrieval [1], biomedical sentence classification [8], or biomedical question answering [9]. As a result, researchers would need either train sentence embeddings on their own from scratch (a data and time-intensive process, together with selection of best model parameters), derive them from individual word embeddings (loss of information about the entire sentence), or use pre-trained sentence embeddings from the general domain (may suffer from the out-of-domain issue). Due to aforementioned problems, suboptimal performance may be obtained.

To facilitate text mining research in biomedicine, we present BioSentVec, a pre-trained model for readily generating sentence embeddings given as input any arbitrary sentence. Specifically, BioSentVec is created by applying sent 2vec, a cutting-edge unsupervised model, to both biological and clinical texts at a large scale. In benchmarking, BioSentVec shows superior performance on two public datasets for computing sentence similarity, compared to the current state of the art.

2 Method and Materials

To maximize the robustness and generalizability of BioSentVec on different text genres in biomedicine, BioSentVec embeddings are trained using both PubMed and the clinical notes from MIMIC-III Clinical Database [10]. Collec-

¹The first two authors contributed equally to this work.

²Correspondence: zhiyong.lu@nih.gov

tively, they consist of more than 30 million documents, ~ 223 million sentences, and ~ 5 billion tokens. The detail statistics are summarized in Table 1.

Table 1: Corpora for training embeddings.

	Documents	Sentences	Tokens
PubMed	28,714,373	181,634,210	4,354,171,148
MIMIC III Clinical notes	2,083,180	41,674,775	539,006,967

Both PubMed and MIMIC-III texts were split and tokenized using NLTK [11]. We then trained our sentence embeddings using sent2vec [7]. It adapts the Continuous Bag-of-Words model - known for training word embeddings - at the sentence level, and extends the model by using n-grams of sentences. By far, it achieves the state-of-the-art performance in a range of text mining tasks in the general domain. In this work, we obtained 700-dimensional vectors by applying its bigram model with a window size of 30 and negative examples of 10, after a set of experiments with various settings (see results online).

We evaluate BioSentVec for the task of finding similar sentences on two separate datasets. BIOSSES consists of 100 sentence pairs from PubMed articles annotated by 5 curators [1]. MedSTS consists of 1,068 sentence pairs from clinical notes where 750 and 318 pairs are used for training and testing, respectively [12]. Stop words and punctuations are removed in all these sentences. Pearson correlation coefficient is used to compare the algorithm results with the gold standard.

Both unsupervised and supervised methods have been attempted in the past on these two datasets. In the unsupervised fashion, previous best-performing approaches used doc2vec and Levenshtein Distance for BIOSSES and MEDSTS, respectively. Instead, we propose several alternatives: sentence embeddings derived by averaging word embeddings (pre-trained in [3]) or directly from pre-trained sentence encoders (BioSentVec or Universal Sentence Encoder). In the supervised setting, previous methods made use of ensemble learning that aggregates a range of human engineered features, including the use of embeddings. In comparison, we propose a straightforward 5-layer deep learning model, which takes two sentence vectors as inputs. The first layer concatenates the two sentence vectors, their absolute differences, multiplications and the dot product. It is then followed by three dense layers of 256, 128, and 64 hidden units, respectively. The final layer is the prediction layer, which outputs the predicted similarity for a sentence pair. For each dense layer, we initialized the weights with Xavier normal initializer. We set bias to be 0.01 and activation function to be ReLU. To train the model, we used SGD as the optimizer with a learning rate of 0.001, mean squared error as the loss function, and a batch size of 8. To prevent overfitting, we used L2 regularization and dropout (p=0.5). The model was run via 1000 epochs and the model with the lowest loss on the validation set was saved.

For BIOSSES, we report different algorithm performance using 10-fold stratified cross-validation as in [1]. For MED-STS, we report the results on the held-out test set.

3 Results and Discussions

Table 2 demonstrates that the highest performance was obtained based on the proposed BioSentVec embeddings in both supervised and unsupervised methods, suggesting BioSentVec can capture sentence meanings consistently better than other approaches such as averaged word vectors or sentence vectors trained from the general domain. For example, a single deep learning model is able to achieve the best results without the need of a complex ensemble approach. BioSentVec also appear to be robust and generalizable on different text genres in biomedicine.

Furthermore, the results in Table 2 show that BioSentVec trained from both PubMed and clinical notes generally have better performance than from a single source (with one exception). It also shows that BioSentVec trained from clinical notes only is not sufficient when used in applications dealing with PubMed articles.

In summary, we introduced a new set of sentence embeddings pre-trained on two different corpora in biomedicine and demonstrated its superior performance in benchmarking. All the embeddings trained with different sources, together

Table 2: Sentence similarity evaluation results.

	BIOSSES	MEDSTS
Unsupervised		
doc2vec[1]*	0.787	_
Levenshtein Distance [12]* [†]	-	0.680
Averaged word embeddings [3]	0.694	0.747
Universal Sentence Encoder [6]	0.345	0.714
BioSentVec (PubMed)	0.817	0.750
BioSentVec (MIMIC-III)	0.350	0.759
BioSentVec (PubMed + MIMIC-III)	0.795	0.767
Supervised		
Regression model [1]*	0.836	_
Random Forest [13]*	_	0.818
Deep learning + Average word embeddings [3]	0.703	0.784
Deep learning + Universal Sentence Encoder [6]	0.401	0.774
Deep learning + BioSentVec (PubMed)	0.824	0.819
Deep learning + BioSentVec (MIMIC-III)	0.353	0.805
Deep learning + BioSentVec (PubMed + MIMIC-III)	0.848	0.836

^{*} The previous best results in terms of single models in literature.

with our deep learning models, are made publicly available. We hope BioSentVec can facilitate the development of deep learning models and text mining applications in biomedical research.

Funding

This research was supported by the Intramural Research Program of the NIH, National Library of Medicine.

Acknowledgements

The authors thank Dr. Yijia Zhang and Dr. Alexis Allot for helpful discussion. We are grateful to the authors of fastText, sent2vec, MayoSRS, UMNSRS, BIOSSES, and MedSTS for making their software and data publicly available.

References

- [1] G. Sogancioglu, H. Öztürk, and A. Özgür, "BIOSSES: a semantic sentence similarity estimation system for the biomedical domain." *Bioinformatics (Oxford, England)*, vol. 33, pp. i49–i58, Jul. 2017.
- [2] Y. Bengio, A. Courville, and P. Vincent, "Representation learning: a review and new perspectives," in *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2013, pp. 1798–1828.
- [3] B. Chiu, G. Crichton, A. Korhonen, and S. Pyysalo, "How to train good word embeddings for biomedical NLP," in *Proceedings of the 15th Workshop on Biomedical Natural Language Processing*, 2016, pp. 166–174.
- [4] Y. Wang, S. Liu, N. Afzal, M. Rastegar-Mojarad, L. Wang, F. Shen, P. Kingsbury, and H. Liu, "A comparison of word embeddings for the biomedical natural language processing," *Journal of biomedical informatics*, vol. 87, pp. 12–20, Sep. 2018.
- [5] Q. Le and T. Mikolov, "Distributed representations of sentences and documents," in *Proceedings of the 31st International Conference on International Conference on Machine Learning Volume 32*, 2014, pp. 1188–1196.

[†] No embedding was used.

- [6] D. Cer, Y. Yang, S. yi Kong, N. Hua, N. Limtiaco, R. S. John, N. Constant, M. Guajardo-Cespedes, S. Yuan, C. Tar, Y.-H. Sung, B. Strope, and R. Kurzweil, "Universal sentence encoder," *arXiv preprint arXiv:1803.11175*, 2018.
- [7] M. Pagliardini, P. Gupta, and M. Jaggi, "Unsupervised learning of sentence embeddings using compositional n-gram features," in *Proceedings of NAACL*, vol. 1, 2018, pp. 528–540.
- [8] A. P. Tafti, E. Behravesh, M. Assefi, E. LaRose, J. Badger, J. Mayer, A. Doan, D. Page, and P. Peissig, "bigNN: an open-source big data toolkit focused on biomedical sentence classification," in 2017 IEEE International Conference on Big Data (Big Data), 2017, pp. 3888–3896.
- [9] M. Sarrouti and S. Ouatik El Alaoui, "A passage retrieval method based on probabilistic information retrieval model and UMLS concepts in biomedical question answering." *Journal of biomedical informatics*, vol. 68, pp. 96–103, Apr. 2017.
- [10] A. E. W. Johnson, T. J. Pollard, L. Shen, L.-W. H. Lehman, M. Feng, M. Ghassemi, B. Moody, P. Szolovits, L. A. Celi, and R. G. Mark, "MIMIC-III, a freely accessible critical care database." *Scientific data*, vol. 3, p. 160035, May 2016.
- [11] S. Bird, E. Klein, and E. Loper, *Natural language processing with Python*, 1st ed. Cambridge Mass.: O'Reilly, 2009.
- [12] Y. Wang, N. Afzal, S. Fu, L. Wang, F. Shen, M. Rastegar-Mojarad, and H. Liu, "MedSTS: a resource for clinical semantic textual similarity," *arXiv preprint arXiv:1808.09397*, 2018.
- [13] Q. Chen, J. Du, S. Kim, W. J. Wilbur, and Z. Lu, "Combining rich features and deep learning for finding similar sentences in electronic medical records," in *Proceedings of the BioCreative/OHNLP Challenge*, 2018.