arXiv:2409.00432v1 [math.OC] 31 Aug 2024 arXiv:2409.00432v1 [math.OC] 31 Aug 2024

Online Learning of Interaction Dynamics with Dual Model Predictive Control for Multi-Agent Systems Using Gaussian Processes

T.M.J.T. Baltussen¹, A. Katriniok¹, E. Lefeber¹, R. Tóth¹, W.P.M.H. Heemels¹

Abstract— Decentralized control in complex and uncertain multi-agent scenarios requires careful consideration of the interactions between the agents. In this context, this paper proposes a dual model predictive control (MPC) method using Gaussian process (GP) models for multi-agent systems. While Gaussian process MPC (GP-MPC) has been shown to be effective in predicting the dynamics of other agents, current methods do not consider the influence of the control input on the covariance of the predictions, and, hence, lack the dual control effect. Therefore, we propose a dual MPC that directly optimizes the actions of the ego agent, and the belief of the other agents by jointly optimizing their state trajectories as well as the associated covariance while considering their interactions through a GP. We demonstrate our GP-MPC method in a simulation study on autonomous driving, showing improved prediction quality compared to a baseline stochastic MPC. Simulation results show that our GP-MPC can learn the interactions between agents online, demonstrating the potential of GPs for dual MPC in uncertain and unseen scenarios.

Keywords — Predictive control for nonlinear systems, Autonomous systems, Statistical learning

I. INTRODUCTION

Many real-world multi-agent systems are complex and unsuitable for centralized control approaches and require distributed or decentralized controllers [1]. Examples include autonomous vehicles (AVs), robotics, aerial vehicles and energy systems, which often have coupled dynamics, constraints or policies, making these systems *interactive*. The control of a single agent requires the awareness and consideration of these interactions with other agents in its environment to realize the system's safety and performance, without relying on communication. In the case of AVs, the control of such an agent includes maneuvering this agent and avoiding collisions with other agents. As AVs often lack explicit communication, we must deduce and consider these uncertain interactions when planning the AV's motion [2].

Model predictive control (MPC) is an interesting paradigm for this local control as it can directly optimize the agent's trajectories while considering safety constraints. Particularly, stochastic MPC (SMPC) can address uncertainties by incorporating a probabilistic description of model uncertainty into a stochastic optimal control problem (SOCP). In SMPC, the control inputs not only affect the system state, but also the probability distribution associated with this state, which is referred to as the dual control effect [3], [4]. This dual control effect is two-fold. Firstly, control policies with the dual control effect causally anticipate future observations, and, hence, will be less conservative in regions of low uncertainty. Secondly, dual control policies can feature an inherent probing effect that facilitates *active learning* [3]. Although solving the SOCP via the Bellman equation naturally yields these aspects of the dual control effect, this is often intractable and requires some approximation which may eliminate the dual control effect [4].

Learning-based MPC uses data-driven modeling and machine learning methods to improve the system model and the parameterization of the SOCP. In particular, Gaussian processes (GPs) are an often-used modeling approach for non-parametric learning-based MPC, as they can compensate for complex model mismatch and enable direct assessment of the approximate model uncertainty [5]. As GPs enable universal and differentiable regression [6], joint conditioning of states [7], and tractable uncertainty propagation [8], they are of great interest for learning-based and interaction-aware dual MPC.

A. Related Work

Dual MPC is shown to be effective in simultaneous identification and control of systems with parametric and structural uncertainties [9]. In addition, Dual Model Predictive Path Integral control, a sampling-based MPC, has recently demonstrated the potential of dual control and active learning in multi-agent environments [10]. However, these methods currently rely on parametric models with fixed model structures. Furthermore, GP-MPC has been used to learn and predict the motion of other agents in autonomous racing [11], [12], and autonomous driving [13]. However, [11] fixes these predictions prior to solving the MPC problem making the controller agnostic to the interactions. Moreover, [11]–[13] do not exploit the dual control effect, as they tighten the constraints based on the predicted covariance of the previous MPC solution, which is independent of the control input sequence to be optimized. While [12], [13] rely on offline training data, using online training data can improve the generalizability of learning-based control in unseen scenarios, as can be observed in [11].

B. Contributions

In this paper, we present a novel learning-based dual MPC method to learn the unknown dynamics and/or policy of other agents, and bridge the previously identified research gap through the following contributions: (i) We extend GP-MPC for the local control of a single agent in a multiagent environment by including the dual control effect. The

 1 Tren Baltussen, Alexander Katriniok, Erjen Lefeber, Jand Tóth and Maurice Heemels are with the Eindhoven Roland Tóth and Maurice Heemels are with the University of Technology, 5600 MB Eindhoven, The Netherlands {t.m.j.t.baltussen, a.katriniok, a.a.j.lefeber, r.toth, m.heemels}@tue.nl

MPC leverages the joint probability of the GP to adapt the state covariance of the other agents through the dual control effect, using Bayesian inference to learn the interactions between the ego agent and other the agents. (ii) We apply the proposed method in a simulation study on lane merging with an autonomous vehicle. In this study, the GP-MPC learns the closed-loop policy of another agent. By collecting training data online, the GP-MPC can adapt its prediction model and handle uncertain as well as unseen behavior of other agents. To the authors' best knowledge, this is the first work that uses GPs to learn and predict the interactions between agents using dual MPC.

II. PROBLEM FORMULATION

We consider a multi-agent system of $n_a \in \mathbb{N}_{\geq 2}$ agents and the task of devising a control policy for the ego Agent 0, which is described by a discrete-time dynamical system

$$
x_{k+1}^0 = f^0(x_k^0, u_k^0) \tag{1}
$$

that is subject to state and input constraints, $x_k^0 \in \mathbb{X}^0 \subseteq \mathbb{R}^{n_x}$, $u_k^0 \in \mathbb{U}^0 \subseteq \mathbb{R}^{n_u}$ at discrete time $k \in \mathbb{N}$. We assume to have perfect knowledge of the function f^0 . The dynamics of Agent $j \in \mathcal{J}$, where $\mathcal{J} = \{1, 2, \ldots, n_a - 1\}$, are composed of a known, nominal function f^j , and, an unknown and uncertain, residual function g^j that influences the state via the full column rank matrix $B^j \in \mathbb{R}^{n_x \times n_g}$:

$$
x_{k+1}^j = f^j(x_k^j) + B^j g^j(\mathbf{x}_k, \mathbf{u}_k),
$$
 (2)

where $\mathbf{x}_k = (x_k^0, x_k^1, \dots, x_k^{n_a-1})$, and $\mathbf{u}_k = (u_k^0, u_k^1, \dots, u_k^{n_a-1})$ are the joint state and input vector. Note that the residual dynamics g^j depends on x_k and u_k , making the agents *interactive*. We assume that the control input of Agent $j \in \mathcal{J}$ is composed of a closed-loop state feedback policy $\kappa^{j}(\mathbf{x}_{k})$ and a stationary zero-mean disturbance process w_k^j :

$$
u_k^j = \kappa^j(\mathbf{x}_k) + w_k^j.
$$
 (3)

As Agent 0 shares its environment with Agent $j \in \mathcal{J}$, we have to consider their coupled safety constraints that define a safe set $X_k^j(x_k^j) = \{x_k^0 \in \mathbb{R}^{n_x} \mid h^j(x_k^0, x_k^j) \le 0\}$. We assume that f , g and h are continuously differentiable functions. We consider the problem of finding a local controller that safely controls Agent 0 in the sense that $x_k^0 \in \bigcap_{j \in \mathcal{J}} \mathbb{X}_k^j(x_k^j) \cap \mathbb{X}^0$.

III. DUAL STOCHASTIC MODEL PREDICTIVE CONTROL

A. Modeling Interactions Between Agents

In this section, we propose a learning-based dual MPC for the control of Agent 0. Since we do not have full knowledge of the dynamics of Agent $j \in \mathcal{J}$, nor of its policy, it is essential that we consider the uncertainty of the residual dynamics g^j in our MPC formulation in order to realize the safety of the controller as these interactions will affect the safe set $\mathbb{X}_{k}^{j}(x_{k}^{j})$.

As we only have partial information of the other agents, we predict their future states through Bayesian inference using GP regression. Firstly, we collect measurements of the states of all agents and the ego's input $\mathbf{z}_k = [\mathbf{x}_k^{\top}, u_k^0]^{\top} \in \mathbb{R}^{n_z}$, and

we collect samples of the residual dynamics $y_k^j \in \mathbb{R}^{n_g}$ as follows:

$$
y_k^j = g^j(\mathbf{x}_k, \mathbf{u}_k) = B^{j^{\dagger}}(x_{k+1}^j - f^j(x_k)),
$$
 (4)

where $B^{j^{\dagger}} = (B^{j^{\dagger}} B^{j})^{-1} B^{j^{\dagger}}$. Subsequently, we use the collected training data $\mathbf{Z} = [\mathbf{z}_1, \mathbf{z}_2, \dots, \mathbf{z}_{n_D}] \in \mathbb{R}^{n_z \times n_D}$ and $\mathbf{y}^j = [y_1^j, y_2^j, \dots, y_{n_D}^j] \in \mathbb{R}^{n_g \times n_D}$ for inference by approximating the residual dynamics by a GP d^j : $\mathbb{R}^{n_z} \to \mathbb{R}^{n_g}$ such that:

$$
g^{j}\left(\mathbf{x}_{k},\mathbf{u}_{k}\right)\approx\mathbf{d}^{j}\left(\mathbf{z}_{k}\right).
$$
 (5)

In order to predict the future states of the other agents, we condition the posterior of the GP on the training data $D = \{Z, (y^j)_{j=1}^{n_a-1}\}.$ For the sake of simplicity, we confine ourselves to scalar GPs ($n_g = 1$). Typically, multiple variables are predicted with $n_g \leq n_x$ independent GPs. We refer the interested reader to [8], for details on vectorial GPs. As we focus on learning the interactions between agents, we assume that **Z** and y^j are measured without being affected by measurement noise. Extending the GP regression to account for measurement noise is part of future work.

B. Gaussian Process Regression

Let us focus on predicting the dynamics of a single Agent $j \in \mathcal{J}$ and omit the superscript j for the sake of readability. Firstly, we impose a prior distribution on the GP d through a user-defined kernel function $k(\mathbf{z}, \mathbf{z}')$ [6]. As we use the GP for model augmentation, we employ a zero mean prior on the GP. We assume the measured training outputs y, and the prior distribution of the GP $d(z)$ to be jointly Gaussian:

$$
\begin{bmatrix} \mathbf{y} \\ d(\mathbf{z}) \end{bmatrix} \sim \mathcal{N}\left(\mathbf{0}, \begin{bmatrix} K_{\mathbf{Z}\mathbf{z}} & \mathbf{k}_{\mathbf{Z}\mathbf{z}} \\ \mathbf{k}_{\mathbf{z}\mathbf{z}} & k_{\mathbf{z}\mathbf{z}} \end{bmatrix}\right),\tag{6}
$$

where $k_{zz'} = k(z, z'), k_{zz} \in \mathbb{R}^{n_D}$ is the concatenation of the kernel function evaluated at the test point z and the training set **Z**, where $[\mathbf{k}_{\mathbf{Zz}}]_i = k(\mathbf{z}_i, \mathbf{z})$ and $\mathbf{k}_{\mathbf{Zz}}^T = \mathbf{k}_{\mathbf{zZ}}$, and $K_{ZZ} \in \mathbb{R}^{n_D \times n_D}$ is a Gramm matrix, which satisfies $[K_{\mathbf{ZZ'}}]_{ij} = k(\mathbf{z}_i, \mathbf{z}'_j)$. Marginalizing the jointly Gaussian prior over the training outputs y yields the GP posterior [6]:

$$
Pr(d | \mathbf{z}, \mathcal{D}) = \mathcal{N}(\mu^{d}(\mathbf{z}), \Sigma^{d}(\mathbf{z})), \tag{7}
$$

where the posterior mean and covariance functions read as:

$$
\mu^d(\mathbf{z}) = \mathbf{k}_{\mathbf{z}\mathbf{Z}} K_{\mathbf{Z}}^{-1} \mathbf{y},\tag{8a}
$$

$$
\Sigma^{d}(\mathbf{z}) = k_{\mathbf{z}\mathbf{z}} - \mathbf{k}_{\mathbf{z}\mathbf{Z}} K_{\mathbf{Z}\mathbf{Z}}^{-1} \mathbf{k}_{\mathbf{Z}\mathbf{z}}.
$$
 (8b)

Subsequently, we query the posterior of the GP $d^{j}(z)$, at a test point $\mathbf{z} \in \mathbb{R}^{n_z}$, to predict the residual dynamics g^j over a time prediction horizon $i = 0, 1, \ldots, N - 1$:

$$
x_{i+1|k}^j = f^j(x_{i|k}^j) + B^j d^j(\mathbf{z}_{i|k}), \tag{9a}
$$

$$
d^{j}(\mathbf{z}) \sim \mathcal{N}(\mu^{d^{j}}(\mathbf{z}), \Sigma^{d^{j}}(\mathbf{z})), \qquad (9b)
$$

where $x_{i|k}$ denotes the *i*-th future prediction of x made at time k, and μ^{d^j} and Σ^{d^j} denote the mean and covariance function of the posterior distribution of the GP at a given test point z.

C. Gaussian Process Prediction Model

We exploit the joint probability of the GP d^j to account for the uncertainty in our safety constraints X^j by formulating *chance constraints* that should be satisfied with a probability $p_x \in (0, 1]$. To this end, we optimize the control sequence of Agent 0 $U_k = (u_{0|k}^0, \dots, u_{N-1|k}^0)$ in the following SOCP:

$$
\min_{U_k} \quad J\big(x_k^0, U_k\big) \tag{10a}
$$

s.t.
$$
x_{i+1|k}^0 = f^0(x_{i|k}^0, u_{i|k}^0), \quad i = 0, 1, ..., N - 1,
$$
 (10b)

$$
x_{i+1|k}^j = f^j(x_{i|k}^j) + B^j d^j(\mathbf{z}_{i|k})
$$

$$
x_{i+1|k}^j = f^j(x_{i|k}^j) + B^j d^j(\mathbf{z}_{i|k})
$$

$$
i = 0, 1, ..., N - 1, \quad j \in \mathcal{J},
$$
 (10c)

$$
\Pr\left(x_{i|k}^0 \in \mathbb{X}_{i|k}^j\left(x_{i|k}^j\right)\right) \ge p_x, \quad i = 1, 2, \dots, N, \ \ j \in \mathcal{J}
$$
\n(10d)

$$
x_{i|k}^{0} \in \mathbb{X}^{0}, \quad i = 1, 2, ..., N,
$$
 (10e)

$$
u_{i|k}^{0} \in \mathbb{U}^{0}, \quad i = 0, 1, ..., N - 1,
$$
 (10f)

$$
x_{0|k}^j = x_k^j, \quad j \in \{0 \cup \mathcal{J}\}.
$$
 (10g)

Note that the posterior GP d^j is a function of the control sequence. As this SOCP [\(10\)](#page-2-0) is generally intractable, we subsequently apply tractable approximations for consecutive evaluations of the GP and the chance constraints, at the expense of formal safety guarantees. In order to propagate the covariance of the predicted state Σ^{x^j} , we make the following assumptions. Firstly, we assume that consecutive GP evaluations are independent. Furthermore, the predicted state x^j and the posterior GP d^j are assumed jointly Gaussian:

$$
\begin{bmatrix} x^j \\ d^j \end{bmatrix} \sim \mathcal{N}\left(\mu^j, \Sigma^j\right) = \mathcal{N}\left(\begin{bmatrix} \mu^{x^j} \\ \mu^{d^j} \end{bmatrix}, \begin{bmatrix} \Sigma^{x^j} & \Sigma^{x^j d^j} \\ \Sigma^{d^j x^j} & \Sigma^{d^j} \end{bmatrix}\right), \quad (11)
$$

such that the covariance can be approximated and propagated over the prediction horizon. We approximate μ^{d^j} , $\Sigma^{x^{\bar{j}}d^{\bar{j}}}$, Σ^{d^j} through a first-order Taylor approximation of the GP evaluated at its posterior mean [14], which provides a good tradeoff between accuracy and computational complexity [8]:

$$
\mu_i^{d^j} = \mu^{d^j} (\mu_i^{\mathbf{z}}),
$$
\n
$$
x^{j,d^j} = x^j \left(-\tau \quad d^j \in \mathbf{z} \right)^{\top}
$$
\n(12a)

$$
\Sigma_i^{x^j d^j} = \Sigma_i^{x^j} \left(\nabla_{x^j}^\top \mu^{d^j} (\mu_i^{\mathbf{z}}) \right)^\top,
$$
\n
$$
= d^j \left(\nabla_{x^j}^\top \mu^{d^j} (\mu_i^{\mathbf{z}}) \right)^\top
$$
\n
$$
(12b)
$$

$$
\Sigma_i^{d^j} = \Sigma^{d^j} \left(\mu_i^{\mathbf{z}} \right) + \nabla_{x^j}^\top \mu^{d^j} \left(\mu_i^{\mathbf{z}} \right) \Sigma_i^{x^j} \left(\nabla_{x^j}^\top \mu^{d^j} \left(\mu_i^{\mathbf{z}} \right) \right)^\top, \tag{12c}
$$

where μ_i^z denotes the mean value of the test point z_i at prediction step i, with μ^{d^j} (z) and Σ^{d^j} (z) as in [\(8\)](#page-1-0). We propagate the mean and covariance of the posterior GP [\(8\)](#page-1-0) over the horizon through the following approximation [8]:

$$
\mu_{i+1|k}^{x^j} = f^j \left(\mu_{i|k}^{x^j} \right) + B^j \mu^{d^j} \left(\mu_{i|k}^{\mathbf{z}} \right),\tag{13a}
$$

$$
\Sigma_{i+1|k}^{x^j} = \left[\nabla^{\top} f^j \left(\mu_{i|k}^{x^j} \right) B^j \right] \Sigma_{i|k}^j \left[\nabla^{\top} f^j \left(\mu_{i|k}^{x^j} \right) B^j \right]^\top, (13b)
$$

for $i = 0, 1, \ldots, N - 1$ where the initial prediction equals the current state $\mu_{0|k}^{x^j} = x^j_k$ with $\Sigma_{0|k}^{x^j} = 0$. We approximate the full GP by a Sparse Pseudo-Input GP (SPGP) [15], which exploits the Gaussian structure to reduce the computational complexity of the GP by preconditioning the GP on heuristic *inducing points*. For details on SPGPs, we refer the reader to [15]. We select the inducing points by uniformly sampling from previously predicted trajectory from the MPC, since the test points can be expected to be close to this trajectory [8].

D. Learning-based Dual Model Predictive Control

In this section, we propose our dual MPC that uses the GP prediction model, presented in Section [III-C,](#page-2-1) to jointly condition the interactions of the other agents with the control inputs of the Agent 0. The dual control effect was first formalized in [3], and according to [4] is defined as follows:

Definition 3.1: A control input is said to have the dual control effect if it can affect, with non-zero probability, at least one rth -order central moment of a state variable $(r \ge 2)$.

We formulate a tractable dual MPC to devise a control policy for Agent 0 and model the interactions g^j by an SPGP:

$$
\min_{U_k} J(x_k^0, U_k) \tag{14a}
$$

s.t.
$$
x_{i+1|k}^0 = f^0(x_{i|k}^0, u_{i|k}^0), \quad i = 0, 1, ..., N-1,
$$

\n
$$
\mu_{i+1|k}^{x^j} = f^j(\mu_{i|k}^{x^j}) + B^j \mu^{d^j}(\mu_{i|k}^{\mathbf{z}}),
$$
\n(14b)

$$
i = 0, 1, \dots, N - 1, \quad j \in \mathcal{J}, \tag{14c}
$$

$$
\Sigma_{i+1|k}^{x^{j}} = \left[\nabla^{\top} f^{j} \left(\mu_{i|k}^{x^{j}}\right) B^{j}\right] \Sigma_{i|k}^{j} \left[\nabla^{\top} f^{j} \left(\mu_{i|k}^{x^{j}}\right) B^{j}\right]^{\top},
$$

\n
$$
i = 0, 1, \dots, N - 1, \quad j \in \mathcal{J},
$$
 (14d)

$$
u_{i|k}^{0} \in \mathbb{U}^{0}, \quad i = 0, 1, \dots, N - 1,
$$
 (14e)

$$
x_{i|k}^0 \in \tilde{\mathbb{X}}_{i|k}^j\left(\mu_{i|k}^{x^j}, \Sigma_{i|k}^{x^j}\right), \quad i = 1, 2, \dots, N, \quad j \in \mathcal{J}, \tag{14f}
$$

$$
x_{i|k}^0 \in \mathbb{X}^0, \quad i = 1, 2, \dots, N,
$$
\n
$$
(14g)
$$
\n
$$
x_0^0 \qquad (14h)
$$

$$
x_{0|k}^{0} = x_k^{0}, \tag{14h}
$$

$$
x_j^{x_j} = x_j^{j} \quad i \in \mathcal{I}
$$

$$
\mu_{0|k}^{x^j} = x_k^j, \quad j \in \mathcal{J},\tag{14i}
$$
\n
$$
\nabla^{x^j} = \mathbf{Q} \tag{14i}
$$

$$
\Sigma_{0|k}^{x^j} = \mathbf{0},\tag{14j}
$$

where the chance constraints from [\(10d\)](#page-2-2) are approximated by a general tightened constraint set $\tilde{X}^j(\mu^{x^j}, \Sigma^{x^j}) \subseteq X^j(\mu^{x^j})$, based on the covariance of the GP [8]. The specific form of constraint tightening may depend on the nature of the problem. An example hereof is provided in Section [IV.](#page-3-0) The dual MPC, detailed in Algorithm [1,](#page-3-1) below, exploits the joint conditioning of the predicted states of all the agents through the regression feature z of the GP. Consequently, the control sequence U_k explicitly affects the constraint tightening $(\tilde{\mathbb{X}}^j)$ through Bayesian inference. The dual control effect provides an inherent degree of caution based on the correlation with past observations [3], which is essential to a truly interaction-aware controller. To this end, we make the following proposition.

Proposition 3.2: The control input sequence of Agent 0 (U_k^*) resulting from the locally optimal solution to the MPC problem [\(14\)](#page-2-3) affects both the trajectory of Agent 0 and the prediction of Agent $j \in \mathcal{J}$ over the horizon. Moreover, U_k^* affects the predicted covariance of the state of Agent $j \in \mathcal{J}$, and, thus the control input u_k^{0*} has the dual control effect.

Proof: By construction, the control sequence resulting from [\(14\)](#page-2-3) $U_{0:i-1|k}^*$ determines the predicted future states of Agent 0 $x_{i|k}^0$, and, consequently, the predicted test points $z_{i|k}$ of the GP. Therefore, the control sequence $U_{0:i-1|k}^*$ affects the posterior mean $\mu_{i|k}^{x^j}$ [\(14c\)](#page-2-4) and posterior covariance $\sum_{i|k}^{x^j}$ [\(14d\)](#page-2-5) of the predicted states of Agent $j \in \mathcal{J}$ at time k such that

$$
\Sigma_{i|k}^{x^j} \triangleq \mathbb{E}\big[\Sigma_i^{x^j} \mid \mathcal{D}_k, U_{0:i-1|k}^*\big] \neq \mathbb{E}\big[\Sigma_i^{x^j} \mid \mathcal{D}_k\big] \tag{15}
$$

for $i = 1, 2, ..., N$. Hence, u_k^{0*} has the dual control effect.

Algorithm 1 Online Learning GP-MPC

1: for each time step $k = 0, 1, 2, \ldots$, do

- 2: Solve MPC problem [\(14\)](#page-2-3) for U_k^*
- 3: if Problem [\(14\)](#page-2-3) is feasible, then
- 4: Apply $u_k^0 \leftarrow u_{0|i}^{0^*}$ $\int_{0/k}^{0^{+}}$ from [\(14\)](#page-2-3) to the system
- 5: else
- 6: Apply shifted input $u_k^0 \leftarrow u_{1|i}^{0*}$ $\int_{1|k-1}^{0^*}$ of the last feasible solution to [\(14\)](#page-2-3) to the system
- 7: end if
- 8: Update training set $\mathcal{D}_{k+1} \leftarrow \mathcal{D}_k \cup (\mathbf{z}_k, \mathbf{y}_k)$
- 9: Update inducing points Z_{ind} from the solution to [\(14\)](#page-2-3) 10: end for

IV. INTERACTION-AWARE MOTION PLANNING

A. Lane Merging Use Case

In this section, we demonstrate the proposed GP-MPC method, along with a stochastic baseline MPC, for the motion planning of an autonomous vehicle in a forced lane merging scenario. In this use case, the target lane is occupied by a leading and a following vehicle, as seen in Fig. [1.](#page-3-2) The Follower tries to close the gap with its Leader and hinders the Ego from merging in between. The Follower's interactive driving policy is modeled by a Merge-Reactive Intelligent Driver Model (MR-IDM) [16]. We assume the target vehicles remain in their lane center. The Ego, Follower and Leader are denoted by $j = 0, 1, 2$, respectively. For simplicity and interpretability, we confine ourselves to learning the residual dynamics of a single agent, the Follower $(g¹)$, assuming the Leader drives at a constant speed $(g^2 = 0)$.

B. Vehicle Modeling

All vehicles are modeled by a kinematic bicycle model. The state of a vehicle is described by the state vector $x = \begin{bmatrix} X & Y & v & \psi & \delta \end{bmatrix}^\top \in \mathbb{R}^5$, where X and Y are the longitudinal and lateral positions of the rear axle, respectively. The longitudinal velocity of the rear axle is denoted by v, ψ is the heading angle of the vehicle, and δ is the steering angle of the front axle. The vehicle's acceleration a and the steering rate r are inputs to the system: $u = \begin{bmatrix} a & r \end{bmatrix}^\top \in \mathbb{R}^2$. The continuous-time dynamics of the kinematic bicycle model $\dot{x}(t) = f_c(x(t), u(t))$ are defined by the state-space equations:

$$
\dot{X}(t) = v(t)\cos(\psi(t)),
$$
\n(16a)

$$
\dot{Y}(t) = v(t)\sin(\psi(t)),\tag{16b}
$$

$$
\dot{v}(t) = a(t),\tag{16c}
$$

$$
\dot{\psi}(t) = \frac{v(t)}{l} \tan(\delta(t)), \qquad (16d)
$$

$$
\dot{\delta}(t) = r(t),\tag{16e}
$$

where $t \in \mathbb{R}$ denotes time and l denotes the vehicle's wheelbase. We discretize [\(16\)](#page-3-3) with the fourth-order Runge-Kutta method using a sampling time of $T_s = 0.25$ [s].

The Follower's MR-IDM policy [16] is a driver model that considers agents merging into its lane. This closed-loop policy $a^1 = a_{MR-IDM}(x, a^0, a^2)$ couples the dynamics of the Ego and the Follower. In order to utilize the framework outlined in Section [III,](#page-1-1) we reformulate this policy as a

Fig. 1. Schematic of the lane merging scenario near the merge point.

function of x_k and a^0 through [\(3\)](#page-1-2). For simulation purposes, we assume the Follower has access to a^0 and a^2 . The MR-IDM maps the relative longitudinal and lateral position to an effective distance gap for an IDM. The parameters of the Follower's MR-IDM are listed in Table [I.](#page-3-4) The vehicle inducing the largest deceleration determines the output of the MR-IDM. For details on the MR-IDM we refer the reader to [16].

TABLE I MERGE-REACTIVE INTELLIGENT DRIVER MODEL PARAMETERS.

IDM Parameter	Value
Desired speed (v_{ref})	36 [m/s]
Headway time (T_{ref})	0.25 [s]
Free acceleration exponent (δ_{IDM})	4 [-]
Jam distance (s_0)	2 [m]
Maximum acceleration (a_{max})	4 $\lfloor m/s^2 \rfloor$
Desired deceleration (b_{max})	3 $\,[\text{m/s}^2]$
Coolness factor (c)	0.99 [-]
Lateral reactivity (ζ)	

C. Motion Planning Problem

We incentivize the Ego to maintain its initial velocity v_0^0 and stay in its lane, until the merge lane closes and the MPC decides that we should merge. We use a logistic function $m(X): \mathbb{R} \to \mathbb{R}$ to describe the center of the merge lane as a function of the longitudinal position, which coincides with the center of the target lane after the merge lane has fully closed. Accordingly, the Ego's reference x^r is defined as:

$$
x^r(X) = \begin{bmatrix} 0 & m(X) & v_0^0 & 0 & 0 \end{bmatrix}^\top.
$$
 (17)

We employ the following objective function:

$$
J\left(x_k^0, u_{k-1}^0, U_k\right) = \sum_{i=1}^N \left\|x_{i|k}^0 - x^r \left(X_{i|k}^0\right)\right\|_Q^2
$$

+
$$
\sum_{i=0}^{N-1} \left\|u_{i|k}^0\right\|_R^2 + \left\|\Delta u_{i|k}^0\right\|_S^2, \tag{18}
$$

where $||z||_Q^2 = z^\top Qz$ with positive (semi-) definite weighing matrices $\tilde{Q}, S \succeq 0$, $R \succ 0$ and $\Delta u_{i|k} = u_{i|k} - u_{i-1|k}$ with $u_{-1|k} = u_{k-1}$. We limit the absolute acceleration and steering angle rate to 5 $[m/s^2]$ and 5 [deg/s] through $u \in \mathbb{U}^0$. Constant state constraints partially govern road boundaries and limit the Ego's maximum velocity to 36 [m/s], its absolute heading to 15 [deg] and its absolute steering angle to 5 [deg]. The right road boundary is dependent on its position and is governed through a separate constraint:

$$
h_r(x_{i|k}^0) = m(X_{i|k}^0) - Y_{i|k}^0 + \frac{W - w}{2} \le 0,
$$
 (19)

where the road boundary is parallel to the center of the merge lane, W and w denote the vehicle and lane width. Consequently, we have the following general state constraints:

$$
\mathbb{X}^0 := \{ x^0 \in \mathbb{R}^5 \mid x_{\min} \le x^0 \le x_{\max}, h_r(x^0) \le 0 \}. \tag{20}
$$

Similar to Zhu *et al.* [12], we account for the uncertainty in the predicted position of the target vehicle by expanding the semi-axes of elliptical collision avoidance constraints. Again, we assume no uncertainty in their lateral position. By expanding the major semi-axis of the ellipse, we obtain a tractable, *tightened* reformulation of the chance constraint:

$$
\tilde{\mathbb{X}}_{i|k}^{j}(x_{i|k}^{j}) = \{x_{i|k}^{0} \in \mathbb{R}^{n_{x}} \mid h_{c}(x_{i|k}^{0}, \mu_{i|k}^{x_{i}^{j}}, \Sigma_{i|k}^{X^{j}}) = \n- \frac{\left(c_{x,i|k}^{j} - c_{x,i|k}^{0}\right)^{2}}{\left(\varepsilon_{c,A} + \sigma \sqrt{\Sigma_{i|k}^{X^{j}}}\right)^{2}} - \frac{\left(c_{y,i|k}^{j} - c_{y,i|k}^{0}\right)^{2}}{\varepsilon_{c,B}^{2}} + 1 \leq 0\},
$$
\n(21)

where $c_{x,i|k}^j$ and $c_{y,i|k}^j$ denote the longitudinal and lateral component of the centroid, respectively, and $\Sigma_{i|k}^{X^j}$ denotes the predicted covariance of the longitudinal position of Agent j at time step $k + i$. The major and minor semi-axis of the ellipse are denoted by $\mathcal{E}_{c,A}$ and $\mathcal{E}_{c,B}$, respectively. The constraint tightening can be tuned with $\sigma \in \mathbb{R}_{\geq 0}$, such that the approximate constraints are enforced with a probability of $p_x \ge \text{erf}(\sigma)$, where erf denotes the Gaussian error function and $\sigma = 2$ is the amount of standard deviation that is accounted for. In absence of formal feasibility guarantees of the MPC, the collision avoidance constraints are softened by an l_1 penalty function to retain feasibility. Since we assume the Leader maintains its initial velocity, we set $\Sigma^{x^2} = 0$.

D. Constant Velocity Model Predictive Control

The stochastic baseline MPC (CV-MPC) uses a constant velocity prediction model for both the Leader and Follower:

$$
v_{i|k}^j = v_k^j, \quad \text{for } i = 0, 1, \dots, N. \tag{22}
$$

Hence, the nominal predictions f^j of the target vehicles are:

$$
\mu_{i+1|k}^{x^j} = A \mu_{i|k}^{x^j}, \quad \text{for } i = 0, 1, \dots, N - 1, \quad j = 1, 2, \tag{23}
$$

where
$$
A = \begin{bmatrix} 1 & 0 & T_s & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}
$$
. (24)

The CV-MPC accounts for the Follower's chance in velocity Δv^1 by a fixed covariance $\sigma_{v^1}^2 = 0.3$ that we propagate as:

$$
\Sigma_{i+1|k}^{x^1} = A \Sigma_{i|k}^{x^1} + B^1 \sigma_{v^1}^2, \quad \text{for } i = 0, 1, \dots, N - 1,
$$
 (25)

where
$$
B^1 = \begin{bmatrix} 0 & 0 & 1 & 0 & 0 \end{bmatrix}^\top
$$
. (26)

E. Gaussian Process Model Predictive Control

With the GP-MPC we predict the change velocity using GP regression by measuring the difference between the Follower's actual velocity and the constant velocity prediction:

$$
g^{1}(\mathbf{x}_{k}, \mathbf{u}_{k}) = y_{k} = v_{k+1}^{1} - v_{k}^{1} = \Delta v_{k}^{1}.
$$
 (27)

We 'select' specific states of interest by applying a linear map C to z , such that we infer these predictions using the velocities and relative positions of the different vehicles:

$$
C \mathbf{z} = [v^0, v^1, v^2, (X^1 - X^0), (X^1 - X^2), (Y^1 - Y^0)]^\top
$$
 (28)

TABLE II RESULTS OF THE MONTE CARLO SIMULATIONS.

Algorithm	Success	$\ e\ $ [m/s]	T_c [ms]	$T_c < T_s$ [%]
CV-MPC	20/51	0.679	50	100
GP-MPC	33/51	0.645	128	95.6
GP-MPC with				
pre-training	35/51	0.440	206	69.0

The relative lateral position of the Follower and Leader is assumed to be zero and is omitted from z. We use past observations y and approximate the incremental velocity by the posterior of the GP through Bayesian inference:

$$
d^1(\mathbf{z}_{i|k}) \mid \mathcal{D}, \mathbf{Z} \approx \Delta v_{i|k}^1 = v_{i+1|k}^1 - v_{i|k}^1,\tag{29}
$$

and the posterior mean and covariance of the GP affect the predictions via the matrix $B¹$ according to [\(14\)](#page-2-3). Note that the MPC only has access to the current state of other agents.

We employ the frequently used squared exponential kernel and map the regression features through C , such that:

$$
k\left(\mathbf{z},\mathbf{z}'\right) = \sigma_d^2 \exp\left(-\frac{1}{2}\left(C\mathbf{z} - C\mathbf{z}'\right)^{\top} L_d^{-2}\left(C\mathbf{z} - C\mathbf{z}'\right)\right),\tag{30}
$$

where σ_d^2 is the prior variance and L_d denotes the lengthscale matrix. If sufficient training data is available, hyperparameters of the kernel could be inferred using loglikelihood optimization [6]. Here, we use fixed hyperparameters for the kernel, with $L_d = diag(3, 3, 3, 17, 17, 5)$. The covariance of the kernel is equal to the prior covariance of the nominal prediction model $\sigma_d^2 = \sigma_{\Delta v^1}^2 = 0.3$, such that the CV-MPC is equivalent to the GP-MPC prior to inference.

V. RESULTS

We compare our proposed learning GP-based dual MPC (GP-MPC), with a stochastic baseline MPC that uses a constant velocity prediction (CV-MPC) for the Follower, and evaluate their performance on the lane merging use case detailed in Section [IV.](#page-3-0) We test the GP-MPC with and without pre-training. Here, we refer to pre-training as the availability of past measurement data at the start of the experiment.

A. Numerical Case Study

We perform 51 Monte Carlo simulations to assess the prediction capabilities of the GP-MPC and CV-MPC. As initial conditions, we take $X_0^1 = -75$ [m], $v_0^1 = 31$ [m/s] for the Follower, and $X_0^2 = 0$ [m], $v_0^2 = 25$ [m/s] for the Leader to ensure a sufficiently challenging scenario. The initial position of the Ego is uniformly sampled from $X_0^0 \in [-100, -75]$ with $v_0^0 = 31$ [m/s]. Computations are performed in MATLAB using CasADi [17], IPOPT [18] and the linear solver MA57 [19]. We take a horizon length of $N = 12$ and $M = 4$ inducing points for the SPGP. To assess the generalizability to unseen behavior without pre-training, we take $\mathcal{D}_0 = \emptyset$. With pre-training, we initialize the GP with observations \mathcal{D}_0 from a single closed-loop experiment with $X_0^0 = -85$ [m].

Table [II](#page-4-0) summarizes the results of the Monte Carlo trials. In this study, we consider a merge successful if the Ego merges between the Follower and Leader. The prediction

Fig. 2. Time lapse of a lane merge by the GP-MPC.

error $||e||(k) := \frac{1}{N} ||\{v_{i|k} - v_{k+i}\}_{i=1}^N ||_1$ is the normalized norm of the difference between the predicted trajectory at time k and the realized trajectory from time k to $k+N$. The average prediction error over all time steps and all trials ∥e∥ quantifies the prediction quality of the CV-MPC and GP-MPC.

B. Discussion

The GP-MPC jointly optimizes the predictions and the associated uncertainty through the dual control effect, as seen in Fig. [2,](#page-5-0) which shows a successful merge by the GP-MPC without pre-training. Here, the two transparent rectangles indicate the 2σ -bounds on the final predicted position of the Follower. The approximate covariance of the GP is exploited to account for uncertain interactions providing inherent caution through dual MPC. As the Ego is agnostic to the Follower's response to the merging action it takes extra caution when merging by further tightening the constraints.

Both the CV-MPC and the GP-MPC without pre-training do not capture the high frequent dynamics during the merge, as seen in Fig. [3.](#page-5-1) During the merge, approximately after $t = 10$ [s], the GP-MPC without pre-training has an increased prediction error as it has not observed these high frequent dynamics. Still, the GP-MPC has superior predictions quality prior to merging and is able to identify a safe gap to merge in between. The GP-MPC with pre-training exploits past observations from a similar scenario, leveraging Bayesian inference and the dual control effect to exercise less caution and shows increased prediction quality. The online learning GP-MPC sees a 25% to 29% increase in successful merges compared to CV-MPC, with and without pre-training, respectively. While the complexity of evaluating the sparse GP is linear in the number of data points [15], which is reflected by the average computation time \overline{T}_c (Table [II\)](#page-4-0), online learning can reduce the required amount of training data. Simulation results show that our GP-MPC can successfully predict the Follower's motion from various initial conditions by only relying on online training data, demonstrating its generalizability beyond a priori available training data.

VI. CONCLUSIONS

We presented a Gaussian process-based MPC that uses the dual control effect to learn and predict the dynamics of other agents while accounting for their joint uncertainty. We demonstrated our GP-MPC in a numerical case study on

Fig. 3. Average prediction error of Follower's velocity in experiments in which all planners merge behind (top) and merge in between (bottom).

autonomous lane merging, by leveraging dual MPC to jointly optimize the motion of the ego vehicle and the predictions of a target vehicle through an interactive GP model. Through online learning, the GP-MPC can adapt to uncertain and unseen behavior of other agents, showing strong potential for scenarios that extend beyond a priori available training data sets. By explicitly considering the effect of control inputs on the covariance of predictions of other agents, our GP-MPC can leverage this uncertainty in the tightening of constraints.

The dual control effect is an important notion that can be leveraged by the MPC. While this paper focuses on a proof of concept of the proposed method, the next research steps for learning-based GP-MPC include: (i) incorporating the probing effect of dual control, i.e., active learning, (ii) predicting the residual dynamics of multiple agents, (iii) certification and validation of the prediction model, and (iv) providing performance and recursive feasibility guarantees of the MPC.

REFERENCES

- [1] D. O. Mayne, "Model predictive control: Recent developments and future promise," *Automatica*, vol. 50, no. 12, Dec. 2014.
- [2] W. Schwarting, J. Alonso-Mora, and D. Rus, "Planning and Decision-Making for Autonomous Vehicles," *Annual Review of Control, Robotics, and Autonomous Systems*, vol. 1, no. 1, May 2018.
- [3] Y. Bar-Shalom and E. Tse, "Dual effect, certainty equivalence, and separation in stochastic control," *IEEE Transactions on Automatic Control*, vol. 19, no. 5, Oct. 1974.
- [4] A. Mesbah, "Stochastic model predictive control with active uncertainty learning: A Survey on dual control," *Annual Reviews in Control*, vol. 45, Jun. 2018.
- [5] L. Hewing, K. P. Wabersich, M. Menner, and M. N. Zeilinger, "Learning-Based Model Predictive Control: Toward Safe Learning in Control," *Annual Review of Control, Robotics, and Autonomous Systems*, vol. 3, no. 1, May 2020.
- [6] C. E. Rasmussen and C. K. I. Williams, *Gaussian processes for machine learning*. MIT Press, 2006.
- [7] P. Trautman and A. Krause, "Unfreezing the robot: Navigation in dense, interacting crowds," in *IEEE/RSJ Int. Conf. on Intell. Robots and Syst. (IROS)*, Oct. 2010.
- [8] L. Hewing, J. Kabzan, and M. N. Zeilinger, "Cautious Model Predictive Control Using Gaussian Process Regression," *IEEE Transactions on Control Systems Technology*, vol. 28, no. 6, Nov. 2020.
- [9] E. Arcari, L. Hewing, M. Schlichting, and M. N. Zeilinger, "Dual Stochastic MPC for Systems with Parametric and Structural Uncertainty," in *Proceedings of the 2nd Conference on Learning for Dynamics and Control*, vol. 120. PMLR, Jun. 2020.
- [10] J. Knaup, J. D'sa, B. Chalaki, T. Naes, H. N. Mahjoub, E. Moradi-Pari, and P. Tsiotras, "Active learning with dual model predictive pathintegral control for interaction-aware autonomous highway on-ramp merging," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024.
- [11] T. Brüdigam, A. Capone, S. Hirche, D. Wollherr, and M. Leibold, "Gaussian Process-based Stochastic Model Predictive Control for Overtaking in Autonomous Racing," *arXiv preprint arXiv:2105.12236*, May 2021.
- [12] E. L. Zhu, F. L. Busch, J. Johnson, and F. Borrelli, "A Gaussian Process" Model for Opponent Prediction in Autonomous Racing," in *IEEE/RSJ Int. Conf. on Intell. Robots and Syst. (IROS)*, Oct. 2023.
- [13] J. Bethge, M. Pfefferkorn, A. Rose, J. Peters, and R. Findeisen, "Model Predictive Control with Gaussian-Process-Supported Dynamical Constraints for Autonomous Vehicles," *IFAC-PapersOnLine*, vol. 56, no. 2, Nov. 2023.
- [14] J. Kocijan, *Modelling and Control of Dynamic Systems Using Gaussian Process Models*. Springer International Publishing, 2016.
- [15] E. Snelson and Z. Ghahramani, "Sparse Gaussian Processes using Pseudo-inputs," *Adv. in Neural Inf. Processing Syst.*, vol. 18, 2005.
- [16] D. Holley, J. D'sa, H. N. Mahjoub, G. Ali, B. Chalaki, and E. Moradi-Pari, "MR-IDM - Merge Reactive Intelligent Driver Model: Towards Enhancing Laterally Aware Car-following Models," in *IEEE Int. Conf. on Intell. Transp. Syst. (ITSC)*, Sep. 2023.
- [17] J. A. E. Andersson, J. Gillis, G. Horn, J. B. Rawlings, and M. Diehl, "CasADi: a software framework for nonlinear optimization and optimal control," *Math. Progam. Comput.*, vol. 11, no. 1, Mar. 2019.
- [18] A. Wächter and L. T. Biegler, "On the implementation of an interiorpoint filter line-search algorithm for large-scale nonlinear programming," *Mathematical Programming*, vol. 106, no. 1, Mar. 2006.
- [19] HSL. (2023, May) Coin-HSL. [Online]. Available: [https://licences.](https://licences.stfc.ac.uk/product/coin-hsl) [stfc.ac.uk/product/coin-hsl](https://licences.stfc.ac.uk/product/coin-hsl)