# The R package psvmSDR: A Unified Algorithm for Sufficient Dimension Reduction via Principal Machines

Jungmin Shin

Department of Statistics, Korea University Seung Jun Shin

Department of Statistics, Korea University

and

Andreas Artemiou

Department of Information Technologies, University of Limassol

September 6, 2024

#### Abstract

Sufficient dimension reduction (SDR), which seeks a lower-dimensional subspace of the predictors containing regression or classification information has been popular in a machine learning community. In this work, we present a new R software package **psvmSDR** that implements a new class of SDR estimators, which we call the principal machine (PM) generalized from the principal support vector machine (PSVM). The package covers both linear and nonlinear SDR and provides a function applicable to realtime update scenarios. The package implements the descent algorithm for the PMs to efficiently compute the SDR estimators in various situations. This easy-touse package will be an attractive alternative to the **dr** R package that implements classical SDR methods.

*Keywords:* nonlinear dimension reduction, principal machines, principal support vector machine, realtime dimension reduction

# 1 Introduction

Dimension reduction is essential in modern applications in statistics and machine learning as the data size grows. In this regard, the sufficient dimension reduction (SDR, Li; 1991; Cook; 1998) has gained great popularity in supervised learning problems. For a given pair of univariate response Y and p-dimensional predictor  $\mathbf{X}$ , SDR assumes

$$Y \perp \mathbf{X} \mid \mathbf{B}^{\mathsf{T}} \mathbf{X},\tag{1}$$

where  $\perp$  denotes statistical independence. Under (1), SDR seeks the minimal space spanned by  $\mathbf{B} \in \mathbb{R}^{p \times d}$ , called the central subspace, and denoted by  $S_{Y|\mathbf{X}}$  that contains a complete regression information of Y on  $\mathbf{X}$ . We assume  $S_{Y|\mathbf{X}} = \operatorname{span}{\mathbf{B}}$  in (1). The dimension of  $S_{Y|\mathbf{X}}$ , d is also an important quantity to be estimated from the data.

There are numerous SDR estimators to estimate  $S_{Y|X}$ . Earliest proposals are based on an inverse moment, such as sliced inverse regression (SIR, Li; 1991), sliced average variance estimates (SAVE, Cook and Weisberg; 1991), and principal Hessian directions (pHd, Li; 1992). The **dr** package in software R (Weisberg; 2015) concisely implements all of these methods and, to the best of our knowledge, the only R-package available for SDR.

The assumption (1) is often called a linear SDR. Cook (2007) generalized (1), and proposed a nonlinear SDR that pursues a function  $\phi : \mathbb{R}^p \to \mathbb{R}^d$  satisfying

$$Y \perp \mathbf{X} \mid \phi(\mathbf{X}). \tag{2}$$

Nonlinear SDR methods have been developed by directly extending the classical inverse methods to Reproducing Kernel Hilbert Space (RKHS, Aronszajn; 1950). However, there is no hands-on R package that implements them.

Meanwhile, Li et al. (2011) proposed the principal support vector machine (PSVM), a unified framework for both linear and nonlinear SDR, by connecting the SDR problem to the support vector machine (SVM, Vapnik; 1999). PSVM is known to outperform the classical SDR methods mentioned above. More importantly, PSVM can be easily generalized to other supervised machine learning approaches other than the SVM with the hinge loss. We call the class of SDR methods that generalizes the PSVM, the principal machine (PM).

In this article, we develop an R package **psvmSDR** that renders a simple gradient descent algorithm to compute a wide variety of the PMs in a unified framework. The package offers two main functions **psdr()** and **npsdr()** that compute a wide variety of PMs for linear and nonlinear SDR, respectively. In addition, it also has a function **rtpsdr()** that executes the realtime SDR estimator for streamed data.

We highlight the main advantages of **psvmSDR** package in the following.

- It can solve both linear and nonlinear SDR problems in a unified framework using a simple and efficient gradient descent algorithm.
- It can be applied to a binary classification, where most inverse-moment-based approaches suffer.
- It can compute a PM estimator with a user-specified arbitrary convex loss, adding flexibility to the methods.
- It can handle the streamed data by directly updating the SDR estimator without storing the entire data.

The package is now available from CRAN at https://cran.r-project.org/web/packages/psvmSDR and can be installed from R with the following command :

#### R> install.packages("psvmSDR")

The rest of the article is organized as follows. In Section 2, we introduce the principal machine (PM) under a linear, nonlinear, and realtime SDR framework along with the corresponding functions psdr(), npsdr(), and rtpsdr(). In Section 3, we describe computational details about the package, and its efficiencies are investigated. In Section 4, we overview the package structure and explain how to implement the functions with examples. We conclude with a summary and discussion in Section 5.

# 2 Principal machines: generalization of PSVM

We start by introducing the PSVM (Li et al.; 2011). For a given sequence of  $c_1 < c_2 < \cdots < c_h$ , the PSVM minimizes the following objective function in the population level:

$$(\alpha_k, \boldsymbol{\beta}_k) = \operatorname*{argmin}_{\alpha, \boldsymbol{\beta}} \boldsymbol{\beta}^T \boldsymbol{\Sigma} \boldsymbol{\beta} + \lambda \mathrm{E} \left[ \tilde{Y}_k \{ \alpha + \boldsymbol{\beta}^\top (\mathbf{X} - \boldsymbol{\mu}) \} \right]_+, \quad k = 1, 2, \cdots, h$$
(3)

where  $\boldsymbol{\mu} = \mathrm{E}(\mathbf{X}), \, \boldsymbol{\Sigma} = \mathrm{COV}(\mathbf{X}), \, \mathrm{and} \, [u]_{+} = \max\{0, u\}.$  Here  $\tilde{Y}_k$  is a pseudo-binary response, taking 1 if  $Y < c_k$  and -1 otherwise, and a positive constant  $\lambda$  is a cost parameter whose choice is not overly sensitive for estimating  $\mathcal{S}_{Y|\mathbf{X}}$ . Li et al. (2011) showed the unbiasedness of  $\boldsymbol{\beta}_k$ , i.e.,  $\boldsymbol{\beta}_k \in \mathcal{S}_{Y|\mathbf{X}}, \forall k = 1, 2, \cdots, h$ .

It is important to note that convexity of the objective function in (3) is the only requirement for the PSVM to be unbiased, and this naturally leads to a generalized version of the PSVM, which we call the principal machine (PM, Shin and Shin; 2024). PMs are categorized into two types: one is response-based PM (RPM), and the other is loss-based PM (LPM). The RPM obtains multiple solutions by perturbing the pseudo-response  $\tilde{Y}_k$ , while the loss function remains unchanged. The PSVM belongs to this category. On the other hand, the LPM calculates multiple solutions by changing the loss functions, while the pseudo-response  $Y_k$  is fixed as Y for all k. The principal weighted support vector machine (PWSVM, Shin et al.; 2017) and the principal quantile regression (PQR, Wang et al.; 2018) are the earliest proposals of the LPM.

### 2.1 Linear principal machines

The linear PM solves

$$(\alpha_k, \boldsymbol{\beta}_k) = \operatorname*{argmin}_{\alpha, \boldsymbol{\beta}} \boldsymbol{\beta}^\top \boldsymbol{\Sigma} \boldsymbol{\beta} + \lambda \mathrm{E} \left[ L_k(\tilde{Y}_k, f(\mathbf{X})) \right], \qquad k = 1, 2, \cdots h,$$
(4)

where  $f(\mathbf{X}) = \alpha + \boldsymbol{\beta}^{\top}(\mathbf{X} - \boldsymbol{\mu})$  and  $L_k(y, f)$  denotes a convex loss function of a margin, yf for a binary  $y \in \{-1, 1\}$  or residual y - f for a continuous  $y \in \mathbb{R}$ . The RPM solves (4) for different values of  $\tilde{Y}_k$  over k to obtain multiple solutions while keeping  $L_k$  fixed as say, L. On the other hand, the LPM solves it with different loss functions  $L_k$  while a pseudo-response  $\tilde{Y}_k$  remains fixed as the original response Y. For example, PWSVM, the first proposal of the LPM solves (4) for  $L_k(y, f) = \pi_k(y)[1 - yf]_+$  where  $\pi_k(y) = c_k$  if y = 1and  $1 - c_k$  otherwise for a given  $c_k \in (0, 1)$  while  $\tilde{Y}$  is fixed as  $Y \in \{-1, 1\}$ . The PWSVM is proposed for SDR in a binary classification, where the PSVM fails when d > 1.

Given  $(y_i, \mathbf{x}_i), i = 1, 2, \cdots, n$ , the sample counter part of (4) is

$$(\hat{\alpha}_k, \hat{\boldsymbol{\beta}}_k) = \operatorname*{argmin}_{\alpha, \boldsymbol{\beta}} \boldsymbol{\beta}^\top \widehat{\boldsymbol{\Sigma}} \boldsymbol{\beta} + \frac{\lambda}{n} \sum_{i=1}^n L_k \left( \widetilde{y}_{k,i}, \alpha + \boldsymbol{\beta}^\top \mathbf{z}_i \right), \qquad k = 1, 2, \cdots h,$$
(5)

where  $\mathbf{z}_i = \mathbf{x}_i - \sum_{i=1}^n \mathbf{x}_i / n$  and  $\widehat{\mathbf{\Sigma}} = n^{-1} \sum_{i=1}^n \mathbf{z}_i \mathbf{z}_i^{\top}$  denotes a sample covariance matrix. The PM working matrix is then

$$\widehat{\mathbf{M}} = \sum_{k=1}^{h} \hat{\boldsymbol{\beta}}_k \hat{\boldsymbol{\beta}}_k^{\top}, \tag{6}$$

and its first d eigenvectors of  $\widehat{\mathbf{M}}$  estimate  $\mathbf{B}$  under (1), where d denotes the dimension of  $\mathcal{S}_{Y|\mathbf{X}}$ , often called as structure dimension. The **psvmSDR** package offers **psdr()** function to compute the linear PM estimates with a given loss function.

In the linear SDR, it is also crucial to estimate the structure dimension d. The linear

PM employs the following BIC-type criterion proposed by Li et al. (2011) to estimate d:

$$\hat{d} = \operatorname*{argmax}_{d \in \{1, \cdots, p\}} \sum_{j=1}^{d} v_j - \rho \frac{d \log n}{\sqrt{n}} v_1, \tag{7}$$

where  $v_1 \geq \cdots \geq v_p (p > d)$  are eigenvalues of  $\widehat{\mathbf{M}}$  in (6), with  $\rho$  being a hyperparameter that can be chosen in a data-adaptive manner. The **psvmSDR** package contains **psdr\_bic()** function for estimating d based on (7).

There are numerous PMs by employing a variety of convex loss function in supervised learning problems. For RPMs, the principal logistic regression with negative log-likelihood loss (PLR, Shin and Artemiou; 2017), the principal  $L_q$ -SVM with  $L_q$  hinge loss ( $L_q$ -PSVM, Artemiou and Dong; 2016), and the principal least square SVM with the squared loss (PLSSVM, Artemiou et al.; 2021) are proposed. For LPMs, Wang et al. (2018) suggested the principal quantile regression (PQR) with the check loss, Kim and Shin (2019) proposed the principal weighted logistic regression (PWLR), Soale and Dong (2022) introduced the principal asymmetric least square regression (PALS) with the asymmetric least square loss, and Jang et al. (2023) proposed the principal weighted least square SVM (PWLSSVM).

Table 1 provides a complete list of PMs implemented in **psvmSDR** with the corresponding loss functions.

### 2.2 Kernel principal machines for nonlinear SDR

A nonlinear generalization of (4) under (2) is

$$(\alpha_{0,k}, g_{0,k}) = \underset{\alpha \in \mathbb{R}, g \in \mathcal{H}}{\operatorname{argmin}} \operatorname{Var}\{\psi(\mathbf{X})\} + \lambda \operatorname{E}\left[L_k\left\{\widetilde{Y}_k, f(\mathbf{X})\right\}\right], \qquad k = 1, 2, \cdots, h, \qquad (8)$$

where  $f(\mathbf{X}) = \alpha + g(\mathbf{X}) - \mathbb{E}\{g(\mathbf{X})\}$  with g being a function in a Hilbert space  $\mathcal{H}$  of functions of  $\mathbf{X}$ . Let  $(\alpha_{0,k}, g_{0,k})$  be the minimizer of (8), then  $g_{0,k}(\mathbf{X})$  is necessarily a function of the sufficient predictor  $\phi(\mathbf{X})$  in (2) and its unbiasedness for the nonlinear SDR is established

Type	Method	Response	Margin (Residual)	Loss	loss
RPM	SVM	$Y \in \mathbb{R}$ $\tilde{Y}_k = \mathbb{1}\{Y \ge c_k\}$ $-\mathbb{1}\{Y < c_k\}$	$m_k = \tilde{Y}_k f$	$[1-m_k]_+$	'svm'
	Logistic			$\log(1 + e^{-m_k})^{-1}$	'logit'
	$L_2$ -SVM			$\{[1-m_k]_+\}^2$	'l2svm'
	LS-SVM			$[1 - m_k]^2$	'lssvm'
LPM	WSVM	$Y = \tilde{Y}_k \in \{-1, 1\}$	m = Yf	$\pi_k(Y)[1-m]_+$	'wsvm'
	Wlogistic			$\pi_k(Y)\log(1+e^{-m})^{-1}$	'wlogit'
	$WL_2$ -SVM			$\pi_k(Y)\{[1-m]_+\}^2$	'wl2svm'
	WLS-SVM			$\pi_k(Y)[1-m]^2$	'wlssvm'
	Quantile	$Y = \tilde{Y}_k \in \mathbb{R}$	r = Y - f	$r\{c_k - I(r < 0)\}$	ʻqr'
	Asym. LS			$r^{2}\{c_{k}-I(r<0)\}$	'asls'

Table 1: Different types of the convex loss functions available in the package **psvmSDR**. The column **loss** indicates a specific syntax of the argument that is passed to **psdr()** and **npsdr()** to implement the corresponding methods.

by Li et al. (2011).

Employing the reproducing kernel Hilbert space (RKHS) generated by a positive definite kernel  $K(\cdot, \cdot)$  for the space of g, we have the following finite-dimensional basis representation of g:

$$g(\mathbf{x}) = \sum_{j=1}^{b} \beta_j \left\{ \psi_j(\mathbf{x}) - \bar{\psi}_j \right\}$$
(9)

with

$$\psi_j(\mathbf{x}) = \{\mathbf{k}(\mathbf{x})\}^\top \mathbf{q}_j / \lambda_j, \quad j = 1, \dots b, \quad \text{and} \quad \bar{\psi}_j = \sum_{i=1}^n \psi_j(\mathbf{x}_i) / n, \quad (10)$$

where  $\mathbf{k}(\cdot) = \{K(\cdot, \mathbf{x}_i) : i = 1, ..., n\}^{\top}$ , and  $\mathbf{q}_j$  and  $\lambda_j$  are the *j*th leading eigenvector and eigenvalue of the centered kernel matrix  $\mathbf{K} = \{K_{ij}\} \in \mathbb{R}^{n \times n}$  with  $K_{ij} = K(\mathbf{x}_i, \mathbf{x}_j) - \sum_{k=1}^{n} K(\mathbf{x}_k, \mathbf{x}_j)/n$ . We refer Section 6 of Li et al. (2011) for the theoretical justification for (9) and (10). In **psvmSDR**, we employ the radial/Gaussian kernel and set b = n/3 as recommended by Li et al. (2011). By employing (9), the sample counter part of (8) is

$$(\hat{\alpha}_k, \hat{\boldsymbol{\beta}}_k) = \operatorname*{argmin}_{\alpha, \boldsymbol{\beta}} \boldsymbol{\beta}^{\mathsf{T}} \hat{\boldsymbol{\Sigma}} \boldsymbol{\beta} + \frac{\lambda}{n} \sum_{i=1}^n L_k \left( \tilde{y}_{k,i}, \alpha + \boldsymbol{\beta}^{\mathsf{T}} \mathbf{z}_i \right), \qquad k = 1, 2, \cdots, h, \qquad (11)$$

where  $\mathbf{z}_i = \sum_{j=1}^b \psi_j(\mathbf{x}_i) - \bar{\psi}_j$  and  $\hat{\mathbf{\Sigma}} = n^{-1} \sum_{i=1}^n \mathbf{z}_i \mathbf{z}_i^\top$ . We note that this kernel PM in (11) is also linear in the parameter, exactly the same as the linear PM (5). For a given  $\mathbf{x}$ , one can compute the sufficient predictors,  $\hat{\phi}(\mathbf{x}) = \widehat{\mathbf{V}}^\top \{\psi_1(\mathbf{x}), \dots, \psi_b(\mathbf{x})\}^\top$ , where  $\widehat{\mathbf{V}}$  denotes the *d*-leading eigenvectors of  $\sum_{k=1}^h \hat{\beta}_k \hat{\beta}_k^\top$ . The **psvmSDR** package offers npsdr() function to compute the nonlinear PM estimates.

### 2.3 Principal least square machines for realtime SDR

When data is collected in a streamed fashion, it is prohibitive to use all data to compute the SDR estimator due to memory constraints. Therefore, it is important to develop real-time SDR algorithms that directly update the SDR estimators without storing entire data. In this regard, Artemiou et al. (2021) proposed PLSSVM which solves (4) with the squared loss  $L(\tilde{y}, f) = (1 - \tilde{y}f)^2$ .

Let's consider the following scenario. In addition to the currently available (old) data  $\mathbb{D}_0 = (y_i, \mathbf{x}_i), i = 1, 2, \cdots, n$ , suppose m additional (new) data  $\mathbb{D}_{\mathbb{N}} = (y_i, \mathbf{x}_i), i = n + 1, \cdots, n + m$  arrives. Let  $\mathbb{D}_{\mathbb{W}} = \mathbb{D}_0 \cup \mathbb{D}_{\mathbb{N}}$  denote the whole data. The subscripts  $\mathbf{0}, \mathbf{N}$ , and  $\mathbb{W}$  are used to denote the quantities related to old, new, and whole data, respectively. Artemiou et al. (2021) showed that the PLSSVM solution for the whole data,  $\mathbf{r}_{\mathbb{W}} = (\hat{\alpha}_{\mathbb{W}}, \hat{\boldsymbol{\beta}}_{\mathbb{W}}^{\top})^{\top} \in \mathbb{R}^{p+1}$ , is given by

$$\mathbf{r}_{\mathsf{W}} = \{\mathbf{I} - \mathbf{A}_{\mathsf{0}}^{-1}\mathbf{B}_{\mathsf{N}}(\mathbf{I} + \mathbf{A}_{\mathsf{0}}^{-1}\mathbf{B}_{\mathsf{N}})^{-1}\}(\mathbf{r}_{\mathsf{0}} + \mathbf{A}_{\mathsf{0}}^{-1}\mathbf{c}_{\mathsf{N}}),\tag{12}$$

where  $\mathbf{r}_0$  is the solution for  $\mathbb{D}_0$ , and  $\mathbf{A}_0^{-1} \in \mathbb{R}^{(p+1) \times (p+1)}$  is also computable from  $\mathbb{D}_0$ , while  $\mathbf{B}_{\mathbb{N}} \in \mathbb{R}^{(p+1) \times (p+1)}$  and  $\mathbf{c}_{\mathbb{N}} \in \mathbb{R}^{p+1}$  are computable from  $\mathbb{D}_{\mathbb{N}}$ . That is, one can directly update

 $\mathbf{r}_{W}$  from  $\mathbf{r}_{0}$  without storing entire  $\mathbb{D}_{0}$ , but  $\mathbf{A}_{0}$  only. We remark that  $\mathbf{A}_{W}$  can be directly updated from  $\mathbf{A}_{0}$  and the new data, and its computational complexity does not depend on the size of  $\mathbb{D}_{0}$ . We refer Section 3 of Artemiou et al. (2021) for the exact forms of these quantities.

The **psvmSVM** package offers **rtpsdr()** that implements the realtime SDR using PLSSVM for a continuous response as well as PWLSSVM by Jang et al. (2023) for a binary response.

# 3 Computation

In this section, we describe computational details about psdr() and npsdr() in psvmSDR. Slightly abusing notation as  $\boldsymbol{\beta}^{\top} = (\alpha, \boldsymbol{\beta}^{\top})$  and  $\mathbf{z}_i^{\top} = (1, \mathbf{z}_i^{\top})$ , the objective functions (5) and (11) are then rewritten as

$$L(\boldsymbol{\beta}) = \boldsymbol{\beta}^{\top} \operatorname{Diag}\{0, \widehat{\boldsymbol{\Sigma}}\} \boldsymbol{\beta} + \frac{\lambda}{n} \sum_{i=1}^{n} L_k\left(\widetilde{y}_{k,i}, \boldsymbol{\beta}^{\top} \mathbf{z}_i\right).$$
(13)

We propose the coordinatewise gradient descent (CGD) algorithm to minimize  $L(\beta)$  in (13), which updates  $\beta$  coordinatewisely as follows until converge:

$$\beta_j \leftarrow \beta_j - \eta \frac{\partial L(\boldsymbol{\beta})}{\partial \beta_j}, \quad j = 0, 1, 2, \cdots, p,$$

where  $\eta > 0$  denotes a learning rate determined by the user. We remark that some loss functions, such as the hinge loss and check loss are not theoretically differentiable at most finite number of points while numerically differentiable. The two main functions psdr() and npsdr() in psvmSDR solve linear and kernel PMs via this CGD algorithm, respectively, and cover a wide variety of PM estimators by simply changing the loss functions (via 'loss' argument) as listed in Table 1. The CGD algorithm is easily extended to any userdefined convex loss function, since the corresponding derivative can be readily evaluated numerically. Both functions take the name of the user-defined-loss function object as the **loss** argument which brings further flexibility to the PM estimators.

The time complexity of the gradient descent method is known as  $\mathcal{O}(np)$  (Luo and Tseng; 1992; Friedman et al.; 2007), where p is the data dimension. Whereas, quadratic programming (QP), which is widely used in the context of solving an SVM-like problem via R package **kernlab**, is known as to have a polynomial rate,  $\mathcal{O}(n^3p^3)$ , at worst (Platt; 1998; Cristianini and Shawe-Taylor; 2000). To illustrate the computational efficiency of the proposed CGD algorithm, we compare its computing times for both linear and kernel PSVM estimators to **ipop()** function in **kernlab**, a standard QP solver for the SVM over 100 independent repetitions. A toy data is generated from the following regression model:

$$y_i = x_{i1} / \left\{ 0.5 + (x_{i2} + 1)^2 \right\} + 0.2\epsilon_i, \tag{14}$$

where both  $x_{ij}$  and  $\epsilon_i$  are i.i.d. random samples from N(0,1) for  $i = 1, \dots, n$  and  $j = 1, 2, \dots, 5$ . Different sample sizes n are considered from 5,000 to 30,000 for linear PSVM while from 300 to 3,000 for the kernel PSVM where the parameter dimension depends on n. Figure 1 contrasts the computing times between the CGD and the QP algorithms. It clearly demonstrates the computational efficiency of CGD algorithm implemented in **psvmSDR**.

# 4 Package overview and implementation

# 4.1 Overview of the package psvmSDR

The **psvmSDR** package is organized to allow users to run different types of PM methods in a unified fashion by calling just a few interface functions. Several auxiliary codes are then internally called to perform computations according to the options specified in those interface functions. The overall design of **psvmSDR** adopts the functional object-oriented programming approach (Chambers; 2014) with **S3** classes and methods. Every function in



Figure 1: Averaged computing times for QP and CGD algorithms over 100 repetitions are depicted. The blue dashed line with asterisks is for QP and the red dashed line with diamond is for CGD algorithm. The computing time gap increases substantially for the linear and nonlinear cases as the sample size gets larger. The dashed lines present the confidence intervals for both algorithms.

the package is either a wrapper that creates a single instance of an object or a method that

can be applied to a class object.

The package can be loaded in an R session via:

### R> install.packages("psvmSDR")

#### R> library("psvmSDR")

The main functions in the package are psdr() and npsdr(). These are designed to be analogous to linear and nonlinear principal sufficient dimension reduction methods, respectively. Each function returns an S3 object, 'psdr' and 'npsdr', respectively. Also, compatible S3 methods plot() and print() let the users enjoy the result of dimension reduction through familiar generic functions. Moreover, some explicit methods of which are related to the main functions are also provided, such as psdr\_bic() and npsdr\_x().

A function rtpsdr() implements the principal least square SVM in a realtime fashion (Artemiou et al.; 2021; Jang et al.; 2023) discussed in Section 2.3. Table 2 summarizes the main functions along with their compatible methods. In the following subsections, we demonstrate the general usage of the main functions and methods of **psvmSDR** by the **S3** class of the function.

Function	Description	Class	Compatible	
			methods	
psdr()	Basic function for applying linear PMs with a various loss functions		<pre>psdr_bic() plot_psdr()</pre>	
rtpsdr()	Real time sufficient dimension reduction throug principal (weighted) least squares SVM	$\overline{h}$ 'psdr'	<pre>print.psdr()</pre>	
npsdr()	Basic function for applying kernel PMs with a various loss functions	'npsdr'	<pre>npsdr_x() plot.npsdr() print.npsdr()</pre>	

Table 2: Main functions and compatible methods in the **psvmSDR** package.

## 4.2 Functions for S3 class 'psdr'

A function psdr() provides a unified interface for all linear PMs solved by the coordinatewise gradient decent algorithm. The following arguments are used (some are mandatory) when calling psdr() function and they must be provided in the order that follows:

R> psdr(x, y, loss = "svm", h = 10, lambda = 1, eps = 1.0e-5, max.iter = 100, eta = 0.1, mtype="m", plot = FALSE)

- x: input matrix; each row is an observation vector. x should have 2 or more columns.
- y: response vector, either can be continuous or  $\{1, -1\}$ -coded binary variable.
- loss: name of loss function objects listed in Table 1, or the name of a user-defined (convex) loss function object.
- h: number of slices.
- lambda: cost parameter.
- eps: stopping criterion of the CGD algorithm.

- max.iter: maximum iteration number of the CGD algorithm.
- eta: learning rate for the CGD algorithm.
- mtype: a margin type, which is either margin ("m") or residual ("r") (See, Table 1).
   Only needed when user-defined loss is used. The default is "m".
- plot: boolean. If TRUE, scatter plots of Y and sufficient predictors are depicted.

The main function psdr() returns an object with S3 class 'psdr' including

- evalues: eigenvalues of the estimated working matrix (6).
- evectors: eigenvectors of the estimated working matrix (6).

To further illustrate how to use function psdr(), we reuse the toy example which is formulated in (14) with n = 200.

R> set.seed(100)
R> n <- 200; p <- 5
R> x <- matrix(rnorm(n\*p, 0, 1), n, p)
R> y <- x[,1]/(0.5 + (x[,2] + 1)^2) + 0.2 \* rnorm(n)</pre>

We then can apply the PSVM (Li et al.; 2011) using function psdr() with calling the argument loss = "svm" (default value) as below:

R> obj <- psdr(x, y)
R> print(obj)

#### \$evalues

[1] 0.7802035134 0.0450979178 0.0069745442 0.0013436194 0.0002315534
\$evectors

[,1] [,2] [,3] [,4] [,5] [1,] 0.996301948 0.0002739995 -0.006936561 0.07908355 0.03286382

[2,]	0.001962004	-0.9577841701	0.125064041	-0.10815774	0.23517339
[3,]	-0.018812750	-0.2384741801	0.125542475	0.57099528	-0.77522875
[4,]	-0.045008311	0.1507599374	0.767379695	0.46014120	0.41790450
[5,]	0.070702982	0.0552350897	0.616180461	-0.66654494	-0.40986542

The output "evectors" correctly estimate the true basis vectors  $(1, 0, 0, 0, 0)^{\top}$  and  $(0, 1, 0, 0, 0)^{\top}$ . The method plot.psdr() creates the scatter plots between response and the *j*-th sufficient predictors.

R> plot(obj)



Figure 2: Scatter plots of Y versus the first sufficient predictor  $\hat{B}_1^{\top} \mathbf{X}$  from the generic method plot.psdr().

The argument obj is the object from the function psdr() which contains information on estimated  $S_{Y|X}$ . The number of sufficient predictors to be plotted is specified by the argument d whose default value is 1. By default, a locally weighted scatterplot smoothing (LOWESS) curve is plotted, unless lowess=FALSE is specified. The argument "..." allows for additional arguments to be passed to generic plot() function such as main, cex, col, lty, and etc. Now, we generate binary response  $\tilde{y}_i = \operatorname{sign}(y_i)$  from (14) to illustrate the PWSVM (Shin et al.; 2017), an example of the LPM. One can apply PWSVM by letting loss = "wsvm".

R> y.binary <- sign(y)
R> obj\_wsvm <- psdr(x, y.binary, loss = "wsvm")
R> print(obj\_wsvm)
R> plot(obj\_wsvm)

\$evalues

[1] 3.476293e-01 7.191191e-12 1.127804e-14 1.307353e-15 1.413672e-16
\$evectors

[,5]	[,4]	[,3]	[,2]	[,1]	
0.0633682181	0.06954918	0.05672899	0.01602173	0.99381714	[1,]
0.0003881853	-0.52608610	-0.56478786	0.63307786	0.05882480	[2,]
0.5209674569	0.41136035	-0.69467381	-0.27655680	-0.01789413	[3,]
0.4794100790	-0.71901964	0.12690122	-0.48647584	0.02034888	[4,]
-0.7033798428	-0.17941503	-0.42322673	-0.53461511	0.09018236	[5,]

Figure 3 visualizes the classification performance with only two sufficient predictors estimated by PWSVM. With only two sufficient predictors, the two classes are well separated.

One of many advantages of psdr() is that it can adopt any convex user-defined loss function in addition to existing choices listed in Table 1. A basic syntax of the arbitrary loss function follows:

loss\_name <- function(u, ...){ body of a function }</pre>

Argument **u** is a variable of a function (any character is possible) and any additional parameters of the loss function can be specified via ... argument. For example, one can define 'mylogistic' and apply it to the function psdr() by specifying loss="mylogistic".



Figure 3: A scatter plot of the predicted projections on the first and second sufficient predictors, i.e.,  $\hat{b}_1^T \mathbf{X}$ ,  $\hat{b}_2^T \mathbf{X}$ , respectively, estimated by PWSVM with loss="wsvm".

```
R> mylogistic <- function(u) log(1+exp(-u))</pre>
```

R> obj\_mylogistic <- psdr(x, y, loss="mylogistic")</pre>

R> print(obj\_mylogistic)

### \$evalues

[1] 1.556551e-01 8.926810e-03 1.407538e-03 2.607252e-04 4.640626e-05

### \$evectors

[,5]	[,4]	[,3]	[,2]	[,1]	
-0.03358709	0.07818789	-0.008433507	0.0002783802	0.996336971	[1,]
-0.23208110	-0.11231156	0.125656435	-0.9579820189	0.002321387	[2,]
0.76617188	0.58427863	0.119983562	-0.2384204646	-0.018941160	[3,]
-0.42166590	0.45467693	0.768896248	0.1495969167	-0.043428997	[4,]
0.42448651	-0.65814903	0.615257540	0.0551979934	0.071150592	[5,]

As aforementioned, psvmSDR provides a function psdr\_bic() that implements the

BIC-type criterion in (7). Following arguments are mandatory when calling the psdr\_bic():

R> d.hat <- psdr\_bic(obj, rho = 0.01, plot = TRUE, ...)

- obj: the output object from the main function psdr()
- rho: A hyperparameter in the BIC criterion.
- plot: Boolean. If TRUE, the plot of BIC values is depicted.
- ...: additional arguments to be passed to generic plot().
- R> d.hat <- psdr\_bic(obj, rho=0.03)</pre>

R> print(d.hat)

[1] 0.7714345 0.8077633 0.8059689 0.7985434 0.7900059



Figure 4: BIC values computed from psdr\_bic() with plot = TRUE.

### 4.3 Functions for S3 class 'npsdr'

The function npsdr() is a nonlinear version of psdr that implements kernel PMs. A function npsdr() receives the following arguments:

All input arguments are identical to those for psdr() except b which denotes the number of basis functions on RKHS in (10). The function npsdr() returns an object with S3 class "npsdr" that contains the following.

- evalues: eigenvalues of the estimated working matrix.
- evectors: eigenvectors of the estimated working matrix.

The kernel information is stored internally and is not explicitly returned unless forced to print the object obj.psi.

To further illustrate how to use function npsdr(), we use the following model used in Li et al. (2011):

$$y_i = 0.5 \left( x_{i1}^2 + x_{i2}^2 \right)^{1/2} \log \left( x_{i1}^2 + x_{i2}^2 \right) + 0.2\epsilon_i, \quad i = 1, \dots, 200.$$
(15)

Following code is for demonstrating kernel PSVM using function npsdr().

```
R> set.seed(100)
R> n <- 200; p <- 5
R> x <- matrix(rnorm(n*p, 0, 1), n, p)
R> y <- 0.5*sqrt((x[,1]^2+x[,2]^2))*(log(x[,1]^2+x[,2]^2))+ 0.2*rnorm(n)
R> obj_kernel <- npsdr(x, y, max.iter = 200, eta = 0.8, plot = FALSE)
R> print(obj_kernel)
```

\$evalues

[1] 1.717934e+02 2.104448e+01 8.189522e+00 4.193012e+00 1.933547e+00
[6] 1.933547e+00 1.447649e+00 ...

\$evectors

[,2] [,3] [,1] [,4] . . . [1.] 0.008226254 -0.034169390 -0.146711415 0.0645862074 [2,] -0.168561065 -0.107815274 -0.174786643 -0.2614510539 . . . . . . . . . . . . . . . . . . [ reached getOption("max.print") -- omitted 51 rows ]

Beside the main function,  $npsdr_x()$  computes the estimated sufficient predictors  $\hat{\phi}(\mathbf{x}) = \hat{\mathbf{V}}_n^{\top} \{\psi_1(\mathbf{x}), \dots, \psi_b(\mathbf{x})\}^{\top}$  in (2) for a given  $\mathbf{x}$ . The usage of function  $npsdr_x()$  is given below.

The arguments object is the object from the result of npsdr(), and newdata is a new data matrix. The argument d is for the number of sufficient predictors and its default value is 2. In the final line of the code above, npsdr\_x() computes  $\hat{\phi}(\mathbf{x})$  the nonlinear dimension reduction of new.x under (2) using kernel PSVM estimates.

Note that the regression function (15) is symmetric about the origin. In such a scenario, linear PMs do not work and the kernel PM would be an attractive alternative. Figure 5 depicts the scatter plots of the response and the first sufficient predictor estimated by (a) the linear PSVM and (b) the kernel PSVM. As expected, the linear PSVM fails to find the central subspace when the regression function is symmetric about the origin, while the nonlinear PSVM still efficiently identifies sufficient predictors.



Figure 5: Scatter plots of the response and the first sufficient predictor estimated by (a) the linear PSVM and (b) the kernel PSVM.

# 4.4 Functions for 'rtpsdr'

The package **psvmSDR** also provides **rtpsdr()** for the realtime SDR using squared loss (Artemiou et al.; 2021; Jang et al.; 2023), and its usage is given below.

R> rtpsdr(x, y, obj = NULL, h = 10, lambda = 1)

- x: covariate matrix of a new data.
- y: response vector of a new data.
- obj: the output object from rtpsdr() for the old data that contains the PM solutions and matrices for the old data. If it is not given, psdr() with the squared loss (PLSSVM) is to be applied to the given data, y and x to obtain the PM solutions and the matrices. The PWLSSVM is applied if y is binary.

- h a number of slices. The default is set to 10.
- lambda hyperparameter for the loss function. The default is set to 0.1.

rtpsdr() returns an object S3 class 'psdr' that includes

- evalues: eigenvalues of the estimated working matrix.
- evectors: eigenvectors of the estimated working matrix.
- **r**: the PLSSVM/PWLSSVM solutions **r** in (12).
- A: updated matrix A for the realtime update.

A returned object from rtpsdr() stores the state of the algorithm at each iteration t. This object is passed to the function as an argument and is returned at each iteration t+1 containing the state of the model parameters at that step.

The following command is an example of rtpsdr() under the streamed data scenario. The data are collected in a batch-wise manner with the batch size of m = 500.

R> round(obj\$evectors, 3)

[,1] [,2] [,3] [,4] [,5]

[1,]	1.000	0.011	0.014	-0.012	-0.002
[2,]	0.011	-0.999	-0.001	-0.033	0.004
[3,]	-0.003	-0.009	0.674	0.336	0.658
[4,]	-0.017	0.014	0.715	-0.521	-0.466
[5,]	-0.006	0.029	-0.186	-0.784	0.592

For binary classification, rtpsdr() computes PWLSSVM solution (Jang et al.; 2023). We note that rtpsdr() returns psdr object and thus print.psdr() and plot.psdr() are applicable.

# 5 Summary and discussion

In this article, we introduced and tutored the R software package **psvmSDR**, by unifying linear and nonlinear SDR under the principal machine (PM) framework. The package emphasizes its practical and convenient utilities through simple and user-friendly code syntax and access to various PMs. The use of gradient descent for computation ensures efficiency and scalability, particularly beneficial in large-scale datasets. Moreover, the package offers realtime update scheme for batch-wise data collection scenarios. The **psvmSDR** invites researchers and practitioners in R communities to explore and use the powerful tools for the principal sufficient dimension reduction in their work.

# **Computational details**

The results in this paper were obtained using R 4.2.1 with the **psvmSDR** package. It is possible to have different simulation results depending on which linear algebra package is installed and which version of R is used.

# References

- Aronszajn, N. (1950). Theory of reproducing kernels, Transactions of the American mathematical society 68(3): 337–404.
- Artemiou, A. and Dong, Y. (2016). Sufficient dimension reduction via principal l q support vector machine, *Electronic Journal of Statistics* **10**(1): 783–805.
- Artemiou, A., Dong, Y. and Shin, S. J. (2021). Real-time sufficient dimension reduction through principal least squares support vector machines, *Pattern Recognition* 112: 107768.
- Chambers, J. M. (2014). Object-oriented programming, functional programming and R, Statistical Science **29**(2): 167 – 180.
- Cook, R. D. (1998). Regression Graphics: Ideas for Studying Regressions Through Graphics,Wiley, New York.
- Cook, R. D. (2007). Fisher lecture: Dimension reduction in regression, *Statistical Science* 22: 1–26.
- Cook, R. D. and Weisberg, S. (1991). Discussion of "sliced inverse regression for dimension reduction", Journal of the American Statistical Association 86: 28–33.
- Cristianini, N. and Shawe-Taylor, J. (2000). An Introduction to Support Vector Machines and Other Kernel-Based Learning Methods, Cambridge university press.
- Friedman, J., Hastie, T., Höfling, H. and Tibshirani, R. (2007). Pathwise Coordinate Optimization, The Annals of Applied Statistics 1(2): 302 – 332.
- Jang, H. J., Shin, S. J. and Artemiou, A. (2023). Principal weighted least square support vector machine: An online dimension-reduction tool for binary classification, *Computational Statistics & Data Analysis* 187: 107818.

- Kim, B. and Shin, S. J. (2019). Principal weighted logistic regression for sufficient dimension reduction in binary classification, *Journal of the Korean Statistical Society* 48(2): 194– 206.
- Li, B., Artemiou, A. and Li, L. (2011). Principal support vector machines for linear and nonlinear sufficient dimension reduction, *Annals of Statistics* **39**(6): 3182–3210.
- Li, K.-C. (1991). Sliced inverse regression for dimension reduction (with discussion), *Journal* of the American Statistical Association **86**: 316–342.
- Li, K.-C. (1992). On principal hessian directions for data visualization and dimension reduction: Another application of stein's lemma, *Journal of the American Statistical Association* 87: 1025–1039.
- Luo, Z.-Q. and Tseng, P. (1992). On the convergence of the coordinate descent method for convex differentiable minimization, *Journal of Optimization Theory and Applications* 72(1): 7–35.
- Platt, J. (1998). Sequential minimal optimization: A fast algorithm for training support vector machines, *Technical Report MSR-TR-98-14*, Microsoft.
- Shin, J. and Shin, S. J. (2024). A concise overview of principal support vector machines and its generalization, *Communications for Statistical Applications and Methods* **31**(2): 235– 246.
- Shin, S. J. and Artemiou, A. (2017). Penalized principal logistic regression for sparse sufficient dimension reduction, *Computational Statistics & Data Analysis* **111**: 48–58.
- Shin, S. J., Wu, Y., Zhang, H. H. and Liu, Y. (2017). Principal weighted support vector machines for sufficient dimension reduction in binary classification, *Biometrika* 104(1): 67– 81.

- Soale, A.-N. and Dong, Y. (2022). On sufficient dimension reduction via principal asymmetric least squares, *Journal of Nonparametric Statistics* **34**(1): 77–94.
- Vapnik, V. (1999). The Nature of Statistical Learning Theory, Springer science & business media.
- Wang, C., Shin, S. J. and Wu, Y. (2018). Principal quantile regression for sufficient dimension reduction with heteroscedasticity, *Electronic Journal of Statistics* 12(2): 2114–2140.
- Weisberg, S. (2015). Dimension reduction regression in R, Journal of Statistical Software 7(1): 1–22. R package version 3.0.10.

**URL:** *https://cran.r-project.org/web/packages/dr*