# Transformation equation for frames undergoing non-uniform acceleration such as SHM and rotational motion

Ranchhaigiri Brahma<sup>1\*</sup> and A.K. Sen<sup>1†</sup>

<sup>1</sup>Department of Physics, Assam University, Silchar-788011, India \* Email: rbrahma084@gmail.com † Email: asokesen@yahoo.com

#### Abstract

Lorentz transformation equations provide us a set of relations between the spacetime co-ordinates as observed from two different inertial frames. In case, one of the frames is moving with a uniform rectilinear we have Rindlers transformation equations under such a situation. In the present work we extend the Rindlers equations to a situation where we have in general non-uniform acceleration. First we consider the non-inertial frame to undergo simple harmonic motion (SHM) and as a second case we consider the non-inertial frame to move uniformly along a circle. This set of transformation equations will have applications in various branches of Physics and in general in Astrophysics.

**Keywords:** Relativity; Frame of references; Rindler transformation; Non-uniform motions; Circular motions; Accelerated frames.

### 1 Introduction

The coordinate transformation relations for a frame of reference moving with a constant velocity with respect to an inertial frame is known as the Lorentz transformation [1]. These relations play a vital role during the investigation of a test particle in a frame moving with constant velocity. In the case of an accelerated frame the general transformation relations are presented in [2, 3]. The coordinate transformations for uniformly accelerated frame with constant proper acceleration is known as Rindler transformation and the consequences of such coordinate frame have been studied in [4, 5]. In Rindler transformation the initial velocity is considered as zero. However the coordinate transformation for accelerated frame with non-zero initial velocity has been discussed in [5]. Additionally the Rindler transformation having acceleration along an arbitrary direction on the XY plane has been analysed in [6]. In the present work we investigate the coordinate transformation relations for a non-uniform acceleration such as a frame executing simple harmonic motion (SHM) and subsequently the transformation relations for a frame having rotational motion. In order to carry out the above calculations, we have to first derive Rindler like transformation equations for coordinates frames having simple harmonic motion. Since the circular motion of an object can be described by two SHMs with same amplitudes in perpendicular directions having phase difference of  $\pi/2$  radians, so the transformation relations for the frame executing SHM can be used to understand the consequences of moving frame in a circular path. Using that knowledge towards the end, we obtain the coordinate transformation relations for a frame of reference moving in a circular path. Such work will have immense applications in the study of the test particles in the non-uniformly accelerated frames such as frames executing SHM and the frames moving in a circular path.

We organised our paper as: In Section 2 we obtain the transformation relations for a frame of reference executing simple harmonic motion (SHM) along X-direction. Additionally in Section 3 we calculated the similar transformation relations for the frame of reference executing SHM along Y-direction. And then as mentioned above since the circular motion can be described by using the two SHMs in perpendicular direction and phase difference of  $\pi/2$  radians, towards the end we obtained the transformation relations for a frame that is moving in a circular path. At last in Section 4 we discussed the results obtained in the above calculations and concluded our findings.

## 2 Transformation relations for a frame of reference executing SHM

The original Rindler transformation equation is meant for constant acceleration. So we have to first derive the transformation relations where proper acceleration or coordinate acceleration is a function of time. Most specifically for a frame executing simple harmonic motion (SHM) the coordinate acceleration is a sinusoidal function of time. Below we derive the transformation relations for the case when the frame is oscillating along the X-direction having displacement proportional to some sinusoidal function of angular frequency  $\omega$ .

Base on Castillo & Sanchez [7] we can write:

$$\int \frac{du_x}{\left(1 - \frac{u_x^2}{c^2}\right)^{3/2}} = \int a_x \, dt \tag{1}$$

where  $u_x$  is the X- component of the three velocity. In case of Castillo & Sanchez [7] they assumed the proper acceleration  $a_x$  in X-direction to be constant. However in our case we take  $a_x$  to represent a simple harmonic motion (SHM), so we take  $a_x = -r_0\omega^2\sin(\omega t)$ , where  $r_0$  is the amplitude of the SHM and  $\omega$  is the angular frequency. Therefore substituting  $a_x = -r_0\omega^2\sin(\omega t)$  in equation (1) and integrating we obtain:

$$\int_{0}^{u_x} \frac{du_x}{\left(1 - \frac{u_x^2}{c^2}\right)^{3/2}} = -\int_{0}^{t} r_0 \omega^2 \sin(\omega t) dt$$
  
or 
$$\frac{u_x}{\sqrt{1 - \frac{u_x^2}{c^2}}} = r_0 \omega \Big[\cos(\omega t) - 1\Big]$$
(2)

Now solving the above equation (2) for  $u_x$  we obtain as:

$$u_{x} = \frac{r_{0}\omega \left\{ \cos(\omega t) - 1 \right\}}{\sqrt{1 + \frac{r_{0}^{2}\omega^{2}}{c^{2}} \left\{ \cos(\omega t) - 1 \right\}^{2}}}$$
  
or  $u_{x} = -\frac{2r_{0}\omega \sin^{2}(\omega t/2)}{\sqrt{1 + \frac{4r_{0}^{2}\omega^{2}}{c^{2}} \sin^{4}(\omega t/2)}}$  (3)

Further from the equation (3) we can obtain the distance x as follows:

$$\frac{dx}{dt} = -\frac{2r_0\omega\sin^2(\omega t/2)}{\sqrt{1 + \frac{4r_0^2\omega^2}{c^2}\sin^4(\omega t/2)}}$$
  
or 
$$\int_0^x dx = -\int_0^t \frac{2r_0\omega\sin^2(\omega t/2)}{\sqrt{1 + \frac{4r_0^2\omega^2}{c^2}\sin^4(\omega t/2)}} dt$$
  
or 
$$x = -\int_0^{\omega t/2} \frac{4r_0\sin^2(\omega t/2)}{\sqrt{1 + \frac{4r_0^2\omega^2}{c^2}\sin^4(\omega t/2)}} d(\omega t/2)$$
(4)

Since  $r_0\omega/c$  would be very small, so we shall be neglecting terms higher than  $(r_0\omega/c)^2$  in order. Therefore we can write the above equation (4) as:

$$x \approx -4r_0 \int_0^{\omega t/2} \sin^2(\omega t/2) \left[ 1 - \frac{1}{2} \frac{4r_0^2 \omega^2}{c^2} \sin^4(\omega t/2) \right] d(\omega t/2)$$
  
or  $x \approx \left( \frac{5r_0^3 \omega^3}{4c^2} - r_0 \omega \right) t + \left( r_0 - \frac{15r_0^3 \omega^2}{8c^2} \right) \sin(\omega t)$ 

$$+\frac{3r_{0}^{3}\omega^{2}\sin(\omega t)\cos(\omega t)}{4c^{2}} - \frac{r_{0}^{3}\omega^{2}}{24c^{2}}\left\{3\sin(\omega t) - 4\sin^{3}(\omega t)\right\}$$
  
or  $x \approx \left(\frac{5r_{0}^{3}\omega^{3}}{4c^{2}} - r_{0}\omega\right)t + \left[\left(r_{0} - \frac{15r_{0}^{3}\omega^{2}}{8c^{2}}\right) + \frac{3r_{0}^{3}\omega^{2}\cos(\omega t)}{4c^{2}} - \frac{r_{0}^{3}\omega^{2}}{24c^{2}}\left\{3 - 4\sin^{2}(\omega t)\right\}\right]\sin(\omega t)$  (5)

Additionally the relation between the proper time and the coordinate time can be written as:  $\tau = \int \sqrt{1 - \frac{u^2}{c^2}} dt$  and hence using equation (3) we obtain the expression for the X- component of the proper time  $(\tau_x)$  as follows:

$$\tau_x = \int_0^t \sqrt{1 - \frac{u_x^2}{c^2}} dt = \int_0^t \left[ 1 - \frac{\frac{r_0^2 \omega^2}{c^2} \left\{ \cos(\omega t) - 1 \right\}^2}{1 + \frac{r_0^2 \omega^2}{c^2} \left\{ \cos(\omega t) - 1 \right\}^2} \right]^{1/2} dt$$
$$= \int_0^t \left[ 1 + \frac{r_0^2 \omega^2}{c^2} \left\{ \cos(\omega t) - 1 \right\}^2 \right]^{-1/2} dt$$
$$\approx \int_0^t \left[ 1 - \frac{r_0^2 \omega^2}{2c^2} \left\{ \cos(\omega t) - 1 \right\}^2 \right] dt \tag{6}$$

$$\approx t \left( 1 - \frac{3r_0^2 \omega^2}{4c^2} \right) + \frac{r_0^2 \omega \sin(\omega t)}{c^2} - \frac{r_0^2 \omega \sin(2\omega t)}{8c^2}$$
(7)

Now we may replace  $\tau_x$  by  $\bar{t}_x$ , like it was done in [7]. Here,  $\bar{t}_x$  represents the time as measured from the accelerated frame. So we may write:

$$\bar{t}_x \approx t \left( 1 - \frac{3r_0^2 \omega^2}{4c^2} \right) + \frac{r_0^2 \omega \sin(\omega t)}{c^2} - \frac{r_0^2 \omega \sin(2\omega t)}{8c^2}$$
(8)

At this stage we find that, from equation (8) it will be difficult to express t in terms of  $\bar{t}_x$ , as no standard solution exists for equation (8). So we consider a special case where the time period of the simple harmonic motion  $(1/\omega)$  is much higher than the time (t) during which the acceleration has been observed. As a result one may write  $\omega t \ll 1$ . So we can write:  $\sin(\omega t) \approx \omega t$ ,  $\cos(\omega t) \approx 1 - \frac{\omega^2 t^2}{2}$ 

and hence the equation (8) can be written as:

$$\bar{t}_x \approx t \left\{ 1 - \frac{3r_0^2 \omega^2}{4c^2} + \frac{r_0^2 \omega^2}{c^2} - \frac{r_0^2 \omega^2}{4c^2} \left(1 - \frac{\omega^2 t^2}{2}\right) \right\}$$
  
or  $\bar{t}_x \approx t + \frac{r_0^2 \omega^4 t^3}{8c^2}$  (9)

The equation (9) is a cubic equation of t that can be written as:

$$t^3 + pt + q = 0 (10)$$

where  $p = \frac{8c^2}{r_0^2\omega^4}$  and  $q = -\frac{8c^2\bar{t}_x}{r_0^2\omega^4}$ . This equation can be solved [8] and one can write:

$$t = \frac{4c}{r_0\omega^2}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_0\omega^2\,\bar{t}_x}{4c}\sqrt{\frac{3}{2}}\right)\right] \tag{11}$$

Then substituting t from equation (11) into equation (5) we obtain as follows:

$$x \approx \left(\frac{5r_{0}^{3}\omega^{3}}{4c^{2}} - r_{0}\omega\right) \frac{4c}{r_{0}\omega^{2}}\sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_{0}\omega^{2}\bar{t}_{x}}{4c}\sqrt{\frac{3}{2}}\right)\right] \\ + \left[\left(r_{0} - \frac{15r_{0}^{3}\omega^{2}}{8c^{2}}\right) + \frac{3r_{0}^{3}\omega^{2}}{4c^{2}}\cos\left\{\frac{4c}{r_{0}\omega}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_{0}\omega^{2}\bar{t}_{x}}{4c}\sqrt{\frac{3}{2}}\right)\right]\right\} - \frac{r_{0}^{3}\omega^{2}}{24c^{2}}\left\{3 - 4\sin^{2}\left\{\frac{4c}{r_{0}\omega}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_{0}\omega^{2}\bar{t}_{x}}{4c}\sqrt{\frac{3}{2}}\right)\right]\right\}\right]\sin\left\{\frac{4c}{r_{0}\omega}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_{0}\omega^{2}\bar{t}_{x}}{4c}\sqrt{\frac{3}{2}}\right)\right]\right\}\right\}$$

$$(12)$$

In the limit of  $\omega \longrightarrow 0$  we obtain from equations (11) and (12):

$$\lim_{\omega \to 0} t = \bar{t}_x \tag{13}$$

and 
$$\lim_{\omega \to 0} x = 0$$
 (14)

The equations (11) and (12) would be the general Rindler-like co-ordinate transformation relation for a frame undergoing Simple Harmonic Motion. Further the equations (13) and (14) above confirm the boundary condition when there is no oscillation ( $\omega = 0$ ). Therefore the transformation relations for the frame of reference executing SHM in X-direction with respect to an inertial frame can be written as follows (using (11) and (12)):

$$ct = \frac{4c^2}{r_0\omega^2}\sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_0\omega^2 \bar{t}_x}{4c}\sqrt{\frac{3}{2}}\right)\right]$$
(15)  

$$x = \bar{x} + \left(\frac{5r_0^3\omega^3}{4c^2} - r_0\omega\right)\frac{4c}{r_0\omega^2}\sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_0\omega^2 \bar{t}_x}{4c}\sqrt{\frac{3}{2}}\right)\right]$$
$$+ \left[\left(r_0 - \frac{15r_0^3\omega^2}{8c^2}\right) + \frac{3r_0^3\omega^2}{4c^2}\cos\left\{\frac{4c}{r_0\omega}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_0\omega^2 \bar{t}_x}{4c}\sqrt{\frac{3}{2}}\right)\right]\right\} - \frac{r_0^3\omega^2}{24c^2}\left\{3 - 4\sin^2\left\{\frac{4c}{r_0\omega}\sqrt{\frac{2}{3}}\sinh\left[\frac{1}{3}\sinh^{-1}\left(\frac{3r_0\omega^2 \bar{t}_x}{4c}\sqrt{\frac{3}{2}}\right)\right]\right\}\right\}$$
(16)  

$$y = \bar{y}$$
(17)  

$$z = \bar{z}$$
(18)

### 3 Transformation relations for the frame moving in a circular path

The circular motion of an object orbiting on the XY plane is best described by two simultaneous SHMs (simple harmonic motions) of same amplitudes in Xand Y directions separated by a phase angle  $\pi/2$  radians. Therefore we may start with coordinate transformation for an accelerated object with non-uniform proper acceleration along the X and Y -axes simultaneously. So as we want the X- and Y-component should together represent a circular motion ( with radius  $r_0$ ), we write proper acceleration in Y-direction  $a_y = -r_0\omega^2\cos(\omega t)$ , as we had written earlier  $a_x = -r_0\omega^2\sin(\omega t)$ .

Therefore considering  $u_y$  as the Y- component of the three velocity, we can write as we did earlier for SHM in Y-direction as follows:

$$\int_{0}^{u_y} \frac{du_y}{\left(1 - \frac{u_y^2}{c^2}\right)^{3/2}} = -\int_{0}^{t} r_0 \omega^2 \cos(\omega t) dt$$
  
or 
$$\frac{u_y}{\sqrt{1 - \frac{u_y^2}{c^2}}} = -r_0 \omega \sin(\omega t)$$
(19)

Then solving for  $u_y$  the above equation (19) can be written as:

$$u_y = \frac{r_0 \,\omega \,\sin(\omega t)}{\sqrt{1 + \frac{r_0^2 \omega^2}{c^2} \,\sin^2(\omega t)}}$$
(20)

So from the equation (20) the distance in the Y-direction can be obtained as follows:

$$\frac{dy}{dt} = \frac{r_0 \omega \sin(\omega t)}{\sqrt{1 + \frac{r_0^2 \omega^2}{c^2} \sin^2(\omega t)}}$$
  
or 
$$\int_0^y dy = \int_0^t \frac{r_0 \omega \sin(\omega t)}{\sqrt{1 + \frac{r_0^2 \omega^2}{c^2} \sin^2(\omega t)}} dt$$
(21)

Now expanding the terms inside the square root and neglecting the terms higher than  $(r_0\omega/c)^2$  we obtain:

$$y = r_0 \omega \int_0^t \sin(\omega t) \left[ 1 - \frac{r_0^2 \omega^2}{2c^2} \sin^2(\omega t) \right] dt$$
$$= r_0 \omega \left[ \int_0^t \sin(\omega t) dt - \int_0^t \frac{r_0^2 \omega^2}{2c^2} \sin^3(\omega t) dt \right]$$

$$= r_0 \left( 1 - \cos(\omega t) \right) - \frac{2r_0^3 \omega^2}{3c^2} \sin^4 \left( \frac{\omega t}{2} \right) \left( 2 + \cos(\omega t) \right)$$
(22)

Now the above equation gives y = 0 at t = 0. But it is not realistic here. The frame is moving on a circle. So the position (x, y) = (0, 0) is unknown. When x = 0, at t = 0 we should have  $y = y_0 = r_0$  at t = 0. Therefore in the above equation we add an initial value of y (at t = 0), which is  $r_0$ . Thus we write:

$$y = r_0 + r_0 \left(1 - \cos(\omega t)\right) - \frac{2r_0^3 \omega^2}{3c^2} \sin^4\left(\frac{\omega t}{2}\right) \left(2 + \cos(\omega t)\right)$$
(23)

Additionally as calculated earlier the Y- component of the proper time  $\tau_y$  can be obtained by using (20) as below:

$$\tau_y = \int_0^t \sqrt{1 - \frac{u_y^2}{c^2}} dt = \int_0^t \frac{dt}{\sqrt{1 + \frac{r_0^2 \omega^2}{c^2} \sin^2(\omega t)}}$$
$$\approx \int_0^t \left[ 1 - \frac{r_0^2 \omega^2}{2c^2} \sin^2(\omega t) \right] dt \tag{24}$$
$$\approx \left( 1 - \frac{r_0^2 \omega^2}{4c^2} \right) t + \frac{r_0^2 \omega \sin(2\omega t)}{8c^2}$$
$$\approx \left( 1 - \frac{r_0^2 \omega^2}{4c^2} \right) t + \frac{r_0^2 \omega}{4c^2} \sin(\omega t) \cos(\omega t) \tag{25}$$

As earlier replacing  $\tau_y$  by  $\bar{t}_y$  and considering  $\omega t \ll 1$  we can write:  $\sin(\omega t) \approx \omega t$ ,  $\cos(\omega t) \approx 1 - \frac{\omega^2 t^2}{2}$  in equation (25) and obtain as:

$$\bar{t}_y \approx \left(1 - \frac{r_0^2 \omega^2}{4c^2}\right) t + \frac{r_0^2 \omega}{4c^2} \omega t \left(1 - \frac{\omega^2 t^2}{2}\right)$$
  
or  $\bar{t}_y \approx t - \frac{r_0^2 \omega^4 t^3}{8c^2}$  (26)

The above equation is a cubic equation of t in the form as below:

$$t^3 + Pt + Q = 0 (27)$$

where  $P = -\frac{8c^2}{r_0^2\omega^4}$  and  $Q = \frac{8c^2 \bar{t}_y}{r_0^2\omega^4}$ . So the solution of this equation can be written as [8]:

$$t = 2\sqrt{-\frac{P}{3}} \sin\left[\frac{1}{3}\sin^{-1}\left(-\frac{3Q}{2P}\sqrt{-\frac{3}{P}}\right)\right]$$
  
or  $t = 2\sqrt{\frac{8c^2}{3r_0^2\omega^4}} \sin\left[\frac{1}{3}\sin^{-1}\left(\frac{3\bar{t}_y}{2}\sqrt{\frac{3r_0^2\omega^4}{8c^2}}\right)\right]$   
or  $t = \frac{4c}{r_0\omega^2}\sqrt{\frac{2}{3}}\sin\left[\frac{1}{3}\sin^{-1}\left(\frac{3r_0\omega^2\bar{t}_y}{4c}\sqrt{\frac{3}{2}}\right)\right]$  (28)

Then substituting t from equation (28) into equation (23) we obtain as follows:

$$y \approx r_0 + r_0 \left[ 1 - \cos \left\{ \frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin \left[ \frac{1}{3} \sin^{-1} \left( \frac{3r_0 \omega^2 \bar{t}_y}{4c} \sqrt{\frac{3}{2}} \right) \right] \right\} \right]$$
$$- \frac{2r_0^3 \omega^2}{3c^2} \sin^4 \left\{ \frac{2c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin \left[ \frac{1}{3} \sin^{-1} \left( \frac{3r_0 \omega^2 \bar{t}_y}{4c} \sqrt{\frac{3}{2}} \right) \right] \right\}$$
$$\times \left[ 2 + \cos \left\{ \frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin \left[ \frac{1}{3} \sin^{-1} \left( \frac{3r_0 \omega^2 \bar{t}_y}{4c} \sqrt{\frac{3}{2}} \right) \right] \right\} \right]$$
(29)

In the limiting condition of  $\omega \longrightarrow 0$  the equations (28) and (29) become:

$$\lim_{\omega \to 0} t = \bar{t}_y \tag{30}$$

and 
$$\lim_{\omega \to 0} y = r_0$$
 (31)

The above equations (30) and (31) confirm the boundary condition when there is no oscillation (i.e.  $\omega = 0$ ).

The transformation relation for time  $\bar{t}$  in a frame orbiting in a circular path can be determined from (9) and (26). We can see from these two equations that,  $\bar{t}_x = t + At^3$  and  $\bar{t}_y = t - At^3$ , where  $A = \frac{r_0^2 \omega^4}{8c^2}$ . So the average value of t as observed from the rotating frame will be just  $\bar{t}$ . Now since A is very small, so for simplicity of our calculations, one can just take  $\bar{t}_x \approx \bar{t}_y \approx t$  as an approximation. Therefore we may write :

$$\bar{t}_x \approx \bar{t}_y \approx \bar{t} \approx t \tag{32}$$

Now since the circular motion of an object orbiting on the XY plane can be described by two simultaneously acting SHM (simple harmonic motion) of same amplitudes in X and Y directions separated by a phase angle  $\pi/2$  radians, so the general coordinate transformation relations for a frame orbiting in a circular path can be written (from eqns. (12) and (29)) as follows:

$$\begin{split} t &= \bar{t} \quad (33) \\ x &= \bar{x} + \left(\frac{5r_0^3 \omega^3}{4c^2} - r_0 \omega\right) \frac{4c}{r_0 \omega^2} \sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3} \sinh^{-1}\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \\ &+ \left[\left(r_0 - \frac{15r_0^3 \omega^2}{8c^2}\right) + \frac{3r_0^3 \omega^2}{4c^2} \cos\left\{\frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3} \sinh^{-1}\right] \\ &\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} - \frac{r_0^3 \omega^2}{24c^2} \left\{3 - 4\sin^2\left\{\frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3} \sinh^{-1}\right] \\ &\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} \right] \sin\left\{\frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sinh\left[\frac{1}{3} \sinh^{-1}\right] \\ &\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} \quad (34) \\ y &= \bar{y} + r_0 + r_0 \left[1 - \cos\left\{\frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin\left[\frac{1}{3} \sin^{-1}\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} \right] \\ &- \frac{2r_0^3 \omega^2}{3c^2} \sin^4\left\{\frac{2c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin\left[\frac{1}{3} \sin^{-1}\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} \\ &\times \left[2 + \cos\left\{\frac{4c}{r_0 \omega} \sqrt{\frac{2}{3}} \sin\left[\frac{1}{3} \sin^{-1}\left(\frac{3r_0 \omega^2 \bar{t}}{4c} \sqrt{\frac{3}{2}}\right)\right] \right\} \right] \quad (35) \\ z &= \bar{z} \quad (36) \end{split}$$

### 4 Discussion of results and conclusions

In this work we obtained the transformation relations between an inertial frame and a frame executing non-uniform acceleration such as SHM. In a similar way calculations were done to determine the co-ordinate transformation relations for an inertial frame and another frame moving along a circle with uniform angular velocity. These transformation relations can be used to investigate the dynamics of the test particles in the above mentioned non-uniformly accelerated frames. Additionally the results in this paper will be applicable for practical calculations of the relativistic effects, such as in a spacecraft orbiting around the Earth etc. These calculations will have applications in different branches of Relativistic Physics and more specifically in Relativistic Astrophysics and General Relativity.

#### References

- T. Padmanabhan. Gravitation : Foundations and Frontiers. Cambridge University Press, Cambridge, 2010.
- Robert A Nelson. Generalized lorentz transformation for an accelerated, rotating frame of reference. *Journal of mathematical physics*, 28(10):2379–2383, 1987.
- [3] Robert A. Nelson. Erratum: Generalized Lorentz transformation for an accelerated, rotating frame of reference [J. Math. Phys.28, 2379–2383 (1987)]. Journal of Mathematical Physics, 35(11):6224–6225, 1994.
- [4] David Tilbrook. General coordinatisations of the flat space-time of constant proper-acceleration. Australian Journal of Physics, 50:851, 1997.
- [5] Sangwha Yi. Expansion of rindler coordinate theory and light's doppler effect. *The African Review of Physics*, 8(0037):243–255, 2013.

- [6] Ranchhaigiri Brahma and A. K. Sen. Gravitational field due a moving schwarzschild object, 2024. https://arxiv.org/abs/2405.01932.
- [7] Gerardo Torres del Castillo and C. Sánchez. Uniformly accelerated observers in special relativity. *Revista Mexicana de Física*, 52:70–73, 2006.
- [8] A.J. Anyaegbunam. Simple formulae for the evaluation of all the exact roots (real and complex) of the general cubic. *Nigerian Journal of technology*, 27, 2008.

This figure "Fig1.png" is available in "png" format from:

http://arxiv.org/ps/2409.01677v1