

Google Quantum AI's Quest for Error-Corrected Quantum Computers

Muhammad AbuGhanem^{1,2}

¹ Faculty of Science, Ain Shams University, Cairo, 11566, Egypt and
² Zewail City of Science, Technology and Innovation, Giza, 12678, Egypt*

(Dated: October 3, 2024)

Quantum computers stand at the forefront of technological innovation, offering exponential computational speed-ups that challenge classical computing capabilities. At the cutting edge of this transformation is Google Quantum AI, a leader in driving forward the development of practical quantum computers. This article provides a comprehensive review of Google Quantum AI's pivotal role in the quantum computing landscape over the past decade, emphasizing their significant strides towards achieving quantum computational supremacy. By exploring their advancements and contributions in quantum hardware, quantum software, error correction, and quantum algorithms, this study highlights the transformative impact of Google Quantum AI's initiatives in shaping the future of quantum computing technology.

Keywords: Google Quantum AI, quantum supremacy, Superconducting quantum computers, Sycamore quantum processors, Foxtail, Bristlecone, Sycamore, Google quantum hardware, quantum software, Cirq, OpenFermion, TensorFlow Quantum, Qsim.

CONTENTS

I. Introduction	1	B. Random circuit sampling	11
II. Google Quantum AI	2	C. The OTOCs and Floquet evolution	11
III. A Decade of Research and Innovation	3	V. The Quantum Computational Supremacy	13
A. 2013: Early developments	3	A. The XEB theory	13
B. 2014: Defining and detecting quantum speedup	3	B. Quantum processors	13
C. 2015: Quantum hardware design and error correction	4	C. The 53-qubits <i>Sycamore</i> processor	13
D. 2016: Quantum algorithms and system performance	4	D. The SYC-67 and SYC-70 quantum processors	16
E. 2017: Commercialize quantum technologies in five years	5	VI. Quantum Software	17
F. 2018: The path to quantum supremacy with superconducting qubits	5	A. Cirq	17
G. 2019: Quantum supremacy—the <i>Sycamore</i> processor and beyond	6	B. OpenFermion	20
H. 2020: Quantum chemistry and simulation techniques	6	C. TensorFlow Quantum	20
I. 2021: Quantum machine learning and optimization	7	D. Qsim	20
J. 2022: Quantum advantage in learning from experiments	8	VII. Grover search algorithm with Cirq	21
K. 2023: Quantum error correction	8	VIII. Towards large-scale useful quantum computers	22
L. 2024: Continuing the quantum quest	10	IX. Conclusion	23
IV. Comparing NISQ processors and classical computers	10	Acknowledgments	23
A. Evaluating the computational cost of noisy quantum processing experiments	10	Funding	23
		References	24

I. INTRODUCTION

The Noisy Intermediate-Scale Quantum (NISQ) computing era [1] has marked a significant milestone in the evolution of quantum technology [2]. While these quantum processors are powerful [3–6], they still face substantial challenges due to escalating error rates, as system sizes increase [7], presenting significant challenges to reliable computation [1, 8].

* gaa1nem@gmail.com
 mghanem@sci.asu.edu.eg

To address these limitations [1], error-corrected quantum computers are crucial for advancing quantum technology in the post-NISQ era. These systems aim to mitigate the inherent errors associated with qubit operations [9, 10], particularly as system sizes increase, enabling more reliable computation. By focusing on reducing operational error rates in quantum processing units (QPUs) [11, 12], we can unlock the full potential of quantum computing [13, 14], paving the way for large-scale quantum computers capable of executing complex, error-corrected computations [15–17]. This progress is essential for pushing the boundaries of quantum technology and realizing meaningful applications across diverse fields, from drug design [18] to cryptography [19] and beyond [2].

At the forefront of this transformation is Google Quantum AI, a key player pushing the boundaries of what quantum technology can achieve [6]. Since its inception, Google Quantum AI has been instrumental in advancing the field, particularly through its innovations in superconducting qubits and its ambitious pursuit of quantum computational supremacy [20, 21].

This paper explores Google Quantum AI’s pivotal role in advancing quantum computing technology. The research highlights the company’s journey from early developments to achieving notable milestones in quantum supremacy. With a focus on their advancements in quantum hardware, quantum software, and quantum error correction (QErC) [15–17].

Our exploration offers insights into their impact on both theoretical and practical aspects of quantum computing. By analyzing their research and development efforts year by year, we aim to provide a comprehensive overview of how Google Quantum AI has shaped the landscape of quantum technology and what lies ahead in their ongoing quest to build error-corrected, large-scale quantum computers.

The subsequent sections of this paper are structured as follows: Section II presents an overview of Google Quantum AI, highlighting its foundational role and key milestones. Section III chronicles the company’s progress year by year from 2013 to 2024. Section IV discusses comparing the performance of NISQ processors with classical computers. Section V addresses Google Quantum AI’s achievement of computational supremacy, with detailed examinations of the 53-qubit *Sycamore* processor (SYC-53) and subsequent quantum processors like the SYC 67- and SYC 70-qubit models. Section VI provides an overview of Google’s contributions to quantum software and open-source tools, highlighting key platforms such as Cirq, OpenFermion, TensorFlow Quantum, Qsim, and discussing their impact on quantum algorithm development and research. Section VIII discusses Google Quantum AI roadmap and the path towards building large-scale useful quantum computers, emphasizing the strategies and challenges involved. The paper concludes with a summary of findings and reflections on the future trajectory of quantum computing technology in Section IX.

II. GOOGLE QUANTUM AI

Google Quantum AI stands at the forefront of quantum computing innovation, shaping the future of the field with transformative advancements in technology and theory [6]. Since its inception, Google Quantum AI has been dedicated to pushing the boundaries of classical computing, leveraging quantum mechanics to solve complex problems across various domains, including physics [6], chemistry [22], and optimization [23, 24].

Central to Google Quantum AI’s efforts is the Quantum Artificial Intelligence Lab (QuAIL), a collaborative initiative established in 2013 with partners such as NASA and the Universities Space Research Association (USRA). This lab has been instrumental in advancing quantum computing research, culminating in the landmark achievement of quantum supremacy regime in 2019 [6]—a milestone that demonstrated the practical capabilities of quantum processors to outperform classical supercomputers on specific tasks [2, 20].

A cornerstone of Google Quantum AI’s research is the development and refinement of superconducting qubits [25–27], which are implemented using superconducting circuits [28, 29]. These circuits, often based on Josephson junctions, represent a promising approach to scalable quantum computing due to their compatibility with existing semiconductor technologies and their potential for high fidelity and coherence [30–32].

One of the key achievements of Google Quantum AI in this area has been the significant improvement in qubit coherence times [33]. Coherence time, the period during which a qubit maintains its quantum state without succumbing to decoherence, is crucial for reliable quantum computations. By addressing environmental noise and enhancing qubit design, Google Quantum AI has successfully extended coherence times, thereby enhancing the stability and reliability of their qubits.

Error management remains another critical focus for Google Quantum AI. Quantum systems are inherently susceptible to errors from noise, control imperfections, and environmental interactions [15, 16]. To address these challenges, the team has made notable progress in reducing error rates through sophisticated error correction techniques and optimization of qubit designs [33–35]. These advancements contribute to more accurate and stable quantum computations.

Google Quantum AI has utilized their quantum processors to explore novel physical phenomena. This includes observing time crystals [36] and Majorana edge modes [37], as well as making new experimental discoveries like robust bound states of interacting photons [38] and the noise resilience of Majorana edge modes in Floquet evolutions [37].

Looking ahead, Google Quantum AI is committed to further advancing qubit performance and expanding its quantum infrastructure. Their ambitious goal is to construct a fully fault-tolerant quantum computer by integrating thousands of surface-encoded logical qubits, sig-




FIG. 1. The roadmap for quantum computing at Google Quantum AI illustrates their commitment to unlocking the ultimate potential of quantum computing through the development of a large-scale, error-corrected computer. The journey is guided by six pivotal milestones. The first milestone, beyond classical, was achieved in 2019, marking a significant advance over classical computing [6]. The second milestone, error-corrected qubits (see Section III K). Subsequent milestones include building a long-lived logical qubit, creating a logical gate, and engineering scale-up. The final milestone, a large error-corrected quantum computer, represents the ultimate goal of connecting and controlling 1 million qubits, pushing the boundaries of quantum technology to realize meaningful applications.

nificantly reducing error rates and overcoming the limitations of current technology [39].

As the field progresses, Google Quantum AI’s ongoing contributions will undoubtedly continue to shape the future of quantum computing and drive the next wave of technological innovation.

III. A DECADE OF RESEARCH AND INNOVATION

In this section, we shed light on the progress and achievements of Google Quantum AI over the past decade, tracing their journey from early developmental stages to achieving quantum computational supremacy and advancing QErC (see Figure 1). As a leader in the field, Google Quantum AI has made significant strides, and we will delve into key research from each year to highlight their major contributions and their impact on the broader quantum computing landscape.

A. 2013: Early developments

The application of quantum computing to machine learning tasks was explored in 2013 [40]. The study examined how quantum algorithms could potentially enhance the efficiency of processing and classifying large datasets within high-dimensional spaces [41]. Unlike classical algorithms, which typically exhibit polynomial time complexity, these quantum algorithms are capable of performing clustering tasks in logarithmic time relative to the number of data points and dimensions, thereby offering an exponential speed-up.

B. 2014: Defining and detecting quantum speedup

In 2014, a superconducting qubit architecture featuring high-coherence qubits and dynamically tunable coupling is presented in [42]. This architecture (known as *gmon*, constructed using the *Xmon* transmon design [43]) allows the coupling to be set to zero and adjusted with nanosecond precision, thereby avoiding frequency crowd-

ing issues and supporting a range of applications, including quantum logic gates and simulations. The approach was demonstrated with a novel, fast adiabatic controlled-Z gate (CZ), showcasing potential for scalable quantum computation.

The research in [44] focused on defining and measuring quantum speedup. Using data from a D-Wave Two device with up to 503 qubits, the study conducted benchmark tests with random spin glass instances [45]. The results showed no clear evidence of quantum speedup, both when analyzing the full dataset and its subsets.

The first experimental evidence of the computational role of multi-qubit quantum tunneling in quantum annealers [46, 47] is presented in [48]. Utilizing the NIBA (Non-interacting Blip Approximation) Quantum Master Equation [49], the researchers developed a model that describes the effects of multi-qubit dissipative tunneling in the presence of complex noise. The model’s predictions align well with experimental data from the D-Wave Two quantum annealer, illustrating an increase in success probabilities for problems with up to 200 qubits.

Quantum coherence in scalable quantum annealing processors using qubit tunneling spectroscopy [50] is explored in [51]. The study revealed that qubits in both two- and eight-qubit systems became entangled during quantum annealing, and this entanglement persisted even at thermal equilibrium.

Advanced superconducting quantum circuits are leveraged in [52], to explore the topological properties of quantum systems. By measuring the deflection of quantum trajectories in the parameter space of a Hamiltonian [53], the researchers applied a quantum analog of the Gauss–Bonnet theorem, revealing essential topological features. They validated their technique using the Haldane model [54] and extended it to interacting systems with a certain qubit architecture [55, 56], uncovering an interaction-induced topological phase. This approach established a robust platform for studying topological phenomena in quantum systems.

Dynamics-based sampling methods are improved [57], by introducing variables that stabilized momentum fluctuations caused by noise from stochastic gradients [58, 59]. Drawing inspiration from statistical mechanics [60], this method enhanced sampling efficiency and stability in large datasets.

C. 2015: Quantum hardware design and error correction

In 2015, a tunable coupler design for superconducting Xmon qubits was investigated in [61], utilizing a flux-biased Josephson junction as a tunable current divider. The study calculated the effective qubit-qubit interaction Hamiltonian, finding that the qubit’s nonlinearity reduces the transverse coupling by about 15% and introduces a small diagonal coupling. The approach offers insights applicable to other complex nonlinear circuits in

quantum hardware design [43].

The simulation of the bond dissociation curve of the helium hydride cation (HeH^+) is thought to be the first molecule formed in the early universe [62] using a solid-state quantum register based on nitrogen-vacancy (NV) centers in diamond [63] was demonstrated in [22]. The researchers achieved an energy uncertainty of about 10^{-14} Hartree, surpassing the precision required for chemical applications. This work marks significant progress toward scalable quantum chemistry simulations using solid-state quantum platforms [64–66].

Advancements in QErC were highlighted in [67], where a nine-qubit linear array was used to protect classical states from bit-flip errors [7]. The researchers demonstrated reduced error rates with increasing system size, achieving a factor of 2.7 improvement with five qubits and 8.5 with nine qubits after eight cycles. Additionally, the preservation of a non-classical Greenberger–Horne–Zeilinger (GHZ) state [68] was verified, and effectively reducing environment-induced errors. Additional research efforts from the same year can be found in [69–71].

D. 2016: Quantum algorithms and system performance

In 2016, the variational quantum eigensolver (VQE) algorithm [72] was improved in [73] by introducing a variational adiabatic ansatz, quantum variational error suppression, and cost-reducing techniques such as truncation. The study demonstrated that modern optimization methods can significantly lower computational costs.

Digitized adiabatic quantum computing [74, 75] was implemented in a superconducting system [76]. This study combined adiabatic [77–79] and digital quantum computing [65, 80–83], using tomography to probe the system’s evolution and assess error scaling with system size [7]. The researchers solved the one-dimensional Ising problem and more complex Hamiltonians with up to nine qubits and 1,000 gates, contributing to the development of scalable quantum computing systems.

The first electronic structure calculation on a quantum computer without extensive pre-compilation was performed in [23]. Using superconducting qubits, the researchers computed the energy surface of molecular hydrogen using two quantum algorithms: the UCC (unitary coupled cluster) [84–87] method via the VQE [72] and Trotterization [88] with quantum phase estimation (QPE) [89]. The VQE achieved chemical accuracy and demonstrated better robustness to errors compared to traditional methods, highlighting its potential for future simulations of complex molecules.

Ergodic dynamics in a 3-qubit superconducting system were demonstrated in [90]. The research showed that the system explores all states over time, similar to classical chaotic systems [91–95]. By measuring entanglement entropy, the study revealed that the system acts as a reser-

voir, increasing entropy through entanglement. For additional research efforts by Google Quantum AI in 2016, readers are directed to [96–102].

E. 2017: Commercialize quantum technologies in five years

In 2017, Google’s Quantum AI outlined strategies for commercializing quantum technologies within five years [103]. Focusing on investment opportunities and steps needed to advance towards fully functional quantum machines, providing a roadmap to accelerate the development and deployment of these technologies (see Section VIII).

A scalable trapped ion quantum computer [104–107] was proposed in [108], featuring a modular design based on silicon microfabrication and long-wavelength radiation-based quantum gates [109, 110]. The design supports fault-tolerant operations through high error-threshold surface codes and allows for interconnection of standalone units via ion transport [111–113]. This approach can be adapted for various quantum computing architectures, including those utilizing photonic interconnects [4, 5].

Chiral ground-state currents of interacting photons were demonstrated in [114] using superconducting qubits in synthetic magnetic fields. By modulating qubit couplings to create artificial magnetic fields, the researchers observed directional photon circulation and strong photon interactions [115–117]. This setup offers a new platform for exploring quantum phases in systems with strongly interacting photons.

The energy levels of interacting photons were analyzed using a chain of nine superconducting qubits in [118]. This study revealed features of the Hofstadter butterfly spectrum [119, 120] and observed a transition from a thermalized to a localized phase by introducing disorder. This technique provides a novel approach to studying quantum phases of matter through many-body spectroscopy [121–123]. Additional research efforts from the same year can be found in [124–132].

F. 2018: The path to quantum supremacy with superconducting qubits

In 2018, several key contributions advanced the quest for quantum supremacy and improved quantum simulations [64–66]. The investigation of unpredictable fluctuations in energy-relaxation times of superconducting qubits was performed in [133]. This study identified individual two-level-system defects as the primary cause of these fluctuations by using qubits as temporal and spectral probes. The findings provide a basis for enhancing qubit stability through improved calibration, design, and fabrication techniques.

A dual plane wave basis for quantum simulation of electronic structures was introduced in [134]. This method reduces the complexity of Hamiltonians from $\mathcal{O}(N^4)$ to $\mathcal{O}(N^2)$ terms, facilitating more efficient Hamiltonian steps and reducing circuit depths for Trotter [135, 136] and Taylor-series simulations [137]. It also requires fewer measurements for variational algorithms.

The simulation of the electronic structure Hamiltonian using a “fermionic swap network” was presented in [138]. This approach achieves Trotter steps with linear depth (N) and requires $\mathcal{O}(N^2)$ two-qubit entangling gates [139–141]. It also allows for the preparation of Slater determinants with a depth of at most $N/2$, even on minimally connected qubit architectures. The authors suggest that this method is optimal in terms of gate count for Trotter steps and represents a significant practical advancement for quantum chemistry simulations [142].

A strategy for achieving quantum computational supremacy using superconducting qubits was outlined in [143]. By tuning nine qubits to generate diverse Hamiltonian evolutions, the researchers observed output probabilities aligning with a universal distribution, indicating uniform sampling of the Hilbert space [144]. These results demonstrate that increasing the qubit count could allow quantum systems to solve problems beyond the reach of classical computers.

The application of the VQE algorithm [72] to molecular energy simulations using the UCC (unitary coupled cluster) ansatz [72, 73, 84] was explored in [145]. The study introduced methods to reduce circuit depth and enhance wave-function optimization through efficient classical approximations of cluster amplitudes [146–149].

The challenges of using random circuits as initial guesses for hybrid quantum-classical algorithms [73] were revealed in [150]. They showed that the probability of obtaining a non-zero gradient decreases exponentially with the number of qubits, highlighting the need for improved designs of parameterized quantum circuits.

A QNN (quantum neural network) for binary classification tasks was presented in [151]. This QNN handles both classical and quantum data by applying parameterized unitary transformations to an input quantum state and measuring a Pauli operator to predict binary labels. The study also explored adapting the QNN for quantum data, suggesting its suitability for near-term quantum processors [1].

Sampling from RQCs as a task to demonstrate quantum supremacy [20] was proposed in [144]. The study argued that classical computation would require exponential time for this task, and introduced XEB [6, 143, 144, 152] to measure experimental fidelity in complex multi-qubit dynamics. It found that a 7×7 qubit grid performing around 40 clock cycles with specific error rates could achieve this milestone [2].

The experimental implementation of the VQE algorithm [72] using a trapped-ion quantum simulator [153] to calculate the ground-state energies of two molecules was reported in [142]. The study demonstrated and com-

pared different encoding methods with up to four qubits, addressed measurement noise and its mitigation, and explored adaptive strategies for achieving chemical accuracy, setting a benchmark for multi-qubit quantum simulators [154–157]. Additional research efforts from the same year can be found in [158–170].

G. 2019: Quantum supremacy—the *Sycamore* processor and beyond

In 2019, significant advancements in quantum computing were achieved. Quantum supremacy regime [20, 21] was demonstrated in [6] using a superconducting qubit processor with 54 qubits (see Figure 2), creating states in a computational space of dimension 2^{53} (approximately 10^{16}). Google Quantum AI and Collaborators revealed that the SYC-53 processor sampled quantum states in about 200 seconds, a task that would take approximately 10,000 years on a state-of-the-art classical supercomputer (see Section IV B). Shortly after the publication, a debate arose concerning the possible overestimation of the time needed to solve the same problem on a supercomputer [172–174]. Nevertheless, this achievement stands as a significant milestone in the field [2].

A quantum algorithm for simulating quantum chemistry was introduced in [175], with gate complexity scaling as $\mathcal{O}(N^{1/3}\eta^{8/3})$, where N is the number of orbitals and η is the number of electrons. This method employs interaction picture techniques in the rotating frame of the kinetic operator, offering significant efficiency improvements over previous algorithms [176–178], particularly for large basis sizes or without the Born-Oppenheimer approximation [179].

Diabatic two-qubit gates for frequency-tunable superconducting qubits were reported in [180], achieving Pauli error rates as low as $4.3 \times 10^{-3} \pm 0.0002$ in 18 ns, with average gate fidelities up to 0.9966 ± 0.0002 . This improvement is attributed to the synchronization of gate parameters with minima in the leakage channel, which enhances gate robustness. This method, validated with CPHASE [181] and iSWAP-like [182] gates, lays the groundwork for extending to multi-body operations.

A prototype cryogenic CMOS quantum controller was presented in [183], designed in a 28-nm CMOS process to manage transmon qubits [184, 185] with a 16-word XY gate instruction set. The study details the controller’s design and performance, noting low error rates, scalability, and cryogenic operation. It achieves under 2 mW power dissipation and a digital data stream of less than 500 Mb/s.

The flexible quantum circuit simulator, qFlex, was introduced in [186]. Using tensor networks, qFlex computes both exact and low-fidelity amplitudes for verifying and mimicking NISQ devices [1, 2]. It efficiently simulates RQCs expected in supremacy experiments [144, 187–196], achieving simulations at a cost $1/f$ of perfect fidelity ones. The study also eliminates rejec-

tion sampling overhead and benchmarks qFlex on NASA HPC clusters [197], achieving a peak performance of 20 PFLOPS, the highest numerical computation in terms of sustained floating-point operations per second (FLOPS) and node usage on these clusters.

The improvement of QNNs through classical neural networks and meta-learning, alternatively referred to as “learning to learn” [198–202], was explored in [203]. By training classical recurrent neural networks to find approximate optimal parameters for quantum algorithms. They investigated the effectiveness of this method for several problem classes, including QAOA for Sherrington-Kirkpatrick Ising models [128], QAOA for MaxCut [204], and a VQE for the Hubbard model [86, 138, 162]. The approach reduces the number of optimization iterations needed, improves convergence to local minima, and generalizes well across different problem sizes.

A framework combining reinforcement learning (RL) and deep neural networks (DNNs) [205–209] to optimize quantum control was introduced in [210]. The framework (namely “Universal control cost Function Optimization” or “UFO”) focuses on improving both speed and fidelity of two-qubit gates by incorporating control noise into the training environment [211–213]. This approach reduces average gate error [214–218] by two orders of magnitude and gate time by up to one order of magnitude compared to traditional methods [219], offering promising applications for quantum simulation [156], quantum chemistry [142], and quantum supremacy [1, 2] tests with near-term quantum devices [2, 144]. Additional research efforts from the same year can be found in [220–227].

H. 2020: Quantum chemistry and simulation techniques

In 2020, several notable advancements were witnessed. Quantum simulations of chemistry, including diazene isomerization, were explored in [228] using up to twelve qubits. This paper introduces error-mitigation techniques based on “ N -representability” [229–231] to enhance fidelity. By employing parameterized ansatz circuits and variationally optimizing Givens rotation for non-interacting fermion evolution, the study prepares the Hartree-Fock wave function [232]. Although this method remains classically tractable, it generates highly entangled states, offering insights into hardware performance and paving the way for larger-scale quantum chemistry simulations [64–66, 233–237].

The introduction of OpenFermion, an open-source Python library for quantum simulations, is detailed in [238]. This library simplifies the simulation of fermionic and bosonic systems, providing an interface to electronic structure packages. It facilitates the translation from molecular specifications to quantum circuits, reducing the need for deep domain expertise (see section VI).

TensorFlow Quantum (TFQ), an open-source library




FIG. 2. Demonstration of quantum computational supremacy using SYCAMORE. The process comprises four steps: First, a specific quantum circuit is selected. Next, the circuit is executed on the quantum processor. Following this, the processor’s fidelity is estimated, and the labor cost is assessed. Finally, the results indicate that quantum computational supremacy has been achieved. Reproduced from [171].

for designing and training hybrid quantum-classical models, was introduced in [239]. TFQ integrates with TensorFlow to support quantum circuit simulations and offers high-level tools for tasks such as quantum classification, control, and optimization. It also facilitates advanced quantum learning applications, including meta-learning [198–202] and VQEs, aiming to enable research in quantum computing and machine learning [240] (see section VI).

The variational quantum unsampling protocol was introduced in [241]. This method learns the features of quantum circuits by unraveling their unknown dynamics using a nonlinear QNN. Tested on a photonic quantum processor [5], the protocol aids in verifying quantum outputs and has broad applications, including quantum measurement [242], quantum tomography [141, 243], sensing [244], quantum imaging [245], and ansatz validation [86, 246, 247].

A 16-qubit digital superconducting quantum processor was used in [248] to simulate the dynamics of the one-dimensional Fermi-Hubbard model [249–253], revealing distinct spreading velocities of charge and spin densities in the highly excited regime. Advanced gate calibration and error-mitigation techniques [248, 254–256] were introduced to address systematic errors and decoherence, enabling accurate simulation despite complex circuits.

The paper [257] presents qFlex, a tensor-network-based classical simulator for benchmarking NISQ computers [2]. The study details high-performance computing simulations of RQCs on *Summit*, the world’s fastest supercomputer (at that time), achieving 281 PFLOP/s. The results highlight the significant energy efficiency advantage of NISQ devices [1, 2] over classical supercom-

puters and propose a standard benchmark for evaluating NISQ systems based on qFlex.

A continuous two-qubit gate set for gmon qubits was demonstrated in [258], achieving a threefold reduction in circuit depth compared to standard methods. The implemented gates include an iSWAP-like gate [182] for arbitrary swap angles and a controlled-phase gate for arbitrary conditional phases [180], enabling the full fSim gate set. Results show an average two-qubit Pauli error of 3.8×10^{-3} , reflecting high fidelity across 525 different fSim gates. Additional research efforts from the same year can be found in [259–269].

I. 2021: Quantum machine learning and optimization

In 2021, Google Quantum AI made significant progress in various areas of quantum computing. The application of quantum computing to machine learning was explored in [270]. The method to factor 2048-bit RSA integers in 8 hours using 20 million noisy qubits is presented in [271]. The paper outlines the requirements for this construction, including logical qubits, Toffoli gates [272, 273], and measurement depth, and discusses its implications for RSA encryption [274] and discrete logarithm-based cryptographic schemes [275].

The use of Google Sycamore’s quantum processor, comprises a 2-dimensional grid of 54 transmon qubits [6], for combinatorial optimization with the QAOA is demonstrated in [276]. The study explores both hardware-native problems (defined on the connectivity graph of the hardware) and non-native ones, such as the Sherrington-

Kirkpatrick model and MaxCut [277]. For native problems, performance improves with circuit depth, while for non-native problems, it decreases with size. Although QAOA [204] circuits outperform random guessing, they do not surpass some classical algorithms, highlighting the difficulty of scaling QAOA [204] for non-native problems and suggesting a focus on non-native problems for benchmarking quantum processors.

The preparation of the ground state of the toric code Hamiltonian using a superconducting quantum processor is reported in [278]. The paper measures topological entanglement entropy close to the expected value and performs anyon interferometry to analyze the braiding statistics of emergent excitations [279–283]. These results highlight the potential of quantum processors to advance understanding in topological quantum matter and QErC [284–286].

The use of one-dimensional repetition codes on a 2-dimensional grid of superconducting qubits to achieve exponential suppression of bit-flip and phase-flip errors is demonstrated in [287]. The study shows that increasing the number of qubits from 5 to 21 reduces logical errors by over 100 times, with stability maintained over 50 rounds of error correction [15, 16, 288]. The paper presents a method for precise error correlation analysis and performs error detection with a small logical qubit using the 2D surface code [289, 290].

An overview of variational quantum algorithms (VQAs) as a promising approach to leveraging quantum computing despite current device limitations is provided in [24]. The rapid development and potential of quantum simulators are discussed in [291]. The paper highlights the use of entanglement and many-particle behavior to tackle complex scientific and engineering problems, noting that over 300 quantum simulators worldwide have emerged in the last two decades [291]. Recent advancements promise a new era for both specialized and programmable simulators, recommending investment to enhance scientific applications and foster multi-disciplinary collaborations. Additional research efforts from the same year can be found in [292–324].

J. 2022: Quantum advantage in learning from experiments

In 2022, the potential of quantum technology to significantly enhance learning from experiments is demonstrated in [325]. The study reveals that quantum machines can offer exponential advantages in predicting system properties, performing quantum principal component analysis on noisy states, and learning physical dynamics [240, 244]. Experimental results using up to 40 superconducting qubits and 1,300 quantum gates confirm that substantial advantages are achievable even with current noisy quantum processors [1].

The observation of a discrete time crystal (DTC) [326–333] in a periodically driven many-body-localized

(MBL) [334, 335] system using superconducting qubits and CPHASE gates is reported in [336]. The study demonstrates the DTC’s characteristic spatiotemporal response from various initial states and employs a time-reversal protocol to measure external decoherence effects. Efficient sampling of the eigen-spectrum and a finite-size analysis identify the phase transition out of the DTC, showcasing a scalable approach for exploring non-equilibrium phases of matter with quantum processors.

The investigation into the QAOA for the Sherrington-Kirkpatrick model [277], a complex optimization problem with random signed couplings among spins, is detailed in [337]. The research assesses whether QAOA can match the performance of a classical algorithm by Montanari [338], which can efficiently approximate the Sherrington-Kirkpatrick model’s ground state energy. Additional contributions from 2022 include [339–367].

K. 2023: Quantum error correction

In 2023, several notable advancements were made, particularly in quantum error correction and achieving quantum computational advantage. The study [9] addressed the challenge of incoherent noise in quantum processors, which disrupts long-range correlations and coherent computation. By employing RCS [144, 187–196] and XEB [6, 143, 144, 152], the researchers identify key phase transitions related to cycle counts and error rates per cycle. Their RCS experiment, involving 67 qubits and 32 cycles, demonstrates that quantum processors can reach a computationally complex phase despite noise, surpassing current classical supercomputers’ capabilities and marking a significant advancement in handling quantum noise (as detailed in Section VD).

The performance of logical qubits in a superconducting qubit system with QErC [15, 16] is reported in [33]. QErC is capable of significantly reducing operational error rates in quantum processing units, albeit with increased demands on both time and qubit resources [369, 370]. Numerous studies have successfully implemented error correction using codes designed to rectify single errors, including color QErC code [371], the distance-3 Bacon-Shor QErC code [372], 5-qubit QErC code [373], surface QErC codes [374, 375], and heavy-hexagon QErC code [376], along with (CV) continuous variable QErC codes [377–380]. Nevertheless, a pivotal question persists: will scaling up the size of the error-correcting code lead to lower logical error rates in practical devices [33]? An answer to this question is reported by Google Quantum AI in [33]. The study shows that increasing the number of physical qubits enhances logical qubit performance, even though it introduces additional error sources. They unveiled a 72-qubit superconducting processor that employs a 49-qubit distance-5 surface code slightly surpasses the performance of its average subset, a 17-qubit distance-3 surface code (see Fig-




FIG. 3. Google’s quantum computer achieves a significant milestone by decreasing error rates. Researchers have shown for the first time that increasing the number of qubits can reduce the error rate in quantum calculations [33]. Image source [368]. Credit: Google Quantum AI.

ure 3). The research also identifies high-energy events affecting performance using a distance-25 repetition code, highlighting progress and ongoing challenges in achieving low logical error rates for practical quantum computing [7, 10, 271, 296, 381–384].

A critical challenge in QErC, specifically leakage of quantum information into non-computational states, is addressed in [385]. The study introduces a technique using a distance-3 surface code and a distance-21 bit-flip code to actively remove leakage from qubits [357, 386, 387]. This approach reduces steady-state leakage by tenfold and maintains an average leakage population of less than 1×10^{-3} , preventing leakage from causing correlated errors and advancing the feasibility of scalable QErC [33].

A control optimization strategy [388] for managing the frequency trajectories of 68 frequency-tunable [389] superconducting transmon qubits [33] is presented in [390]. This strategy improves gate execution and error mitigation, significantly reducing physical error rates compared to non-optimized systems. The approach is projected to be effective for larger systems, such as a distance-23 surface code with 1057 physical qubits, offering a scalable solution adaptable to various quantum algorithms and architectures.

The development of a high dynamic range Josephson parametric amplifier [391], using an array of rf-SQUIDs, is detailed in [392]. The amplifier achieves a bandwidth of 250-300 MHz and handles input saturation powers up to -95 dBm at 20 dB gain, tested with a Sycamore (54-

qubit) quantum processor. The amplifier exhibits no negative effects on system noise, readout fidelity, or qubit dephasing, with added noise only 1.6 times the quantum limit, addressing gain compression issues common in traditional Josephson parametric amplifiers used for multi-tone multiplexed readout.

The challenges and opportunities in leveraging quantum computing for drug development are examined in [18]. The perspective highlights the transformative potential of quantum computing in this field and outlines the necessary steps to achieve these advancements [393–395]. Additionally, the potential for exponential quantum advantage in quantum chemistry is examined in [396]. The review evaluates the efficiency of quantum state preparation features and classical heuristics [23, 397]. The findings suggest that while quantum computers may offer polynomial speedups, exponential speedups for ground-state quantum chemistry are unlikely to be generically achievable.

A review of quantum error mitigation techniques, essential for addressing noise in quantum computers, is provided in [17]. The review evaluates various mitigation strategies, summarizes current hardware demonstrations, and discusses open challenges. It offers guidance on selecting appropriate techniques based on noise types and explores the potential of these strategies to advance quantum devices in science and industry [11, 12, 253, 349, 384, 398–406]. Further details on Google Quantum AI’s research in 2023 can be found in [357, 407–434].

L. 2024: Continuing the quantum quest

In 2024, the study in [435] introduces a model-based optimization technique aimed at enhancing the accuracy of quantum measurements in superconducting qubits. This technique achieves a measurement error rate of 1.5% per qubit with a 500 ns end-to-end duration by addressing issues like excess reset errors and state transitions [357, 390]. Effective across 17 qubits, this method promises improvements in QErC and other near-term quantum applications.

The research [436] demonstrates how engineered dissipative reservoirs can direct many-body quantum systems towards useful steady states, with applications in simulating phenomena such as high-temperature superconductivity. Using up to 49-qubit superconducting (transmon) quantum processor, the researchers observed significant results [33]; including long-range quantum correlations in one dimension and mutual information beyond nearest neighbors in two dimensions. Their findings suggest that engineered dissipation [437–443] could be a scalable alternative to unitary evolution for preparing entangled many-body states on NISQ processors.

In [444], a quantum simulator with 69 superconducting qubits is presented, capable of both universal quantum gates and high-fidelity analog evolution. This simulator surpasses classical simulation limits in XEB [6, 143, 144, 152] and models a 2D XY quantum magnet. The study reveals signatures of the Kosterlitz-Thouless phase transition [445] and deviations from Kibble-Zurek scaling [446] due to quantum-classical domain coarsening [447]. It also examines the eigenstate thermalization hypothesis (ETH) [448–450] and investigates energy and vorticity transport in pairwise-entangled dimer states, highlighting the simulator’s effectiveness for exploring many-body spectra and thermalization dynamics [451].

The method introduced in [452] uses quantum information theory to simplify many-body Hamiltonians for near-term quantum devices [72, 453–455]. By applying similarity transformations [456–460] as a preprocessing step, this method reduces circuit depth and improves performance on quantum hardware [456–459, 461–464]. It enhances zero and finite temperature free energy calculations, demonstrating increased effectiveness with higher-quality transformations. This approach represents a practical advance for quantum chemistry on current hardware [233–237].

The work in [465] explores the interplay between measurement-induced dynamics and conditional unitary evolution, focusing on their effects on entanglement negativity in quantum systems. By analyzing random measurement and feed-forward (MFF) processes [466, 467], the study identifies a sharp transition in the ability to generate entanglement negativity as the number of MFF channels changes. The research links these findings to transitions caused by random dephasing with broken time-reversal symmetry [468] and rigorously proves the transition using free probability theory [469], with impli-

cations for dynamic circuit representations tested on current quantum computing platforms. For further details on Google Quantum AI’s research in 2024, refer to [470–474].

Through these pioneering efforts, Google Quantum AI continues to pushing the boundaries of what is possible and paving the way for groundbreaking discoveries and applications in quantum computation.

IV. COMPARING NISQ PROCESSORS AND CLASSICAL COMPUTERS

Currently, NISQ processors are limited to executing a few thousand quantum operations or gates before noise significantly impacts the quantum state [1]. Google Quantum AI anticipates that even within this intermediate, noisy regime, their quantum processors will enable applications where quantum experiments can be performed significantly faster than classical supercomputers allow.

To assess the performance of error-corrected quantum algorithms versus classical algorithms, one can compare their computational costs, as discussed in the field of computational complexity [475–480]. However, this comparison is less straightforward with current experimental quantum processors [481].

In [483], Google Quantum AI introduced a framework known as the “effective quantum volume” (EFQV) for evaluating the computational cost of quantum experiments. This measure quantifies the number of quantum operations or gates involved in producing a measurement outcome. The scheme has been applied to assess the computational cost of various recent experiments, including RCS [9], measurements of “out-of-time-order correlators” (OTOCs)[484], and a recent IBM and UC Berkeley experiment “Evidence for the utility of quantum computing before fault tolerance,” which explores Floquet evolutions related to the Ising model [384]. OTOCs are particularly noteworthy as they offer a direct method for experimentally measuring the EFQV of a circuit, a task that remains computationally challenging for classical computers. Furthermore, OTOCs are valuable in fields such as nuclear magnetic resonance (NMR) and electron spin resonance spectroscopy. Consequently, Google Quantum AI considers OTOC experiments to be promising candidates for demonstrating the practical applications of quantum processors, as detailed in Section IV C.

A. Evaluating the computational cost of noisy quantum processing experiments

Running a quantum circuit on a “noisy quantum processor” involves balancing two key factors. On one hand, Google Quantum AI aims to tackle problems that are challenging for classical computers [20, 21]. The computational cost, or the number of operations required for a

classical computer to complete a task, is related to the circuit’s EFQV. A larger effective volume generally implies a higher computational cost, indicating that a quantum processor could outperform classical counterparts.

Conversely, each quantum gate on a noisy processor can introduce errors [15–17], which degrade the fidelity of the quantum circuit’s measurements [139, 141, 460]. As the number of operations increases, so does the error rate, reducing the accuracy of the results [485, 486]. Thus, simpler circuits with smaller effective volumes might be preferred, although they are more easily simulated by classical computers. Google Quantum AI seeks to optimize this trade-off, aiming to maximize the “computational resource,” a measure of how well a quantum processor balances these considerations.

A prime example of this trade-off is the RCS experiment [9], a fundamental benchmark in quantum computing. RCS [144, 187–196], which first demonstrated a quantum processor’s ability to surpass a classical computer, is highly sensitive to errors. Any gate error [15–17] can compromise the experiment, making it a rigorous test of system fidelity while also representing the highest computational cost achievable by a quantum processor. Google Quantum AI recently reported their most advanced RCS experiment to date, featuring a low experimental fidelity of 1.7×10^{-3} and a theoretical computational cost of approximately 10^{23} . This experiment, which involved 700 two-qubit gates, would take around 47 years to simulate on the world’s largest supercomputer (at the time of estimation). While this confirms the quantum processor’s superiority over classical computers [481, 482], it does not represent a particularly practical application on its own.

B. Random circuit sampling

Achieving quantum advantage [2, 20, 21] with noisy processors is a key goal in NISQ computing era [1]. A leading approach to this challenge is RCS [191], which involves sampling from probability distributions created by randomly chosen quantum circuits. Random quantum circuits are generally considered challenging for classical systems to simulate [195, 196, 407]. This challenge has been pivotal in the quest for quantum supremacy [20], where a quantum computer achieves a task deemed infeasible for classical computers [1, 20, 21].

The aim of RCS [144, 187–196] is to generate a bit string from a distribution that approximates the output distribution of a random quantum circuit. It is important to recognize that a certain level of error is inevitable, as even fault-tolerant quantum computers can only perform RCS with a small acceptable error margin.

From an experimental standpoint, performing RCS on noisy quantum computers without error correction is relatively straightforward. The quality of the samples depends on the fidelity of the quantum device [6, 144, 165]. Theoretical studies have furthered our understanding of

RCS’s computational complexity [189, 190]. The RCS supremacy conjecture, in particular, suggests that no classical algorithm can efficiently perform RCS within polynomial time while maintaining a small, reasonable error margin.

Historically, the exploration of circuit sampling began with studying quantum circuits from specific families with structured properties. For instance, simulating instantaneous quantum polynomial (IQP) circuits classically has been notably difficult under reasonable average-case assumptions [187, 188]. RCS is also acknowledged as computationally demanding for fully random quantum circuits, according to widely accepted conjectures [191, 192, 407].

RCS has proven to meet average-case hardness conditions [187, 189, 190], which is crucial for understanding computational difficulty in the presence of experimental noise [191]. Additionally, RCS demonstrates an anti-concentration property, meaning errors in estimating output probabilities are relatively small compared to the probabilities themselves [407]. These features make RCS a leading candidate for achieving quantum advantage and drive its use in experiments aimed at demonstrating quantum supremacy [191]. For a more detailed examination of RCS and its computational complexity, readers are referred to [195, 196, 407].

C. The OTOCs and Floquet evolution

Many complex questions in quantum many-body physics [487] remain beyond classical computation, presenting significant opportunities for quantum processors [488]. Unlike RCS, which measures the entire quantum state at the end of an experiment, these investigations often focus on specific local observables. The EFQV for a local observable can be smaller than that of the complete circuit due to the localized impact of quantum operations on the observable [483].

To illustrate this, Google Quantum AI use the concept of a “*butterfly cone*,” analogous to the light cone in the “theory of relativity,” which defines the causal connections between events. In quantum systems, the *butterfly cone* (depicted in Figure 4) represents the area where quantum information spreads, with its growth rate determined by the butterfly speed—measured by OTOCs. The EFQV of a local observable corresponds to the volume within this *butterfly cone*, encompassing only those operations causally related to the observable. Thus, faster information spreading results in a larger effective volume, making classical simulation more challenging.

In [483], Google Quantum AI explores and elucidates the trade-off between the sensitivity of an experimental observable to noise and the corresponding classical computational cost required to evaluate this observable. Given an operator Q with an ideal expectation value $\langle Q \rangle_{\text{ideal}}$ and an experimental expectation $\text{tr}(\mathcal{L}Q)$, where \mathcal{L} denotes a noisy quantum state density matrix. Their

findings suggest that, under certain experimental conditions [483], we have:

$$\text{tr}(\mathcal{L}\mathcal{Q}) = \mathcal{F}_{\text{eff}}\langle\mathcal{Q}\rangle_{\text{ideal}}, \quad (1)$$

where \mathcal{F}_{eff} represents the effective fidelity of the observable. This fidelity is anticipated to decrease exponentially as:

$$\mathcal{F}_{\text{eff}} \sim e^{-\varpi V_{\text{eff}}}, \quad (2)$$

with V_{eff} the effective circuit volume and ϖ being the dominant error per 2-qubit entangling gate. For systems lacking conservation laws, V_{eff} equates to the number of entangling 2-qubit gates influencing the expectation value $\langle\mathcal{Q}\rangle_{\text{ideal}}$. The computational cost associated with tensor network contraction is expected to grow exponentially with an effective area A_{eff} related to a specific cut of the effective volume V_{eff} , given by:

$$\text{cost} \propto 2^{\gamma A_{\text{eff}}}, \quad (3)$$

where γ is a constant. Consequently, Google Quantum AI anticipates a trade-off between achieving a high signal-to-noise ratio and incurring high classical computational costs (large A_{eff}). A depiction of the EFQV, V_{eff} , associated with the gates influencing the local observable B is shown in Figure 4. Additionally, the effective area, A_{eff} , is illustrated as the cross-sectional area of the cone. The perimeter of the cone's base represents the boundary of information propagation, moving at the butterfly velocity, v_B . For further details on this framework, especially in the context of RCS where it is more naturally applicable, see [483].

In a recent experiment involving a Floquet Ising model [384], related to time crystal and Majorana edge mode studies, a pioneering experiment by IBM Quantum and UC Berkeley unveiled a significant advancement towards practical quantum computing [384]. The study revealed that quantum computers can perform circuits that surpass the limits of classical brute-force simulations. Notably, IBM Quantum [406] now possesses both hardware and software capable of running quantum circuits involving 100 qubits and 3,000 gates, all without prior outcome knowledge [10].

Later on, Google quantum AI applied its scheme [483] to the data from [384]. They noted that an effective fidelity of 0.37 was estimated for the largest circuits. Given a gate error rate of approximately 1%, this corresponds to an effective volume of around 100, significantly smaller than the light cone volume, which includes about 2,000 gates across 127 qubits. Numerical simulations suggest that the effective volume is closer to 28 qubits. This discrepancy [482] in effective volume is consistent with OTOC measurements. Despite the experiment's depth, the computational cost is about 5×10^{11} , nearly a *trillion* times less than that of the recent RCS experiment. Consequently, this experiment can be simulated in under a second per data point on an A100 GPU, making




FIG. 4. A schematic representation shows a conical surface in the (x, y, t) space, encompassing the effective volume V_{eff} that envelops the tensorial structure of entangling gates affecting the local observable $B(t) = U^\dagger(t)BU(t)$, with $B(0) = B$ indicated by a black dot. The cross-section of this cone, with area A_{eff} , is highlighted where the plane intersects the cone. The cone's base represents the subset of qubits in the (x, y) plane engaged in the operator spreading of B at time t , while the perimeter of this base signifies the scrambling front advancing with velocity v_B . Reproduced under a creative common license (<https://creativecommons.org/licenses/by/4.0/>) from [483].

it a valuable application but not yet surpassing classical simulations [483].

OTOC experiments hold promise for computational applications by revealing critical physical insights [484], such as butterfly velocity, which is essential for accurately measuring a circuit's EFQV. Experiments with rapid entangling gates may pave the way for the first beyond-classical demonstration using quantum processors. Google quantum AI's 2021 OTOC experiment [484] achieved an effective fidelity of approximately 0.06 with a signal-to-noise ratio of ≈ 1 , resulting in an effective volume of around 250 gates and a computational cost of 2×10^{12} .

Although current OTOC experiments do not yet exceed classical simulation capabilities, their potential is significant. Quantum circuits exploring extensive energy levels, which are typically chaotic, are hard to simulate classically and quickly decay in standard time-order correlators (TOCs) [29]. OTOCs, however, allow for growing complexity, limited primarily by gate errors. A reduction in error rates could double the computational cost, moving the experiment into the beyond-classical regime.

V. THE QUANTUM COMPUTATIONAL SUPREMACY

In this section, we explore Google Quantum AI’s pursuit of quantum computational supremacy [1, 20, 21]. For a comprehensive review of the broader quest for quantum supremacy, including experiments beyond those conducted by Google, as well as a variety of pioneering proof-of-principle experiments in various quantum computing domains, readers are encouraged to consult [2].

A. The XEB theory

To confirm the accurate performance of the Google’s quantum processors during the quantum supremacy experiment, Google Quantum AI and its collaborators utilize a technique known as cross-entropy benchmarking (XEB) [143, 144, 191]. XEB evaluates how closely the distribution of observed bit strings from the quantum processor matches the expected probabilities from classical simulations [6, 143, 144, 152]. This method allows for a rigorous performance assessment by comparing experimental results with theoretical predictions [6].

XEB [143, 489] offers a method for calibrating single- and 2-qubit gates and assessing fidelity in RQCs [144, 187–196], even those with numerous qubits. It capitalizes on the analogy between the measurement probabilities of random quantum states and the patterns of laser “speckles,” where some bit strings are more likely than others [490, 491]. By analyzing distortions in these speckle patterns, XEB can assess error rates and fidelity without needing to reconstruct complex experimental output probabilities, which would be impractical due to the exponential increase in measurements with more qubits [6, 143, 144, 492].

The XEB fidelity (\mathcal{F}_{XEB}) gauges how often high-probability bit strings are sampled, with values ranging from 0 to 1 reflecting the degree of error in the circuit execution. Google Quantum AI aims to achieve a high \mathcal{F}_{XEB} for a quantum circuit with adequate width and depth, making classical computation costs prohibitive. This goal is challenging due to the imperfections in logic gates and the susceptibility of the quantum states to errors [6]. Even a small error, such as a bit or phase flip during the algorithm’s execution, can drastically alter the speckle pattern, resulting in nearly *zero* fidelity [144]. Therefore, quantum processors capable of executing circuits with minimal error rates are required to demonstrate quantum supremacy [9].

B. Quantum processors

Google Quantum AI’s quantum processors are at the cutting edge of computational technology, designed to address problems that exceed the capabilities of classical

computers [6, 9]. The company has developed several significant quantum processors, including *Foxtail* [28, 493], *Bristlecone* [494], and *Sycamore* [6]. These processors are characterized by their advanced control and precision, enabling the manipulation and measurement of qubits with remarkable accuracy [6, 9].

Sycamore: The *Sycamore* processor, a key player in Google Quantum AI’s portfolio, utilizes superconducting qubits and gained widespread attention for its role in achieving quantum supremacy in 2019 [6]. The SYC-53, specifically, is engineered to perform intricate quantum computations using a 2-dimensional array of 54 transmon qubits [184, 185]. It stands out for its ability to execute high-fidelity 1-qubit and 2-qubit quantum gates, which are crucial for conducting practical and complex quantum operations [485, 486].

Bristlecone: *Bristlecone* QPUs [186] represent a significant advancement in quantum processor design with a larger array of qubits compared to *Sycamore*. This processor aims to enhance the scalability and performance of quantum computing [186]. *Bristlecone*’s design focuses on improving qubit coherence times and reducing error rates, setting the stage for more sophisticated quantum computations and demonstrating the progress towards more robust and scalable quantum systems. An architectural overview of Google’s *Bristlecone-72* quantum processor and series of sub-lattices (*Bristlecone-24*, *Bristlecone-30*, *Bristlecone-40*, *Bristlecone-48*, *Bristlecone-60*, *Bristlecone-64*, and *Bristlecone-70*) are shown in Figure 5.

Weber: Google’s universal gate-based superconducting quantum computer, known as *Weber* (part of the *Sycamore* family). The qubit grid of *Weber* is shown in Figure 6, general specifications are detailed in Table I. Although these values reflect historical data [495], they are important for documenting the evolution of Google’s quantum computing technology in the NISQ era [1].

Recent performance metrics, including system characteristics of Google’s *Sycamore* quantum processors during the quantum supremacy experiments, are discussed in the subsequent sections VC and VD. This section provides updated insights into the hardware performance of these advanced quantum processors, highlighting their capabilities and improvements achieved over time. These quantum processors exemplify Google Quantum AI’s dedication to pushing the frontiers of quantum computing.

C. The 53-qubits *Sycamore* processor

Google’s *Sycamore* (SYC-53) quantum processor [6] features a two-dimensional grid of 54 superconducting transmon qubits [184]. Each qubit is linked to its four nearest neighbors, creating a rectangular lattice, as shown in Figure 7. A landmark achievement of the SYC-53 processor was its ability to perform a computation in just 200 seconds that would have taken a classical com-




FIG. 5. Architectural overview of Google’s *Bristlecone* quantum processor. The sub-lattices of the complete *Bristlecone-72* (shown in the bottom right) are arranged in order of increasing complexity for a given depth. Notably, *Bristlecone-72* is not more difficult to simulate than *Bristlecone-70*, as the corner tensors can be contracted with minimal computational expense. Additionally, *Bristlecone-64* exhibits similar simulation complexity to *Bristlecone-48*, while being significantly easier to simulate than *Bristlecone-60* [186]. Google Quantum AI has identified a series of sub-lattices, specifically *Bristlecone-24*, *Bristlecone-30*, *Bristlecone-40*, *Bristlecone-48*, *Bristlecone-60*, *Bristlecone-64*, and *Bristlecone-70*, arranged from top left to bottom left, all of which present significant challenges for classical simulation while maintaining a low qubit count.

puter roughly 10,000 years [6].

In this experiment [6], Google’s Quantum AI team programmed the SYC-53 quantum processor to perform RCS [144, 187–196]. This task was executed in a computational space of 9×10^{15} —a scale too complex for traditional machines. The initial estimation for performing

this computation on *Summit*, the leading supercomputer at the time of Google’s quantum supremacy demonstration, was about 10,000 years. In contrast, the SYC-53 completed the same task in just 200 seconds. This milestone demonstrated the potential of quantum computing [2] to tackle problems that are beyond the reach of

TABLE I. The general service specifications of Google’s universal gate-based superconducting quantum processor, *Weber* (*Sycamore* family) [495]. Recorded for historical documentation in the NISQ era literature.

System characteristic	Symbol	Condition	90 th percentile ^a	Median ^b	10 th percentile ^c	Units
1-qubit gate error rate	e_1	isolated	0.1	0.1	0.2	% error per gate
2-qubit gate error	$e_2(\sqrt{i\text{SWAP}})$	isolated	1.9	0.9	0.7	% error per gate
		parallel	3.3	1.4	0.8	XEB
Readout error ($ 1\rangle$)	e_{r1}	isolated	9.0	5.0	3.0	% error
		simultaneous	9.0	7.0	3.0	% error
Readout error ($ 0\rangle$)	e_{r0}	isolated	2.6	1.1	0.5	% error
		simultaneous	3.0	2.0	1.0	% error
Relaxation	T1	isolated	21	15	11	μs
		single circuit, 2,000 reps.	0.3	0.3	0.2	KHz
System timing ^b	repetition rate	25 sweeps, 2,000 reps. each	1.1	1.1	1.1	KHz
		single circuit, 20,000 reps.	2.1	2.1	1.9	KHz
		25 sweeps, 20,000 reps. each	4.1	4.1	4.0	KHz
Latency	–	–	2.8	2.3	1.6	seconds

^a The 90th percentile value from the overall distribution of post-calibration characterizations for all qubits from January to March 2021.

^b The median value derived from the 90-day distribution of median values across all qubits from January to March 2021.

^c The 10th percentile value from the aggregated distribution of post-calibration characterizations for all qubits between January and March 2021.

TABLE II. Aggregate system characteristics of Google’s SYC-53 quantum processor [6].

System characteristics	Min.	Mean	Median	Stdev.	Max.	units
Qubit idle frequency	6.553	6.665	6.661	0.064	6.830	GHz
Qubit anharmonicity	-0.226	-0.208	-0.208	0.0047	-0.202	GHz
Qubit maximum frequency	6.634	6.927	6.911	0.120	7.237	GHz
Qubit frequency at readout	5.180	5.784	5.760	0.384	6.730	GHz
T1 at Idle Frequency	9.70	16.035	15.50	3.991	27.8	μs
Resonator linewidth ($\kappa/2\pi$)	0.360	0.691	0.640	0.233	1.250	MHz
Readout drive frequency	4.470	4.588	4.618	0.076	4.690	GHz
Qubit-resonator coupling ($\xi/2\pi$)	63.90	72.10	72.30	2.794	79.10	MHz
Readout error $ 1\rangle$ isolated	2.40	4.984	4.5	1.774	9.40	(%)
Readout error $ 1\rangle$ simultaneous	2.50	5.477	5.1	2.253	15.60	(%)
Readout error $ 0\rangle$ isolated	0.20	1.158	1.0	0.7548	3.80	(%)
Readout error $ 0\rangle$ simultaneous	0.40	2.256	1.8	2.128	13.0	(%)
1-qubit XEB ^a e_1 simultaneous/isolated	-	0.16/0.15	0.14/0.13	0.05/0.05	-	(%)
2-qubit XEB ^a e_2 simultaneous/isolated	-	0.62/0.36	0.60/0.30	0.24/0.17	-	(%)
Measurement e_m simultaneous/isolated	-	3.77/3.05	3.50/2.83	1.61/1.09	-	(%)

classical methods.

However, after the publication, a discussion emerged about the potential overestimation of the time required to tackle the same problem on a supercomputer. Pednault *et al.* [172] later argued that a similar task could be achieved with high accuracy using a classical supercomputer like *Summit*, within a few days. Additionally, Huang *et al.* [173] presented a classical simulation algorithm based on tensor networks that can accomplish the task in under 20 days. Another tensor network approach, detailed by Pan *et al.* [174], addressed the sampling problem of Sycamore’s quantum circuits and was executed on a computational cluster with 512 GPUs, completing the computation in 15 hours.

Google Quantum AI and its collaborators tested the largest circuit, which included 53 qubits and 20 cycles. They collected 30×10^6 samples from ten runs of the circuit, finding an observed \mathcal{F}_{XEB} of $(2.24 \pm 0.21) \times 10^{-3}$ for

the truncated circuits. They assert that the average fidelity of running these circuits on the quantum processor is at least 0.1% [6].

To reach this quantum supremacy milestone [20, 143], the SYC-53 processor incorporated several technological innovations, as detailed in [6]. These advancements allowed the execution of RQCs composed of alternating layers of 1-qubit and 2-qubit gates, organized into cycles (as depicted in Figure 8). Each random circuit includes s -cycles, where a cycle is defined by a sequence of one-qubit gates, followed by two-qubit gates, and concluding with another layer of single-qubit gates before measurement.

The SYC-53 uses transmon qubits [184, 185], which are nonlinear superconducting resonators operating between 5 and 7 GHz. Each qubit utilizes the two lowest energy states of the resonant circuit and has two control mechanisms: a microwave drive for excitation and

TABLE III. Estimated computational costs for simulations with various superconducting quantum computers: SYC-53, SYC-67, SYC-70, Zuchongzhi 2.0, and Zuchongzhi 2.1. The fifth column shows the number of FLOPs required to compute a single output amplitude without memory constraints. The subsequent three columns detail the computational resources required to simulate noisy sampling of one million bit-strings. These estimates are based on *Frontier*, a leading supercomputer with a theoretical peak performance of 1.685×10^{18} single-precision FLOPs. A 20% efficiency in FLOP utilization is assumed [173, 174, 496], and the simulation’s lower fidelity is factored into the cost [165, 173, 186, 496]. Each single-precision complex FLOP requires eight machine FLOPs. For SYC-67, costs are estimated assuming memory is distributed across all RAM[≠] or secondary storage[≠], without considering bandwidth constraints. Other entries use tensor contraction algorithms that are easily parallelizable across GPUs [173, 174, 497]. Adapted under a Creative Commons license (<https://creativecommons.org/licenses/by/4.0/>) from [9].

Quantum processor	Single amplitude			1,000,000 noisy samples			
	experiment	year	qubits	FLOPs	\mathcal{F}_{XEB}	FLOPs	time
Google’s SYC-53	Arute <i>et al.</i> [6]	2019	53	6.0×10^{17}	2.0×10^{-3}	2.0×10^{17}	6 seconds
Zuchongzhi 2.0	Wu <i>et al.</i> [497]	2021	56	6.0×10^{19}	6.0×10^{-4}	6.0×10^{19}	20 minutes
Zuchongzhi 2.1	Zhu <i>et al.</i> [498]	2022	60	1.0×10^{21}	3.0×10^{-4}	1.0×10^{23}	40 days
Google’s SYC-70	Morvan <i>et al.</i> [9]	2023	70	5.0×10^{23}	2.0×10^{-3}	6.0×10^{25}	50 years
Google’s SYC-67	Morvan <i>et al.</i> [9]	2023	67	2.0×10^{23}	1.0×10^{-3}	2.0×10^{37}	1.0×10^{13} years
						2.0×10^{28}	1.0×10^4 years [≠]
						2.0×10^{25}	12 years [≠]




FIG. 6. Qubit grid of the *Weber* quantum computer (part of the *Sycamore* family), a universal gate-based quantum computer, features 53 superconducting qubits.

a magnetic flux control for frequency tuning. For state readout, each qubit is linked to a linear resonator [25], and adjustable couplers [389, 500] enable dynamic tuning of qubit coupling from fully disengaged to 40 MHz. During the supremacy experiment, one qubit malfunctioned, leaving the device operational with 53 qubits and 86 couplers [1]. For more information on Google’s SYC-53 quantum AI, refer to [485, 486], which details the characterization of the *Sycamore* quantum processes through comprehensive quantum tomography experiments.




FIG. 7. Architecture of Google’s Sycamore (SYC-53) quantum processor. The processor features a rectangular array of 54 programmable superconducting transmon qubits, with adjustable couplers linking each qubit to its four nearest neighbors. Due to one non-functional qubit during the supremacy regime experiment [6], the device operated with 53 qubits and 86 couplers.

D. The SYC-67 and SYC-70 quantum processors

In late 2023, Google Quantum AI and its collaborators conducted groundbreaking experiments [9] using quantum processors with 67 (SYC-67) and 70 (SYC-70) qubits, targeting the realm of quantum supremacy [2, 20, 21]. These experiments provided valuable insights into how quantum dynamics interact with noise [9]. The identified phase boundaries offer crucial information about the conditions needed for noisy quantum devices to maximize their computational potential. Notably, they




FIG. 8. Schematic diagram of an s -cycle circuit for the SYC-53 RQCs. Each cycle includes a layer of random single-qubit gates (selected from $\{X^{1/2}, W^{1/2}, Y^{1/2}\}$), followed by a layer of 2-qubit gates labeled A, B, C, or D. In longer circuits, the sequence of layers repeats as A; B; C; D - C; D; A; B. 1-qubit gates are not repeated consecutively, and there is an additional layer of 1-qubit gates before measurement.

achieved new results in RCS [144, 187–196] with an estimated fidelity of 1.5×10^{-3} for 67 qubits and 32 cycles (or 880 entanglement gates). This represents a significant expansion in circuit complexity compared to earlier studies [6], while maintaining the same fidelity level.

To realistically assess the computational resources needed to simulate RCS [144, 187–196], one must account for the limitations of supercomputers, including FLOPS, memory capacity, and bandwidth constraints. Table III provides estimates for simulating the largest RCS instances from previous studies [6, 498, 499] and the recent Google study [9]. These estimates consider sampling 1 million uncorrelated bit-strings with fidelity comparable to the experimental results, using the top-performing supercomputer, *Frontier*, which has a theoretical peak performance of 1.7×10^{18} single-precision FLOPS across GPUs with 128 GB of RAM each.

By demonstrating an RCS experiment with 67 qubits at 32 cycles, Google Quantum AI and its collaborators show that their computational requirements exceed the capabilities of current classical supercomputers, even in the presence of unavoidable noise. Additionally, the dominance of global correlations over XEB [6, 143, 144, 152] in the weak noise phase offers protection against “spoofing” attacks, a notable distinction from Boson-Sampling (BoS) experiments [501]. Recent BoS metrics [502–504] have been predominantly influenced by local correlations [312]. For a more exploration of BoS and Gaussian Boson-Sampling (GBoS) experiments, as well as their significance in achieving quantum supremacy with photonic quantum computers [505], readers are directed to [4, 5].

Figures 9 and 10 offer critical insights into the performance of the SYC-67 and SYC-70 devices, respectively. Both figures detail the performance metrics and benchmarking results, including 1-qubit and 2-qubit Pauli error rates, readout error rates, and T1 and T2 echo times, along with the cumulative distribution function (CDF) of various errors [9].

Figure 11 illustrates the upper bounds on the required bond dimension to achieve a target fidelity of $\mathcal{F} = 10^{-4}$, comparing analytical and numerical results as functions of qubit count and circuit depth. It also details the memory footprint needed to store complex tensors of dimension $(2^{n/2} \times \chi)$, with varying memory capacities for different computing resources, including laptops, cluster nodes, and high-performance systems like *Frontier*. Additionally, the figure shows the density map, which is obtained by averaging over circuits with specific patterns, including A;B;C;D;C;D;A;B/B;A;D;C;D;C;B;A and various diagonal or vertical cuts [9]. By continually advancing their hardware capabilities, Google Quantum AI is driving the development of quantum technology and facilitating breakthroughs across various fields.

VI. QUANTUM SOFTWARE

Google Quantum AI is advancing the field of quantum computing; creating powerful tools that enable researchers to go beyond the limits of classical computing [2, 20, 21]. Google’s dedicated software and hardware solutions are specifically crafted to facilitate the development of innovative quantum algorithms capable of tackling practical problems in the near term [506]. They have created various tools, which we explore in this section.

A. Cirq

Cirq is a *Python* software library for creating, manipulating, and optimizing quantum circuits [507]. It enables precise control over quantum gates and operations, allowing researchers to fully utilize quantum computers and simulators. Developed by Google Quantum AI, this open-source framework addresses the unique challenges of NISQ devices [1, 2]. Cirq provides essential tools




FIG. 9. SYC-67 Device Benchmarking: A: Single-qubit Pauli error rate from Randomized Benchmarking. B: Readout error rate averaged from random bitstrings. C: Two-qubit Pauli error rate via parallel 2-qubit XEB. D: T_1 , and E: T_2 echo times. F: Cumulative distribution function (CDF) of errors, with the solid vertical line indicating the average and the dashed line showing the median. Regenerated under a Creative Commons license (<https://creativecommons.org/licenses/by/4.0/>) from [9].




FIG. 10. Device Benchmarking for SYC-70: Assessment of random circuit elements. A: Single-qubit Pauli error rate via Randomized Benchmarking. B: Readout error rate from averaging random bitstrings. C: Two-qubit Pauli error rate using parallel 2-qubit XEB. D: T_1 , and E: T_2 echo times. F: CDF of various error types, with the solid vertical line denoting the average and the dashed line representing the average from Ref. [6]. Regenerated under a Creative Commons license (<https://creativecommons.org/licenses/by/4.0/>) from [9].




FIG. 11. Upper bounds on the required bond dimension for achieving a target fidelity of $\mathcal{F} = 10^{-4}$, shown analytically (left) and numerically (right) as functions of qubit count and circuit depth. The memory footprint (blue dashed-and-dotted lines) represents the memory needed to store two complex 32 tensors of dimension $2^{n/2} \times \chi$. Memory specifications are: Laptop (RAM) = 32GB, cluster node (RAM) = 256GB, Frontier (RAM) = 9.2PB, and Frontier (storage) = 700PB. The density map averages over circuits with patterns A;B;C;D;C;D;A;B/B;A;D;C;D;C;B;A and diagonal/vertical cuts. Regenerated under a Creative Commons license (<https://creativecommons.org/licenses/by/4.0/>) from [9].

for working with NISQ systems [2, 20, 21], where detailed hardware knowledge is crucial for optimal performance [15–17]. Additionally, Cirq is specifically tailored for crafting innovative quantum algorithms for near-term quantum computers [506].

B. OpenFermion

Another valuable library developed by Google Quantum AI is OpenFermion [238]. OpenFermion is an open-source tool for translating chemistry and materials science problems into quantum circuits that can be executed on current quantum computing platforms [2, 20, 21]. It specializes in compiling and analyzing quantum algorithms specifically designed for simulating fermionic systems, including quantum chemistry [64–66, 233–237]. The library offers efficient data structures for fermionic operators and circuit primitives for execution on quantum devices. Its plugins further streamline the translation of electronic structure calculations into quantum circuits [228].

Recent research highlights OpenFermion’s application in variational simulations of chemistry. The study in [228] involved simulating molecules with up to a dozen qubits, demonstrating the use of error-mitigation strategies and parameterized ansatz circuits [73] to prepare Hartree-Fock wavefunctions [232]. These experiments benchmark the hardware performance and lay the groundwork for more complex simulations of molecular and correlated systems [64–66, 233–237], illustrating OpenFermion’s utility in advancing quantum chemistry and material science research.

C. TensorFlow Quantum

TensorFlow Quantum [239] is a unique library that combines the power of quantum computing with classical machine learning. It enables researchers to rapidly prototype hybrid quantum-classical machine learning models, opening up new avenues for exploration and innovation [508–512].

It facilitates the design and training of both discriminative and generative quantum models while leveraging high-performance quantum circuit simulators. TFQ supports seamless integration with quantum algorithms and logic from Google’s Cirq [507], providing essential quantum computing primitives that are compatible with TensorFlow’s existing APIs. This framework is designed for exploring and developing models for quantum data and applications, supporting a range of applications, from basic supervised learning and quantum control to advanced quantum learning techniques [198–202]. For further details, refer to [239].

D. Qsim

Qsim is an advanced (optimized) quantum circuit simulator that seamlessly integrates with Cirq [507], offering high-performance capabilities. It is a comprehensive wave function simulator developed in C++. Developed in C++, it serves as a comprehensive wave function simulator. Qsim utilizes AVX/FMA vector operations, OpenMP multi-threading, and gate fusion [513, 514] to accelerate simulation speed and perform complex quantum circuit simulations. Integrated with Cirq [507], qsim

is capable of executing simulations for up to 40 qubits on a 90-core Intel® Xeon® processor [515]. Its performance is effectively showcased through its application in XEB [6].

These quantum software tools from Google Quantum AI [228, 238, 239, 507, 516] equip researchers with the necessary resources and capabilities to explore and expand the frontiers of quantum computing. By offering robust libraries such as Cirq [507], OpenFermion [238], and TensorFlow Quantum [239], Google enables researchers to explore the potential of quantum computing and push the boundaries of what is possible in solving complex problems.

VII. GROVER SEARCH ALGORITHM WITH CRIQ

Grover's algorithm [517] is a quantum search algorithm designed to find a specific item from an unsorted database with quadratic speedup over classical search methods [518]. Given a black-box oracle function $\xi(x)$ that marks the target solution x^\oplus by flipping its phase, Grover's search algorithm (\mathcal{GSA}) identifies x^\oplus with high probability. The algorithm operates in $\mathcal{O}(\sqrt{N})$ quantum operations, where N is the number of possible items, compared to the $\mathcal{O}(N)$ operations required classically. The core of \mathcal{GSA} involves the following steps:

1. **Initialization:** Create a superposition of all possible states using Hadamard gates.
2. **Oracle Query:** Apply the oracle to flip the phase of the state corresponding to the target solution.
3. **Diffusion Operator:** Enhance the probability amplitude of the target state through inversion about the average amplitude.
4. **Measurement:** Measure the quantum state to determine the solution.

By iterating the oracle and diffusion operator, \mathcal{GSA} converges to the solution with a high probability, making it an efficient tool for unstructured search problems. This section provides a demonstration of \mathcal{GSA} using the Cirq framework. This demonstration adapted from [507]. The implementation includes the initialization of qubits, construction of the oracle, application of the Grover operator, and measurement of the results.

- **Initialization of qubits:** Set up the qubits required for the algorithm. This includes initializing input qubits and an output qubit.

```
def setup_qubits(num_qubits):
    """Initialize input qubits and an output qubit."""
    inputs = [cirq.GridQubit(i, 0) for i in range(num_qubits)]
    output = cirq.GridQubit(num_qubits, 0)
    return inputs, output
```

- **Oracle construction:** Create an oracle function that marks the correct solution by flipping the sign of

the amplitude of the state that matches the target bit sequence.

```
def create_oracle(inputs, output, target_bits):
    """Define the oracle function f(x) that flips the phase if x
    matches the target."""
    # Apply X gates to zero bits
    yield (cirq.X(q) for q, bit in zip(inputs, target_bits) if
           not bit)
    # Apply Toffoli gate to flip the phase of the target state
    yield cirq.TOFFOLI(inputs[0], inputs[1], output)
    # Reapply X gates to zero bits
    yield (cirq.X(q) for q, bit in zip(inputs, target_bits) if
           not bit)
```

- **Grover operator implementation:** Implement the Grover operator, which includes initialization, applying the oracle, and performing amplitude amplification.

```
def build_grover_circuit(inputs, output, oracle):
    """Construct the quantum circuit incorporating the Grover
    operator and oracle."""
    circuit = cirq.Circuit()

    # Initialization phase
    circuit.append([cirq.X(output), cirq.H(output),
                   cirq.H.on_each(*inputs)])

    # Apply oracle
    circuit.append(oracle)

    # Apply Grover diffusion operator
    circuit.append(cirq.H.on_each(*inputs))
    circuit.append(cirq.X.on_each(*inputs))
    circuit.append(cirq.H.on(inputs[1]))
    circuit.append(cirq.CNOT(inputs[0], inputs[1]))
    circuit.append(cirq.H.on(inputs[1]))
    circuit.append(cirq.X.on_each(*inputs))
    circuit.append(cirq.H.on_each(*inputs))

    # Measurement
    circuit.append(cirq.measure(*inputs, key='result'))

    return circuit
```

- **Simulation and measurement:** Simulate the quantum circuit and measure the results. Analyze the measurement results to find the most frequent outcome.

```

def run_simulation():
    num_qubits = 2
    samples = 10

    # Initialize qubits
    inputs, output = setup_qubits(num_qubits)

    # Randomly select the target bit sequence
    target_bits = [random.randint(0, 1) for _ in
    ↪ range(num_qubits)]
    print(f'Target bit sequence: {target_bits}')

    # Create the oracle
    oracle = create_oracle(inputs, output, target_bits)

    # Build and display the Grover circuit
    grover_circuit = build_grover_circuit(inputs, output,
    ↪ oracle)
    print('Quantum Circuit:')
    print(grover_circuit)

    # Run the simulation
    simulator = cirq.Simulator()
    result = simulator.run(grover_circuit, repetitions=samples)

    # Analyze results
    outcomes = result.histogram(key='result', fold_func=lambda
    ↪ b: ''.join(str(int(x)) for x in b))
    print(f'Results:\n{outcomes}')

    # Determine the most common result
    most_common_result = outcomes.most_common(1)[0][0]
    print(f'Most frequent bitstring: {most_common_result}')
    print(f'Target identified: {most_common_result ==
    ↪ ''.join(str(bit) for bit in target_bits)}')

```

- **Result analysis:** Examine the results from the simulation to determine if the algorithm successfully identified the target bit sequence.

```

outcomes = result.histogram(key='result', fold_func=lambda
↪ b: ''.join(str(int(x)) for x in b))
print(f'Results:\n{outcomes}')

most_common_result = outcomes.most_common(1)[0][0]
print(f'Most frequent bitstring: {most_common_result}')
print(f'Target identified: {most_common_result ==
↪ ''.join(str(bit) for bit in target_bits)}')

```

The output of the \mathcal{GSA} is as follows: The target bit sequence identified by the algorithm was [1, 0]. Upon simulation, the results showed a counter with a frequency of '10': 10, indicating that the bitstring '10' was observed in all measurement repetitions. The most frequent bitstring was therefore '10', which matched the target sequence. This confirms that the \mathcal{GSA} successfully identified the target bitstring [1, 0] as the most common result from multiple circuit runs. A comprehensive characterization of \mathcal{GSA} on state-of-the-art large-scale superconducting quantum hardware is presented in [518]. End-to-end experiments conducted on Google's quantum processors, utilizing algorithms and experiments that can be run with ReCirq [519], a GitHub repository dedicated to research code that extends and leverages Cirq [507].

VIII. TOWARDS LARGE-SCALE USEFUL QUANTUM COMPUTERS

Google's Quantum AI aims to unlock the full potential of quantum computing by developing a large-scale quantum computer capable of complex, error-corrected computations. A roadmap for Quantum Computing

at Google Quantum AI is shown in Figure 12. Their roadmap outlines six key milestones towards achieving high-quality quantum hardware and software for impactful applications [520]:

1. **Beyond classical (2019)** (physical qubits: 54): This milestone marked the achievement of quantum computational advantage. Google's Quantum AI team demonstrated this with their 53-qubit (SYC-53) quantum processor [6], which completed a specific computation (see Section VC) in 200 seconds—an endeavor that would have taken classical supercomputers 10,000 years [6]. This result signifies a pivotal advancement in quantum computing capabilities beyond classical limitations.
2. **Error-corrected qubits (2023)** (physical qubits: 10^2 , logical qubit error rate: 10^{-2}): Achieving reliable quantum computing necessitates the use of error-corrected qubits, or logical qubits [15–17]. In 2023, Google Quantum AI successfully demonstrated a prototype for a logical qubit, showing that errors could be mitigated by employing quantum error correction techniques [9]. This achievement marks a transition from theoretical to practical quantum error correction, laying the groundwork for large-scale, functional quantum computers.
3. **Building a long-lived logical qubit (2025+)** (physical qubits: 10^3 , logical qubit error rate: 10^{-6}): This milestone focuses on developing logical qubits that can maintain coherence over long durations, performing up to one million operations with minimal errors. Achieving this involves scaling up error correction, enhancing qubit performance, and expanding infrastructure. The goal is to dramatically reduce error rates while increasing qubit count, with a requirement for meaningful computational benchmarks.
4. **Creating a logical gate** (physical qubits: 10^4 , logical qubit error rate: 10^{-6}): The development of logical gates is crucial for executing reliable quantum computations. This stage involves demonstrating low-error gates between logical qubits, akin to the universal gates in classical computers. Successfully creating these gates will advance the realization of practical error-corrected quantum applications.
5. **Engineering scale-up** (physical qubits: 10^5 , logical qubit error rate: 10^{-6}): This milestone aims at scaling quantum systems to incorporate more logical qubits with high-fidelity gate operations. The objective is to enable the implementation of several error-corrected quantum computing applications, marking a significant step toward practical and scalable quantum computing.
6. **Large error-corrected quantum computer** (physical qubits: 10^6 , logical qubit error rate:




FIG. 12. The roadmap for Google Quantum AI’s quantum computing. Aiming to fully realize the potential of this technology by creating a large-scale quantum computer that can handle complex computations with error correction. This journey is guided by six key milestones designed to advance their quantum computing hardware and software towards impactful applications. Image source [520].

10⁻¹³): The ultimate milestone targets the development of a quantum computer with the capability to manage and control 1,000,000 qubits. This ambitious goal seeks to push the boundaries of quantum technology, with the potential to revolutionize various fields, including medicine and sustainable technology. Upon reaching this milestone, Google Quantum AI anticipates unveiling over 10 error-corrected quantum computing applications.

IX. CONCLUSION

Quantum computing stands at the precipice of transforming technology, offering computational capabilities that promise to reshape industries and scientific endeavors. In this review, we have traced the remarkable journey of Google Quantum AI over the past decade, highlighting its pivotal role in advancing quantum computing technology. From its early developmental milestones to its groundbreaking achievements in quantum supremacy, Google Quantum AI’s achievements underscore the transformative potential of quantum technology and its capacity to address complex computational problems that are currently beyond the reach of classical systems. Through these pioneering efforts, Google Quantum AI has consistently pushed the boundaries of what is possible, in the realm of quantum computation, and paving the way for groundbreaking discoveries and applications.

Throughout the years (2013-2024), Google Quantum AI has demonstrated significant progress in various areas, including quantum hardware development, error correction, and software innovations. The evolution from initial experimental setups to the sophisticated quantum processors like *Foxtail*, *Bristlecone*, *Weber*, *Sycamore* (SYC-53, SYC-67 and SYC-70) and the ambitious quest for error-corrected quantum computers reflects a commit-

ment to overcoming the fundamental challenges of quantum computing. Their work in extending qubit coherence times, reducing error rates, and enhancing computational capabilities has paved the way for more practical and scalable quantum systems.

Google Quantum AI’s approach to evaluating effective quantum volume has provided valuable insights into the computational costs associated with RCS, OTOC experiments, and recent Floquet evolution studies. Although these experiments have not yet reached the stage of practical computational applications, Google Quantum AI is optimistic that advancements in error rates will enable OTOC experiments to achieve the first truly practical, beyond-classical applications of quantum processors.

As we look towards the future, Google Quantum AI’s continued efforts in improving quantum error correction, expanding quantum hardware, and refining quantum algorithms will be crucial in realizing the vision of large-scale, fault-tolerant quantum computers. While a full-scale error-corrected quantum computer has the potential to tackle problems beyond the reach of classical computers, developing such a device remains a formidable challenge and is still several years away.

ACKNOWLEDGMENTS

The views and conclusions expressed in this paper are solely those of the author and do not necessarily represent the views of Google Quantum AI, NASA, the Universities Space Research Association, IBM Quantum, UC Berkeley, or any affiliated organization.

FUNDING

The author declares that no funding, grants, or other forms of support were received at any point throughout this research.

- [1] J. Preskill, Quantum Computing in the NISQ era and beyond, *Quantum* **2**, 79 (2018).
- [2] M. AbuGhanem and H. Eleuch, NISQ computers: a path to quantum supremacy, *IEEE Access*, **12**, 102941-102961, (2024).
- [3] Travis L. Scholten, Carl J. Williams, Dustin Moody, Michele Mosca, William Hurley, William J. Zeng, Matthias Troyer, Jay M. Gambetta, Assessing the benefits and risks of quantum computers, *arXiv preprint arXiv:2401.16317v2* (2024).
- [4] M. AbuGhanem, Information processing at the speed of light. Elsevier, *SSRN 4748781* (2024). <http://dx.doi.org/10.2139/ssrn.4748781>
- [5] M. AbuGhanem, Photonic Quantum Computers, *arXiv preprint arXiv:2409.08229*, (2024). <https://doi.org/10.48550/arXiv.2409.08229>
- [6] Frank Arute, Kunal Arya, Ryan Babbush, Dave Bacon, Joseph C Bardin, Rami Barends, Rupak Biswas, Sergio Boixo, Fernando GSL Brandao, David A Buell, Brian Burkett, Yu Chen, Zijun Chen, Ben Chiaro, Roberto Collins, William Courtney, Andrew Dunsworth, Edward Farhi, Brooks Foxen, Austin Fowler, Craig Gidney, Marissa Giustina, Rob Graff, Keith Guerin, Steve Habegger, Matthew P Harrigan, Michael J Hartmann, Alan Ho, Markus Hoffmann, Trent Huang, Travis S Humble, Sergei V Isakov, Evan Jeffrey, Zhang Jiang, Dvir Kafri, Kostyantyn Kechedzhi, Julian Kelly, Paul V Klimov, Sergey Knysh, Alexander Korotkov, Fedor Kostritsa, David Landhuis, Mike Lindmark, Erik Lucero, Dmitry Lyakh, Salvatore Mandrà, Jarrod R McClean, Matthew McEwen, Anthony Megrant, Xiao Mi, Kristel Michielsen, Masoud Mohseni, Josh Mutus, Ofer Naaman, Matthew Neeley, Charles Neill, Murphy Yuezhen Niu, Eric Ostby, Andre Petukhov, John C Platt, Chris Quintana, Eleanor G Rieffel, Pedram Roushan, Nicholas C Rubin, Daniel Sank, Kevin J Satzinger, Vadim Smelyanskiy, Kevin J Sung, Matthew D Trevithick, Amit Vainsencher, Benjamin Villalonga, Theodore White, Z Jamie Yao, Ping Yeh, Adam Zalcman, Hartmut Neven, John M Martinis, Quantum supremacy using a programmable superconducting processor, *Nature* **574** (7779), 505-510, (2019).
- [7] A. G. Fowler, M. Mariantoni, J. M. Martinis, and A. N. Cleland, Surface codes: Towards practical large-scale quantum computation, *Phys. Rev. A* **86**, 032324 (2012).
- [8] David P. DiVincenzo, The Physical Implementation of Quantum Computation, *Fortschr. Phys.* **48**, 9-11 (2000).
- [9] A. Morvan, B. Villalonga, X. Mi, S. Mandrà *et al.* Phase transition in Random Circuit Sampling. *arXiv preprint arXiv:2304.11119* (2023).
- [10] Göran Wendin and Jonas Bylander, Quantum computer scales up by mitigating errors, *Nature* **618**, 462-463 (2023). <https://www.nature.com/articles/d41586-023-01884-3>
- [11] Filip B. Maciejewski, Zoltán Zimborás, and Michał Oszmaniec, Mitigation of readout noise in near-term quantum devices by classical post-processing based on detector tomography, *Quantum* **4**, 257 (2020).
- [12] Filip B. Maciejewski, Flavio Baccari, Zoltán Zimborás, and Michał Oszmaniec, Modeling and mitigation of cross-talk effects in readout noise with applications to the Quantum Approximate Optimization Algorithm, *Quantum* **5**, 464 (2021).
- [13] D. R. Simon, On the power of quantum computation, *SIAM J. Comput.* **26**(5), 1474-1483 (1997).
- [14] T. D. Ladd, F. Jelezko, R. Laflamme *et al.*, Quantum computers, *Nature* **464**, 45 (2010).
- [15] Shor, P. W. Scheme for reducing decoherence in quantum computer memory. *Phys. Rev. A* **52**, R2493 (1995).
- [16] Gottesman, D. Stabilizer Codes and Quantum Error Correction. PhD thesis, California Institute of Technology (1997).
- [17] Z Cai, R Babbush, SC Benjamin, S Endo, WJ Huggins, Y Li, JR McClean, *et al.* Quantum error mitigation, *Rev. Mod. Phys.* **95** (4), 045005 (2023).
- [18] Raffaele Santagati *et al.* Drug design on quantum computers, *arXiv preprint arXiv:2301.04114*, (2023).
- [19] Peter W. Shor, Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer, *SIAM Journal on Computing* **26**, 5 (1997).
- [20] J. Preskill, Quantum computing and the entanglement frontier, *arXiv preprint arXiv:1203.5813v3* [quant-ph] (2012).
- [21] A. W. Harrow, A. Montanaro, Quantum computational supremacy, *Nature* **549**(7671), 203-209 (2017).
- [22] Ya Wang, Florian Dolde, Jacob Biamonte, Ryan Babbush, Ville Bergholm, Sen Yang, Ingmar Jakobi, Philipp Neumann, Alán Aspuru-Guzik, James D Whitfield, Jorg Wrachtrup, Quantum simulation of helium hydride cation in a solid-state spin register, *ACS nano* **9** (8), 7769-7774, (2015).
- [23] Peter JJ O'Malley, Ryan Babbush, Ian D Kivlichan, Jonathan Romero, Jarrod R McClean, Rami Barends, Julian Kelly, Pedram Roushan, Andrew Tranter, Nan Ding, Brooks Campbell, Yu Chen, Zijun Chen, Ben Chiaro, Andrew Dunsworth, Austin G Fowler, Evan Jeffrey, Erik Lucero, Anthony Megrant, Josh Y Mutus, Matthew Neeley, Charles Neill, Chris Quintana, Daniel Sank, Amit Vainsencher, Jim Wenner, Ted C White, Peter V Coveney, Peter J Love, Hartmut Neven, Alain Aspuru-Guzik, John M Martinis, Scalable quantum simulation of molecular energies, *Phys. Rev. X* **6** (3), 031007, (2016).
- [24] Marco Cerezo, Andrew Arrasmith, Ryan Babbush, Simon C Benjamin, Suguru Endo, Keisuke Fujii, Jarrod R McClean, Kosuke Mitarai, Xiao Yuan, Lukasz Cincio, Patrick J Coles, Variational quantum algorithms, *Nat Rev Phys* **3**, 9, 625-644 (2021).
- [25] A. Wallraff *et al.*, Strong coupling of a single photon to a superconducting qubit using circuit quantum electrodynamics, *Nature* **431**, 162-167 (2004).
- [26] J. Q. You and F. Nori. Atomic physics and quantum optics using superconducting circuits. *Nature* **474**, 589-597 (2011).
- [27] Kjaergaard, M. *et al.* Superconducting qubits: current state of play. *Annu. Rev. Condens. Matter Phys.* **11**, 369-395 (2020).
- [28] R. Barends, A. Shabani, L. Lamata *et al.*, Digitized adiabatic quantum computing with a superconducting circuit. *Nature* **534**, 222-226 (2016).

- [29] Xiao Mi, Pedram Roushan, Chris Quintana *et al.*, Information Scrambling in Computationally Complex Quantum Circuits, *Science* **374**, 1479 (2021).
- [30] M. H. Devoret, J. M. Martinis and J. Clarke. Measurements of macroscopic quantum tunneling out of the zero-voltage state of a current-biased Josephson junction. *Phys. Rev. Lett.* **55**, 1908 (1985).
- [31] Y. Nakamura, C. D. Chen and J. S. Tsai. Spectroscopy of energy-level splitting between two macroscopic quantum states of charge coherently superposed by Josephson coupling. *Phys. Rev. Lett.* **79**, 2328 (1997).
- [32] J. Mooij *et al.* Josephson persistent-current qubit. *Science* **285**, 1036-1039 (1999).
- [33] Rajeev Acharya, *et al.* Suppressing quantum errors by scaling a surface code logical qubit, *Nature* **614** (7949), 676-681 (2023).
- [34] B. Swingle, Unscrambling the physics of out-of-time-order correlators. *Nature Phys.* **14**, 988-990 (2018).
- [35] Ryan Babbush, Jarrod R. McClean, Michael Newman *et al.*, Focus beyond Quadratic Speedups for Error-Corrected Quantum Advantage, *PRX Quantum* **2**, 010103 (2021).
- [36] X. Mi, M. Ippoliti, C. Quintana *et al.* Time-crystalline eigenstate order on a quantum processor. *Nature* **601**, 531-536 (2022). <https://doi.org/10.1038/s41586-021-04257-w>
- [37] X. Mi *et al.* Noise-resilient edge modes on a chain of superconducting qubits, *Science* **378**, 6621, 785-790, 17 Nov (2022).
- [38] A. Morvan and T. Andersen, Formation of robust bound states of interacting photons, (December 8, 2022), <https://research.google/blog/formation-of-robust-bound-states-of-interacting-photons/>, accessed August 19, (2024).
- [39] Kelly, J. and Barends, R. and Fowler, *et al.* , Scalable in situ qubit calibration during repetitive error detection, *Phys. Rev. A* **94**, 032321, (2016).
- [40] Seth Lloyd, Masoud Mohseni, Patrick Rebentrost, Quantum algorithms for supervised and unsupervised machine learning, arXiv preprint arXiv:1307.0411, (2013).
- [41] D. Mackay, Information Theory, Inference and Learning Algorithms, Cambridge University Press, Cambridge (2003).
- [42] Yu Chen, C Neill, Pedram Roushan, Nelson Leung, Michael Fang, Rami Barends, Julian Kelly, Brooks Campbell, Z Chen, Benjamin Chiaro, Andrew Dunsworth, Evan Jeffrey, Anthony Megrant, JY Mutus, PJJ O'Malley, CM Quintana, D Sank, Amit Vainsencher, J Wenner, TC White, Michael R Geller, Andrew N Cleland, John M Martinis, Qubit architecture with high coherence and fast tunable coupling, *Phys. Rev. Lett.* **113** (22), 220502, 2014
- [43] R. Barends *et al.* Coherent Josephson qubit suitable for scalable quantum integrated circuits, *Phys. Rev. Lett.* **111**, 080502 (2013).
- [44] Troels F Rønnow, Zhihui Wang, Joshua Job, Sergio Boixo, Sergei V Isakov, David Wecker, John M Martinis, Daniel A Lidar, Matthias Troyer, Defining and detecting quantum speedup, *Science* **345** (6195), 420-424, (2014).
- [45] Brooke, J., Bitko, D., Rosenbaum, T. and Aeppli, G. Quantum annealing of a disordered magnet. *Science* **284**, 779–781 (1999).
- [46] Brooke, J., Bitko, D., Rosenbaum, T. F. and Aeppli, G. Quantum annealing of a disordered spin system. *Science* **284**, 779–781 (1999).
- [47] Santoro, G. E., Martoňák, R., Tosatti, E. and Car, R. Theory of quantum annealing of an Ising spin glass. *Science* **295**, 2427–2430 (2002).
- [48] Sergio Boixo, Vadim N Smelyanskiy, Alireza Shabani, Sergei V Isakov, Mark Dykman, Vasil S Denchev, Mohammad Amin, Anatoly Smirnov, Masoud Mohseni, Hartmut Neven, Computational role of collective tunneling in a quantum annealer, arXiv preprint arXiv:1411.4036, (2014).
- [49] Leggett, A. J. *et al.* Dynamics of the dissipative two-state system. *Rev. Mod. Phys.* **59**, 1–85 (1987).
- [50] A. J. Berkley, A. J. Przybysz, T. Lanting, R. Harris, N. Dickson, F. Altomare, M. H. Amin, P. Bunyk, C. Enderud, E. Hoskinson, M. W. Johnson, E. Ladizinsky, R. Neufeld, C. Rich, A. Yu. Smirnov, E. Tolkacheva, S. Uchaikin, and A. B. Wilson, Tunneling spectroscopy using a probe qubit, *Phys. Rev. B* **87**, 020502 (2013).
- [51] Trevor Lanting, Anthony J Przybysz, A Yu Smirnov, Federico M Spedalieri, Mohammad H Amin, Andrew J Berkley, Richard Harris, Fabio Altomare, Sergio Boixo, Paul Bunyk, Neil Dickson, C Enderud, Jeremy P Hilton, Emile Hoskinson, Mark W Johnson, Eric Ladizinsky, Nicholas Ladizinsky, Richard Neufeld, Travis Oh, Ilya Perminov, Chris Rich, Murray C Thom, E Tolkacheva, Sergey Uchaikin, AB Wilson, Geordie Rose, Entanglement in a quantum annealing processor, *Phys. Rev. X* **4** (2), 021041, (2014).
- [52] Pedram Roushan, C Neill, Yu Chen, M Kolodrubetz, C Quintana, N Leung, M Fang, R Barends, B Campbell, Z Chen, B Chiaro, A Dunsworth, E Jeffrey, J Kelly, A Megrant, J Mutus, PJJ O'Malley, D Sank, A Vainsencher, J Wenner, T White, A Polkovnikov, AN Cleland, JM Martinis. Observation of topological transitions in interacting quantum circuits, *Nature* **515** (7526), 241-244, (2014).
- [53] Gritsev, V. and Polkovnikov, A. Dynamical quantum Hall effect in the parameter space. *Proc. Natl Acad. Sci. USA* **109**, 6457–6462 (2012).
- [54] Haldane, F. D. M. Model for a quantum Hall effect without Landau levels: condensed-matter realization of the “parity anomaly”. *Phys. Rev. Lett.* **61**, 2015–2018 (1988)
- [55] Geller, M. *et al.* Tunable coupler for superconducting Xmon qubits: perturbative nonlinear model. Preprint at <http://arXiv.org/abs/1405.1915> (2014)
- [56] Chen, Y. *et al.* Qubit architecture with high coherence and fast tunable coupling. Preprint at <http://arXiv.org/abs/1402.7367> (2014).
- [57] Nan Ding, Youhan Fang, Ryan Babbush, Changyuo Chen, Robert D Skeel, Hartmut Neven, Bayesian sampling using stochastic gradient thermostats, *Advances in neural information processing systems* **27**, (2014).
- [58] M. D. Hoffman, D. M. Blei, C. Wang, and J. Paisley. Stochastic Variational Inference. *Journal of Machine Learning Research*, **14**(1):1303–1347, (2013).
- [59] T. Chen, E. B. Fox, and C. Guestrin. Stochastic Gradient Hamiltonian Monte Carlo. *Proceedings of the 31st International Conference on Machine Learning*, (2014).
- [60] M. E. Tuckerman. Statistical Mechanics: Theory and Molecular Simulation. Oxford University Press, (2010).
- [61] Michael R Geller, Emmanuel Donate, Yu Chen, Michael T Fang, Nelson Leung, Charles Neill, Pedram Roushan,

- John M Martinis, Tunable coupler for superconducting Xmon qubits: Perturbative nonlinear model, *Phys. Rev. A* **92** (1), 012320, 2015
- [62] E. A. Engel, N. Doss, G. J. Harris, and J. Tennyson, Calculated spectra for HeH^+ and its effect on the opacity of cool metal-poor stars, *Mon. Not. R. Astron. Soc.* **357**, 471 (2005).
- [63] A. Bermudez, F. Jelezko, M. B. Plenio, and A. Retzker, Electron-Mediated Nuclear-Spin Interactions between Distant Nitrogen-Vacancy Centers, *Phys. Rev. Lett.* **107**, 150503 (2011).
- [64] R. P. Feynman, Simulating physics with computers, *Int. J. Theor. Phys.* **21**, 467 (1982).
- [65] S. Lloyd, Universal Quantum Simulators, *Science* **273**, 1073 (1996).
- [66] Smith, A., Kim, M.S., Pollmann, F. *et al.* Simulating quantum many-body dynamics on a current digital quantum computer. *npj Quantum Inf* **5**, 106 (2019).
- [67] Julian Kelly, Rami Barends, Austin G Fowler, Anthony Megrant, Evan Jeffrey, Theodore C White, Daniel Sank, Josh Y Mutus, Brooks Campbell, Yu Chen, Zijun Chen, Ben Chiaro, Andrew Dunsworth, I-C Hoi, Charles Neill, Peter JJ O'Malley, Christopher Quintana, Pedran Roushan, Amit Vainsencher, James Wenner, Andrew N Cleland, John M Martinis, State preservation by repetitive error detection in a superconducting quantum circuit, *Nature* **519** (7541), 66-69, 2015
- [68] Greenberger, D. M., Horne, M. A., Shimony, A. and Zeilinger, A. Bell's theorem without inequalities. *Am. J. Phys.* **58**, 1131–1143 (1990).
- [69] Rami Barends, Lucas Lamata, Julian Kelly, L García-Álvarez, Austin G Fowler, A Megrant, Evan Jeffrey, Ted C White, Daniel Sank, Josh Y Mutus, B Campbell, Yu Chen, Zhaoshi Chen, B Chiaro, A Dunsworth, I-C Hoi, C Neill, PJJ O'Malley, Céline Quintana, P Roushan, A Vainsencher, J Wenner, E Solano, John M Martinis, Digital quantum simulation of fermionic models with a superconducting circuit, *Nat. Comm.* **6** (1), 7654, (2015).
- [70] Xiaoting Wang, Michele Allegra, Kurt Jacobs, Seth Lloyd, Cosmo Lupo, Masoud Mohseni, Quantum brachistochrone curves as geodesics: Obtaining accurate minimum-time protocols for the control of quantum systems, *Phys. Rev. Lett.* **114** (17), 170501, (2015).
- [71] Sergio Boixo, Gerardo Ortiz, Rolando Somma, Fast quantum methods for optimization, *The European Physical Journal Special Topics* **224** (1), 35-49, (2015).
- [72] A. Peruzzo, J. McClean, P. Shadbolt, M.-H. Yung, X.-Q. Zhou, P. J. Love, A. Aspuru-Guzik, and J. L. O'Brien. A variational eigenvalue solver on a photonic quantum processor. *Nat. Comm.*, **5**(1):4213, (2014).
- [73] J. R. McClean, J. Romero, R. Babbush, A. Aspuru-Guzik, The theory of variational hybrid quantum-classical algorithms, *New J. Phys.* **18** (2), 023023 (2016).
- [74] Aharonov, D. *et al.* Adiabatic quantum computation is equivalent to standard quantum computation. *SIAM Rev.* **50**, 755–787 (2008).
- [75] Lloyd, S. and Terhal, B. M. Adiabatic and Hamiltonian computing on a 2D lattice with simple two-qubit interactions. *New J. Phys.* **18**, 023042 (2016).
- [76] Rami Barends, Alireza Shabani, Lucas Lamata, Julian Kelly, Antonio Mezzacapo, U Las Heras, Ryan Babbush, Austin G Fowler, Brooks Campbell, Yu Chen, Zijun Chen, Ben Chiaro, Andrew Dunsworth, Evan Jeffrey, Erik Lucero, Anthony Megrant, JY Mutus, Matthew Neeley, Charles Neill, PJJ O'Malley, Chris Quintana, Pedran Roushan, D Sank, Amit Vainsencher, James Wenner, TC White, Enrique Solano, Hartmut Neven, John M Martinis, Digitized adiabatic quantum computing with a superconducting circuit, *Nature* **534** (7606), 222-226, 2016
- [77] Farhi, E., Goldstone, J., Gutmann, S. and Sipser, M. Quantum computation by adiabatic evolution. Preprint at <http://arxiv.org/abs/quant-ph/0001106> (2000).
- [78] Farhi, E. *et al.* A quantum adiabatic evolution algorithm applied to random instances of an NP-complete problem. *Science* **292**, 472–475 (2001).
- [79] Nishimori, H. *Statistical Physics of Spin Glasses and Information Processing: An Introduction* (Oxford Univ. Press, 2001).
- [80] Steffen, M. *et al.* Experimental implementation of an adiabatic quantum optimization algorithm. *Phys. Rev. Lett.* **90**, 067903 (2003).
- [81] Lanyon, B. P. *et al.* Universal digital quantum simulation with trapped ions. *Science* **334**, 57–61 (2011).
- [82] Barends, R. *et al.* Digital quantum simulation of fermionic models with a superconducting circuit. *Nat. Commun.* **6**, 7654 (2015).
- [83] Salathé, Y. *et al.* Digital quantum simulation of spin models with circuit quantum electrodynamics. *Phys. Rev. X* **5**, 021027 (2015).
- [84] Man-Hong Yung, J Casanova, A Mezzacapo, J McClean, L Lamata, A Aspuru-Guzik, and E Solano, From transistor to trapped-ion computers for quantum chemistry, *Scientific Reports* **4**, 9 (2014).
- [85] J. R. McClean, R. Babbush, P. J. Love, and A. Aspuru-Guzik, Exploiting locality in quantum computation for quantum chemistry, *The Journal of Physical Chemistry Letters* **5**, 4368–4380 (2014).
- [86] Dave Wecker, Matthew B. Hastings, and Matthias Troyer, Progress towards practical quantum variational algorithms, *Phys. Rev. A* **92**, 042303 (2015).
- [87] Yangchao Shen, Xiang Zhang, Shuaining Zhang, Jing-Ning Zhang, Man-Hong Yung, and Kihwan Kim, Quantum Implementation of Unitary Coupled Cluster for Simulating Molecular Electronic Structure, e-print arXiv: 1506.00443 (2015).
- [88] Hale F Trotter, On the product of semi-groups of operators, *Proc. Am. Math. Soc.* **10**, 545–551 (1959).
- [89] Alexei Y. Kitaev, Quantum measurements and the Abelian Stabilizer Problem, e-print arXiv: 9511026 (1995).
- [90] Charles Neill, P Roushan, M Fang, Y Chen, M Koldrubez, Z Chen, A Megrant, R Barends, B Campbell, B Chiaro, A Dunsworth, E Jeffrey, J Kelly, J Mutus, PJJ O'malley, C Quintana, D Sank, A Vainsencher, J Wenner, TC White, Anatoli Polkovnikov, JM Martinis, Ergodic dynamics and thermalization in an isolated quantum system, *Nature Physics* **12** (11), 1037-1041, 2016
- [91] Haake, F., Kuś, M. and Scharf, R. Classical and quantum chaos for a kicked top. *Z. Phys. B* **65**, 381–395 (1987).
- [92] Wang, X., Ghose, S., Sanders, B. C. and Hu, B. Entanglement as a signature of quantum chaos. *Phys. Rev. E* **70**, 016217 (2004).

- [93] Ghose, S., Stock, R., Jessen, P., Lal, R. and Silberfarb, A. Chaos, entanglement, and decoherence in the quantum kicked top. *Phys. Rev. A* **78**, 042318 (2008).
- [94] Chaudhury, S., Smith, A., Anderson, B., Ghose, S. and Jessen, P. Quantum signatures of chaos in a kicked top. *Nature* **461**, 768–771 (2009).
- [95] Lombardi, M. and Matzkin, A. Entanglement and chaos in the kicked top. *Phys. Rev. E* **83**, 016207 (2011).
- [96] Sergio Boixo, Vadim N Smelyanskiy, Alireza Shabani, Sergei V Isakov, Mark Dykman, Vasil S Denchev, Mohammad H Amin, Anatoly Yu Smirnov, Masoud Mohseni, Hartmut Neven, Computational multiqubit tunnelling in programmable quantum annealers, *Nat. Comm.* **7** (1), 10327, 2016
- [97] Vasil S Denchev, Sergio Boixo, Sergei V Isakov, Nan Ding, Ryan Babbush, Vadim Smelyanskiy, John Martinis, Hartmut Neven, What is the computational value of finite-range tunneling?, *Phys. Rev. X* **6** (3), 031015, 2016
- [98] Ryan Babbush, Dominic W Berry, Ian D Kivlichan, Annie Y Wei, Peter J Love, Alán Aspuru-Guzik, Exponentially more precise quantum simulation of fermions in second quantization, *New J. Phys.* **18** (3), 033032, 2016
- [99] Sergei V Isakov, Guglielmo Mazzola, Vadim N Smelyanskiy, Zhang Jiang, Sergio Boixo, Hartmut Neven, Matthias Troyer, Understanding quantum tunneling through quantum Monte Carlo simulations, *Phys. Rev. Lett.* **117** (18), 180402, 2016
- [100] Jirawat Tangpanitanon, Victor M Bastidas, Sarah Al-Assam, Pedram Roushan, Dieter Jaksch, Dimitris G Angelakis, Topological pumping of photons in nonlinear resonator arrays, *Phys. Rev. Lett.* **117** (21), 213603, 2016
- [101] Theodore C White, JY Mutus, Justin Dressel, J Kelly, R Barends, E Jeffrey, D Sank, A Megrant, B Campbell, Yu Chen, Z Chen, B Chiaro, A Dunsworth, IC Hoi, C Neill, PJJ O’Malley, P Roushan, A Vainsencher, J Wenner, AN Korotkov, John M Martinis, Preserving entanglement during weak measurement demonstrated with a violation of the Bell-Leggett-Garg inequality, *npj Quantum Inf* **2** (1), 1-5, (2016).
- [102] Marek M Rams, Masoud Mohseni, Adolfo Del Campo, Inhomogeneous quasi-adiabatic driving of quantum critical dynamics in weakly disordered spin chains, *New J. Phys.* **18** (12), 123034, (2016).
- [103] Masoud Mohseni, Peter Read, Hartmut Neven, Sergio Boixo, Vasil Denchev, Ryan Babbush, Austin Fowler, Vadim Smelyanskiy, John Martinis, Commercialize quantum technologies in five years, *Nature* **543** (7644), 171-174, (2017).
- [104] D. Kielpinski, C. Monroe, D. J. Wineland, Architecture for a large-scale ion-trap quantum computer. *Nature* **417**, 709–711 (2002).
- [105] C. Monroe, J. Kim, Scaling the ion trap quantum processor. *Science* **339**, 1164–1169 (2013).
- [106] C. Monroe, R. Raussendorf, A. Ruthven, K. R. Brown, P. Maunz, L.-M. Duan, J. Kim, Large-scale modular quantum-computer architecture with atomic memory and photonic interconnects. *Phys. Rev. A* **89**, 022317 (2014).
- [107] N. H. Nickerson, J. F. Fitzsimons, S. C. Benjamin, Freely scalable quantum technologies using cells of 5-to-50 qubits with very lossy and noisy photonic links. *Phys. Rev. X* **4**, 041041 (2014).
- [108] Bjoern Lekitsch, Sebastian Weidt, Austin G Fowler, Klaus Mølmer, Simon J Devitt, Christof Wunderlich, Winfried K Hensinger, Blueprint for a microwave trapped ion quantum computer, *Science Advances* **3** (2), e1601540, (2017).
- [109] S. Weidt, J. Randall, S. C. Webster, K. Lake, A. E. Webb, I. Cohen, T. Navickas, B. Lekitsch, A. Retzker, W. K. Hensinger, Trapped-ion quantum logic with global radiation fields. *Phys. Rev. Lett.* **117**, 220501 (2016).
- [110] F. Mintert, C. Wunderlich, Ion-trap quantum logic using long-wavelength radiation. *Phys. Rev. Lett.* **87**, 257904 (2001).
- [111] A. G. Fowler, A. M. Stephens, P. Groszkowski, High-threshold universal quantum computation on the surface code. *Phys. Rev. A* **80**, 052312 (2009).
- [112] R. Bowler, J. Gaebler, Y. Lin, T. R. Tan, D. Hanneke, J. D. Jost, J. P. Home, D. Leibfried, D. J. Wineland, Coherent diabatic ion transport and separation in a multizone trap array. *Phys. Rev. Lett.* **109**, 080502 (2012).
- [113] A. Walther, F. Ziesel, T. Ruster, S. T. Dawkins, K. Ott, M. Hettrich, K. Singer, F. Schmidt-Kaler, U. Poschinger, Controlling fast transport of cold trapped ions. *Phys. Rev. Lett.* **109**, 080501 (2012).
- [114] Pedram Roushan, Charles Neill, Anthony Megrant, Yu Chen, Ryan Babbush, Rami Barends, Brooks Campbell, Zijun Chen, Ben Chiaro, Andrew Dunsworth, Austin Fowler, Evan Jeffrey, Julian Kelly, Erik Lucero, Josh Mutus, PJJ O’Malley, Matthew Neeley, Chris Quintana, Daniel Sank, Amit Vainsencher, Jim Wenner, Ted White, Eliot Kapit, Hartmut Neven, John Martinis, Chiral ground-state currents of interacting photons in a synthetic magnetic field, *Nature Physics* **13** (2), 146-151, (2017).
- [115] Fang, K., Yu, Z. and Fan, S. Realizing effective magnetic field for photons by controlling the phase of dynamic modulation. *Nat. Photon.* **6**, 782–787 (2012).
- [116] Hafezi, M., Adhikari, P. and Taylor, J. M. Engineering three-body interaction and Pfaffian states in circuit QED systems. *Phys. Rev. B* **90**, 060503 (2014).
- [117] Kapit, E. Universal two-qubit interactions, measurement, and cooling for quantum simulation and computing. *Phys. Rev. A* **92**, 012302 (2015).
- [118] Pedram Roushan, Charles Neill, J Tangpanitanon, Victor M Bastidas, A Megrant, Rami Barends, Yu Chen, Z Chen, B Chiaro, A Dunsworth, A Fowler, B Foxen, Marissa Giustina, E Jeffrey, J Kelly, Erik Lucero, J Mutus, Matthew Neeley, Chris Quintana, D Sank, Amit Vainsencher, James Wenner, T White, H Neven, DG Angelakis, J Martinis, Spectroscopic signatures of localization with interacting photons in superconducting qubits, *Science* **358** (6367), 1175-1179, (2017).
- [119] D. Jaksch and P. Zoller, Creation of effective magnetic fields in optical lattices: the hofstadter butterfly for cold neutral atoms, *New J. Phys.* **5** (2003).
- [120] B. Hunt, J. D. Sanchez-Yamagishi, A. F. Young, M. Yankowitz, B. J. LeRoy, K. Watanabe, T. Taniguchi, P. Moon, M. Koshino, P. Jarillo-Herrero, and R. C. Ashoori, Massive dirac fermions and hofstadter butterfly in a van der waals heterostructure, *Science* **340**, 1427–602 (2013).
- [121] A. Pal and D. A. Huse, Many-body localization phase transition, *Phys. Rev. B* **82**, 174411 (2010).

- [122] A. M. Kaufman, M. E. Tai, A. Lukin, M. Rispoli, R. Schittko, P. M. Preiss, and M. Greiner, Quantum thermalization through entanglement in an isolated many-body system, *Science* **353**, 794–800 (2016).
- [123] J. Choi, S. Hild, J. Zeiher, P. Schauss, T. Yefsah A. Rubio-Abadal, V. Khemani, D. A. Huse, I. Bloch, and C. Gross, Exploring the many-body localization transition in two dimensions, *Science* **352**, 1547–1552 (2016).
- [124] Sergio Boixo, Vadim N Smelyanskiy, Hartmut Neven, Fourier analysis of sampling from noisy chaotic quantum circuits, arXiv preprint arXiv:1708.01875, (2017).
- [125] Zhang Jiang, Vadim N Smelyanskiy, Sergei V Isakov, Sergio Boixo, Guglielmo Mazzola, Matthias Troyer, Hartmut Neven, Scaling analysis and instantons for thermally assisted tunneling and quantum Monte Carlo simulations, *Phys. Rev. A* **95** (1), 012322, (2017).
- [126] Ryan Babbush, Dominic W Berry, Yuval R Sanders, Ian D Kivlichan, Artur Scherer, Annie Y Wei, Peter J Love, Alán Aspuru-Guzik, Exponentially more precise quantum simulation of fermions in the configuration interaction representation, *Quantum Sci. Technol.* **3** (1), 015006, (2017).
- [127] CM Quintana, Yu Chen, Daniel Sank, AG Petukhov, TC White, Dvir Kafri, Ben Chiaro, Anthony Megrant, Rami Barends, Brooks Campbell, Zijun Chen, Andrew Dunsworth, Austin G Fowler, Rob Graff, Evan Jeffrey, Julian Kelly, Erik Lucero, JY Mutus, Matthew Neeley, Charles Neill, PJJ O’Malley, Pedram Roushan, Alireza Shabani, VN Smelyanskiy, Amit Vainsencher, James Wenner, Hartmut Neven, John M Martinis, Observation of Classical-Quantum Crossover of Flux Noise and Its Paramagnetic Temperature Dependence, *Phys. Rev. Lett.* **118** (5), 057702, (2017).
- [128] Zhi-Cheng Yang, Armin Rahmani, Alireza Shabani, Hartmut Neven, Claudio Chamon, Optimizing variational quantum algorithms using pontryagin’s minimum principle, *Phys. Rev. X* **7** (2), 021027, (2017).
- [129] Sergio Boixo, Sergei V Isakov, Vadim N Smelyanskiy, Hartmut Neven, Simulation of low-depth quantum circuits as complex undirected graphical models, *arXiv preprint* arXiv:1712.05384, (2017).
- [130] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, Hartmut Neven, Quantum algorithms for fixed qubit architectures, *arXiv preprint* arXiv:1703.06199, (2017).
- [131] Ian D Kivlichan, Nathan Wiebe, Ryan Babbush, Alán Aspuru-Guzik, Bounding the costs of quantum simulation of many-body physics in real space, *Journal of Physics A: Mathematical and Theoretical* **50** (30), 305301, (2017).
- [132] Craig Gidney, Factoring with $n+2$ clean qubits and $n-1$ dirty qubits, arXiv preprint arXiv:1706.07884, (2017).
- [133] PV Klimov, Julian Kelly, Zijun Chen, Matthew Neeley, Anthony Megrant, Brian Burkett, Rami Barends, Kunal Arya, Ben Chiaro, Yu Chen, Andrew Dunsworth, Austin Fowler, Brooks Foxen, Craig Gidney, Marissa Giustina, Rob Graff, Trent Huang, Evan Jeffrey, Erik Lucero, Josh Y Mutus, Ofer Naaman, Charles Neill, Chris Quintana, Pedram Roushan, Daniel Sank, Amit Vainsencher, Jim Wenner, Timothy C White, Sergio Boixo, Ryan Babbush, Vadim N Smelyanskiy, Hartmut Neven, John M Martinis, Fluctuations of energy-relaxation times in superconducting qubits, *Phys. Rev. Lett.* **121** (9), 090502, (2018).
- [134] Ryan Babbush, Nathan Wiebe, Jarrod McClean, James McClain, Hartmut Neven, Garnet Kin-Lic Chan, Low-depth quantum simulation of materials, *Phys. Rev. X* **8** (1), 011044, (2018).
- [135] H. F. Trotter, On the Product of Semi-Groups of Operators, *Proc. Amer. Math. Soci.* **10**, 4, 545-551 (1959).
- [136] Masuo Suzuki, Improved Trotter-like formula, *Physics Letters A*, **180**, 3, 232-234, (1993).
- [137] Ryan Babbush *et al.* Exponentially more precise quantum simulation of fermions in second quantization, *New J. Phys.* **18** 033032 (2016).
- [138] Ian D Kivlichan, Jarrod McClean, Nathan Wiebe, Craig Gidney, Alán Aspuru-Guzik, Garnet Kin-Lic Chan, Ryan Babbush, Quantum simulation of electronic structure with linear depth and connectivity, *Phys. Rev. Lett.* **120** (11), 110501, (2018).
- [139] M. AbuGhanem and H. Eleuch, Two-qubit entangling gates for superconducting quantum computers, *Results in Physics* **56**, 107236 (2024).
- [140] M. AbuGhanem *et al.*, Fast universal entangling gate for superconducting quantum computers, *Elsevier, SSRN*, 4726035 (2024). <http://dx.doi.org/10.2139/ssrn.4726035>
- [141] M. AbuGhanem, Full quantum process tomography of a universal entangling gate on an IBM’s quantum computer, *arXiv preprint* arXiv:2402.06946, (2024).
- [142] Cornelius Hempel, Christine Maier, Jonathan Romero, Jarrod McClean, Thomas Monz, Heng Shen, Petar Jurcevic, Ben P Lanyon, Peter Love, Ryan Babbush, Alán Aspuru-Guzik, Rainer Blatt, Christian F Roos, Quantum chemistry calculations on a trapped-ion quantum simulator, *Phys. Rev. X*, **8**, 031022 (2018).
- [143] Charles Neill, Pedram Roushan, K Kechedzhi, Sergio Boixo, Sergei V Isakov, V Smelyanskiy, A Megrant, B Chiaro, A Dunsworth, K Arya, Rami Barends, B Burkett, Y Chen, Z Chen, A Fowler, B Foxen, M Giustina, R Graff, E Jeffrey, T Huang, J Kelly, P Klimov, E Lucero, J Mutus, M Neeley, C Quintana, D Sank, A Vainsencher, J Wenner, TC White, Hartmut Neven, John M Martinis, A blueprint for demonstrating quantum supremacy with superconducting qubits, *Science* **360** (6385), 195-199, (2018).
- [144] Sergio Boixo, Sergei V Isakov, Vadim N Smelyanskiy, Ryan Babbush, Nan Ding, Zhang Jiang, Michael J Bremner, John M Martinis, Hartmut Neven, Characterizing quantum supremacy in near-term devices, *Nature Physics* **14** (6), 595-600, (2018).
- [145] Jonathan Romero, Ryan Babbush, Jarrod R McClean, Cornelius Hempel, Peter J Love, Alán Aspuru-Guzik, Strategies for quantum computing molecular energies using the unitary coupled cluster ansatz, *Quantum Sci. Technol.* **4** (1), 014008, (2018).
- [146] M. R. Hoffmann and J. Simons, A unitary multiconfigurational coupled-cluster method: Theory and applications, *J. Chem. Phys.* **88**, 993 (1988).
- [147] R. J. Bartlett, S. A. Kucharski, and J. Noga, Alternative coupled-cluster ansätze II. The unitary coupled-cluster method, *Chem. Phys. Lett.* **155**, 133 (1989).
- [148] B. Cooper and P. J. Knowles, Benchmark studies of variational, unitary and extended coupled cluster methods, *J. Chem. Phys.* **133**, 234102 (2010).
- [149] F. A. Evangelista, Alternative single-reference coupled cluster approaches for multireference problems: The simpler, the better, *J. Chem. Phys.* **134**, 224102 (2011).

- [150] McClean, J.R., Boixo, S., Smelyanskiy, V.N. *et al.* Barren plateaus in quantum neural network training landscapes. *Nat Commun* **9**, 4812 (2018).
- [151] Edward Farhi, Hartmut Neven, Classification with quantum neural networks on near term processors, arXiv preprint arXiv:1802.06002, (2018).
- [152] Y. Liu, M. Otten, R. Bassirianjahromi, L. Jiang, and B. Fefferman, Benchmarking near-term quantum computers via random circuit sampling, arXiv:2105.05232 (2021).
- [153] D Leibfried, B DeMarco, V Meyer, M Rowe, A Ben-Kish, J Britton, Wayne M Itano, B Jelenkovic, C Langer, T Rosenband, and David J Wineland, Trapped-ion quantum simulator: Experimental application to nonlinear interferometers, *Phys. Rev. Lett.* **89**, 247901 (2002).
- [154] Iulia Buluta and Franco Nori, Quantum Simulators, *Science* **326**, 108 (2009).
- [155] Tobias Schaetz, Christopher Roy Monroe, and Tilman Esslinger, Focus on quantum simulation, *New J. Phys.* **15**, 085009 (2013).
- [156] I M Georgescu, S. Ashhab, and Franco Nori, Quantum simulation, *Rev. Mod. Phys.* **86**, 153–185 (2014).
- [157] Tomi H Johnson, Stephen R Clark, and Dieter Jaksch, What is a quantum simulator? *EPJ Quantum Technology* **1**, **10** (2014).
- [158] Dominic W Berry, Mária Kieferová, Artur Scherer, Yuval R Sanders, Guang Hao Low, Nathan Wiebe, Craig Gidney, Ryan Babbush, Improved techniques for preparing eigenstates of fermionic Hamiltonians, *npj Quantum Inf* **4** (1), 22, (2018).
- [159] Raffaele Santagati, Jianwei Wang, Antonio A Gentile, Stefano Paesani, Nathan Wiebe, Jarrod R McClean, Sam Morley-Short, Peter J Shadbolt, Damien Bonneau, Joshua W Silverstone, David P Tew, Xiaoqi Zhou, Jeremy L O’Brien, Mark G Thompson, Witnessing eigenstates for quantum simulation of Hamiltonian spectra, *Science advances* **4** (1), eaap9646, (2018).
- [160] Ryan Babbush, Craig Gidney, Dominic W Berry, Nathan Wiebe, Jarrod McClean, Alexandru Paler, Austin Fowler, Hartmut Neven, Encoding electronic spectra in quantum circuits with linear T complexity, *Phys. Rev. X* **8** (4), 041015, (2018).
- [161] Craig Gidney, Halving the cost of quantum addition, *Quantum* **2**, 74, (2018).
- [162] Zhang Jiang, Kevin J Sung, Kostyantyn Kechedzhi, Vadim N Smelyanskiy, Sergio Boixo, Quantum algorithms to simulate many-body physics of correlated fermions, *Phys. Rev. Applied* **9** (4), 044036, (2018).
- [163] Nicholas C Rubin, Ryan Babbush, Jarrod McClean, Application of fermionic marginal constraints to hybrid quantum algorithms, *New J. Phys.* **20** (5), 053020, (2018).
- [164] Fernando GSL Brandao, Michael Broughton, Edward Farhi, Sam Gutmann, Hartmut Neven, For fixed control parameters the quantum approximate optimization algorithm’s objective function value concentrates for typical instances, arXiv preprint arXiv:1812.04170, (2018).
- [165] Igor L Markov, Aneeqa Fatima, Sergei V Isakov, Sergio Boixo, Quantum supremacy is both closer and farther than it appears, arXiv preprint arXiv:1807.10749, (2018).
- [166] Austin G Fowler, Craig Gidney, Low overhead quantum computation using lattice surgery, arXiv preprint arXiv:1808.06709, (2018).
- [167] Norm M Tubman, Carlos Mejuto-Zaera, Jeffrey M Epstein, Diptarka Hait, Daniel S Levine, William Huggins, Zhang Jiang, Jarrod R McClean, Ryan Babbush, Martin Head-Gordon, K Birgitta Whaley, Postponing the orthogonality catastrophe: efficient state preparation for electronic structure simulations on quantum devices, arXiv preprint arXiv:1809.05523, (2018).
- [168] Kostyantyn Kechedzhi, Vadim Smelyanskiy, Jarrod R McClean, Vasil S Denchev, Masoud Mohseni, Sergei Isakov, Sergio Boixo, Boris Altshuler, Hartmut Neven, Efficient population transfer via non-ergodic extended states in quantum spin glass, arXiv preprint arXiv:1807.04792, (2018).
- [169] Alan Ho, Jarrod McClean, Shyue Ping Ong, The promise and challenges of quantum computing for energy storage, *Joule* **2** (5), 810-813, (2018).
- [170] Masoud Mohseni, Johan Strumpfer, Marek M Rams, Engineering non-equilibrium quantum phase transitions via causally gapped Hamiltonians, *Journal of Physics* **20** (10), 105002, (2018).
- [171] John Martinis and Sergio Boixo, Quantum Supremacy Using a Programmable Superconducting Processor, (October 23, 2019) <https://research.google/blog/quantum-supremacy-using-a-programmable-superconducting-processor/>, accessed August 19, (2024).
- [172] E. Pednault *et al.* Leveraging secondary storage to simulate deep 54-qubit Sycamore Circuits. *arXiv preprint* arXiv:1910.09534 [quant-ph] (2019).
- [173] Cupjin Huang *et al.* Classical Simulation of Quantum Supremacy Circuits. *arXiv preprint* arXiv:2005.06787 [quant-ph] (2020).
- [174] Feng Pan, Keyang Chen, and Pan Zhang, Solving the sampling problem of the Sycamore quantum circuits. *Phys. Rev. Lett.* **129**, 090502 (2022).
- [175] Ryan Babbush, Dominic W Berry, Jarrod R McClean, Hartmut Neven, Quantum simulation of chemistry with sublinear scaling in basis size, *npj Quantum Inf* **5** (1), 92, (2019).
- [176] Markus Reiher, Nathan Wiebe, Krysta M Svore, Dave Wecker, and Matthias Troyer, Elucidating reaction mechanisms on quantum computers, *Proceedings of the National Academy of Sciences* **114**, 7555-7560 (2017).
- [177] Guang Hao Low and Nathan Wiebe, Hamiltonian simulation in the interaction picture, arXiv:1805.00675 (2018).
- [178] Ryan Babbush, Craig Gidney, Dominic W Berry, Nathan Wiebe, Jarrod McClean, Alexandru Paler, Austin Fowler, and Hartmut Neven, Encoding electronic spectra in quantum circuits with linear T complexity, *Phys. Rev. X* **8**, 041015 (2018).
- [179] Combes, J.M., Duclos, P., Seiler, R. (1981). The Born-Oppenheimer Approximation. In: Velo, G., Wightman, A.S. (eds) *Rigorous Atomic and Molecular Physics*. NATO Advanced Study Institutes Series, vol 74. Springer, Boston, MA. https://doi.org/10.1007/978-1-4613-3350-0_5.
- [180] Rami Barends, CM Quintana, AG Petukhov, Yu Chen, Dvir Kafri, Kostyantyn Kechedzhi, Roberto Collins, Ofer Naaman, Sergio Boixo, F Arute, Kunal Arya, D Buell, Brian Burkett, Z Chen, Ben Chiaro, Andrew Dunsworth, Brooks Foxen, Austin Fowler, C Gidney, Marissa Giustina, Rob Graff, Trent Huang, Evan Jeffrey, J Kelly, Paul Victor Klimov, Fedor Kostritsa,

- Dave Landhuis, Erik Lucero, Matt McEwen, Anthony Megrant, Xiao Mi, Josh Mutus, Matthew Neeley, Charles Neill, Eric Ostby, Pedram Roushan, Daniel Sank, KJ Satzinger, A Vainsencher, T White, J Yao, P Yeh, A Zalcman, H Neven, VN Smelyanskiy, John M Martinis, Diabatic gates for frequency-tunable superconducting qubits, *Phys. Rev. Lett.* **123** (21), 210501, (2019).
- [181] L. DiCarlo, M. D. Reed, L. Sun, B. R. Johnson, J. M. Chow, J. M. Gambetta, L. Frunzio, S. M. Girvin, M. H. Devoret, and R. J. Schoelkopf, Preparation and measurement of three-qubit entanglement in a superconducting circuit, *Nature* **467**, 574 (2010).
- [182] Peng Xu, Qingli Jing, Peng Zhao, and Yang Yu, Microwave-driven iswap-like gate for fixed-frequency superconducting transmon qutrits, *Phys. Rev. A* **108**, 032615 (2023).
- [183] Joseph C Bardin, Evan Jeffrey, Erik Lucero, Trent Huang, Sayan Das, Daniel Thomas Sank, Ofer Naaman, Anthony Edward Megrant, Rami Barends, Ted White, Marissa Giustina, Kevin J Satzinger, Kunal Arya, Pedram Roushan, Benjamin Chiaro, Julian Kelly, Zijun Chen, Brian Burkett, Yu Chen, Andrew Dunsworth, Austin Fowler, Brooks Foxen, Craig Gidney, Rob Graff, Paul Klimov, Josh Mutus, Matthew J McEwen, Matthew Neeley, Charles J Neill, Chris Quintana, Amit Vainsencher, Hartmut Neven, John Martinis, Design and characterization of a 28-nm bulk-CMOS cryogenic quantum controller dissipating less than 2 mW at 3 K, *IEEE Journal of Solid-State Circuits* **54** (11), 3043-3060, (2019).
- [184] J. Koch *et al.*, Charge-insensitive qubit design derived from the Cooper pair box, *Phys. Rev. A* **76**, 042319 (2007).
- [185] J. Chow, J. Gambetta, E. Magesan *et al.* Implementing a strand of a scalable fault-tolerant quantum computing fabric." *Nat Commun.* **5**, 4015 (2014).
- [186] Benjamin Villalonga, Sergio Boixo, Bron Nelson, Christopher Henze, Eleanor Rieffel, Rupak Biswas, Salvatore Mandrà, A flexible high-performance simulator for verifying and benchmarking quantum circuits implemented on real hardware, *npj Quantum Inf* **5** (1), 86, (2019).
- [187] Bremner, M. J., Montanaro, A. and Shepherd, D. J. Average-case complexity versus approximate simulation of commuting quantum computations. *Phys. Rev. Lett.* **117**, 080501 (2016).
- [188] Bremner, M. J., Montanaro, A. and Shepherd, D. J. Achieving quantum supremacy with sparse and noisy commuting quantum computations. *Quantum* **1**, **8** (2017).
- [189] Adam Bouland, Bill Fefferman, Chinmay Nirkhe, and Umesh Vazirani. Quantum supremacy and the complexity of random circuit sampling. arXiv preprint arXiv:1803.04402, (2018).
- [190] Ramis Movassagh. Efficient unitary paths and quantum computational supremacy: A proof of average-case hardness of random circuit sampling. arXiv preprint arXiv:1810.04681, (2018).
- [191] Bouland, A., Fefferman, B., Nirkhe, C. *et al.* On the complexity and verification of quantum random circuit sampling. *Nature Phys* **15**, 159-163 (2019).
- [192] Movassagh, R. Cayley path and quantum computational supremacy: A proof of average-case #P-hardness of random circuit sampling with quantified robustness. arXiv preprint arXiv:1909.06210v1 [quant-ph] (2019).
- [193] R. Movassagh, Quantum supremacy and random circuits, arXiv:1909.06210 (2019).
- [194] A. M. Dalzell *et al.*, Random quantum circuits anticoncentrate in log depth, *PRX Quantum* **3**, 010333 (2022).
- [195] Matthew P.A. Fisher, Vedika Khemani, Adam Nahum, Sagar Vijay, Random Quantum Circuits, *Annual Review of Condensed Matter Physics* **14**:1, 335-379 (2023).
- [196] Meng Zhang, Chao Wang, Yongjian Han, Noisy Random Quantum Circuit Sampling and its Classical Simulation, *Advanced Quantum Technologies* **6**, 2300030 (2023).
- [197] HPC Environment Overview, NASA, Article ID: **25**, (Last updated: 14 Jun, 2024) available at https://www.nas.nasa.gov/hecc/support/kb/hpc-environment-overview_25.html, accessed September 19, (2024).
- [198] M. Long, Y. Cao, J. Wang, and M. I. Jordan, Learning Transferable Features with Deep Adaptation Networks, *arXiv preprint* arXiv:1502.02791 (2015).
- [199] M. Andrychowicz, M. Denil, S. Gomez, M. W. Hoffman, D. Pfau, T. Schaul, B. Shillingford, and N. De Freitas, Learning to learn by gradient descent by gradient descent, *arXiv preprint* arXiv:1606.04474 (2016).
- [200] Y. Chen, M. W. Hoffman, S. G. Colmenarejo, M. Denil, T. P. Lillicrap, M. Botvinick, and N. de Freitas, Learning to Learn without Gradient Descent by Gradient Descent, *arXiv preprint* arXiv:1611.03824 (2016).
- [201] B. Zoph and Q. V. Le, Neural Architecture Search with Reinforcement Learning, *arXiv preprint* arXiv:1611.01578 (2016).
- [202] C. Finn, P. Abbeel, and S. Levine, Model-Agnostic Meta-Learning for Fast Adaptation of Deep Networks, *arXiv preprint* arXiv:1703.03400 (2017).
- [203] Guillaume Verdon, Michael Broughton, Jarrod R McClean, Kevin J Sung, Ryan Babbush, Zhang Jiang, Hartmut Neven, Masoud Mohseni, Learning to learn with quantum neural networks via classical neural networks, *arXiv preprint* arXiv:1907.05415, (2019).
- [204] Edward Farhi, Jeffrey Goldstone, and Sam Gutmann, A quantum approximate optimization algorithm, arXiv:1411.4028, (2014).
- [205] Chen, C. *et al.* Fidelity-based probabilistic Q-learning for control of quantum systems. *IEEE Trans. Neural Netw. Learn. Syst.* **25**, 920 (2014).
- [206] Schulman, J., Moritz, P., Levine, S., Jordan, M. and Abbeel, P. High-dimensional continuous control using generalized advantage estimation. arXiv:1506.02438 (2015).
- [207] Mnih, V. *et al.* Asynchronous methods for deep reinforcement learning. *Int. Conf. Mach. Learn.* (Eds. Balcan, M. F. and Weinberger, K. Q.) **48**, 1928–1937 (2016).
- [208] Silver, D. *et al.* Mastering the game of Go with deep neural networks and tree search. *Nature* **529**, 484 (2016).
- [209] Bukov, M. *et al.* Reinforcement learning in different phases of quantum control. *Phys. Rev. X* **8**, 031086 (2018).
- [210] Murphy Yuezhen Niu, Sergio Boixo, Vadim N Smelyanskiy, Hartmut Neven, Universal quantum control through deep reinforcement learning, *npj Quantum Inf* **5** (1), 33, (2019).

- [211] Khaneja, N. *et al.* Optimal control of coupled spin dynamics: design of NMR pulse sequences by gradient ascent algorithms. *J. Magn. Reson.* **172**, 296 (2005).
- [212] Spörl, A. *et al.* Optimal control of coupled Josephson qubits. *Phys. Rev. A* **75**, 012302 (2007).
- [213] Chakrabarti, R. and Rabitz, H. Robust control of quantum gates via sequential convex programming. *Int. Rev. Phys. Chem.* **26**, 671 (2007).
- [214] Barends, R. *et al.* Superconducting quantum circuits at the surface code threshold for fault tolerance. *Nature* **508**, 500 (2014).
- [215] Gambetta, J. M. *et al.* Analytic control methods for high-fidelity unitary operations in a weakly nonlinear oscillator. *Phys. Rev. A* **83**, 012308 (2011).
- [216] Martinis, J. M. and Geller, M. R. Fast adiabatic qubit gates using only σ_z . *Control. Phys. Rev. A* **90**, 022307 (2014).
- [217] Zahedinejad, E., Ghosh, J. and Sanders, B. C. High-fidelity single-shot Toffoli gate via quantum control. *Phys. Rev. Lett.* **114**, 200502 (2015).
- [218] Zahedinejad, E., Ghosh, J. and Sanders, B. C. Designing high-fidelity single-shot three-qubit gates: a machine-learning approach. *Phys. Rev. App.* **6**, 054005 (2016).
- [219] Dauphin, Y. N. *et al.* Identifying and attacking the saddle point problem in high-dimensional non-convex optimization. *Adv. Neural Inf. Process. Syst.* **27**, 2933–2941 (2014).
- [220] James King, Masoud Mohseni, William Bernoudy, Alexandre Fréchet, Hossein Sadeghi, Sergei V Isakov, Hartmut Neven, Mohammad H Amin, Quantum-assisted genetic algorithm, arXiv preprint arXiv:1907.00707, (2019).
- [221] Ryan Babbush, Dominic W Berry, Hartmut Neven, Quantum simulation of the Sachdev-Ye-Kitaev model by asymmetric qubitization, *Phys. Rev. A* **99** (4), 040301, (2019).
- [222] Dominic W Berry, Craig Gidney, Mario Motta, Jarrod R McClean, Ryan Babbush, Qubitization of arbitrary basis quantum chemistry leveraging sparsity and low rank factorization, *Quantum* **3**, 208, (2019).
- [223] Craig Gidney, Austin G Fowler, Efficient magic state factories with a catalyzed transformation, *Quantum* **3**, 135, (2019).
- [224] Zhang Jiang, Jarrod McClean, Ryan Babbush, Hartmut Neven, Majorana loop stabilizer codes for error mitigation in fermionic quantum simulations, *Phys. Rev. Applied* **12** (6), 064041, (2019).
- [225] Craig Gidney, Austin G Fowler, Flexible layout of surface code computations using AutoCCZ states, arXiv preprint arXiv:1905.08916, (2019).
- [226] Craig Gidney, Asymptotically efficient quantum Karatsuba multiplication, arXiv preprint arXiv:1904.07356, (2019).
- [227] Craig Gidney, Windowed quantum arithmetic, arXiv preprint arXiv:1905.07682, (2019).
- [228] Frank Arute, Kunal Arya, Ryan Babbush, Dave Bacon, Joseph C. Bardin, Rami Barends, Sergio Boixo, Michael Broughton, Bob B. Buckley, David A. Buell, Brian Burkett, Nicholas Bushnell, Yu Chen, Zijun Chen, Benjamin Chiaro, Roberto Collins, William Courtney, Sean Demura, Andrew Dunsworth, Daniel Eppens, Edward Farhi, Austin Fowler, Brooks Foxen, Craig Gidney, Marissa Giustina, Rob Graff, Steve Habegger, Matthew P. Harrigan, Alan Ho, Sabrina Hong, Trent Huang, William J. Huggins, Lev Ioffe, Sergei V. Isakov, Evan Jeffrey, Zhang Jiang, Cody Jones, Dvir Kafri, Kostyantyn Kechedzhi, Julian Kelly, Seon Kim, Paul V. Klimov, Alexander Korotkov, Fedor Kostritsa, David Landhuis, Pavel Laptev, Mike Lindmark, Erik Lucero, Orion Martin, John M. Martinis, Jarrod R. McClean, Matt McEwen, Anthony Megrant, Xiao Mi, Masoud Mohseni, Wojciech Mruczkiewicz, Josh Mutus, Ofer Naaman, Matthew Neeley, Charles Neill, Hartmut Neven, Murphy Yuezhen Niu, Thomas E. O’Brien, Eric Ostby, Andre Petukhov, Harald Putterman, Chris Quintana, Pedram Roushan, Nicholas C. Rubin, Daniel Sank, Kevin J. Satzinger, Vadim Smelyanskiy, Doug Strain, Kevin J. Sung, Marco Szalay, Tyler Y. Takeshita, Amit Vainsencher, Theodore White, Nathan Wiebe, Z. Jamie Yao, Ping Yeh, Adam Zalcman, Hartree-Fock on a superconducting qubit quantum computer, arXiv preprint arXiv:2004.04174 (2020).
- [229] David A. Mazziotti, Pure-n-representability conditions of two-fermion reduced density matrices, *Phys. Rev. A* **94**, 032516 (2016).
- [230] Nicholas C. Rubin, Ryan Babbush, and Jarrod McClean, Application of fermionic marginal constraints to hybrid quantum algorithms, *New J. Phys.* **20**, 053020 (2018).
- [231] Alexander A Klyachko, Quantum marginal problem and n-representability, in *Journal of Physics: Conference Series*, **36**, 72 (IOP Publishing, 2006).
- [232] David J Thouless, Stability conditions and nuclear rotations in the Hartree-Fock theory, *Nuclear Physics* **21**, 225-232 (1960).
- [233] J. F. Donoghue, B. R. Holstein, and R. Robinett. Quantum electrodynamics at finite temperature. *Annals of Physics*, 164(2):233-276, (1985).
- [234] N. Haldolaarachchige, A. B. Karki, W. A. Phelan, Y. M. Xiong, R. Jin, J. Y. Chan, S. Stadler, and D. P. Young. Effect of chemical doping on the thermoelectric properties of FeGa3. *Journal of Applied Physics*, **109**(10), (2011).
- [235] B. J. Brown, D. Loss, J. K. Pachos, C. N. Self, and J. R. Wootton. Quantum memories at finite temperature. *Rev. Mod. Phys.*, 88:045005, (2016).
- [236] S.-N. Sun, M. Motta, R. N. Tazhigulov, A. T. Tan, G. K.-L. Chan, and A. J. Minnich. Quantum Computation of Finite-Temperature Static and Dynamical Properties of Spin Systems Using Quantum Imaginary Time Evolution. *PRX Quantum*, **2**(1), (2021).
- [237] C. Powers, L. Bassman Oftelie, D. Camps, and W. A. De Jong. Exploring finite temperature properties of materials with quantum computers. *Scientific Reports*, **13**(1):1986, (2023).
- [238] Jarrod R McClean, Nicholas C Rubin, Kevin J Sung, Ian D Kivlichan, Xavier Bonet-Monroig, Yudong Cao, Chengyu Dai, E Schuyler Fried, Craig Gidney, Brendan Gimby, Pranav Gokhale, Thomas Häner, Tarini Hardikar, Vojtěch Havlíček, Oscar Higgott, Cupjin Huang, Josh Izaac, Zhang Jiang, Xinle Liu, Sam McArdle, Matthew Neeley, Thomas O’Brien, Bryan O’gorman, Isil Ozfidan, Maxwell D Radin, Jhonathan Romero, Nicolas PD Sawaya, Bruno Senjean, Kanav Setia, Sukin Sim, Damian S Steiger, Mark Steudtner, Qiming Sun, Wei Sun, Daochen Wang, Fang Zhang, Ryan Babbush, OpenFermion: the electronic structure package for quantum computers, *Quantum Sci. Tech-*

- vol.* **5** (3), 034014, (2020).
- [239] Michael Broughton, Guillaume Verdon, Trevor McCourt, Antonio J. Martinez, Jae Hyeon Yoo, Sergei V. Isakov, Philip Massey, Ramin Halavati, Murphy Yuezhen Niu, Alexander Zlokapa, Evan Peters, Owen Lockwood, Andrea Skolik, Sofiene Jerbi, Vedran Dunjko, Martin Leib, Michael Streif, David Von Dollen, Hongxiang Chen, Shuxiang Cao, Roeland Wiersema, Hsin-Yuan Huang, Jarrod R. McClean, Ryan Babbush, Sergio Boixo, Dave Bacon, Alan K. Ho, Hartmut Neven, Masoud Mohseni, TensorFlow Quantum: A Software Framework for Quantum Machine Learning, arXiv preprint arXiv:2003.02989 (2020).
- [240] J. Biamonte, P. Wittek, N. Pancotti, P. Rebentrost, N. Wiebe, and S. Lloyd, Quantum machine learning, *Nature* **549**, 195 (2017).
- [241] Jacques Carolan, Masoud Mohseni, Jonathan P Olson, Mihika Prabhu, Changchen Chen, Darius Bunandar, Murphy Yuezhen Niu, Nicholas C Harris, Franco NC Wong, Michael Hochberg, Seth Lloyd, Dirk Englund, Variational quantum unsampling on a quantum photonic processor, *Nature Physics* **16** (3), 322-327, (2020).
- [242] Vladimir B. Braginsky, Farid Ya Khalili, Kip S. Thorne, Quantum measurement, *Cambridge University Press*, (2009).
- [243] Mohseni, M., Reza khani, A. T. and Lidar, D. A. Quantum-process tomography: resource analysis of different strategies. *Phys. Rev. A* **77**, 032322 (2008).
- [244] C. L. Degen, F. Reinhard, and P. Cappellaro, Quantum sensing, *Rev. Mod. Phys.* **89**, 035002 (2017).
- [245] Alessandra Gatti, Enrico Brambilla, Luigi Lugiato, Chapter 5 Quantum imaging, Editor(s): E. Wolf, *Progress in Optics* **51**, 251-348 (2008).
- [246] Khatri, S. *et al.* Quantum-assisted quantum compiling. *Quantum* **3**, 140 (2019).
- [247] Mitarai, K., Negoro, M., Kitagawa, M. and Fujii, K. Quantum circuit learning. *Phys. Rev. A* **98**, 032309 (2018).
- [248] Frank Arute, Kunal Arya, Ryan Babbush, Dave Bacon, Joseph C Bardin, Rami Barends, Andreas Bengtsson, Sergio Boixo, Michael Broughton, Bob B Buckley, David A Buell, Brian Burkett, Nicholas Bushnell, Yu Chen, Zijun Chen, Yu-An Chen, Ben Chiaro, Roberto Collins, Stephen J Cotton, William Courtney, Sean Demura, Alan Derk, Andrew Dunsworth, Daniel Eppens, Thomas Eckl, Catherine Erickson, Edward Farhi, Austin Fowler, Brooks Foxen, Craig Gidney, Marissa Giustina, Rob Graff, Jonathan A Gross, Steve Habegger, Matthew P Harrigan, Alan Ho, Sabrina Hong, Trent Huang, William Huggins, Lev B Ioffe, Sergei V Isakov, Evan Jeffrey, Zhang Jiang, Cody Jones, Dvir Kafri, Kostyantyn Kechedzhi, Julian Kelly, Seon Kim, Paul V Klimov, Alexander N Korotkov, Fedor Kostritsa, David Landhuis, Pavel Laptev, Mike Lindmark, Erik Lucero, Michael Marthaler, Orion Martin, John M Martinis, Anika Maruszczyk, Sam McArdle, Jarrod R McClean, Trevor McCourt, Matt McEwen, Anthony Megrant, Carlos Mejuto-Zaera, Xiao Mi, Masoud Mohseni, Wojciech Mroczkiewicz, Josh Mutus, Ofer Naaman, Matthew Neeley, Charles Neill, Hartmut Neven, Michael Newman, Murphy Yuezhen Niu, Thomas E O'Brien, Eric Ostby, Bálint Pató, Andre Petukhov, Harald Putterman, Chris Quintana, Jan-Michael Reiner, Pedram Roushan, Nicholas C Rubin, Daniel Sank, Kevin J Satzinger, Vadim Smelyanskiy, Doug Strain, Kevin J Sung, Peter Schmitteckert, Marco Szalay, Norm M Tubman, Amit Vainsencher, Theodore White, Nicolas Vogt, Z Jamie Yao, Ping Yeh, Adam Zalcman, Sebastian Zanker, Observation of separated dynamics of charge and spin in the fermi-hubbard model, arXiv preprint arXiv:2010.07965, (2020).
- [249] P. A. Lee, N. Nagaosa, and X.-G. Wen, Doping a Mott insulator: Physics of high-temperature superconductivity, *Rev. Mod. Phys.* **78**, 17 (2006).
- [250] M. Imada, A. Fujimori, and Y. Tokura, Metal-insulator transitions, *Rev. Mod. Phys.* **70**, 1039 (1998).
- [251] M. F. Parsons, A. Mazurenko, C. S. Chiu, G. Ji, D. Greif, and M. Greiner, Site-resolved measurement of the spin-correlation function in the Fermi-Hubbard model, *Science* **353**, 1253 (2016).
- [252] T. Hensgens, T. Fujita, L. Janssen, X. Li, C. J. Van Diepen, C. Reichl, W. Wegscheider, S. Das Sarma, and L. M. K. Vandersypen, Quantum simulation of a Fermi-Hubbard model using a semiconductor quantum dot array, *Nature* **548**, 70 (2017).
- [253] Stasja Stanisic, Jan Lukas Bosse, Filippo Maria Gambetta, Raul A. Santos, Wojciech Mroczkiewicz, Thomas E. O'Brien, Eric Ostby, and Ashley Montanaro, Observing ground-state properties of the Fermi-Hubbard model using a scalable algorithm on a quantum computer, *Nat. Comm.* **13** (1), 5743 (2022).
- [254] Cade, C., Mineh, L., Montanaro, A. and Stanisic, S. Strategies for solving the Fermi-Hubbard model on near-term quantum computers. *Phys. Rev. B* **102**, 235122 (2020).
- [255] Montanaro, A. and Stanisic, S. Error mitigation by training with fermionic linear optics. arXiv:2102.02120 (2021).
- [256] Terhal, B. M. and DiVincenzo, D. P. Classical simulation of noninteracting-fermion quantum circuits. *Phys. Rev. A* **65**, 032325 (2002).
- [257] Benjamin Villalonga, Dmitry Lyakh, Sergio Boixo, Hartmut Neven, Travis S Humble, Rupak Biswas, Eleanor G Rieffel, Alan Ho, Salvatore Mandrà, Establishing the quantum supremacy frontier with a 281 pflop/s simulation, *Quantum Sci. Technol.* **5** (3), 034003, (2020).
- [258] Brooks Foxen, Charles Neill, Andrew Dunsworth, Pedram Roushan, Ben Chiaro, Anthony Megrant, Julian Kelly, Zijun Chen, Kevin Satzinger, Rami Barends, F Arute, Kunal Arya, Ryan Babbush, Dave Bacon, JC Bardin, Sergio Boixo, D Buell, Brian Burkett, Yu Chen, Roberto Collins, Edward Farhi, Austin Fowler, C Gidney, Marissa Giustina, Rob Graff, M Harrigan, Trent Huang, SV Isakov, Evan Jeffrey, Zhang Jiang, Dvir Kafri, Kostyantyn Kechedzhi, Paul Klimov, Alexander Korotkov, Fedor Kostritsa, Dave Landhuis, Erik Lucero, Jarrod McClean, Matthew McEwen, Xiao Mi, Masoud Mohseni, JY Mutus, Ofer Naaman, Matthew Neeley, M Niu, A Petukhov, C Quintana, N Rubin, D Sank, V Smelyanskiy, A Vainsencher, TC White, Z Yao, P Yeh, A Zalcman, H Neven, John M Martinis, Google AI Quantum, Demonstrating a continuous set of two-qubit gates for near-term quantum algorithms, *Phys. Rev. Lett.* **125** (12), 120504, (2020).
- [259] Kevin J Sung, Jiahao Yao, Matthew P Harrigan, Nicholas C Rubin, Zhang Jiang, Lin Lin, Ryan Babbush, Jarrod R McClean, Using models to improve op-

- timizers for variational quantum algorithms, *Quantum Sci. Technol.* **5** (4), 044008, (2020).
- [260] Xavier Bonet-Monroig, Ryan Babbush, Thomas E O'Brien, Nearly optimal measurement scheduling for partial tomography of quantum states, *Phys. Rev. X* **10** (3), 031064, (2020).
- [261] Jarrod R McClean, Zhang Jiang, Nicholas C Rubin, Ryan Babbush, Hartmut Neven, Decoding quantum errors with subspace expansions, *Nat. Comm.* **11** (1), 636, (2020).
- [262] Ian D Kivlichan, Craig Gidney, Dominic W Berry, Nathan Wiebe, Jarrod McClean, Wei Sun, Zhang Jiang, Nicholas Rubin, Austin Fowler, Alán Aspuru-Guzik, Hartmut Neven, Ryan Babbush, Improved fault-tolerant quantum simulation of condensed-phase correlated electrons via trotterization, *Quantum* **4**, 296, (2020).
- [263] Tyler Takeshita, Nicholas C Rubin, Zhang Jiang, Eunseok Lee, Ryan Babbush, Jarrod R McClean, Increasing the representation accuracy of quantum simulations of chemistry without extra quantum resources, *Phys. Rev. X* **10** (1), 011004, (2020).
- [264] Paul V Klimov, Julian Kelly, John M Martinis, Hartmut Neven, The snake optimizer for learning quantum processor control parameters, arXiv preprint arXiv:2006.04594, (2020).
- [265] Edward Farhi, David Gamarnik, Sam Gutmann, The quantum approximate optimization algorithm needs to see the whole graph: A typical case, arXiv preprint arXiv:2004.09002, (2020).
- [266] Yuval R Sanders, Dominic W Berry, Pedro CS Costa, Louis W Tessler, Nathan Wiebe, Craig Gidney, Hartmut Neven, Ryan Babbush, Compilation of fault-tolerant quantum heuristics for combinatorial optimization, *PRX Quantum* **1** (2), 020312, (2020).
- [267] Zhang Jiang, Amir Kalev, Wojciech Mruczkiewicz, Hartmut Neven, Optimal fermion-to-qubit mapping via ternary trees with applications to reduced quantum states learning, *Quantum* **4**, 276, (2020).
- [268] Vadim N Smelyanskiy, Kostyantyn Kechedzhi, Sergio Boixo, Sergei V Isakov, Hartmut Neven, Boris Altshuler, Nonergodic delocalized states for efficient population transfer within a narrow band of the energy landscape, *Phys. Rev. X* **10** (1), 011017, (2020).
- [269] Jarrod R McClean, Fabian M Faulstich, Qinyi Zhu, Bryan O'Gorman, Yiheng Qiu, Steven R White, Ryan Babbush, Lin Lin, Discontinuous Galerkin discretization for quantum simulation of chemistry, *New J. Phys.* **22** (9), 093015, (2020).
- [270] HY Huang, M Broughton, M Mohseni, R Babbush, S Boixo, H Neven, JR McClean, Power of data in quantum machine learning, *Nat. Comm.* **12**, 2631 (2021).
- [271] C Gidney, M Ekerå, How to factor 2048 bit RSA integers in 8 hours using 20 million noisy qubits, *Quantum* **5**, 433 (2021).
- [272] T. Toffoli, Reversible computing, In: de Bakker, J., van Leeuwen, J. (eds) *Automata, Languages and Programming. ICALP 1980*. Lecture Notes in Computer Science, vol 85. Springer, Berlin, Heidelberg. (1980). https://doi.org/10.1007/3-540-10003-2_104.
- [273] M. AbuGhanem, A Toffoli Gate Decomposition via Echoed Cross-Resonance Gates, (2024).
- [274] R. L. Rivest, A. Shamir, and L. Adleman. A Method for Obtaining Digital Signatures and Public-Key Cryptosystems. *Communications of the ACM*, **21**(2):120-126, (1978).
- [275] P. W. Shor, Algorithms for quantum computation: discrete logarithms and factoring, in: Proceedings 35th Annual Symposium on Foundations of Computer Science, IEEE, pp 124-134 (1994).
- [276] MP Harrigan, KJ Sung, M Neeley, KJ Satzinger, F Arute, K Arya, J Atalaya, *et al.* Quantum approximate optimization of non-planar graph problems on a planar superconducting processor, *Nature Physics* **17** (3), 332-336 (2021).
- [277] Edward Farhi, Jeffrey Goldstone, Sam Gutmann, and Leo Zhou, The quantum approximate optimization algorithm and the Sherrington-Kirkpatrick model at infinite size, arXiv:1910.08187 (2019).
- [278] KJ Satzinger, YJ Liu, A Smith, C Knapp, M Newman, C Jones, Z Chen, *et al.* Realizing topologically ordered states on a quantum processor, *Science* **374** (6572), 1237-1241 (2021).
- [279] Michael A. Levin and Xiao-Gang Wen, String-net condensation: A physical mechanism for topological phases, *Phys. Rev. B* **71**, 045110 (2005).
- [280] A. Kitaev and J. Preskill, Topological Entanglement Entropy, *Phys. Rev. Lett.* **96**, 110404 (2006).
- [281] M. Levin and X.-G. Wen, Detecting Topological Order in a Ground State Wave Function, *Phys. Rev. Lett.* **96**, 110405 (2006).
- [282] S. T. Flammia, A. Hamma, T. L. Hughes, and X.-G. Wen, Topological Entanglement Rényi Entropy and Reduced Density Matrix Structure, *Phys. Rev. Lett.* **103**, 261601 (2009).
- [283] P. Bonderson, C. Knapp, and K. Patel, Anyonic entanglement and topological entanglement entropy, *Annals of Physics* **385**, 399-468 (2017).
- [284] S. J. van Enk and C. W. J. Beenakker, Measuring $\text{Tr } \rho$ on Single Copies of ρ Using Random Measurements, *Phys. Rev. Lett.* **108**, 110503 (2012).
- [285] A. Elben, B. Vermersch, M. Dalmonte, J. I. Cirac, and P. Zoller, Rényi Entropies from Random Quenches in Atomic Hubbard and Spin Models, *Phys. Rev. Lett.* **120**, 050406 (2018).
- [286] T. Brydges, A. Elben, P. Jurcevic, B. Vermersch, C. Maier, B. P. Lanyon, P. Zoller, R. Blatt, and C. F. Roos, Probing Rényi entanglement entropy via randomized measurements, *Science* **364**, 260 (2019)
- [287] Zijun Chen *et al.* Exponential suppression of bit or phase errors with cyclic error correction, *Nature* **595** (7867), 383-387 (2021).
- [288] Terhal, B. M. Quantum error correction for quantum memories. *Rev. Mod. Phys.* **87**, 307 (2015).
- [289] Horsman, C., Fowler, A. G., Devitt, S. and Van Meter, R. Surface code quantum computing by lattice surgery. *New J. Phys.* **14**, 123011 (2012).
- [290] Andersen, C. K. *et al.* Repeated quantum error detection in a surface code. *Nat. Phys.* **16**, 875-880 (2020).
- [291] E Altman, KR Brown, G Carleo, LD Carr, E Demler, C Chin, B DeMarco, *et al.* Quantum simulators: Architectures and opportunities, *PRX Quantum* **2** (1), 017003 (2021).
- [292] Andrea Skolik, Jarrod R McClean, Masoud Mohseni, Patrick van der Smagt, Martin Leib, Layerwise learning for quantum neural networks, *Quantum Mach. Intell.* **3**, 1-11, (2021).

- [293] Xiao Mi *et al.* Information scrambling in quantum circuits, *Science* **374** (6574), 1479-1483, (2021).
- [294] William J Huggins, Jarrod R McClean, Nicholas C Rubin, Zhang Jiang, Nathan Wiebe, K Birgitta Whaley, Ryan Babbush, Efficient and noise resilient measurements for quantum chemistry on near-term quantum computers, *npj Quantum Inf* **7** (1), 23, (2021).
- [295] William J Huggins, Sam McArdle, Thomas E O'Brien, Joonho Lee, Nicholas C Rubin, Sergio Boixo, K Birgitta Whaley, Ryan Babbush, Jarrod R McClean, Virtual distillation for quantum error mitigation, *Phys. Rev. X* **11** (4), 041036, (2021).
- [296] Joonho Lee, Dominic W Berry, Craig Gidney, William J Huggins, Jarrod R McClean, Nathan Wiebe, Ryan Babbush, Even more efficient quantum computations of chemistry through tensor hypercontraction, *PRX Quantum* **2** (3), 030305, (2021).
- [297] Andrew D King *et al.* Scaling advantage over path-integral Monte Carlo in quantum simulation of geometrically frustrated magnets, *Nat. Comm.* **12** (1), 1113, (2021).
- [298] Ryan Babbush, Jarrod R McClean, Michael Newman, Craig Gidney, Sergio Boixo, Hartmut Neven, Focus beyond quadratic speedups for error-corrected quantum advantage, *PRX Quantum* **2** (1), 010103, (2021).
- [299] Craig Gidney, Stim: a fast stabilizer circuit simulator, *Quantum* **5**, 497, (2021).
- [300] Mario Motta, Erika Ye, Jarrod R McClean, Zhendong Li, Austin J Minnich, Ryan Babbush, Garnet Kin-Lic Chan, Low rank representations for quantum simulation of electronic structure, *npj Quantum Inf* **7** (1), 83, (2021).
- [301] Alicia B Magann, Christian Arenz, Matthew D Grace, Tak-San Ho, Robert L Kosut, Jarrod R McClean, Herschel A Rabitz, Mohan Sarovar, From pulses to circuits and back again: A quantum optimal control perspective on variational quantum algorithms, *PRX Quantum* **2** (1), 010101, (2021).
- [302] Andrew Zhao, Nicholas C Rubin, Akimasa Miyake, Fermionic partial tomography via classical shadows, *Phys. Rev. Lett.* **127** (11), 110504, (2021).
- [303] Matt McEwen *et al.* Removing leakage-induced correlated errors in superconducting quantum error correction, *Nat. Comm.* **12** (1), 1761, (2021).
- [304] C Neill, *et al.* Accurately computing the electronic properties of a quantum ring, *Nature* **594** (7864), 508-512, (2021).
- [305] Yuan Su, Dominic W Berry, Nathan Wiebe, Nicholas Rubin, Ryan Babbush, Fault-tolerant quantum simulations of chemistry in first quantization, *PRX Quantum* **2** (4), 040332, (2021).
- [306] Thomas E O'Brien, Stefano Polla, Nicholas C Rubin, William J Huggins, Sam McArdle, Sergio Boixo, Jarrod R McClean, Ryan Babbush, Error mitigation via verified phase estimation, *PRX Quantum* **2** (2), 020317, (2021).
- [307] Hongxiang Chen, Leonard Wossnig, Simone Severini, Hartmut Neven, Masoud Mohseni, Universal discriminative quantum neural networks, *Quantum Mach. Intell.* **3**, 1-11, (2021).
- [308] Evan Peters, João Caldeira, Alan Ho, Stefan Leichenauer, Masoud Mohseni, Hartmut Neven, Panagiotis Spentzouris, Doug Strain, Gabriel N Perdue, Machine learning of high dimensional data on a noisy quantum processor, *npj Quantum Inf* **7** (1), 161, (2021).
- [309] Joao Basso, Edward Farhi, Kunal Marwaha, Benjamin Villalonga, Leo Zhou, The quantum approximate optimization algorithm at high depth for MaxCut on large-girth regular graphs and the Sherrington-Kirkpatrick model, arXiv preprint arXiv:2110.14206, (2021).
- [310] Craig Gidney, Michael Newman, Austin Fowler, Michael Broughton, A fault-tolerant honeycomb memory, *Quantum* **5**, 605, (2021).
- [311] Jarrod R McClean, Matthew P Harrigan, Masoud Mohseni, Nicholas C Rubin, Zhang Jiang, Sergio Boixo, Vadim N Smelyanskiy, Ryan Babbush, Hartmut Neven, Low-depth mechanisms for quantum optimization, *PRX Quantum* **2** (3), 030312, (2021).
- [312] Benjamin Villalonga, Murphy Yuezhen Niu, Li Li, Hartmut Neven, John C Platt, Vadim N Smelyanskiy, Sergio Boixo, Efficient approximation of experimental Gaussian boson sampling, arXiv preprint arXiv:2109.11525, (2021).
- [313] Jordan Cotler, Hsin-Yuan Huang, Jarrod R McClean, Revisiting dequantization and quantum advantage in learning tasks, arXiv preprint arXiv:2112.00811, (2021).
- [314] Haozhi Wang, Suren Singh, CRH McRae, Joseph C Bardin, SX Lin, N Messaoudi, AR Castelli, YJ Rosen, ET Holland, DP Pappas, JY Mutus, Cryogenic single-port calibration for superconducting microwave resonator measurements, *Quantum Sci. Technol.* **6** (3), 035015, (2021).
- [315] Jarrod R McClean, Nicholas C Rubin, Joonho Lee, Matthew P Harrigan, Thomas E O'Brien, Ryan Babbush, William J Huggins, Hsin-Yuan Huang, What the foundations of quantum computer science teach us about chemistry, *The Journal of Chemical Physics* **155** (15), (2021).
- [316] Nicholas C Rubin, Klaas Gunst, Alec White, Leon Freitag, Kyle Throssell, Garnet Kin-Lic Chan, Ryan Babbush, Toru Shiozaki, The Fermionic Quantum Emulator, *Quantum* **5**, 568, (2021).
- [317] Joseph C Bardin, Cryogenic low-noise amplifiers: Noise performance and power dissipation, *IEEE Solid-State Circuits Magazine* **13** (2), 22-35, (2021).
- [318] Alexander Zlokapa, Hartmut Neven, Seth Lloyd, A quantum algorithm for training wide and deep classical neural networks, arXiv preprint arXiv:2107.09200, (2021).
- [319] Dominik Hangleiter, Ingo Roth, Jens Eisert, Pedram Roushan, Precise Hamiltonian identification of a superconducting quantum processor, arXiv preprint arXiv:2108.08319, (2021).
- [320] Poulami Das, Aditya Locharla, Cody Jones, Lilliput: A lightweight low-latency lookup-table based decoder for near-term quantum error correction, arXiv preprint arXiv:2108.06569, (2021).
- [321] Masoud Mohseni, Daniel Eppens, Johan Stumpfer, Raffaele Marino, Vasil Denchev, Alan K Ho, Sergei V Isakov, Sergio Boixo, Federico Ricci-Tersenghi, Hartmut Neven, Nonequilibrium Monte Carlo for unfreezing variables in hard combinatorial optimization, arXiv preprint arXiv:2111.13628, (2021).
- [322] Zhenjie Zou, Mohsen Hosseini, Randy Kwende, Sanjay Raman, Joseph C Bardin, A frequency and bandwidth reconfigurable 3-6 GHz cryogenic SiGe BiCMOS LNA with a power consumption of ≤ 2.9 mW, (2021). IEEE MTT-S International Microwave Symposium (IMS),

- 653-656, (2021).
- [323] Sayan Das, Joseph C Bardin, Characterization of shot noise suppression in nanometer MOSFETs, (2021). IEEE MTT-S International Microwave Symposium (IMS), 892-895, (2021).
- [324] Craig Gidney, N Cody Jones, A CCCZ gate performed with 6 T gates, arXiv preprint arXiv:2106.11513, (2021).
- [325] HY Huang, M Broughton, J Cotler, S Chen, J Li, M Mohseni, H Neven, *et al.* Quantum advantage in learning from experiments, *Science* **376** (6598), 1182-1186 (2022).
- [326] Wilczek, F. Quantum time crystals. *Phys. Rev. Lett.* **109**, 160401 (2012).
- [327] Bruno, P. Impossibility of spontaneously rotating time crystals: a no-go theorem. *Phys. Rev. Lett.* **111**, 070402 (2013).
- [328] Watanabe, H. and Oshikawa, M. Absence of quantum time crystals. *Phys. Rev. Lett.* **114**, 251603 (2015).
- [329] Else, D. V., Bauer, B. and Nayak, C. Floquet time crystals. *Phys. Rev. Lett.* **117**, 090402 (2016).
- [330] Khemani, V., Lazarides, A., Moessner, R. and Sondhi, S. Phase structure of driven quantum systems. *Phys. Rev. Lett.* **116**, 250401 (2016).
- [331] von Keyserlingk, C. W., Khemani, V. and Sondhi, S. L. Absolute stability and spatiotemporal long-range order in Floquet systems. *Phys. Rev. B* **94**, 085112 (2016).
- [332] Sacha, K. and Zakrzewski, J. Time crystals: a review. *Rep. Prog. Phys.* **81**, 016401 (2017).
- [333] Khemani, V., Moessner, R. and Sondhi, S. A brief history of time crystals. Preprint at <https://arxiv.org/abs/1910.10745> (2019).
- [334] Huse, D. A., Nandkishore, R., Oganesyan, V., Pal, A. and Sondhi, S. L. Localization-protected quantum order. *Phys. Rev. B* **88**, 014206 (2013).
- [335] Pekker, D., Refael, G., Altman, E., Demler, E. and Oganesyan, V. Hilbert-glass transition: new universality of temperature-tuned many-body dynamical quantum criticality. *Phys. Rev. X* **4**, 011052 (2014).
- [336] X Mi, M Ippoliti, C Quintana, A Greene, Z Chen, J Gross, F Arute, K Arya, *et al.* Time-crystalline eigenstate order on a quantum processor, *Nature* **601** (7894), 531-536 (2022).
- [337] E Farhi, J Goldstone, S Gutmann, L Zhou, The quantum approximate optimization algorithm and the Sherrington-Kirkpatrick model at infinite size, *Quantum* **6**, 759 (2022).
- [338] A. Montanari. Optimization of the Sherrington-Kirkpatrick Hamiltonian. In Proceedings of the 60th Annual Symposium on Foundations of Computer Science (FOCS '19). Pages 1417-1433. (2019).
- [339] William J Huggins, Bryan A O’Gorman, Nicholas C Rubin, David R Reichman, Ryan Babbush, Joonho Lee, Unbiasing fermionic quantum Monte Carlo with a quantum computer, *Nature* **603** (7901), 416-420, (2022).
- [340] Matt McEwen *et al.* Resolving catastrophic error bursts from cosmic rays in large arrays of superconducting qubits, *Nature Physics* **18** (1), 107-111, (2022).
- [341] Daniel Jafferis, Alexander Zlokapa, Joseph D Lykken, David K Kolchmeyer, Samantha I Davis, Nikolai Lauk, Hartmut Neven, Maria Spiropulu, Traversable wormhole dynamics on a quantum processor, *Nature* **612** (7938), 51-55, (2022).
- [342] Murphy Yuezhen Niu, Alexander Zlokapa, Michael Broughton, Sergio Boixo, Masoud Mohseni, Vadim Smelyanskiy, Hartmut Neven, Entangling quantum generative adversarial networks, *Phys. Rev. Lett.* **128** (22), 220505, (2022).
- [343] Ben Chiaro *et al.* Direct measurement of nonlocal interactions in the many-body localized phase, *Physical Review Research* **4** (1), 013148, (2022).
- [344] Pedro CS Costa, Dong An, Yuval R Sanders, Yuan Su, Ryan Babbush, Dominic W Berry, Optimal scaling quantum linear-systems solver via discrete adiabatic theorem, *PRX Quantum* **3** (4), 040303, (2022).
- [345] Yu Tong, Victor V Albert, Jarrod R McClean, John Preskill, Yuan Su, Provably accurate simulation of gauge theories and bosonic systems, *Quantum* **6**, 816, (2022).
- [346] Xiao Mi *et al.* Noise-resilient edge modes on a chain of superconducting qubits, *Science* **378** (6621), 785-790, (2022).
- [347] Joshua J Goings, Alec White, Joonho Lee, Christofer S Tautermann, Matthias Degroote, Craig Gidney, Toru Shiozaki, Ryan Babbush, Nicholas C Rubin, Reliably assessing the electronic structure of cytochrome p450 on today’s classical computers and tomorrow’s quantum computers, *Proceedings of the National Academy of Sciences* **119** (38), e2203533119, (2022).
- [348] Ruslan N Tazhigulov, Shi-Ning Sun, Reza Haghshenas, Huanchen Zhai, Adrian TK Tan, Nicholas C Rubin, Ryan Babbush, Austin J Minnich, Garnet Kin-Lic Chan, Simulating models of challenging correlated molecules and materials on the Sycamore quantum processor, *PRX Quantum* **3** (4), 040318, (2022).
- [349] Alexis Morvane *et al.* Formation of robust bound states of interacting microwave photons, *Nature* **612** (7939), 240-245, (2022).
- [350] Craig Gidney, Michael Newman, Matt McEwen, Benchmarking the planar honeycomb code, *Quantum* **6**, 813, (2022).
- [351] William J Huggins, Kianna Wan, Jarrod McClean, Thomas E O’Brien, Nathan Wiebe, Ryan Babbush, Nearly optimal quantum algorithm for estimating multiple expectation values, *Phys. Rev. Lett.* **129** (24), 240501, (2022).
- [352] Thomas E O’Brien *et al.* Purification-based quantum error mitigation of pair-correlated electron simulations, arXiv preprint arXiv:2210.10799, (2022).
- [353] Ofer Naaman, José Aumentado, Synthesis of parametrically coupled networks, *PRX Quantum* **3** (2), 020201, (2022).
- [354] Nicholas C Rubin, Joonho Lee, Ryan Babbush, Compressing many-body fermion operators under unitary constraints, *Journal of Chemical Theory and Computation* **18** (3), 1480-1488, (2022).
- [355] Thomas E O’Brien, Michael Streif, Nicholas C Rubin, Raffaele Santagati, Yuan Su, William J Huggins, Joshua J Goings, Nikolaj Moll, Elica Kyoseva, Matthias Degroote, Christofer S Tautermann, Joonho Lee, Dominic W Berry, Nathan Wiebe, Ryan Babbush, Efficient quantum computation of molecular forces and other energy gradients, *Physical Review Research* **4** (4), 043210, (2022).
- [356] Dominic W Berry, Yuan Su, Casper Gyurik, Robbie King, Joao Basso, Alexander Del Toro Barba, Abhishek Rajput, Nathan Wiebe, Vedran Dunjko, Ryan Babbush, Quantifying quantum advantage in topological data analysis, arXiv preprint arXiv:2209.13581, (2022).

- [357] Mostafa Khezri *et al.* Measurement-induced state transitions in a superconducting qubit: Within the rotating wave approximation, arXiv preprint arXiv:2212.05097, (2022).
- [358] Thomas E O'Brien, Lev B Ioffe, Yuan Su, David Fushman, Hartmut Neven, Ryan Babbush, Vadim Smelyanskiy, Quantum computation of molecular structure using data from challenging-to-classically-simulate nuclear magnetic resonance experiments, *PRX Quantum* **3** (3), 030345, (2022).
- [359] Joseph Bardin, Beyond-classical computing using superconducting quantum processors, (2022). IEEE International Solid-State Circuits Conference (ISSCC) 65, 422-424, (2022).
- [360] Trond I Andersen *et al.* Observation of non-Abelian exchange statistics on a superconducting processor, arXiv preprint arXiv:2210.10255, (2022).
- [361] Lingling Lao, Alexander Korotkov, Zhang Jiang, Wojciech Mruzekiewicz, Thomas E O'Brien, Dan E Browne, Software mitigation of coherent two-qubit gate errors, *Quantum Sci. Technol.* **7** (2), 025021, (2022).
- [362] Eric B Jones, Logan E Hillberry, Matthew T Jones, Mina Fasihi, Pedram Roushan, Zhang Jiang, Alan Ho, Charles Neill, Eric Ostby, Peter Graf, Eliot Kapit, Lincoln D Carr, Small-world complex network generation on a digital quantum processor, *Nat. Comm.* **13** (1), 4483, (2022).
- [363] Madelyn Cain, Edward Farhi, Sam Gutmann, Daniel Ranard, Eugene Tang, The QAOA gets stuck starting from a good classical string, arXiv preprint arXiv:2207.05089, (2022).
- [364] Kevin C Miao *et al.* Overcoming leakage in scalable quantum error correction, arXiv preprint arXiv:2211.04728, (2022).
- [365] Thomas Schuster, Murphy Niu, Jordan Cotler, Thomas O'Brien, Jarrod R McClean, Masoud Mohseni, Learning quantum systems via out-of-time-order correlators, arXiv preprint arXiv:2208.02254, (2022).
- [366] Jordan Cotler, Thomas Schuster, Masoud Mohseni, Information-theoretic hardness of out-of-time-order correlators, arXiv preprint arXiv:2208.02256, (2022).
- [367] Dominic W Berry, Yuan Su, Casper Gyurik, Robbie King, Joao Basso, Alexander Del Toro Barba, Abhishek Rajput, Nathan Wiebe, Vedran Dunjko, Ryan Babbush, Analyzing prospects for quantum advantage in topological data analysis, arXiv preprint arXiv:2209.13581, (2022).
- [368] Davide Castelvecchi, Google's quantum computer hits key milestone by reducing errors. *Nature* (22 February 2023) <https://doi.org/10.1038/d41586-023-00536-w>, accessed September 22, (2024).
- [369] Knill, E., Laflamme, R. and Zurek, W. H. Resilient quantum computation. *Science* **279**, 342-345 (1998).
- [370] Aharonov, D. and Ben-Or, M. Fault-tolerant quantum computation with constant error rate. *SIAM J. Comput.* **38**, 1207-1282 (2008).
- [371] Ryan-Anderson, C. *et al.* Realization of real-time fault-tolerant quantum error correction. *Phys. Rev. X* **11**, 041058 (2021).
- [372] Egan, L. *et al.* Fault-tolerant control of an error-corrected qubit. *Nature* **598**, 281-286 (2021).
- [373] Abobeih, M. *et al.* Fault-tolerant operation of a logical qubit in a diamond quantum processor. *Nature* **606**, 884-889 (2022).
- [374] Krinner, S. *et al.* Realizing repeated quantum error correction in a distance-three surface code. *Nature* **605**, 669-674 (2022).
- [375] Zhao, Y. *et al.* Realization of an error-correcting surface code with superconducting qubits. *Phys. Rev. Lett.* **129**, 030501 (2022).
- [376] Sundaresan, N. *et al.* Matching and maximum likelihood decoding of a multi-round subsystem quantum error correction experiment. <https://arxiv.org/abs/2203.07205> (2022).
- [377] Ofek, N. *et al.* Extending the lifetime of a quantum bit with error correction in superconducting circuits. *Nature* **536**, 441-445 (2016).
- [378] Flühmann, C. *et al.* Encoding a qubit in a trapped-ion mechanical oscillator. *Nature* **566**, 513-517 (2019).
- [379] Campagne-Ibarcq, P. *et al.* Quantum error correction of a qubit encoded in grid states of an oscillator. *Nature* **584**, 368-372 (2020).
- [380] Grimm, A. *et al.* Stabilization and operation of a Kerr-cat qubit. *Nature* **584**, 205-209 (2020).
- [381] Ballance, C., Harty, T., Linke, N., Sepiol, M. and Lucas, D. High-fidelity quantum logic gates using trapped-ion hyperfine qubits. *Phys. Rev. Lett.* **117**, 060504 (2016).
- [382] Huang, W. *et al.* Fidelity benchmarks for two-qubit gates in silicon. *Nature* **569**, 532-536 (2019).
- [383] Foxen, B. *et al.* Demonstrating a continuous set of two-qubit gates for near-term quantum algorithms. *Phys. Rev. Lett.* **125**, 120504 (2020).
- [384] Kim, Y., Eddins, A., Anand, S. *et al.* Evidence for the utility of quantum computing before fault tolerance." *Nature* **618**, 500-505 (2023). <https://doi.org/10.1038/s41586-023-06096-3>
- [385] Kevin C Miao *et al.*, Overcoming leakage in quantum error correction, *Nature Physics* **19** (12), 1780-1786, (2023).
- [386] Sank, D. *et al.* Measurement-induced state transitions in a superconducting qubit: beyond the rotating wave approximation. *Phys. Rev. Lett.* **117**, 190503 (2016).
- [387] Shillito, R. Dynamics of transmon ionization. *Phys. Rev. Appl.* **18**, 034031 (2022).
- [388] Klimov, P. V., Kelly, J., Martinis, J. M. and Neven, H. The snake optimizer for learning quantum processor control parameters Preprint at <http://arxiv.org/abs/2006.04594>, (2020).
- [389] F. Yan *et al.*, Tunable coupling scheme for implementing high-fidelity two-qubit gates, *Phys. Rev. Appl.* **10**, 054062 (2018).
- [390] Paul V Klimov, *et al.* Optimizing quantum gates towards the scale of logical qubits, arXiv preprint arXiv:2308.02321, (2023).
- [391] J. Mutus, T. White, R. Barends, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, E. Jeffrey, J. Kelly, *et al.*, Strong environmental coupling in a Josephson parametric amplifier, *Appl. Phys. Lett.* **104**, 263513 (2014).
- [392] Theodore White *et al.* Readout of a quantum processor with high dynamic range Josephson parametric amplifiers, *Applied Physics Letters* **122** (1), (2023).
- [393] Scannell, J., Blanckley, A., Boldon, H. *et al.* Diagnosing the decline in pharmaceutical R&D efficiency. *Nature Reviews Drug Discovery* **11**, 191-200 (2012).
- [394] Madura K.P. Jayatunga, Wen Xie, Ludwig Ruder, Ulrik Schulze and Christoph Meier, AI in small-molecule drug discovery: a coming wave?, *Nature Reviews Drug Discovery* **21**, 175-176 (2022).

- [395] Ruslan N. Tazhigulov *et al.* Simulating challenging correlated molecules and materials on the Sycamore quantum processor, arXiv:2203.15291 (2022).
- [396] Evaluating the evidence for exponential quantum advantage in ground-state quantum chemistry S Lee, J Lee, H Zhai, Y Tong, AM Dalzell, A Kumar, P Helms, J Gray, *et al. Nat. Comm.* **14** (1), 1952 (2023).
- [397] O'Brien, T. E., Tarasinski, B. and Terhal, B. M. Quantum phase estimation of multiple eigenvalues for small-scale (noisy) experiments. *N. J. Phys.* **21**, 023022 (2019).
- [398] Ville Bergholm, Josh Izaac, Maria Schuld, Christian Gogolin, Shah Nawaz Ahmed, Vishnu Ajith, M. Sohaib Alam, Guillermo Alonso-Linaje, B. Akash Narayanan, Ali Asadi, Juan Miguel Arrazola, Utkarsh Azad, Sam Banning, Carsten Blank, Thomas R Bromley, Benjamin A. Cordier, Jack Ceroni, Alain Delgado, Olivia Di Matteo, Amintor Dusko, Tanya Garg, Diego Guala, Anthony Hayes, Ryan Hill, Aroosa Ijaz, Theodor Isaacson, David Ittah, Soran Jahangiri, Prateek Jain, Edward Jiang, Ankit Khandelwal, Korbini Kottmann, Robert A. Lang, Christina Lee, Thomas Loke, Angus Lowe, Keri McKiernan, Johannes Jakob Meyer, J. A. Montañez-Barrera, Romain Moyard, Zeyue Niu, Lee James O'Riordan, Steven Oud, Ashish Panigrahi, Chae-Yeun Park, Daniel Polatajko, Nicolás Quesada, Chase Roberts, Nahum Sá, Isidor Schoch, Borun Shi, Shuli Shu, Sukin Sim, Arshpreet Singh, Ingrid Strandberg, Jay Soni, Antal Száva, Slimane Thabet, Rodrigo A. Vargas-Hernández, Trevor Vincent, Nicola Vitucci, Maurice Weber, David Wierichs, Roeland Wiersema, Moritz Willmann, Vincent Wong, Shaoming Zhang, Nathan Killoran, PennyLane: Automatic differentiation of hybrid quantum-classical computations, arXiv:1811.04968 [quant-ph], (2018).
- [399] Yongdan Yang, Bing-Nan Lu, and Ying Li, Accelerated Quantum Monte Carlo with Mitigated Error on Noisy Quantum Computer, *PRX Quantum* **2** (4), 040361 (2021).
- [400] Almudena Carrera Vazquez, Ralf Hiptmair, and Stefan Woerner, Enhancing the Quantum Linear Systems Algorithm Using Richardson Extrapolation, *ACM Transactions on Quantum Computing* **3** (1), 2:1-2:37 (2022).
- [401] Kaoru Yamamoto, Suguru Endo, Hideaki Hakoshima, Yuichiro Matsuzaki, and Yuuki Tokunaga, Error-Mitigated Quantum Metrology via Virtual Purification, *Phys. Rev. Lett.* **129** (25), 250503 (2022).
- [402] Ryan LaRose, Andrea Mari, Sarah Kaiser, Peter Karalekas, Andre Alves, Piotr Czarnik, Mohamed El Mandouh, Max Gordon, Yousef Hindy, Aaron Robertson, Purva Thakre, Nathan Shammah, and William Zeng, Mitiq: A software package for error mitigation on noisy quantum computers, *Quantum* **6**, 774 (2022).
- [403] L. O Conlon, Tobias Vogl, Christian D. Marciniak, Ivan Pogorelov, Simon K. Yung, Falk Eilenberger, Dominic W. Berry, Fabiana S. Santana, Rainer Blatt, Thomas Monz, Ping Koy Lam, and Syed M. Assad, Approaching optimal entangling collective measurements on quantum computing platforms, *Nature Physics* **19** (3), 351-357 (2023).
- [404] Cristina Cirstoiu, Silas Dilkes, Daniel Mills, Seyon Sivarajah, and Ross Duncan, Volumetric Benchmarking of Error Mitigation with Qermit, *Quantum* **7**, 1059 (2023).
- [405] A. Javadi-Abhari *et al.* Quantum computing with Qiskit, *arXiv preprint* arXiv:2405.08810 (2024).
- [406] M. AbuGhanem, IBM Quantum Computers: Evolution, Performance, and Future Directions, <https://arxiv.org/submit/5859971> (2024).
- [407] Alexander Zlokapa, Benjamin Villalonga, Sergio Boixo, Daniel A Lidar, Boundaries of quantum supremacy via random circuit sampling, *npj Quantum Inf* **9** (1), 36, (2023).
- [408] Jesse C Hoke, *et al.* Measurement-induced entanglement and teleportation on a noisy quantum processor, *Nature* **622** (7983), 481-486, (2023).
- [409] Oscar Higgott, Craig Gidney, Sparse Blossom: correcting a million errors per core second with minimum-weight matching, arXiv preprint arXiv:2303.15933, (2023).
- [410] Matt McEwen, Dave Bacon, Craig Gidney, Relaxing hardware requirements for surface code circuits using time-dynamics, arXiv preprint arXiv:2302.02192, (2023).
- [411] Craig Gidney, A pair measurement surface code on pentagons, *Quantum* **7**, 1156, (2023).
- [412] Nicholas C Rubin, Dominic W Berry, Fionn D Malone, Alec F White, Tanuj Khattar, A Eugene De-Prince III, Sabrina Siculo, Michael Kühn, Michael Kaicher, Joonho Lee, Ryan Babbush, Fault-tolerant quantum simulation of materials using Bloch orbitals, *PRX Quantum* **4** (4), 040303, (2023).
- [413] Amira Abbas, Robbie King, Hsin-Yuan Huang, William J Huggins, Ramis Movassagh, Dar Gilboa, Jarrod R McClean, On quantum backpropagation, information reuse, and cheating measurement collapse, arXiv preprint arXiv:2305.13362, (2023).
- [414] Ryan Babbush, Dominic W Berry, Robin Kothari, Rolando D Somma, Nathan Wiebe, Exponential quantum speedup in simulating coupled classical oscillators, arXiv preprint arXiv:2303.13012, (2023).
- [415] X Mi, *et al.*, Stable quantum-correlated many body states via engineered dissipation, arXiv preprint arXiv:2304.13878, (2023).
- [416] Randy Kwende, Theodore White, Ofer Naaman, Josephson parametric circulator with same-frequency signal ports, 200 MHz bandwidth, and high dynamic range, *Applied Physics Letters* **122** (22), (2023).
- [417] Ryan Babbush, William J Huggins, Dominic W Berry, Shu Fay Ung, Andrew Zhao, David R Reichman, Hartmut Neven, Andrew D Baczewski, Joonho Lee, Quantum simulation of exact electron dynamics can be more efficient than classical mean-field methods, *Nat. Comm.* **14**, 4058, (2023).
- [418] Elliott Rosenberg *et al.*, Dynamics of magnetization at infinite temperature in a Heisenberg spin chain, arXiv preprint arXiv:2306.09333, (2023).
- [419] Yilun Yang, Arthur Christianen, Sandra Coll-Vinent, Vadim Smelyanskiy, Mari Carmen Bañuls, Thomas E O'Brien, Dominik S Wild, J Ignacio Cirac, Simulating prethermalization using near-term quantum computers, *PRX Quantum* **4** (3), 030320, (2023).
- [420] Ryan Kaufman, Theodore White, Mark I Dykman, Andrea Iorio, George Stirling, Sabrina Hong, Alex Opremcak, Andreas Bengtsson, Lara Faoro, Joseph C Bardin, Tim Burger, Robert Gasca, Ofer Naaman, Josephson parametric amplifier with Chebyshev gain profile and high saturation, arXiv preprint arXiv:2305.17816,

- (2023).
- [421] Sofia Gonzalez-Garcia, Shengqi Sang, Timothy H Hsieh, Sergio Boixo, Guifre Vidal, Andrew C Potter, Romain Vasseur, Random insights into the complexity of two-dimensional tensor network calculations, arXiv preprint arXiv:2307.11053, (2023).
- [422] Craig Gidney, Dave Bacon, Less Bacon More Threshold, arXiv preprint arXiv:2305.12046, (2023).
- [423] William J Huggins, Jarrod R McClean, Accelerating quantum algorithms with precomputation, arXiv preprint arXiv:2305.09638, (2023).
- [424] Ryan Kaufman, Ofer Naaman, Parametric Amplifier Matching Using Legendre Prototypes, arXiv preprint arXiv:2303.00184, (2023).
- [425] Craig Gidney, Cleaner magic states with hook injection, arXiv preprint arXiv:2302.12292, (2023).
- [426] Kianna Wan, William J Huggins, Joonho Lee, Ryan Babbush, Matchgate shadows for fermionic quantum simulation, *Communications in Mathematical Physics*, 1-72, (2023).
- [427] Harry Lane, Hao Zhang, David Dahlbom, Sam Quinn, Rolando D Somma, Martin Mourigal, Cristian D Batista, Kipton Barros, Kernel Polynomial Method for Linear Spin Wave Theory, arXiv preprint arXiv:2312.08349, (2023).
- [428] Pedro Costa, Dong An, Ryan Babbush, Dominic Berry, The discrete adiabatic quantum linear system solver has lower constant factors than the randomized adiabatic solver, arXiv preprint arXiv:2312.07690, (2023).
- [429] Dominic W Berry *et al.*, Quantum Simulation of Realistic Materials in First Quantization Using Non-local Pseudopotentials, arXiv preprint arXiv:2312.07654, (2023).
- [430] Lea M Trenkwalder, Eleanor Scerri, Thomas E O'Brien, Vedran Dunjko, Compilation of product-formula Hamiltonian simulation via reinforcement learning, arXiv preprint arXiv:2311.04285, (2023).
- [431] Haimeng Zhao, Laura Lewis, Ishaan Kannan, Yihui Quek, Hsin-Yuan Huang, Matthias C Caro, Learning quantum states and unitaries of bounded gate complexity, arXiv preprint arXiv:2310.19882, (2023).
- [432] Oles Shtanko, Derek S Wang, Haimeng Zhang, Nikhil Harle, Alireza Seif, Ramis Movassagh, Zlatko Mineev, Uncovering local integrability in quantum many-body dynamics, arXiv preprint arXiv:2307.07552, (2023).
- [433] Alicja Dutkiewicz, Thomas E O'Brien, Thomas Schuster, The advantage of quantum control in many-body Hamiltonian learning, arXiv preprint arXiv:2304.07172, (2023).
- [434] Xavier Bonet-Monroig, Hao Wang, Diederick Vermetten, Bruno Senjean, Charles Moussa, Thomas Bäck, Vedran Dunjko, Thomas E O'Brien, Performance comparison of optimization methods on variational quantum algorithms, *Phys. Rev. A* **107** (3), 032407, (2023).
- [435] Andreas Bengtsson *et al.* Model-based Optimization of Superconducting Qubit Readout, *Phys. Rev. Lett.* **132** (10), 100603, (2024).
- [436] Xiao Mi, AA Michailidis, Sara Shabani *et al.* et al. Stable quantum-correlated many-body states through engineered dissipation, *Science* **383** (6689), 1332-1337, (2024).
- [437] M. B. Plenio, S. F. Huelga, A. Beige, P. L. Knight, Cavity-loss-induced generation of entangled atoms, *Phys. Rev. A* **59**, 2468 (1999).
- [438] B. Kraus, *et al.*, Preparation of entangled states by quantum Markov processes, *Phys. Rev. A* **78**, 042307 (2008).
- [439] S. Diehl, *et al.* Quantum states and phases in driven open quantum systems with cold atoms, *Nat. Phys.* **4**, 878 (2008).
- [440] F. Verstraete, M. M. Wolf, J. Ignacio Cirac, Quantum computation and quantum-state engineering driven by dissipation, *Nat. Phys.* **5**, 633 (2009).
- [441] C. Aron, M. Kulkarni, H. E. Türeci, Photon-Mediated Interactions: A Scalable Tool to Create and Sustain Entangled States of N Atoms, *Phys. Rev. X* **6**, 011032 (2016).
- [442] M. AbuGhanem *et al.*, Cavity control as a new quantum algorithms implementation treatment, *Front. Phys.* **13** 1, 130303 (2018).
- [443] P. M. Harrington, E. J. Mueller, K. W. Murch, Engineered Dissipation for Quantum Information Science, *Nat. Rev. Phys.* **4**, 660 (2022).
- [444] Trond I Andersen, Nikita Astrakhantsev, Amir Karamlou *et al.* Thermalization and Criticality on an Analog-Digital Quantum Simulator, arXiv preprint arXiv:2405.17385, (2024).
- [445] Kosterlitz, J. M. and Thouless, D. J. Ordering, metastability and phase transitions in two-dimensional systems. *J. Phys. C: Solid State Phys.* **6**, 1181 (1973).
- [446] del Campo, A. and Zurek, W. H. Universality of phase transition dynamics: Topological defects from symmetry breaking. *Int. J. Mod. Phys. A* **29**, 1430018 (2014).
- [447] Samajdar, R. and Huse, D. A. Quantum and classical coarsening and their interplay with the kibble-zurek mechanism, arXiv:2401.15144 (2024).
- [448] Deutsch, J. M. Quantum statistical mechanics in a closed system. *Phys. Rev. A* **43**, 2046-2049 (1991).
- [449] Srednicki, M. Chaos and quantum thermalization. *Phys. Rev. E* **50**, 888-901 (1994).
- [450] D'Alessio, L., Kafri, Y., Polkovnikov, A. and Rigol, M. From quantum chaos and eigenstate thermalization to statistical mechanics and thermodynamics. *Adv. Phys.* **65**, 239-362 (2016).
- [451] Zhou, Z.-Y. *et al.* Thermalization dynamics of a gauge theory on a quantum simulator. *Science* **377**, 311-314 (2022).
- [452] Andi Gu, Hong-Ye Hu, Di Luo, Taylor L Patti, Nicholas C Rubin, Susanne F Yelin, Zero and finite temperature quantum simulations powered by quantum magic, *Quantum* **8**, 1422, (2024).
- [453] X. Yu, D. Pekker, and B. K. Clark. Bulk Geometry of the Many Body Localized Phase from Wilson-Wegner Flow. arXiv e-prints, arXiv:1909.11097, (2019).
- [454] X. Yuan, S. Endo, Q. Zhao, Y. Li, and S. C. Benjamin. Theory of variational quantum simulation. *Quantum*, **3**:191, (2019).
- [455] C. Kang, N. P. Bauman, S. Krishnamoorthy, and K. Kowalski. Optimized Quantum Phase Estimation for Simulating Electronic States in Various Energy Regimes. *Journal of Chemical Theory and Computation*, **18**(11):6567-6576, (2022).
- [456] G. Roussy. An approximate block diagonalization for hermitian matrices as an improvement on successive Van Vleck transformations. *Molecular Physics*, **26**(5):1085-1092 (1973).
- [457] L. S. Cederbaum, J. Schirmer, and H. D. Meyer. Block diagonalisation of Hermitian matrices. *Journal*

- of *Physics A: Mathematical and General*, **22**(13):2427-2439 (1989).
- [458] S. R. White. Numerical canonical transformation approach to quantum many-body problems. *The Journal of Chemical Physics*, **117**(16):7472-7482, (2002).
- [459] S. Bravyi, D. P. DiVincenzo, and D. Loss. Schrieffer-Wolff transformation for quantum many-body systems. *Annals of Physics*, **326**(10): 2793-2826, (2011).
- [460] M. AbuGhanem, Properties of some quantum computing models, Master's Thesis, Fac. Sci., Ain Shams Univ. (2019).
- [461] V. Khemani, F. Pollmann, and S. L. Sondhi. Obtaining Highly Excited Eigenstates of Many-Body Localized Hamiltonians by the Density Matrix Renormalization Group Approach. *Phys. Rev. Lett.*, **116**:247204, June 2016.
- [462] S. P. Lim and D. N. Sheng. Many-body localization and transition by density matrix renormalization group and exact diagonalization studies. *Phys. Rev. B*, **94**:045111, (2016).
- [463] Y.-Z. You, X.-L. Qi, and C. Xu. Entanglement holographic mapping of many-body localized system by spectrum bifurcation renormalization group. *Phys. Rev. B*, **93**:104205, (2016).
- [464] C. M. Duque, H.-Y. Hu, Y.-Z. You, V. Khemani, R. Verresen, and R. Vasseur. Topological and symmetry-enriched random quantum critical points. *Phys. Rev. B*, **103**:L100207, (2021).
- [465] Alireza Seif, Yu-Xin Wang, Ramis Movassagh, Aashish A Clerk, Measurement and Feed Forward Induced Entanglement Negativity Transition, *Phys. Rev. Lett.* **133** (5), 050402, (2024).
- [466] H. M. Wiseman and G. J. Milburn, Quantum Measurement and Control (Cambridge University Press, 2009).
- [467] A. Metelmann and A. A. Clerk, Nonreciprocal quantum interactions and devices via autonomous feed-forward, *Phys. Rev. A* **95**, 013837 (2017).
- [468] A. Seif, Y.-X. Wang, and A. A. Clerk, Distinguishing between quantum and classical markovian dephasing dissipation, *Phys. Rev. Lett.* **128**, 070402 (2022).
- [469] X. Feng, B. Skinner, and A. Nahum, Measurement-induced phase transitions on dynamical quantum trees, *PRX Quantum* **4**, 030333 (2023).
- [470] Chi-Fang Chen, Hsin-Yuan Huang, John Preskill, Leo Zhou, Local minima in quantum systems, Proceedings of the 56th Annual ACM Symposium on Theory of Computing, 1323-1330, (2024).
- [471] Nicholas C Rubin, Dominic W Berry, Alina Kononov, Fionn D Malone, Tanuj Khattar, Alec White, Joonho Lee, Hartmut Neven, Ryan Babbush, Andrew D Baczewski, Quantum computation of stopping power for inertial fusion target design, *Proceedings of the National Academy of Sciences* **121** (23), e2317772121, (2024).
- [472] Maximilian Scheurer, Gian-Luca R Anselmetti, Oumarou Oumarou, Tailored and externally corrected coupled cluster with quantum inputs, Christian Gogolin, Nicholas C Rubin, *Journal of Chemical Theory and Computation* **20** (12), 5068-5093, (2024).
- [473] Yongtao Zhan, Andreas Elben, Hsin-Yuan Huang, Yu Tong, Learning conservation laws in unknown quantum dynamics, *PRX Quantum* **5** (1), 010350, (2024).
- [474] Emiel Koridon, Joana Fraxanet, Alexandre Dauphin, Lucas Visscher, Thomas E O'Brien, Stefano Polla, A hybrid quantum algorithm to detect conical intersections, *Quantum* **8**, 1259, (2024).
- [475] Aaronson, S. Quantum computing, postselection, and probabilistic polynomial-time. *Proc. R. Soc. A* **461**, 3473-3482 (2005).
- [476] Bremner, M. J., Jozsa, R. and Shepherd, D. J. Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy. *Proc. R. Soc. A* **467**, 459-472 (2011).
- [477] Aaronson, S. and Arkhipov, A. The computational complexity of linear optics. In STOC '11 Proc. Forty-Third Annual ACM Symp. Theory of Computing 333-342 (ACM, New York, NY, 2011).
- [478] Bremner, M. J., Montanaro, A. and Shepherd, D. J. Average-case complexity versus approximate simulation of commuting quantum computations. *Phys. Rev. Lett.* **117**, 080501 (2016).
- [479] Fujii, K. and Morimae, T. Commuting quantum circuits and complexity of Ising partition functions. *New J. Phys.* **19**, 033003 (2017).
- [480] Goldberg, L. A. and Guo, H. The complexity of approximating complex-valued Ising and Tutte partition functions. *Comput. Complex.* **26**, 765-833 (2017).
- [481] S. Boixo and V. Smelyanskiy, How to compare a noisy quantum processor to a classical computer, (August 24, 2023) <https://research.google/blog/how-to-compare-a-noisy-quantum-processor-to-a-classical-computer/>, accessed August 19, (2024).
- [482] Sajant Anand, Kristan Temme, Abhinav Kandala, Michael Zaletel, Classical benchmarking of zero noise extrapolation beyond the exactly-verifiable regime, arXiv:2306.17839, (2023).
- [483] K. Kechedzhi, S.V. Isakov, S. Mandrà, B. Villalonga, X. Mi, S. Boixo, V. Smelyanskiy, Effective quantum volume, fidelity and computational cost of noisy quantum processing experiments, *Future Generation Computer Systems* **153**, 431-441, (2024).
- [484] Xiao Mi *et al.*, Information scrambling in quantum circuits. *Science* **374**,1479-1483 (2021).
- [485] M. AbuGhanem and H. Eleuch, Full quantum tomography study of Google's Sycamore gate on IBM's quantum computers, *EPJ Quantum Technology* **11**(1), 36 (2024).
- [486] M. AbuGhanem and H. Eleuch, Experimental characterization of Google's Sycamore quantum AI on an IBM's quantum computer, *Elsevier, SSRN* 4299338 (2023). <http://dx.doi.org/10.2139/ssrn.4299338>
- [487] Ayral, T., Besserve, P., Lacroix, D. *et al.* Quantum computing with and for many-body physics. *Eur. Phys. J. A* **59**, 227 (2023).
- [488] Fauseweh, B. Quantum many-body simulations on digital quantum computers: State-of-the-art and future challenges. *Nat Commun* **15**, 2123 (2024).
- [489] Chen, Y. *et al.* Multiplexed dispersive readout of superconducting phase qubits. *Appl. Phys. Lett.* **101**, 182601 (2012).
- [490] Wootters, W. K. Random quantum states. *Found. Phys.* **20**, 1365-1378 (1990).
- [491] Emerson, J., Livine, E. and Lloyd, S. Convergence conditions for random quantum circuits. *Phys. Rev. A* **72**, 060302 (2005).
- [492] Aaronson, S. and Chen, L. Complexity-theoretic foundations of quantum supremacy experiments. In *32nd Computational Complexity Conf.* <https://doi.org/10.4230/LIPIcs.CCC.2017.22> (Schloss Dagstuhl - Leibniz Zentrum für Informatik, 2017).

- [493] J. Kelly, R. Barends, A. Fowler *et al.*, State preservation by repetitive error detection in a superconducting quantum circuit, *Nature* **519**, 66-69 (2015).
- [494] Julian Kelly, A Preview of Bristlecone Google's New Quantum Processor, Google Quantum AI Lab, (2018).
- [495] Quantum Computer Datasheet, Google Quantum AI, (May 14, 2021). Available at <https://quantumai.google/hardware/datasheet>, accessed (2023).
- [496] J. Gray and S. Kourtis, Hyper-optimized tensor network contraction, *Quantum* **5**, 410 (2021).
- [497] J. Chen, F. Zhang, C. Huang, M. Newman, and Y. Shi, Classical simulation of intermediate-size quantum circuits, arXiv:1805.01450 (2018).
- [498] Y. Wu *et al.*, Strong quantum computational advantage using a superconducting quantum processor, *Phys. Rev. Lett.* **127**, 180501 (2021).
- [499] Q. Zhu *et al.*, Quantum computational advantage via 60-qubit 24-cycle random circuit sampling, *Sci. Bull.* **67**, 240-245 (2022).
- [500] Y. Chen *et al.*, Qubit architecture with high coherence and fast tunable coupling circuits, *Phys. Rev. Lett.* **113**, 220502 (2014).
- [501] S. Aaronson, A. Arkhipov, The computational complexity of linear optics, in *Proceedings of the Forty-third Annual ACM Symposium on Theory of Computing*, pp. 333-342 (2011). <https://doi.org/10.1145/1993636.1993682>
- [502] H.-S. Zhong *et al.*, Quantum computational advantage using photons, *arXiv preprint* arXiv:2012.01625v1, (2020).
- [503] H.-S. Zhong *et al.*, Phase-Programmable Gaussian Boson Sampling Using Stimulated Squeezed Light, *arXiv preprint* arXiv:2106.15534v2 (2021).
- [504] L. S. Madsen, F. Laudenbach, M. F. Askarani, F. Rortais, T. Vincent, J. F. Bulmer, F. M. Miatto, L. Neuhaus, L. G. Helt, M. J. Collins *et al.*, Quantum computational advantage with a programmable photonic processor, *Nature* **606** (7912), 75-81 (2022).
- [505] A. Deshpande *et al.*, Quantum computational advantage via high-dimensional gaussian boson sampling, *Sci. Adv.* **8**, eabi7894 (2022).
- [506] Kishor Bharti, Alba Cervera-Lierta, Thi Ha Kyaw, Tobias Haug, Sumner Alperin-Lea, Abhinav Anand, Matthias Degroote, Hermanni Heimonen, Jakob S. Kottmann, Tim Menke, Wai-Keong Mok, Sukin Sim, Leong-Chuan Kwek, and Alán Aspuru-Guzik, Noisy intermediate-scale quantum algorithms, *Rev. Mod. Phys.* **94**, 015004 (2022).
- [507] Quantum AI team and collaborators, Cirq, *Zenodo*, (May 2024) Available: <https://doi.org/10.5281/zenodo.4062499>. Accessed August 15 (2024).
- [508] Cao, Y., Romero, J. and Aspuru-Guzik, A. Potential of quantum computing for drug discovery. *IBM J. Res. Dev.* **62**, 6-1. (2018).
- [509] McArdle, S., Endo, S., Aspuru-Guzik, A., Benjamin, S. C. and Yuan, X. Quantum computational chemistry. *Rev. Mod. Phys.* **92**, 015003. (2020).
- [510] Bauer, B., Bravyi, S., Motta, M. and Chan, G.K.-L. Quantum algorithms for quantum chemistry and quantum materials science. *Chem. Rev.* **120**, 12685-12717. (2020).
- [511] Fedorov, A. K. and Gelfand, M. S. Towards practical applications in quantum computational biology. *Nat. Comput. Sci.* **1**, 114-119. (2021).
- [512] A. I. Gircha, A. S. Boev, K. Avchaciov, P. O. Fedichev and A. K. Fedorov, Hybrid quantum-classical machine learning for generative chemistry and drug design. *Sci Rep* **13**, 8250 (2023).
- [513] M. Smelyanskiy, N. P. Sawaya, A. Aspuru-Guzik, "qHiPSTER: The Quantum High Performance Software Testing Environment", arXiv:1601.07195 (2016).
- [514] T. Häner, D. S. Steiger, "0.5 Petabyte Simulation of a 45-Qubit Quantum Circuit", arXiv:1704.01127 (2017).
- [515] Intel® Xeon® Processors, <https://ark.intel.com/content/www/us/en/ark/products/series/595/intel-xeon-processors.html>, accessed September 21, (2024).
- [516] qism, <https://github.com/quantumlib/qsim>, accessed September 21, (2024).
- [517] L. K. Grover, Quantum mechanics helps in searching for a needle in a haystack, *Phys. Rev. Lett.*, **79**(2), 325 (1997).
- [518] M. AbuGhanem, Comprehensive characterization of three-qubit Grover search algorithm on IBM's 127-qubit superconducting quantum computers, *arXiv preprint* arXiv:2406.16018, (2024).
- [519] Quantum AI team and collaborators, ReCirq, *Zenodo*, (Oct. 2020) Available: <https://doi.org/10.5281/zenodo.4091470>. Accessed August 15 (2024).
- [520] Our quantum computing roadmap, <https://quantumai.google/>, accessed September 21, (2024).