

# Megahertz cycling of ultrafast structural dynamics enabled by nanosecond thermal dissipation

Till Domröse,<sup>1,2</sup> Leonardo da Camara Silva,<sup>1,2</sup> and Claus Ropers<sup>1,2, a)</sup>

<sup>1)</sup>*Department of Ultrafast Dynamics, Max Planck Institute for Multidisciplinary Sciences, 37077 Göttingen, Germany*

<sup>2)</sup>*4th Physical Institute – Solids and Nanostructures, University of Göttingen, 37077 Göttingen, Germany*

Light-matter interactions are of fundamental scientific and technological interest. Ultrafast electron microscopy and diffraction with combined femtosecond-nanometer resolution elucidate the laser-induced dynamics in structurally heterogeneous systems. These measurements, however, remain challenging due to the brightness limitation of pulsed electron sources, leading to an experimental trade-off between resolution and contrast. Higher signals without compromising the electron beam coherence can be achieved by enhanced duty cycles, thus far limited to few-kHz repetition rates by the cooling times in thin-film specimens. Here, we combine nanometric electron-beam probing with sample support structures tailored to accommodate rapid thermal relaxation. A charge-density wave (CDW) phase transformation allows us to quantify the mean temperature increase induced by pulsed laser illumination. Varying the excitation fluence and repetition rate, we gauge the impact of excitation confinement and efficient dissipation on the thermal relaxation of different sample designs. In particular, a thermally optimized support can dissipate average laser intensities of up to  $200 \mu\text{W}/\mu\text{m}^2$  within a few nanoseconds, allowing for reversible driving and probing of the CDW transition at a repetition rate of 2 MHz. Sample designs tailored to ultrafast measurement schemes will thus extend the capabilities of electron diffraction and microscopy, enabling high-resolution investigations of structural dynamics.

Electron microscopy and diffraction are versatile experimental tools used to explore steady-state dynamics and image heterogeneous systems in both materials and life science. Over the past years, advances in aberration correction<sup>1</sup>, detector development<sup>2</sup> and sample preparation<sup>3,4</sup> have enabled profound insights in the fields of structural biology<sup>5,6</sup>, heterogeneous catalysis<sup>7</sup> and solid-state physics<sup>8–10</sup> with down to atomic resolution. Beyond the imaging of stationary structures, ultrafast electron microscopy and diffraction<sup>11–21</sup> promise the investigation of non-equilibrium processes and transient states of matter<sup>22–24</sup>. Such dynamics are induced by ultrashort optical or electrical pulses and evolve on femtosecond to picosecond time scales, far below the shutter speeds of the fastest available electron detectors. Pioneering works in ultrafast transmission electron microscopy (UTEM)<sup>25,26</sup> have allowed to directly image phenomena such as structural phase transformations<sup>27,28</sup> and strain-wave propagation<sup>29–31</sup> on nanometer length scales. Similarly, in ultrafast electron diffraction (UED)<sup>32</sup>, atomic-scale information on evolving crystalline order and phonon populations are obtained by tracing diffraction intensities<sup>32–50</sup>, spot profiles<sup>51–54</sup>, and momentum-dependent diffuse scattering<sup>55–58</sup>.

UTEM and UED measurements rely on the stroboscopic principle: femtosecond probe pulses take snapshots of the non-equilibrium state at a temporal delay  $\Delta t$  after the optical excitation<sup>23,24,59–61</sup>. Critically, such a scheme is only sensitive to reversible processes, as sufficient contrast in imaging or diffraction arises from averaging over many individual probe events at a set pump-probe delay. A full reconstruction of the structural dynamics thus necessitates complete relaxation within one pump-probe cycle. This entails sample cooling prior to the arrival of the subsequent laser excitation<sup>62</sup>,


as well as, in the case of structural phase transformations, a re-formation of the initial phase (Fig. 1c). For a given total measurement time, the maximum available repetition rate  $f_{\text{rep}}$  satisfying these conditions will determine the signal-to-noise ratio of the experiment.

Obtaining enhanced contrast by higher repetition rates may be realized in two ways. First, cooling down to a lower initial temperature can compensate for some average heating at higher duty cycles. Second, the thermal relaxation time in thin-film specimens, typically investigated in transmission diffraction and imaging, scales quadratically with the pump beam diameter (Fig. 1d; and Supplementary Material). Consequently, reducing the laser-excited area allows for an efficient suppression of cumulative sample heating. This approach facilitates reversible high-repetition rate driving also in materials with reduced thermal conductivity, and phase diagrams characterized by a succession of multiple structural orders within a small temperature range become fully accessible to ultrafast methodology.

The subtle, sub-Ångstrom structural changes associated with phase transformations are resolved by ultrafast electron diffraction<sup>15,27,33–35,43,44,47,49,51,53,63–73</sup>. As a prerequisite for spatially-averaging measurements, a clear interpretation of the data requires a homogeneous excitation across the electron beam diameter  $d_{\text{probe}}$ , limiting the smallest possible focus of the laser spot. Figure 1a displays documented experimental parameters in prior UED characterizations of structural transitions. Even though these investigations span a broad range of systems and beam energies, the quadratic relationship between cooling time and pump beam diameter translates into a fundamental limitation of the available repetition rate. Importantly, surface-sensitive techniques allow for higher duty cycles<sup>43,51,72,73</sup>, as thicker samples additionally feature thermal dissipation into the bulk.

Electron beam diameter and divergence, which directly af-

<sup>a)</sup>Corresponding author: claus.ropers@mpinat.mpg.de



**FIG. 1 Ultrafast electron diffraction of structural phase transitions.** **a** Literature overview of repetition rates  $f_{\text{rep}}$  and collimated electron beam diameters in UED probing structural phase transitions. In-plane thermal dissipation in thin material films limits the repetition rates for 100- $\mu\text{m}$  probing (black diamonds) to 1 kHz. Surface-sensitive techniques (blue squares) offer faster thermal relaxation into the bulk, and thus higher duty cycles. Smaller pump beams allow to enhance  $f_{\text{rep}}$  also in transmission probing (red open circles). Combined nanobeam diffraction and optimized thermal management (filled red circles) extend the available  $f_{\text{rep}}$  into the MHz-regime. **b** Schematic sample design in nano-UED. A gold reflection layer confines the optical excitation, and ensures efficient thermal dissipation. **c** Stroboscopic probing requires sufficient thermal relaxation between subsequent excitation events. **d** Small probe volumes allow for smaller pump profiles (diameter  $d_{\text{pump}}$ ), leading to faster sample cooling times  $\tau_{\text{rec}}$  and higher higher  $f_{\text{rep}}$ .


fects the momentum resolution in diffraction, are defined by the emittance of the beam used. A small effective electron source size is thus beneficial for both, high repetition-rate pumping and high-resolution probing. Setups employing micrometer-sized, flat photocathodes operate in the nanometer-radian emittance regime<sup>74</sup>, corresponding to electron beam diameters of tens to hundreds of micrometers. Dynamics are excited and probed at rates between 100 Hz and 1 kHz. In contrast, picometer-radian beam emittances offer enhanced resolution in collimated electron nanobeams, reduced spatial averaging, confined excitation, and faster sample cooling times.

In this work, we investigate the thermal properties of tailored sample environments optimized for rapid thermal relaxation. A confinement of the laser excitation and enhanced thermal dissipation enable nanosecond cooling times, allowing for megahertz cycling of structural dynamics and transitions in thin material films. We benchmark these capabilities in a nanobeam ultrafast electron diffraction (nano-UED) study of a structural phase transformation in the layered material  $1T'-\text{TaTe}_2$ <sup>49,68</sup>. Structural dynamics are reversibly driven at a repetition rate of 2 MHz and an incident fluence of  $10 \text{ mJ}/\text{cm}^2$ , and probed by a high-coherence ultrashort electron nanobeam. Featuring also high momentum resolution, our measurements advance ultrafast electron diffraction into the parameter space of picometer-radian beam emittances, nanometer beam diameters, quantified femtosecond pulse durations, and megahertz repetition rates.

Our experiments are carried out in an ultrafast trans-

mission electron microscope (UTEM)<sup>22,26,29,45,75–84</sup>. Non-equilibrium dynamics are excited by ultrashort laser pulses with tunable wavelength and repetition rate [between 690 nm and 940 nm wavelength, 50 fs duration, between 101 kHz and 2 MHz repetition rate; Fig. 2(a)], and probed by ultrashort electron pulses generated via linear photoemission. The Göttingen UTEM features a high-brightness pulsed field-emitter electron source (120–200 keV electron energy)<sup>29</sup>. The confinement of the photoemission to the front-apex of the emitter tip yields a particularly small effective source size, and thus enables nanoscale investigations of, e.g., charge-density wave (CDW) transformations at high momentum resolution<sup>28,49,51–53</sup>. While such electron sources are primarily found in UTEMs<sup>29,77–81</sup>, their usage is not restricted to electron microscopes, and has also been demonstrated in dedicated UED setups for investigations of structural dynamics in transmission<sup>36</sup> and reflection<sup>52</sup>.

The versatility of electron microscopy in forming electron beams also beyond collimated diffraction measurements enables additional control over other key experimental parameters such as the temporal resolution. In particular, spectroscopic characterizations of inelastic electron scattering at optical near-fields [photon-induced near-field electron microscopy, PINEM<sup>83,85,86</sup>; Fig. 2(b)] allow for a quantitative determination of the electron pulse duration and shape, as well as time zero<sup>87</sup>. For low pulse charge, we obtain a pulse duration of 200 fs (full-width-at-half maximum). Importantly, this pulse characterization can be performed *in-situ*, accounting for, on the one hand, small changes of the sample posi-



**FIG. 2 Nanobeam ultrafast electron diffraction.** **a** Ultrafast transmission electron microscope. Electron pulses are generated via photoemission from a tip emitter. Laser-induced dynamics in heterogeneous thin films are probed at high  $k$ -space resolution with a collimated nanobeam, enabled by a picometer-radian transverse beam emittance. **b** *In-situ* pulse-duration measurement in the sample plane (right). Inelastic electron-light scattering leads to the population of discrete side-bands in the electron spectra separated by the photon energy  $\hbar\omega$ . The intensity in the outer energy sidebands (grey rectangle) yields a quantitative measure of the instrument resolution function (left, grey). Its derivative corresponds to the electron pulse structure (green). We obtain durations of 200 fs. **c** Example diffractogram of the  $3 \times 3$  phase of  $1T'$ -TaTe<sub>2</sub> measured before time zero, recorded with ultrashort electron pulses (beam diameter 670 nm) and under full thermal load ( $10 \text{ mJ/cm}^2$  incident fluence at 2 MHz rate). The superstructure formation leads to low-intensity second-order satellites (blue circles), the order parameter of the structural transformation. **d** Electron micrograph of a  $1T'$ -TaTe<sub>2</sub> thin film suspended below a gold aperture array ( $2 \mu\text{m}$  hole diameter,  $4 \mu\text{m}$  pitch). Inset: enlarged view of a single  $2\text{-}\mu\text{m}$  hole. The green circle illustrates the electron spot size.


tion and tilt that may alter the relative timing between pump and probe pulses. Measured signals can then be corrected by an instrument resolution function recorded under the same experimental conditions<sup>49</sup>. On the other hand, direct access to the electron pulse properties also allows for balancing the bunch charge and temporal resolution, optimizing image contrast at the expense of moderate Coulomb-induced temporal pulse broadening<sup>88–92</sup>, tailored to the fastest features in the investigated dynamics.

In the following, we illustrate the technical capabilities of the setup by investigating charge-density wave dynamics in the layered quantum material  $1T'$ -TaTe<sub>2</sub>. Comprised out of weakly-bound tellurium-tantalum-tellurium trilayers, the reduced dimensionality and strong electron-phonon coupling in this material favour the formation of charge-density waves (CDWs) accompanied by a large-amplitude periodic lattice distortion (PLD)<sup>93,94</sup>. These types of charge-ordered phases occur in a range of quantum materials<sup>95</sup>, and were investigated by ultrafast diffraction and microscopy employing x-rays<sup>96–101</sup> or electrons<sup>28,33–35,37–45,49,51–54,58,64–69,72,73</sup>, including investigations of the structural transitions in  $1T'$ -TaTe<sub>2</sub><sup>49,68</sup>. The material's room-temperature phase is characterized by a  $(3 \times 1)$  superstructure when compared to the undistorted  $1T$ -polytype found in, e.g., the chemically related compounds  $1T$ -TaS<sub>2</sub> and  $1T$ -TaSe<sub>2</sub>. Below a temperature of 174 K, the system undergoes a first-order structural transformation into a  $(3 \times 3)$  phase<sup>93</sup>. In electron diffractograms, this superstructure can be identified by the appearance of ad-

ditional low-intensity satellite peaks surrounding the high-intensity reflections of the undistorted host lattice [Fig. 3(a)].

The first-order transition allows for a measurement of the time-averaged temperature increase in electron diffraction under various incident laser fluences and repetition rates. Specifically, the cumulative thermal response is encoded in the intensity of the second-order ( $3 \times 3$ ) spots, i.e., the order parameter of the transformation both in- and out-of equilibrium, when measured by a continuous electron beam (Fig. 3). For sufficiently low laser intensities, and starting from an estimated base temperature of 120 K, the presence of PLD spots in the diffractograms indicates that the sample remains in its low-temperature state for the majority of the pump cycle. Steady-state heating at higher thermal loads increases the mean temperature, and a suppression of the PLD amplitude sets in upon approaching the phase transition threshold. Finally, for an insufficient temporal separation of the excitation pulses, the average temperature rises above 174 K, such that the PLD spots disappear. As expected for cumulative heating, we find that different combinations of repetition rates and fluences that correspond to the same average intensity yield the same thermal suppression (see also Supplementary Fig. S1).

We measure this temporal average over the laser-induced dynamics in sample support structures comprised of different arrangements of circular apertures in a gold film (Fig. 3), showing rather different thermal responses. This includes (i) hole arrays placed above a  $1T'$ -TaTe<sub>2</sub> sample after deposition on a SiN membrane, (ii) arrays directly suspending a  $1T'$ -



**FIG. 3 Thermal characterization of different sample supports.** (a) Example diffractogram of  $1T'$ -TaTe<sub>2</sub>. The intensity of  $(3 \times 3)$  PLD spots (red circles) measured with a continuous-wave electron beam is indicative of cumulative sample heating. (b) Schematics of the sample supports. Arrays of micrometer-sized gold apertures on top of a  $1T'$ -TaTe<sub>2</sub> thin film confine the optical excitation [structure (i)], and additionally provide an efficient heat bath [structure (ii)]. A single-hole design [structure (iii)] provides optimized thermal resistance. (c) Normalized PLD spot intensities for different average laser intensities employing the support structures in (b). The solid lines are phenomenological fits to estimate the average temperature rise. (d) Simulated temperature profiles in a hole array (top half) and in the single-hole support (bottom). The gold film shapes the initial excitation pattern (image at  $\Delta t_0$ ), and the heat dissipation unfolds in a two-step process: a local equilibration around the temperature hotspots ( $\Delta t_{1,2}$ ), followed by global cooling at reduced maximum temperatures on longer timescales ( $\Delta t_3$ ). The single-hole geometry only includes local relaxation, thereby drastically accelerating the cooling. (e) Temporal evolution of the average temperature in the central  $2\text{-}\mu\text{m}$  sample region derived from the simulation for a single-hole (red), a hole-array (black), a shadowed (blue) and a bare  $1T'$ -TaTe<sub>2</sub> sample (grey).

TaTe<sub>2</sub> flake, as well as (iii) a  $1T'$ -TaTe<sub>2</sub> film spanned across a single aperture. The gold film reflects a substantial amount of the incident laser radiation, reducing the excited sample area. Moreover, for designs (ii) and (iii), direct contact with the respective films also provides an efficient heat bath for the subsequent dissipation.

In structure (i), a square array of apertures with a diameter and separation of  $2\text{ }\mu\text{m}$  in the  $50\text{-nm}$  gold layer<sup>4</sup> shields about 80 % of the  $1T'$ -TaTe<sub>2</sub> film from the incident illumina-

tion. The mask thereby reduces the thermal load compared to a bare  $1T'$ -TaTe<sub>2</sub> sample. Nevertheless, cumulative heating suppresses the PLD spots already at intensities of around  $2\text{ }\mu\text{W}/\mu\text{m}^2$  (here:  $0.8\text{ mJ}/\text{cm}^2$  at  $254\text{ kHz}$ ), at which the average temperature increases by more than  $54\text{ K}$  [blue curve in Fig. 3(c)]. We envision such a design to be used primarily in special cases where delicate specimens such as few-layer heterostructures require a continuous support membrane. In comparison, placing the millimeter-sized  $1T'$ -TaTe<sub>2</sub> flake directly behind and in contact with the aperture array [structure (ii)] further enhances the thermal resistance by about a factor of five [black curve in Fig. 3(c)].

Heat transport simulations quantitatively capture the spatiotemporal relaxation after an instantaneous temperature increase in the different supports (Fig. 3(d), (e)); see also Supplementary Material and Supplementary Fig. S1). For an excitation structured by an aperture array, the dissipation unfolds in a two-step process. First, local equilibration of the micrometer-sized hotspots with the regions shadowed by the gold film reduces the temperature in the excited sample areas [Fig. 3(e)]. Compared to a  $1T'$ -TaTe<sub>2</sub> film, the high thermal diffusivity of gold accelerates this process, and the initial cooling is more pronounced. After the local heat bath is exhausted, i.e., when the temperatures in shadowed and unshadowed regions have equalized, the macroscopic dissipation evolves as in the case of an unstructured excitation, but with substantially reduced thermal load. Importantly, the residual heat left to dissipate depends on the number of excited holes and their distances [Fig. 3(d)].

These results illustrate the improvements gained for ultrafast electron diffraction experiments by a reduced excitation area and optimized thermal dissipation. In particular, an individual  $2\text{-}\mu\text{m}$  aperture confining the excitation, and a large heat bath provided by a  $250\text{-nm}$  thick gold film extend the thermal resistance by more than two orders of magnitude [red curves in Fig. 3(c), (e)]. As we show here, such a sample [support (iii)] can accommodate laser intensities of up to  $200\text{ }\mu\text{W}/\mu\text{m}^2$ , at which we observe minor cumulative heating, and an estimated temperature increase of around  $40\text{ K}$  (see Supplementary Material).

The enhanced thermal resistance of the different sample designs enable ultrafast electron diffraction measurements across a broad fluence range and at very high repetition rates. Support structure (ii) allows for stroboscopic probing at  $290\text{ kHz}$  [Fig. 4(b)]. In contrast, we employed a single-aperture sample [structure (iii)] in the investigation of CDW transformations in  $1T'$ -TaS<sub>2</sub> via imaging<sup>28</sup> and diffraction<sup>53</sup> at up to  $609\text{ kHz}$  repetition rate, limited by the maximum available pulse rate of the laser setup used. Investigating the structural transitions in  $1T'$ -TaTe<sub>2</sub>, we enter UED in the MHz-regime [Fig. 4(a)]<sup>49</sup>. In these measurements, the second-order PLD spots in the diffractograms recorded under highest thermal load [ $10\text{ mJ}/\text{cm}^2$  and  $2\text{ MHz}$  in Fig. 2(c)] are both clearly visible and sharp, underlining the drastically reduced cumulative heating and the high reciprocal-space resolution for the  $670\text{-nm}$  collimated electron illumination.

The structural dynamics are evident from the temporal evolution of the  $(3 \times 3)$  diffraction spot intensities which can be




FIG. 4 Nano-UED measurements at high repetition rates. (a) Delay curves for second-order ( $3 \times 3$ ) PLD spot intensities after the optical excitation in support structure (iii)<sup>49</sup>. The transition is reversibly cycled at a repetition rate of 2 MHz. Enhanced thermal dissipation leads to a recovery of the low-temperature phase after 4 ns. Insets: simulated temperature profiles as displayed in Figure 3. (b) Delay curves similar to (a), recorded at a repetition rate of 290 kHz and with a  $1T'$ -TaTe<sub>2</sub> thin film in support structure (ii). While the PLD is reestablished before the arrival of the next pump pulse, cooling times are longer than for the single-hole sample.

quantitatively mapped onto the PLD amplitude by dynamical diffraction simulations<sup>49</sup>. Higher repetition rates allow us to reduce the image acquisition times without compromising the temporal resolution or the signal-to-noise ratio, enabling the recording of detailed datasets that cover a large parameter range, and which are not influenced by long-term sample drifts. For the dynamics excited at 2 MHz [Fig. 4(a)], we integrate for a period of 90 s per set time delay, and, in conjunction with direct electron detection, derive a signal-to-noise ratio of 50. In comparison, a noise level of 5% is achieved in the measurements with support structure (ii) at 290 kHz for image acquisition times of 4 min per delay [Fig. 4(b)]. At early delays, both experiments show the temporal PLD amplitude evolution reported previously for  $1T'$ -TaTe<sub>2</sub><sup>49</sup> that is in line with the dynamics in other TMDC-CDW phases<sup>102</sup>. The structural distortions are suppressed within 500 fs, followed by a partial recovery for low and intermediate pump fluences. Presumably, the slightly larger variations in the recorded spot intensities in the second set of measurements are related to the fragility of the 50-nm gold net that carries the specimen. The optical excitation induces a global oscillation of the sample that modulates all scattered intensities at larger delays, inducing a second PLD spot suppression beyond 10 ps. Such effects could be reduced by thicker gold films, increasing the rigidity of the support. Furthermore, the thermal recovery of the low-temperature phase occurs at temporal delays outside the measurement range, but is sufficiently fast to reestablish the ( $3 \times 3$ ) PLD before the arrival of the next pump pulse af-

ter 3.5  $\mu$ s. In comparison, long-term oscillations are absent for the single-hole structure in the 2-MHz measurements, and the PLD amplitude reverts to its initial configuration after only 4 ns. Therefore, even higher thermal loads might be compatible with the sample design, particularly when combined with a larger temperature difference between the initial and the final structural state.

In conclusion, electron-source coherence and thermal dissipation limit resolution and contrast in ultrafast diffraction experiments. Both small effective electron source sizes and sample designs tailored to high-repetition rate driving are required to overcome these experimental challenges, enabling the formation of collimated electron nanobeams with high transverse momentum and temporal resolution that probe dynamics at megahertz repetition rates. An immediate benefit of smaller probe volumes and high-contrast data acquisition is the possibility to avoid micrometer spatial inhomogeneities contributing to the recorded dynamics. This includes varying crystal orientations, the influence of sample edges, and heterogeneous excitation densities. Moreover, nanoscale probe beams will enable the investigation of heterostructures comprised of different compounds, and functional devices that exploit the tunability of quantum materials<sup>103,104</sup>. For the latter, electrical contacting of thin films includes patterning with thick metallic layers that, simultaneously, can serve as laser reflection layers and efficient thermal conductors, analogous to the gold apertures in the support structures presented here. As a consequence, we expect that high repetition rates are also applicable in these types of samples.

Additionally, due to the strong interaction of electron beams with matter, quantitative data evaluations either require explicitly accounting for multiple scattering, or considering integrated diffraction spot intensities, i.e., averaging over the rocking curve of a reflection. The latter is almost always given in large specimen, as even single-crystal samples feature a locally varying morphology. Therefore, while qualitative evaluations of dynamics in different Laue zones are possible<sup>47,67</sup>, quantifying structural dynamics parallel to the incident electron illumination seems challenging for 100- $\mu$ m beams. In contrast, reducing the spatial averaging while correlating the measurements to dynamical diffraction simulations immediately enables recording and analysing rocking curve dynamics in ultrafast tilt-series electron diffraction<sup>53</sup>.

Alternatively, tilt-series diffraction may be used to map the entire reciprocal lattice by combining beam- and sample-tilting as employed in, e.g., precession electron diffraction<sup>105,106</sup>, which was recently transferred to the ultrafast time domain<sup>71</sup>. In the future, these measurements will allow for both a complete structural refinement with femtosecond resolution and the extraction of element-specific dynamics. Such characterizations may be particularly beneficial for investigations of materials with more complex unit cells<sup>107</sup>.

Beyond ultrafast diffraction measurements, the increase in coherent current gained by higher repetition rates can also directly compensate a reduction of the electron probe signal resulting from smaller beam-limiting apertures. Approaching an ideal, fully-coherent electron point source, this type of beam shaping is routinely found in continuous-wave TEM

techniques that operate at higher electron emission from the source<sup>10</sup>. As such beam-shaping leaves the transverse coherence length unchanged, sample designs as presented here seem imperative to extend the possibilities of UTEM to reach combined atomic-scale spatial and femtosecond temporal resolutions. Finally, the drastically accelerated sample cooling after optical excitation may enhance the observation of transient states in biological specimens by cryo-electron microscopy, offering a more rapid, nanosecond or even faster revitrification of samples after laser-induced ultrafast melting<sup>108,109</sup>.

## SUPPLEMENTARY MATERIAL

The Supplementary Material contains further information on the experimental setup and the sample preparation, and descriptions of the thermal transport simulations and the experimental characterizations of cumulative heating in the different sample supports.

## ACKNOWLEDGMENTS

The authors thank M. Sivis for technical support in focused ion beam milling. Furthermore, we gratefully acknowledge insightful discussions with I. Vinograd, and continued support from the Göttingen UTEM team. This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) in the Collaborative Research Centre “Atomic scale control of energy conversion” (217133147/SFB 1073, Project No. A05) and via resources from the Gottfried Wilhelm Leibniz Prize (RO 3936/4-1).

## AUTHOR CONTRIBUTIONS

T.D. and L.d.C.S. conducted the experiments and simulations, analysed the data, and prepared the specimens. C.R. directed the study. All authors discussed the results and their interpretation. T.D. and C.R. wrote the manuscript with discussions and input from all authors.

## COMPETING INTERESTS

The authors have no conflicts to disclose.

## DATA AVAILABILITY

The data that support the findings of this study are available from the corresponding author upon reasonable request.

<sup>1</sup>M. Haider, H. Rose, S. Uhlemann, E. Schwan, B. Kabius, and K. Urban, “A spherical-aberration-corrected 200 kV transmission electron microscope,” *Ultramicroscopy* **75**, 53–60 (1998).

- <sup>2</sup>B. D. A. Levin, “Direct detectors and their applications in electron microscopy for materials science,” *Journal of Physics: Materials* **4**, 042005 (2021).
- <sup>3</sup>J. Mayer, L. A. Giannuzzi, T. Kamino, and J. Michael, “TEM Sample Preparation and FIB-Induced Damage,” *MRS Bulletin* **32**, 400–407 (2007).
- <sup>4</sup>C. J. Russo and L. A. Passmore, “Ultrastable gold substrates for electron cryomicroscopy,” *Science* **346**, 1377–1380 (2014).
- <sup>5</sup>Y. Cheng, “Single-Particle Cryo-EM at Crystallographic Resolution,” *Cell* **161**, 450–457 (2015).
- <sup>6</sup>K. M. Yip, N. Fischer, E. Paknia, A. Chari, and H. Stark, “Atomic-resolution protein structure determination by cryo-EM,” *Nature* **587**, 157–161 (2020).
- <sup>7</sup>S. W. Chee, T. Lunkenbein, R. Schlögl, and B. Roldán Cuenya, “Operando Electron Microscopy of Catalysts: The Missing Cornerstone in Heterogeneous Catalysis Research?” *Chemical Reviews* **123**, 13374–13418 (2023).
- <sup>8</sup>M. C. Scott, C.-C. Chen, M. Mecklenburg, C. Zhu, R. Xu, P. Ercius, U. Dahmen, B. C. Regan, and J. Miao, “Electron tomography at 2.4-ångström resolution,” *Nature* **483**, 444–447 (2012).
- <sup>9</sup>C. Ophus, “Four-Dimensional Scanning Transmission Electron Microscopy (4D-STEM): From Scanning Nanodiffraction to Ptychography and Beyond,” *Microscopy and Microanalysis* **25**, 563–582 (2019).
- <sup>10</sup>P. W. Hawkes and J. C. H. Spence, eds., *Springer Handbook of Microscopy*, Springer Handbooks (Springer International Publishing, Cham, 2019).
- <sup>11</sup>T. van Oudheusden, E. F. de Jong, S. B. van der Geer, W. P. E. M. O. ’t Root, O. J. Luiten, and B. J. Siwick, “Electron source concept for single-shot sub-100 fs electron diffraction in the 100 keV range,” *Journal of Applied Physics* **102**, 093501 (2007).
- <sup>12</sup>S. P. Weathersby, G. Brown, M. Centurion, T. F. Chase, R. Coffee, J. Corbett, J. P. Eichner, J. C. Frisch, A. R. Fry, M. Gühr, N. Hartmann, C. Hast, R. Hettel, R. K. Jobe, E. N. Jongewaard, J. R. Lewandowski, R. K. Li, A. M. Lindenberg, I. Makasyuk, J. E. May, D. McCormick, M. N. Nguyen, A. H. Reid, X. Shen, K. Sokolowski-Tinten, T. Vecchione, S. L. Vetter, J. Wu, J. Yang, H. A. Dürr, and X. J. Wang, “Mega-electron-volt ultrafast electron diffraction at SLAC National Accelerator Laboratory,” *Review of Scientific Instruments* **86**, 073702 (2015).
- <sup>13</sup>P. Zhu, Y. Zhu, Y. Hidaka, L. Wu, J. Cao, H. Berger, J. Geck, R. Kraus, S. Pjerov, Y. Shen, R. I. Tobey, J. P. Hill, and X. J. Wang, “Femtosecond time-resolved MeV electron diffraction,” *New Journal of Physics* **17**, 063004 (2015).
- <sup>14</sup>Z.-H. He, B. Beaurepaire, J. A. Nees, G. Gallé, S. A. Scott, J. R. S. Pérez, M. G. Lagally, K. Krushelnick, A. G. R. Thomas, and J. Faure, “Capturing Structural Dynamics in Crystalline Silicon Using Chirped Electrons from a Laser Wakefield Accelerator,” *Scientific Reports* **6**, 36224 (2016).
- <sup>15</sup>X. Shen, R. K. Li, U. Lundström, T. J. Lane, A. H. Reid, S. P. Weathersby, and X. J. Wang, “Femtosecond mega-electron-volt electron microdiffraction,” *Ultramicroscopy* **184**, 172–176 (2018).
- <sup>16</sup>X. Shen, J. P. F. Nunes, J. Yang, R. K. Jobe, R. K. Li, M.-F. Lin, B. Moore, M. Niebuhr, S. P. Weathersby, T. J. A. Wolf, C. Yoneda, M. Guehr, M. Centurion, and X. J. Wang, “Femtosecond gas-phase mega-electron-volt ultrafast electron diffraction,” *Structural Dynamics* **6**, 054305 (2019).
- <sup>17</sup>B. Hafke, T. Witte, C. Brand, Th. Duden, and M. Horn-von Hoegen, “Pulsed electron gun for electron diffraction at surfaces with femtosecond temporal resolution and high coherence length,” *Review of Scientific Instruments* **90**, 045119 (2019).
- <sup>18</sup>F. Qi, Z. Ma, L. Zhao, Y. Cheng, W. Jiang, C. Lu, T. Jiang, D. Qian, Z. Wang, W. Zhang, P. Zhu, X. Zou, W. Wan, D. Xiang, and J. Zhang, “Breaking 50 Femtosecond Resolution Barrier in MeV Ultrafast Electron Diffraction with a Double Bend Achromat Compressor,” *Physical Review Letters* **124**, 134803 (2020).
- <sup>19</sup>W. H. Li, C. J. R. Duncan, M. B. Andorf, A. C. Bartnik, E. Bianco, L. Cultrera, A. Galdi, M. Gordon, M. Kaemingk, C. A. Pennington, L. F. Kourkoutis, I. V. Bazarov, and J. M. Maxson, “A kiloelectron-volt ultrafast electron micro-diffraction apparatus using low emittance semiconductor photocathodes,” *Structural Dynamics* **9**, 024302 (2022).
- <sup>20</sup>K. M. Siddiqui, D. B. Durham, F. Cropp, F. Ji, S. Paiagua, C. Ophus, N. C. Andersen, L. Jin, J. Wu, S. Wang, X. Zhang, W. You, M. Murnane, M. Centurion, X. Wang, D. S. Slaughter, R. A. Kaindl, P. Musumeci, A. M. Minor, and D. Filippetto, “Relativistic ultrafast electron diffraction at high

- repetition rates,” *Structural Dynamics* **10**, 064302 (2023).
- <sup>21</sup>F. R. Diaz, M. Mero, and K. Amini, “High-repetition-rate ultrafast electron diffraction with direct electron detection,” *Structural Dynamics* **11**, 054302 (2024).
  - <sup>22</sup>F. M. Alcorn, P. K. Jain, and R. M. van der Veen, “Time-resolved transmission electron microscopy for nanoscale chemical dynamics,” *Nature Reviews Chemistry* **7**, 256–272 (2023).
  - <sup>23</sup>D. Filippetto, P. Musumeci, R. K. Li, B. J. Siwick, M. R. Otto, M. Centurion, and J. P. F. Nunes, “Ultrafast electron diffraction: Visualizing dynamic states of matter,” *Reviews of Modern Physics* **94**, 045004 (2022).
  - <sup>24</sup>Y. Lee, K. Y. Oang, D. Kim, and H. Ihee, “A comparative review of time-resolved x-ray and electron scattering to probe structural dynamics,” *Structural Dynamics* **11**, 031301 (2024).
  - <sup>25</sup>H. Dömer and O. Bostanjoglo, “High-speed transmission electron microscope,” *Review of Scientific Instruments* **74**, 4369–4372 (2003).
  - <sup>26</sup>A. H. Zewail, “Four-Dimensional Electron Microscopy,” *Science* **328**, 187–193 (2010).
  - <sup>27</sup>R. M. van der Veen, O.-H. Kwon, A. Tissot, A. Hauser, and A. H. Zewail, “Single-nanoparticle phase transitions visualized by four-dimensional electron microscopy,” *Nature Chemistry* **5**, 395–402 (2013).
  - <sup>28</sup>T. Danz, T. Domröse, and C. Ropers, “Ultrafast nanoimaging of the order parameter in a structural phase transition,” *Science* **371**, 371–374 (2021).
  - <sup>29</sup>A. Feist, N. Bach, N. Rubiano da Silva, T. Danz, M. Möller, K. E. Priebe, T. Domröse, J. G. Gatzmann, S. Rost, J. Schauss, S. Strauch, R. Bormann, M. Sivilis, S. Schäfer, and C. Ropers, “Ultrafast transmission electron microscopy using a laser-driven field emitter: Femtosecond resolution with a high coherence electron beam,” *Ultramicroscopy* **176**, 63–73 (2017).
  - <sup>30</sup>A. J. McKenna, J. K. Eliason, and D. J. Flannigan, “Spatiotemporal Evolution of Coherent Elastic Strain Waves in a Single MoS<sub>2</sub> Flake,” *Nano Letters* **17**, 3952–3958 (2017).
  - <sup>31</sup>Y. Zhang and D. J. Flannigan, “Observation of Anisotropic Strain-Wave Dynamics and Few-Layer Dephasing in MoS<sub>2</sub> with Ultrafast Electron Microscopy,” *Nano Letters* **19**, 8216–8224 (2019).
  - <sup>32</sup>B. J. Siwick, J. R. Dwyer, R. E. Jordan, and R. J. D. Miller, “An Atomic-Level View of Melting Using Femtosecond Electron Diffraction,” *Science* **302**, 1382–1385 (2003).
  - <sup>33</sup>M. Eichberger, H. Schäfer, M. Krumova, M. Beyer, J. Demsar, H. Berger, G. Moriena, G. Sciaini, and R. J. D. Miller, “Snapshots of cooperative atomic motions in the optical suppression of charge density waves,” *Nature* **468**, 799–802 (2010).
  - <sup>34</sup>N. Erasmus, M. Eichberger, K. Haupt, I. Boshoff, G. Kassier, R. Birnurske, H. Berger, J. Demsar, and H. Schwoerer, “Ultrafast Dynamics of Charge Density Waves in 4H<sub>b</sub>-TaSe<sub>2</sub> Probed by Femtosecond Electron Diffraction,” *Physical Review Letters* **109**, 167402 (2012).
  - <sup>35</sup>V. R. Morrison, Robert. P. Chatelain, K. L. Tiwari, A. Hendaoui, A. Bruhács, M. Chaker, and B. J. Siwick, “A photoinduced metal-like phase of monoclinic VO<sub>2</sub> revealed by ultrafast electron diffraction,” *Science* **346**, 445–448 (2014).
  - <sup>36</sup>M. Gulde, S. Schweda, G. Storeck, M. Maiti, H. K. Yu, A. M. Wodtke, S. Schäfer, and C. Ropers, “Ultrafast low-energy electron diffraction in transmission resolves polymer/graphene superstructure dynamics,” *Science* **345**, 200–204 (2014).
  - <sup>37</sup>T.-R. T. Han, F. Zhou, C. D. Malliakas, P. M. Duxbury, S. D. Mahanti, M. G. Kanatzidis, and C.-Y. Ruan, “Exploration of metastability and hidden phases in correlated electron crystals visualized by femtosecond optical doping and electron crystallography,” *Science Advances* **1**, e1400173 (2015).
  - <sup>38</sup>K. Haupt, M. Eichberger, N. Erasmus, A. Rohwer, J. Demsar, K. Rossnagel, and H. Schwoerer, “Ultrafast Metamorphosis of a Complex Charge-Density Wave,” *Physical Review Letters* **116**, 016402 (2016).
  - <sup>39</sup>T. Frigge, B. Hafke, T. Witte, B. Krenzer, C. Streubühr, A. Samad Syed, V. Mikšić Trontl, I. Avigo, P. Zhou, M. Ligges, D. von der Linde, U. Bovensiepen, M. Horn-von Hoegen, S. Wippermann, A. Lücke, S. Sanna, U. Gerstmann, and W. G. Schmidt, “Optically excited structural transition in atomic wires on surfaces at the quantum limit,” *Nature* **544**, 207–211 (2017).
  - <sup>40</sup>A. Zong, X. Shen, A. Kogar, L. Ye, C. Marks, D. Chowdhury, T. Rohwer, B. Freelon, S. Weathersby, R. Li, J. Yang, J. Checkelsky, X. Wang, and N. Gedik, “Ultrafast manipulation of mirror domain walls in a charge density wave,” *Science Advances* **4**, eaau5501 (2018).
  - <sup>41</sup>S.-i. Ideta, D. Zhang, A. G. Dijkstra, S. Artyukhin, S. Keskin, R. Cingolani, T. Shimojima, K. Ishizaka, H. Ishii, K. Kudo, M. Nohara, and R. J. D. Miller, “Ultrafast dissolution and creation of bonds in IrTe<sub>2</sub> induced by photodoping,” *Science Advances* **4**, eaar3867 (2018).
  - <sup>42</sup>E. J. Sie, C. M. Nyby, C. D. Pemmaraju, S. J. Park, X. Shen, J. Yang, M. C. Hoffmann, B. K. Ofori-Okai, R. Li, A. H. Reid, S. Weathersby, E. Mannebach, N. Finney, D. Rhodes, D. Chenet, A. Antony, L. Balicas, J. Hone, T. P. Devereaux, T. F. Heinz, X. Wang, and A. M. Lindenberg, “An ultrafast symmetry switch in a Weyl semimetal,” *Nature* **565**, 61–66 (2019).
  - <sup>43</sup>J. G. Horstmann, H. Böckmann, B. Wit, F. Kurtz, G. Storeck, and C. Ropers, “Coherent control of a surface structural phase transition,” *Nature* **583**, 232–236 (2020).
  - <sup>44</sup>A. Kogar, A. Zong, P. E. Dolgirev, X. Shen, J. Straquadine, Y.-Q. Bie, X. Wang, T. Rohwer, I.-C. Tung, Y. Yang, R. Li, J. Yang, S. Weathersby, S. Park, M. E. Kozina, E. J. Sie, H. Wen, P. Jarillo-Herrero, I. R. Fisher, X. Wang, and N. Gedik, “Light-induced charge density wave in LaTe<sub>3</sub>,” *Nature Physics* **16**, 159–163 (2020).
  - <sup>45</sup>S. Ji, O. Grånäs, K. Rossnagel, and J. Weissenrieder, “Transient three-dimensional structural dynamics in 1T-TaSe<sub>2</sub>,” *Physical Review B* **101**, 094303 (2020).
  - <sup>46</sup>A. Nakamura, T. Shimojima, Y. Chiashi, M. Kamitani, H. Sakai, S. Ishiwata, H. Li, and K. Ishizaka, “Nanoscale Imaging of Unusual Photoacoustic Waves in Thin Flake VTe<sub>2</sub>,” *Nano Letters* **20**, 4932–4938 (2020).
  - <sup>47</sup>Y. Cheng, A. Zong, J. Li, W. Xia, S. Duan, W. Zhao, Y. Li, F. Qi, J. Wu, L. Zhao, P. Zhu, X. Zou, T. Jiang, Y. Guo, L. Yang, D. Qian, W. Zhang, A. Kogar, M. W. Zuerch, D. Xiang, and J. Zhang, “Light-induced dimension crossover dictated by excitonic correlations,” *Nature Communications* **13**, 963 (2022).
  - <sup>48</sup>S. R. Tauchert, M. Volkov, D. Ehberger, D. Kazenwadel, M. Evers, H. Lange, A. Donges, A. Book, W. Kreuzpaintner, U. Nowak, and P. Baum, “Polarized phonons carry angular momentum in ultrafast demagnetization,” *Nature* **602**, 73–77 (2022).
  - <sup>49</sup>T. Domröse and C. Ropers, “Femtosecond trimer quench in the unconventional charge-density-wave material 1T'-TaTe<sub>2</sub>,” *Physical Review B* **110**, 085155 (2024).
  - <sup>50</sup>A. Ungeheuer, N. Bach, M. T. Mir, A. S. Hassanien, L. Nöding, T. Baumert, S. Schäfer, and A. Sentfleben, “Coherent acoustic phonons in a coupled hexagonal boron nitride–graphite heterostructure,” *Structural Dynamics* **11**, 014501 (2024).
  - <sup>51</sup>S. Vogelgesang, G. Storeck, J. G. Horstmann, T. Diekmann, M. Sivilis, S. Schramm, K. Rossnagel, S. Schäfer, and C. Ropers, “Phase ordering of charge density waves traced by ultrafast low-energy electron diffraction,” *Nature Physics* **14**, 184–190 (2018).
  - <sup>52</sup>G. Storeck, K. Rossnagel, and C. Ropers, “Ultrafast spot-profile LEED of a charge-density wave phase transition,” *Applied Physics Letters* **118**, 221603 (2021).
  - <sup>53</sup>T. Domröse, T. Danz, S. F. Schaible, K. Rossnagel, S. V. Yalunin, and C. Ropers, “Light-induced hexatic state in a layered quantum material,” *Nature Materials* **22**, 1345–1351 (2023).
  - <sup>54</sup>Y. Cheng, A. Zong, L. Wu, Q. Meng, W. Xia, F. Qi, P. Zhu, X. Zou, T. Jiang, Y. Guo, J. van Wezel, A. Kogar, M. W. Zuerch, J. Zhang, Y. Zhu, and D. Xiang, “Ultrafast formation of topological defects in a two-dimensional charge density wave,” *Nature Physics* **20**, 54–60 (2024).
  - <sup>55</sup>L. Waldecker, R. Bertoni, H. Hübener, T. Brumme, T. Vasileiadis, D. Zahn, A. Rubio, and R. Ernstorfer, “Momentum-resolved view of electron-phonon coupling in multilayer WSe<sub>2</sub>,” *Physical Review Letters* **119**, 036803 (2017).
  - <sup>56</sup>M. R. Otto, J.-H. Pöhl, L. P. René de Cotret, M. J. Stern, M. Sutton, and B. J. Siwick, “Mechanisms of electron-phonon coupling unraveled in momentum and time: The case of soft phonons in TiSe<sub>2</sub>,” *Science Advances* **7**, eabf2810 (2021).
  - <sup>57</sup>H. A. Dürr, R. Ernstorfer, and B. J. Siwick, “Revealing momentum-dependent electron–phonon and phonon–phonon coupling in complex materials with ultrafast electron diffuse scattering,” *MRS Bulletin* **46**, 731–737 (2021).
  - <sup>58</sup>F. Kurtz, T. N. Dauwe, S. V. Yalunin, G. Storeck, J. G. Horstmann, H. Böckmann, and C. Ropers, “Non-thermal phonon dynamics and a quenched exciton condensate probed by surface-sensitive electron diffraction,” *Nature Materials* **23**, 890–897 (2024).

- <sup>59</sup>D. N. Basov, R. D. Averitt, and D. Hsieh, “Towards properties on demand in quantum materials,” *Nature Materials* **16**, 1077–1088 (2017).
- <sup>60</sup>M. Buzzi, M. Först, R. Mankowsky, and A. Cavalleri, “Probing dynamics in quantum materials with femtosecond X-rays,” *Nature Reviews Materials* **3**, 299–311 (2018).
- <sup>61</sup>A. de la Torre, D. M. Kennes, M. Claassen, S. Gerber, J. W. McIver, and M. A. Sentef, “Colloquium: Nonthermal pathways to ultrafast control in quantum materials,” *Reviews of Modern Physics* **93**, 041002 (2021).
- <sup>62</sup>D. Kazenwadel, N. Neathery, S. Prakash, A. Ariando, and P. Baum, “Cooling times in femtosecond pump-probe experiments of phase transitions with latent heat,” *Physical Review Research* **5**, 043077 (2023).
- <sup>63</sup>G. Sciaini, M. Harb, S. G. Kruglik, T. Payer, C. T. Hebeisen, F.-J. M. zu Heringdorf, M. Yamaguchi, M. H.-v. Hoegen, R. Ernstorfer, and R. J. D. Miller, “Electronic acceleration of atomic motions and disordering in bismuth,” *Nature* **458**, 56–59 (2009).
- <sup>64</sup>S. Sun, L. Wei, Z. Li, G. Cao, Y. Liu, W. J. Lu, Y. P. Sun, H. Tian, H. Yang, and J. Li, “Direct observation of an optically induced charge density wave transition in 1T-TaSe<sub>2</sub>,” *Physical Review B* **92**, 224303 (2015).
- <sup>65</sup>J. Li, W.-G. Yin, L. Wu, P. Zhu, T. Konstantinova, J. Tao, J. Yang, S.-W. Cheong, F. Carbone, J. A. Misewich, J. P. Hill, X. Wang, R. J. Cava, and Y. Zhu, “Dichotomy in ultrafast atomic dynamics as direct evidence of polaron formation in manganites,” *npj Quantum Materials* **1**, 1–7 (2016).
- <sup>66</sup>Z. Tao, F. Zhou, T.-R. T. Han, D. Torres, T. Wang, N. Sepulveda, K. Chang, M. Young, R. R. Lunt, and C.-Y. Ruan, “The nature of photoinduced phase transition and metastable states in vanadium dioxide,” *Scientific Reports* **6**, 38514 (2016).
- <sup>67</sup>L. Le Guyader, T. Chase, A. H. Reid, R. K. Li, D. Svetin, X. Shen, T. Vecchione, X. J. Wang, D. Mihailovic, and H. A. Dürr, “Stacking order dynamics in the quasi-two-dimensional dichalcogenide 1T-TaS<sub>2</sub> probed with MeV ultrafast electron diffraction,” *Structural Dynamics* **4**, 044020 (2017).
- <sup>68</sup>K. M. Siddiqui, D. B. Durham, F. Cropp, C. Ophus, S. Rajpurohit, Y. Zhu, J. D. Carlström, C. Stavrakas, Z. Mao, A. Raja, P. Musumeci, L. Z. Tan, A. M. Minor, D. Filippetto, and R. A. Kaindl, “Ultrafast optical melting of trimer superstructure in layered 1T'-TaTe<sub>2</sub>,” *Communications Physics* **4**, 1–7 (2021).
- <sup>69</sup>A. Sood, X. Shen, Y. Shi, S. Kumar, S. J. Park, M. Zajac, Y. Sun, L.-Q. Chen, S. Ramanathan, X. Wang, W. C. Chueh, and A. M. Lindenberg, “Universal phase dynamics in VO<sub>2</sub> switches revealed by ultrafast operando diffraction,” *Science* **373**, 352–355 (2021).
- <sup>70</sup>C. Xu, C. Jin, Z. Chen, Q. Lu, Y. Cheng, B. Zhang, F. Qi, J. Chen, X. Yin, G. Wang, D. Xiang, and D. Qian, “Transient dynamics of the phase transition in VO<sub>2</sub> revealed by mega-electron-volt ultrafast electron diffraction,” *Nature Communications* **14**, 1265 (2023).
- <sup>71</sup>T. Shiratori, J. Koga, T. Shimojima, K. Ishizaka, and A. Nakamura, “Development of ultrafast four-dimensional precession electron diffraction,” (2024), arXiv:2407.06708 [cond-mat].
- <sup>72</sup>S. Wall, B. Krenzer, S. Wippermann, S. Sanna, F. Klasing, A. Hanisch-Blicharski, M. Kammler, W. G. Schmidt, and M. Horn-von Hoegen, “Atomistic Picture of Charge Density Wave Formation at Surfaces,” *Physical Review Letters* **109**, 186101 (2012).
- <sup>73</sup>D.-S. Yang, P. Baum, and A. H. Zewail, “Ultrafast electron crystallography of the cooperative reaction path in vanadium dioxide,” *Structural Dynamics* **3**, 034304 (2016).
- <sup>74</sup>Alternatively, emittances may be specified in  $\mu\text{m mrad}$ .
- <sup>75</sup>L. Piazza, D. Masiel, T. LaGrange, B. Reed, B. Barwick, and F. Carbone, “Design and implementation of a fs-resolved transmission electron microscope based on thermionic gun technology,” *Chemical Physics* **423**, 79–84 (2013).
- <sup>76</sup>D. R. Cremons, D. A. Plemmons, and D. J. Flannigan, “Defect-mediated phonon dynamics in TaS<sub>2</sub> and WSe<sub>2</sub>,” *Structural Dynamics* **4**, 044019 (2017).
- <sup>77</sup>F. Houdellier, G. Caruso, S. Weber, M. Kociak, and A. Arbouet, “Development of a high brightness ultrafast Transmission Electron Microscope based on a laser-driven cold field emission source,” *Ultramicroscopy* **186**, 128–138 (2018).
- <sup>78</sup>C. Zhu, D. Zheng, H. Wang, M. Zhang, Z. Li, S. Sun, P. Xu, H. Tian, Z. Li, H. Yang, and J. Li, “Development of analytical ultrafast transmission electron microscopy based on laser-driven Schottky field emission,” *Ultramicroscopy* **209**, 112887 (2020).
- <sup>79</sup>P. K. Olshin, M. Drabells, and U. J. Lorenz, “Characterization of a time-resolved electron microscope with a Schottky field emission gun,” *Structural Dynamics* **7**, 054304 (2020).
- <sup>80</sup>J. Kuttruff, D. Nabben, A.-C. Zimmermann, A. Ryabov, and P. Baum, “Terahertz control and timing correlations in a transmission electron microscope,” *Science Advances* **10**, ead16543 (2024).
- <sup>81</sup>J. T. Weber and S. Schäfer, “Electron Imaging of Nanoscale Charge Distributions Induced by Femtosecond Light Pulses,” *Nano Letters* **24**, 5746–5753 (2024).
- <sup>82</sup>X. Fu, E. Wang, Y. Zhao, A. Liu, E. Montgomery, V. J. Gokhale, J. J. Gorman, C. Jing, J. W. Lau, and Y. Zhu, “Direct visualization of electromagnetic wave dynamics by laser-free ultrafast electron microscopy,” *Science Advances* **6**, eabc3456 (2020).
- <sup>83</sup>R. Dahan, A. Gorlach, U. Haeusler, A. Karnieli, O. Eyal, P. Yousefi, M. Segev, A. Arie, G. Eisenstein, P. Hommelhoff, and I. Kaminer, “Imprinting the quantum statistics of photons on free electrons,” *Science* **373**, eabj7128 (2021).
- <sup>84</sup>Y.-J. Kim, H.-W. Nho, S. Ji, H. Lee, H. Ko, J. Weissenrieder, and O.-H. Kwon, “Femtosecond-resolved imaging of a single-particle phase transition in energy-filtered ultrafast electron microscopy,” *Science Advances* **9**, eadd5375 (2023).
- <sup>85</sup>B. Barwick, D. J. Flannigan, and A. H. Zewail, “Photon-induced near-field electron microscopy,” *Nature* **462**, 902–906 (2009).
- <sup>86</sup>A. Feist, K. E. Echternkamp, J. Schauss, S. V. Yalunin, S. Schäfer, and C. Ropers, “Quantum coherent optical phase modulation in an ultrafast transmission electron microscope,” *Nature* **521**, 200–203 (2015).
- <sup>87</sup>D. A. Plemmons, S. Tae Park, A. H. Zewail, and D. J. Flannigan, “Characterization of fast photoelectron packets in weak and strong laser fields in ultrafast electron microscopy,” *Ultramicroscopy* **146**, 97–102 (2014).
- <sup>88</sup>B. J. Siwick, J. R. Dwyer, R. E. Jordan, and R. J. D. Miller, “Ultrafast electron optics: Propagation dynamics of femtosecond electron packets,” *Journal of Applied Physics* **92**, 1643–1648 (2002).
- <sup>89</sup>S. Collin, M. Merano, M. Gatri, S. Sonderegger, P. Renucci, J.-D. Ganière, and B. Deveaud, “Transverse and longitudinal space-charge-induced broadenings of ultrafast electron packets,” *Journal of Applied Physics* **98**, 094910 (2005).
- <sup>90</sup>X. Wang, S. Nie, H. Park, J. Li, R. Clinite, R. Li, X. Wang, and J. Cao, “Measurement of femtosecond electron pulse length and the temporal broadening due to space charge,” *Review of Scientific Instruments* **80**, 013902 (2009).
- <sup>91</sup>M. Aidelsburger, F. O. Kirchner, F. Krausz, and P. Baum, “Single-electron pulses for ultrafast diffraction,” *Proceedings of the National Academy of Sciences* **107**, 19714–19719 (2010).
- <sup>92</sup>R. Haindl, A. Feist, T. Domröse, M. Möller, J. H. Gaida, S. V. Yalunin, and C. Ropers, “Coulomb-correlated electron number states in a transmission electron microscope beam,” *Nature Physics* **19**, 1410–1417 (2023).
- <sup>93</sup>T. Sörgel, J. Nuss, U. Wedig, R. K. Kremer, and M. Jansen, “A new low temperature modification of TaTe<sub>2</sub>—Comparison to the room temperature and the hypotheticalal 1T-TaTe<sub>2</sub> modification,” *Materials Research Bulletin Special Issue Dedicated to Prof. Gerard Ferey*, **41**, 987–1000 (2006).
- <sup>94</sup>I. El Baggari, N. Sivasdas, G. M. Stiehl, J. Waelder, D. C. Ralph, C. J. Fennie, and L. F. Kourkoutis, “Direct Visualization of Trimerized States in 1T'-TaTe<sub>2</sub>,” *Physical Review Letters* **125**, 165302 (2020).
- <sup>95</sup>K. Rossnagel, “On the origin of charge-density waves in select layered transition-metal dichalcogenides,” *Journal of Physics: Condensed Matter* **23**, 213001 (2011).
- <sup>96</sup>A. M. Lindenberg, I. Kang, S. L. Johnson, T. Missalla, P. A. Heimann, Z. Chang, J. Larsson, P. H. Bucksbaum, H. C. Kapteyn, H. A. Padmore, R. W. Lee, J. S. Wark, and R. W. Falcone, “Time-Resolved X-Ray Diffraction from Coherent Phonons during a Laser-Induced Phase Transition,” *Physical Review Letters* **84**, 111–114 (2000).
- <sup>97</sup>P. Beaud, A. Caviezel, S. O. Mariager, L. Rettig, G. Ingold, C. Dornes, S.-W. Huang, J. A. Johnson, M. Radovic, T. Huber, T. Kubacka, A. Ferrer, H. T. Lemke, M. Chollet, D. Zhu, J. M. Glowina, M. Sikorski, A. Robert, H. Wadati, M. Nakamura, M. Kawasaki, Y. Tokura, S. L. Johnson, and U. Staub, “A time-dependent order parameter for ultrafast photoinduced phase transitions,” *Nature Materials* **13**, 923–927 (2014).
- <sup>98</sup>S. Gerber, S.-L. Yang, D. Zhu, H. Soifer, J. A. Sobota, S. Rebec, J. J. Lee, T. Jia, B. Moritz, C. Jia, A. Gauthier, Y. Li, D. Leuenberger, Y. Zhang, L. Chaix, W. Li, H. Jang, J.-S. Lee, M. Yi, G. L. Dakovski, S. Song,



- J. M. Glownia, S. Nelson, K. W. Kim, Y.-D. Chuang, Z. Hussain, R. G. Moore, T. P. Devereaux, W.-S. Lee, P. S. Kirchmann, and Z.-X. Shen, “Femtosecond electron-phonon lock-in by photoemission and x-ray free-electron laser,” *Science* **357**, 71–75 (2017).
- <sup>99</sup>C. Laulhé, T. Huber, G. Lantz, A. Ferrer, S. O. Mariager, S. Grübel, J. Rittmann, J. A. Johnson, V. Esposito, A. Lübcke, L. Huber, M. Kubli, M. Savoini, V. L. R. Jacques, L. Cario, B. Corraze, E. Janod, G. Ingold, P. Beaud, S. L. Johnson, and S. Ravy, “Ultrafast Formation of a Charge Density Wave State in 1T-TaS<sub>2</sub>: Observation at Nanometer Scales Using Time-Resolved X-Ray Diffraction,” *Physical Review Letters* **118**, 247401 (2017).
- <sup>100</sup>A. Singer, J. G. Ramirez, I. Valmianski, D. Cela, N. Hua, R. Kukreja, J. Wingert, O. Kovalchuk, J. M. Glownia, M. Sikorski, M. Chollet, M. Holt, I. K. Schuller, and O. G. Shpyrko, “Nonequilibrium Phase Precursors during a Photoexcited Insulator-to-Metal Transition in V<sub>2</sub>O<sub>3</sub>,” *Physical Review Letters* **120**, 207601 (2018).
- <sup>101</sup>A. S. Johnson, E. Pastor, S. Batlle-Porro, H. Benzidi, T. Katayama, G. A. de la Peña Muñoz, V. Krapivin, S. Kim, N. López, M. Trigo, and S. E. Wall, “All-optical seeding of a light-induced phase transition with correlated disorder,” *Nature Physics* **20**, 970–975 (2024).
- <sup>102</sup>S. Hellmann, T. Rohwer, M. Kalläne, K. Hanff, C. Sohrt, A. Stange, A. Carr, M. M. Murnane, H. C. Kapteyn, L. Kipp, M. Bauer, and K. Rossnagel, “Time-domain classification of charge-density-wave insulators,” *Nature Communications* **3**, 1069 (2012).
- <sup>103</sup>D. Jariwala, V. K. Sangwan, L. J. Lauhon, T. J. Marks, and M. C. Hersam, “Emerging Device Applications for Semiconducting Two-Dimensional Transition Metal Dichalcogenides,” *ACS Nano* **8**, 1102–1120 (2014), 24476095.
- <sup>104</sup>K. F. Mak and J. Shan, “Photonics and optoelectronics of 2D semiconductor transition metal dichalcogenides,” *Nature Photonics* **10**, 216–226 (2016).
- <sup>105</sup>E. Mugnaioli, T. Gorelik, and U. Kolb, ““Ab initio” structure solution from electron diffraction data obtained by a combination of automated diffraction tomography and precession technique,” *Ultramicroscopy* **109**, 758–765 (2009).
- <sup>106</sup>M. Gemmi, E. Mugnaioli, T. E. Gorelik, U. Kolb, L. Palatinus, P. Boullay, S. Hovmöller, and J. P. Abrahams, “3D Electron Diffraction: The Nanocrystallography Revolution,” *ACS Central Science* **5**, 1315–1329 (2019).
- <sup>107</sup>R. Mankowsky, M. Först, T. Loew, J. Porras, B. Keimer, and A. Cavalleri, “Coherent modulation of the YBa<sub>2</sub>Cu<sub>3</sub>O<sub>6+x</sub> atomic structure by displacive stimulated ionic Raman scattering,” *Physical Review B* **91**, 094308 (2015).
- <sup>108</sup>O. F. Harder, J. M. Voss, P. K. Olshin, M. Drabbels, and U. J. Lorenz, “Microsecond melting and revitrification of cryo samples: Protein structure and beam-induced motion,” *Acta Crystallographica Section D: Structural Biology* **78**, 883–889 (2022).
- <sup>109</sup>G. Bongiovanni, O. F. Harder, M. Drabbels, and U. J. Lorenz, “Microsecond melting and revitrification of cryo samples with a correlative light-electron microscopy approach,” *Frontiers in Molecular Biosciences* **9** (2022), 10.3389/fmolb.2022.1044509.

Supplementary Material for

# Megahertz cycling of ultrafast structural dynamics enabled by nanosecond thermal dissipation

Till Domröse,<sup>1,2</sup> Leonardo da Camara Silva,<sup>1,2</sup> and Claus Ropers<sup>1,2, a)</sup>

<sup>1)</sup>Department of Ultrafast Dynamics, Max Planck Institute for Multidisciplinary Sciences, 37077 Göttingen, Germany

<sup>2)</sup>4th Physical Institute – Solids and Nanostructures, University of Göttingen, 37077 Göttingen, Germany

## I. SETUP AND DATA ACQUISITIONS

The Göttingen UTEM is a modified “JEOL JEM-2100F”, equipped with a Schottky-type ZrO/W emitter. Our laser setup is a “Light Conversion Carbide” (40 fs pulse duration, 1030 nm wavelength, up to 2 MHz repetition rate) whose output is split into two optical paths. A fraction is frequency-doubled and used for the generation of ultrashort electron pulses via linear photoemission by illuminating the electron emitter. The remaining laser light is coupled into an optical parametric amplifier (“Light Conversion Orpheus F”) where the laser pulses are converted to 800 nm wave length and coupled into the microscope’s column, illuminating the sample under close to perpendicular incidence. The laser focus in the sample plane amounts to 50  $\mu\text{m}$  full-width at half-maximum. Electron diffractograms are recorded with a direct electron detector (“Direct Electron DE16”) in electron-counting mode. The thermal characterizations of the different support structures include image acquisition times of 100 s per measured laser intensity. For the time-resolved data, we integrate for a total of 90 s per delay in the 2 MHz measurements, and for 4 min in the measurements conducted at 290 kHz. The spectroscopic electron pulse characterizations were conducted using an electron spectrometer and energy filtering device (“CEOS CEFID”), and spectrograms were recorded with a hybrid pixel detector based on the Timepix3 chip (“Amsterdam Scientific Instrument’s Cheeta T3”). The TEM sample holder for cooling with liquid nitrogen was a “Gatan Liquid Nitrogen Cooling Holder, model 636”. The estimated base temperature is 120 K.

## II. SAMPLE PREPARATION

Thin film  $1T'$ -TaTe<sub>2</sub> crystals (“HQ graphene”) were cut to a nominal thickness of 50 nm by Ultramicrotomy. For sample design (i), the  $1T'$ -TaTe<sub>2</sub> flakes were transferred onto a 50 nm silicon nitride membrane spanned over a standard 3 mm silicon wafer. The gold aperture arrays used for support structures (i) and (ii) are commercially available TEM grids (“Quantifoil UltraAuFoil R2/2”) with 2  $\mu\text{m}$ -sized holes and 4  $\mu\text{m}$  pitch<sup>1</sup>. The gold film has a thickness of 50 nm.

Placing the gold masks over the silicon wafer with micrometer precision is realized with a custom-made apparatus, and the arrays are glued to the silicon wafers with poly(methyl 2-methylpropenoate). Sample support (ii) features the same TEM grids, but the  $1T'$ -TaTe<sub>2</sub> specimen was suspended onto the sample carrier directly. Finally, support (iii) consists of a 250 nm gold layer applied to a commercially available silicon-nitride TEM membrane by argon plasma sputtering. Transparency for high-energy electrons was ensured by placing the  $1T'$ -TaTe<sub>2</sub> thin film above a hole with a diameter of 2  $\mu\text{m}$  drilled by focus ion beam milling. Optimal thermal properties of all sample designs was achieved by placing the samples in the TEM with the gold-side facing the laser illumination. Besides investigations of structural dynamics by electron diffraction, such a sample design can also be employed to investigate magnetization dynamics via x-ray microscopy at up to 50 MHz rates<sup>2,3</sup>.

## III. THERMAL RESISTANCE OF DIFFERENT SAMPLE SUPPORT STRUCTURES

### A. Thermal transport simulations

In addition to the experimental measurements, we evaluate the suitability of the different sample designs for high-repetition-rate nano-UED by means of thermal transport simulations [cf. Fig. S1 and Fig. 3 in the main text]. Solving the heat diffusion equation in two dimensions, we assume that the heat flow in the investigated thin films predominantly unfolds laterally. The temporal evolution of a temperature profile  $T(x, y, t)$  in a two-dimensional coordinate system  $(x, y)$  at time  $t$  then follows

$$\frac{1}{\alpha} \frac{\partial T}{\partial t} = \frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2}, \quad (\text{S1})$$

where  $\alpha = \frac{\lambda}{\rho c_p}$  is the thermal diffusivity. The associated material parameters, i.e., the thermal conductivity  $\lambda$ , the mass density  $\rho$  and the heat capacity  $c_p$  of  $1T'$ -TaTe<sub>2</sub> and gold are listed in Table I.

For a single material and a simple, gaussian-shaped initial temperature profile,

$$T(x, y, 0) = T_{\text{max}} \exp \left[ -\frac{x^2 + y^2}{2\sigma^2} \right]. \quad (\text{S2})$$

<sup>a)</sup>Corresponding author: claus.ropers@mpinat.mpg.de




FIG. S1 **Thermal characterization of sample support structures, and heat diffusion simulations.** (a)-(c) Details on the thermal characterizations of the different sample supports described in the main text. The intensity of the  $(3 \times 3)$  PLD satellite spots normalized by the intensity of the main lattice reflections for different fluences and repetition rates is a measure of cumulative sample heating. The average temperature increase is more pronounced in support structure (i) than in structure (ii), and suppressed most efficiently in support structure (iii). (d) Temperature evolution in the central hole for the geometries depicted in (f). The early-stage dynamics are governed by the hole diameter, where smaller values lead to a faster initial relaxation. The temperature evolution at later times is determined by the relative pitch of the gold grid, i.e., the hole-diameter to hole-distance ratio. A larger available heat bath and the reflection of the incident excitation enable a faster dissipation. (e) Temperature evolution after the spatially structured excitation, illustrating the transition from local thermal relaxation, given by dynamics within the individual holes, to global heat dissipation determined by the overall input of heat and the hole-to-hole distance. (f) Schematic sample geometry for the thermal transport simulations. We assume a spatially structured thermal diffusivity, i.e., holes possessing the thermal properties of  $1T'$ -TaTe<sub>2</sub> (grey) within a gold film (gold). Furthermore, the aperture array structures the optical excitation profile.

Equation S1 can be solved with the heat kernel<sup>4</sup>

$$H(x', y', t) = \frac{1}{4\pi\alpha t} \exp\left[-\frac{(x'^2 + y'^2)}{4\alpha t}\right], \quad (\text{S3})$$

such that

$$T(x, y, t) = T_{\max} \frac{2\sigma^2}{4\alpha t + 2\sigma^2} \exp\left[\frac{-(x^2 + y^2)}{4\alpha t + 2\sigma^2}\right]. \quad (\text{S4})$$

Accordingly, for large times  $t$ , the decay time  $\tau$  associated with a critical decay of the initial maximum temperature  $T_{\max}$  scales quadratically with the width  $\sigma$  of the initial temperature distribution. Qualitatively, this already captures the achieved enhancement of the available repetition rate by shadowing parts of the  $1T'$ -TaTe<sub>2</sub> specimen which confines the excitation to a few micrometers.

In order to account for spatial heterogeneities, we integrate equation S1 numerically, considering spatially-dependent

$T(x, y, 0)$  and  $\alpha(x, y)$  as given by the sample supports [see Fig. S1(f) and Fig. 3(b) in the main text]. The holes and the surrounding regions are modelled with the thermal properties of  $1T'$ -TaTe<sub>2</sub> and gold, respectively. The initial temperature profile  $T(x, y, 0)$  is given by a two-dimensional Gaussian with a full-width at half-maximum of  $50\mu\text{m}$ , superimposed with the hole pattern of the simulated sample: as the gold film reflects the incoming laser light,  $T(x, y, 0) = 0$  where  $\alpha(x, y) = \alpha_{\text{Gold}}$ . Throughout the temporal evolution of  $T(x, y, t)$ , we evaluate the temperature in the sample region of interest by taking the average within the central hole of the simulation area.

The results are depicted in Figure 3(d) and (e) in the main text, and in Figure S1(d) and (e). An efficient thermal management depends on two factors: the size of the temperature hotspots, and the overall amount of absorbed heat. The former is given by the hole diameter, while the number and the distance of the holes within the optically excited region de-

termines the latter. Accordingly, the fastest cooling time is achieved for the sample used in the measurements at 2 MHz, i.e., a single 2- $\mu\text{m}$  hole in an otherwise closed gold film. Our simulations yield a recovery of the initial sample temperature after around 100 ns. In contrast, heat dissipation in a bare 1T'-TaTe<sub>2</sub> thin film with significantly lower thermal diffusivity takes several microseconds, even without the effect of cumulative heating, i.e., repetitive laser excitation.

The dynamics in the aperture-array sample supports unfold as an intermediate between these two cases. During the first few nanoseconds, the temperature in the individual holes closely follows the case of the single-hole structure as the dissipation is given by local heat flow, and thus determined by the hole diameter. This fast thermal relaxation persists until the width of the individual temperature hotspots approaches their initial distance. From here on,  $T(x, y, t)$  qualitatively evolves similar to the excitation of a bare gold film after a temperature increase with reduced magnitude. The available unexcited heat bath makes these sample designs suitable for UED experiments with repetition rates in the kHz-regime, as exemplified by the curves shown in Figure 4(b) in the main text. Furthermore, investigations of structural dynamics that can accommodate a larger degree of cumulative heating due to, e.g., a larger difference between the base and the phase transition temperature, may further extend the range of available repetition rates. Additionally, smaller hole diameters for a faster initial thermal relaxation, or larger gold array pitches to increase the available heat bath may have similar effects [Fig. 4(d)].

	1T'-TaTe <sub>2</sub>	Gold
molar mass $M$ [g/mol]	436	197
density $\rho$ [g/cm <sup>3</sup> ]	9.3 <sup>5</sup>	19.3 <sup>6</sup>
thermal conductivity $\lambda$ [W/(m·K)]	1.4 <sup>7</sup>	317 <sup>6</sup>
heat capacity $C_p$	60J/(mol·K) <sup>5</sup>	129J/(kg·K) <sup>6</sup>
thermal diffusivity $\alpha$ [ $\mu\text{m}^2/\text{s}$ ]	1.1	127

TABLE I Parameters used in the heat transport simulations.

## B. Details on the experimental characterizations

Figure S1(a)–(c) display the PLD spot intensities in the different support structures under variable thermal load, normalized by the mean intensity of the main lattice spots. In

principle, these measurements average over a thermal PLD suppression where cumulative heating reduces the spot intensity as the system moves closer to the threshold, and over times where, transiently, the PLD spot amplitude disappears completely due to the structural transition. In the ultrafast measurements, however, the sample recovers its initial low-temperature phase after a full quench already within 4 ns, whereas the laser pulse separation amounts to 500 ns. Consequently, the transient dynamics contribute around 1 % to the time-averaged spot intensities. For simplicity, we therefore only consider thermal effects, and evaluate the laser-induced temperature change  $\Delta T$  with a phenomenological model that includes a minimal set of parameters. We find that a square-root dependence of the PLD spot intensity  $I_{\text{PLD}}$  on  $\Delta T$  captures the observed abrupt spot suppression expected for a first-order transition close to the threshold. Specifically,

$$I_{\text{PLD}}(\Delta T) = I_0 \sqrt{1 - g \frac{\Delta T}{T_C - T_0}}, \quad (\text{S5})$$

with the maximum PLD spot intensity  $I_0$  at the estimated base temperature  $T_0 = 120\text{K}$ , the critical temperature  $T_C = 174\text{K}$ <sup>5</sup>, and a scaling factor  $g$  describing the thermal resistance of the individual sample supports. Assuming that  $\Delta T$  is proportional to the average laser intensity, the fits to the recorded data are displayed in Figure 3(c) in the main text. A complete spot suppression corresponds to cumulative heating by  $\Delta T = 54\text{K}$ , observed in structure (i) and (ii). Evaluating Equation S5 at the highest laser intensity applied, we estimate a maximum temperature increase  $\Delta T$  of 40 K in structure (iii). The observed relative PLD spot suppression from 8 % to 5 % [Fig. S1(c)] corresponds to a 20 % reduction of the PLD amplitude.

<sup>1</sup>C. J. Russo and L. A. Passmore, "Ultrastable gold substrates for electron cryomicroscopy," *Science* **346**, 1377–1380 (2014).

<sup>2</sup>S. Zayko, O. Kfir, M. Heigl, M. Lohmann, M. Sivis, M. Albrecht, and C. Ropers, "Ultrafast high-harmonic nanoscopy of magnetization dynamics," *Nature Communications* **12**, 6337 (2021).

<sup>3</sup>K. Gerlinger, B. Pfau, M. Hennecke, L.-M. Kern, I. Will, T. Noll, M. Weigand, J. Gräfe, N. Träger, M. Schneider, C. M. Günther, D. Engel, G. Schütz, and S. Eisebitt, "Pump-probe x-ray microscopy of photo-induced magnetization dynamics at MHz repetition rates," *Structural Dynamics* **10**, 024301 (2023).

<sup>4</sup>T. Rother, *Green's Functions in Classical Physics*, Lecture Notes in Physics, Vol. 938 (Springer International Publishing, Cham, 2017).

<sup>5</sup>T. Sörgel, J. Nuss, U. Wedig, R. K. Kremer, and M. Jansen, "A new low temperature modification of TaTe<sub>2</sub>—Comparison to the room temperature and the hypothetical 1T'-TaTe<sub>2</sub> modification," *Materials Research Bulletin Special Issue Dedicated to Prof. Gerard Ferey*, **41**, 987–1000 (2006).

<sup>6</sup>W. M. Haynes, ed., *CRC Handbook of Chemistry and Physics*, 97th ed. (CRC Press, Boca Raton, 2016).

<sup>7</sup>L. H. Brixner, "Preparation and properties of the single crystalline AB<sub>2</sub>-type selenides and tellurides of niobium, tantalum, molybdenum and tungsten," *Journal of Inorganic and Nuclear Chemistry* **24**, 257–263 (1962).