A Family of LZ78-based Universal Sequential Probability Assignments

Naomi Sagan and Tsachy Weissman

Abstract

We propose and study a family of universal sequential probability assignments on individual sequences, based on the incremental parsing procedure of the Lempel-Ziv (LZ78) compression algorithm. We show that the normalized log loss under any of these models converges to the normalized LZ78 codelength, uniformly over all individual sequences. To establish the universality of these models, we consolidate a set of results from the literature relating finite-state compressibility to optimal log-loss under Markovian and finite-state models. We also consider some theoretical and computational properties of these models when viewed as probabilistic sources. Finally, we present experimental results showcasing the potential benefit of using this family—as models and as sources—for compression, generation, and classification.

Index Terms

LZ78, universal compression, sequential probability assignment, finite-state compressibility.

I. INTRODUCTION

I N the celebrated [1], [2], Lempel and Ziv introduced two compression schemes that are universal; *i.e.*, achieving, among other things, the fundamental limits of compression in an individual sequence setting. In particular, LZ78 [2] incrementally parses a sequence into phrases based on an efficiently-computable prefix tree. Since then, LZ78 (and, to a lesser extent, LZ77) have been used in numerous universal sequential schemes in probability modeling, decision making, filtering, *etc.*

Intuition behind the universality of LZ78 via a prefix-tree-based probability model and arithmetic coding [3] is described in [4], hinting at the use of LZ78 for universal sequence modeling in the process. In [5], a similar probability model is used for universal gambling, and the model is later used in [6] for universal sequence prediction. [6] also establishes a correspondence between finite-state compressibility and finite-state predictability under Hamming prediction loss, and [7] establishes part of a similar result under log loss. [8] explores optimality in different classes of sequential modeling for individual sequences, concluding that, for any bounded loss function, Markovian schemes asymptotically achieve the same performance as finite state machines. In [9], an LZ78-based scheme is applied to universal decoding of finite-state channels where the channel statistics are unknown. [10] uses several prefix tree schemes, including one based on LZ78, for sequence prediction in a setting with training and test data. Interestingly, though the LZ78-based predictor did not perform the best overall, it outperformed all other schemes on a protein classification task. Significant among the other predictors mentioned is context tree weighting [11], which achieves universality over the class of finite-depth tree sources. Universal prediction is connected to the problem of universal filtering in [12], which also shows a similar result to [8] in a filtering context and devises an LZ78-based universal denoiser. For more uses of LZ78 incremental parsing, see [13].

Also of interest in universal modeling of individual sequences is mixture distributions under Dirichlet priors. Gilbert [14] was among the first to describe such a model for encoding i.i.d. sources with unknown distribution via an additive perturbation of the empirical distribution. This model, as proven by [15], is a Bayesian scheme under a Dirichlet prior. Further exploration of a Bayesian sequential probability assignment under the Jeffreys prior in [16] yielded the Krichevskiy-Trofimov estimator for universal encoding. [17] contains a broader discussion of these probability models, in the context of both individual sequence and probability source modeling. As an alternative to the Krichevskiy-Trofimov mixture, [18] presents an explicit finite-state machine formulation that achieves the same asymptotic log likelihood with far less memory.

More recently, LZ78-based universal lossy compression algorithms have arisen. A universal rate-distortion code was proposed in [19], where the members of the reconstruction codebook were ordered by their LZ78 codelength. A possibly more computationally-efficient variation was described in [20], which uses a randomly generated codebook, with the codewords

drawn with log likelihood equal to the LZ78 codelength (up to a constant). In [21], fundamental limits of such universal lossy compressors are established. Recent efforts have also been made to understand the finite-state redundancy of LZ78, *e.g.*, [22], [23].

In addition, the use of compressors for tasks such as classification and sequence generation has been receiving increasing attention. The use of an LZ-based scheme for universal classification was first suggested in [24], which proposes cross-parsing (loosely, how few phrases a sequence can be parsed given a reference sequence) as a measure of universal relative entropy. Ziv-Merhav cross parsing has been successfully used in several domains, including biometrics identification [25], document similarity [26], and genomics [27]. An LZ77-based scheme is proposed in [28], which concatenates test sequences to the training sequence and then compresses. [29] utilizes a variant of LZ78 for determining cellular phone location. Analogously, [30] uses an LZ78 variant with accelerated convergence for prediction of device usage in a smart home. Most recently, [31] explores connections between language modeling and compression, using language models for compression and the GZIP compressor for sequence generation. Language models performed quite well as compressors, but at the cost of high memory and compute usage. GZIP outperformed language models for audio generation but fell behind in text generation, a task for which we hope to close the gap between neural networks and compression-based models.

In this paper, we concretely define a family of LZ78-based sequential probability assignments, of which formulations from [4]–[6], [12] are a special case. Loosely, models in this family are mixture distributions over an arbitrary prior, conditioned on the LZ78 context of each symbol. Each SPA in this family, to first order, incurs a log loss that is a scaled version of the LZ78 codelength. This correspondence, though intuitive to expect, has not been formally established in the literature outside of limited special cases. This family of sequential probability assignments also induces a rich family of LZ78-based compressors (*i.e.*, via arithmetic coding [3]) that have the same asymptotic universality guarantees as LZ78 but whose performance may differ in a finite-sequence environment. An empirical exploration of these compression properties will be included in future work.

We prove that the LZ78 family of models is universal, in the sense that its log-loss asymptotically matches or outperforms any finite-state sequential probability assignment. In the process, we consolidate a set of results from throughout the literature [2], [6], [8], [12]: the optimal asymptotic performance of finite-state probability models (under log loss) is no better than the optimal performance of Markovian models, and the corresponding log loss is a scaled version of the finite-state compressibility, as defined in [2].

Additionally, we define a family of probability sources based on the LZ78 sequential probability assignments. A thorough theoretical investigation of these sources is deferred to a future work, but we show promising initial results, pertaining to the compression framework of [20]. Unlike the LZ78 probability model, which has a limited number of computationally-efficient formulations, this probability source includes a formulation that allows us to generate realizations from any prior with roughly the same computational simplicity. Using this probability source, we generate a family of sequences for which our family of sequential probability assignments achieves substantially better asymptotic performance than any finite-state machine.

The rest of the paper is organized as follows. In Section II, we introduce notation that will be used throughout the remainder of the paper. Section III-B defines the LZ78 family of sequential probability assignments, with special cases highlighted in Section III-C, and the uniform convergence of the self-entropy log loss (for any model in the family) to the LZ78 codelength proven in Section III-D. Then, Section III-E defines two notions of universality for sequential probability assignments, and the equivalence of both of those notions and finite-state compressibility is in Section III-F. Section IV contains the universality result of the LZ78 family of models with respect to individual sequences, with extensions to stationary and ergodic probability sources in Section IV-A. In Section V, we define the LZ78-based probability source, and elaborate on a special case in Section V-B. Finally, Section VI is dedicated to the potential use of the LZ78 sequential probability assignments for text generation and classification, and the LZ78 probability source for compression. We conclude in Section VII.

II. PRELIMINARIES: NOTATION AND CONVENTIONS

We refer to a deterministic (albeit arbitrary) infinite sequence of symbols as an *individual sequence*. An individual sequence is denoted $\mathbf{x} = (x_1 \ x_2 \ \cdots \ x_n \ \cdots)$, where the symbols x_i take on values in a fixed alphabet \mathcal{A} . For instance, a sequence that takes on values from 1 to m will have $\mathcal{A} = \{1, 2, \dots, m\}$, denoted in shorthand as [m]. A *binary sequence* has alphabet $\mathcal{A} = \{0, 1\}$. We assume the size of the alphabet is fixed as $|\mathcal{A}| = A < \infty$.

For sequence x, x^n denotes the first n symbols and x_k^{ℓ} is the window $(x_k \ x_{k+1} \ \cdots \ x_{\ell})$. If $k > \ell$, then we, by convention, take x_k^{ℓ} to be the empty string.

 $\mathcal{A}^* \triangleq \bigcup_{k>0} \mathcal{A}^k$ is defined as the set of all finite sequences, of any length (including 0) over the alphabet \mathcal{A} .

Given some finite sequence, x^n , and $a \in A$, $N(a|x^n)$ is the number of times that the symbol a appears in the sequence x^n : $N(a|x^n) = \sum_{i=1}^n \mathbf{1} \{x_i = a\}.$

A probability source is denoted $\mathbf{X} = \begin{pmatrix} X_1 & X_2 & \cdots & X_n & \cdots \end{pmatrix}$, where each symbol X_i is a random variable with a distribution from $\mathcal{M}(\mathcal{A})$, *i.e.*, the simplex of probability mass functions over \mathcal{A} .

For this paper, log refers to the base-2 logarithm unless otherwise specified.

III. THE LZ78 FAMILY OF SEQUENTIAL PROBABILITY ASSIGNMENTS

In this section, we discuss how the LZ78 compression algorithm [2] induces a sequential probability assignment (SPA) on individual sequences. Before precisely defining this SPA, we review SPAs on individual sequences, the SPA log loss function, and the LZ78 compression algorithm.

Definition III.1 (Sequential Probability Assignment). For sequence x, a sequential probability assignment, q, maps each finite sequence x^{t-1} to the simplex of probability assignments for the next symbol, x_t :

$$q \triangleq \left\{ q_t(x_t | x^{t-1}) \right\}_{t \ge 1} \text{ where } q_t(\cdot | x^{t-1}) \in \mathcal{M}(\mathcal{A}).$$

It is understood that $q(x_t|x^{t-1})$ refers to $q_t(x_t|x^{t-1})$, so we will omit the subscript in q_t when possible.

The quality of an SPA is usually evaluated via log loss:

Definition III.2 (SPA Log Loss). The asymptotic log loss incurred by an SPA, q, on infinite sequence x, is

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q(x^n)} = \limsup_{n \to \infty} \frac{1}{n} \sum_{t=1}^n \log \frac{1}{q(x_t | x^{t-1})}.$$

The objective of minimizing log loss shapes the construction of the LZ78 family of sequential probability assignments in Section III-B, and provides a framework for discussing its universality in Section IV.

To understand the structure of an LZ78-based sequential probability assignment, we first restate the LZ78 procedure and define key notations.

A. Review: LZ78 Compression Algorithm

LZ78 encoding [2] revolves around the formation of a prefix tree. This tree is formed by parsing an individual sequence into a list of consecutive subsequences called *phrases*.

Appendix A contains a simple example of this parsing and the associated formation of the LZ78 prefix tree.

Construction III.3 (LZ78 Tree). In general, a sequence is parsed into phrases as follows:

- 1) The LZ78 tree starts off as a singular root node.
- 2) Repeat the following until we reach the end of the sequence:
 - a) Starting at the root, traverse the prefix tree according to the next symbols in the sequence until we reach a leaf.
 - b) Add a new node branching off of the leaf, corresponding to the next symbol in the input sequence.
 - c) The LZ78 phrase is defined as the slice of the input sequence used in traversing the tree, including the symbol corresponding to the new branch.

4

The number of nodes in prefix tree, excluding the root, is equivalent to the number of phrases that have been parsed.

For sequence compression, we assign an index to each node of the tree in the order that the nodes were created, and encode each phrase by the index of the leaf node found in step (1), plus the new symbol used to create the branch in step (2). For sequential probability assignment, we keep track of the number of times we traverse each node of the tree, as we will describe in detail in Section III.

Algorithm 1 describes the formal LZ78 encoding algorithm.

Algorithm 1 LZ78 Compression Algorithm

1: $\mathcal{Z} \leftarrow (())$ {List of phrases seen so far, represented as a prefix tree. It starts off with just the empty phrase.} 2: Output \leftarrow () {Compression output} 3: $t' \leftarrow 1$ {Start of the current phrase} 4: $k \leftarrow 0$ {How many phrases we've seen so far} 5: while $t \le n$ do $t \leftarrow$ smallest index such that $x_{t'}^t \notin \mathcal{Z}$, or n if no such index exists {End of the current phrase} 6: {The phrase $x_{t'}^t$ now has the prefix $x_{t'}^{t-1}$, which is $\in \mathbb{Z}$, followed by one new character, x_t .} 7: $i \leftarrow$ the index of \mathcal{Z} where you can find the prefix $x_{t'}^{t-1}$ 8: Output \leftarrow Output $\frown(i)$ { $\frown}$ represents concatenation.} 9: Output \leftarrow Output \cap (x_t) {Add the last symbol of $x_{t'}^t$ to the compression output} 10: $\mathcal{Z}(k+1) \leftarrow x_{t'}^t$ {Add the new phrase to the list of phrases in the parsing} 11: $t' \leftarrow t+1$ 12: $k \leftarrow k + 1$ 13: 14: end while

From this algorithm, let us define some quantities.

- 1) Let \mathcal{Z} represent the list of all phrases in the LZ78 parsing of x^n from Algorithm 1, including the empty phrase.
- 2) For a prefix, x^t , of x^n , $\mathcal{Z}(x^t)$ is the list of phrases (including the phrase currently being parsed) in the LZ78 parsing of x^t . Each phrase is a node in the LZ78 prefix tree.
- 3) $C(x^n) \triangleq |\mathcal{Z}|$, or the total number of phrases.
- 4) For any x^t , let $z(x^t)$ be the prefix of the phrase to which x_t belongs, including the symbol x_t . If t' is the starting index of that phrase, then $z(x^t) = x_{t'}^t$. In the LZ78 tree, this is the node we reach after parsing the symbol x_t .
- 5) For any x^t , let $z_c(x^{t-1})$ be the **context** associated with x_t , *i.e.*, the beginning of the phrase to which x_t belongs, not including the symbol x_t itself.¹ If x_t is the beginning of a new phrase, then $z_c(x^{t-1})$ will be the empty sequence.
- 6) Let N(a|x^t, z), a ∈ A, z ∈ A*, be the number of phrases in Z(x^t) that start with z ∩a, where ∩ represents concatenation of sequences. z is typically a context ∈ Z, and a is a potential "next symbol," which may or may not equal x_{t+1}. This is the number of times the node corresponding to z ∩a has been traversed so far in the prefix tree.
- 7) Similarly, $N(x^t, z)$ is the number of phrases in $\mathcal{Z}(x^t)$ that start with z.

A crucial property of the LZ parsing is that the number of phrases in an LZ78 parsing of an individual sequence is sublinear in the sequence length; by equation (9) of [2], the maximum number of phrases in the LZ78 parsing of any individual sequence is uniformly $O\left(\frac{1}{\log n}\right)$. As a consequence, for any individual sequence, the phrases in the corresponding LZ78 parsing will grow infinitely long as $n \to \infty$, which we prove in Lemma B.1 of the appendix.

B. Defining the LZ78 Family of Sequential Probability Assignments

We aim to use LZ78 to create an SPA that, loosely speaking, is efficient to compute and has a small log loss for any individual sequence. We will defer the discussion of "small log loss" to Section III-E, and define efficiency as the ability to be computed in a streaming fashion (*i.e.*, only knowledge of x^{t-1} is required to compute $q(x_t|x^{t-1})$, rather than the full sequence), where the computation of the full set $\{q(x_t|x^{t-1}) : t \in [n]\}$, is linear in the sequence length.

¹The notation $z_c(x^{t-1})$ is used to highlight the dependence only on x^{t-1} , rather than x^t .

To motivate the specific form of the LZ78 family of SPAs, we consider one of the simplest SPAs that can be computed in a streaming fashion, the one that defines $q(a|x^{t-1})$ based on the empirical distribution of x^{t-1} :

$$q^{\text{naive}}(a|x^{t-1}) = \frac{N(a|x^{t-1})}{t-1}.$$

This SPA, however, incurs infinite loss if $\exists t \text{ s.t. } N(x_t | x^{t-1}) = 0$. This can be amended by placing a prior distribution on the frequencies of each symbol. Loosely, we start by assuming that the distribution of symbols matches the mean of the prior, and gradually update our assumption as we see more symbols. If the prior distribution is not degenerate, then the issue of unbounded loss is alleviated.

Formally, define q^f as the probability mass function of the following mixture distribution:

- 1) Let Π be a prior distribution on the simplex $\mathcal{M}(\mathcal{A})$ with density $f(\cdot)$. We first sample $\Theta \sim \Pi$, which is a probability mass function on \mathcal{A} .
- 2) We then sample $X_1, \ldots, X_n \stackrel{\text{i.i.d.}}{\sim} \Theta$. Define the SPA $q^f(x^n)$ as the joint PMF for X_1, \ldots, X_n .

By Bayes' theorem, $q^f(x_t|x^{t-1})$ is

$$q^{f}(x_{t}|x^{t-1}) = \frac{q^{f}(x^{t})}{q^{f}(x^{t-1})} = \frac{\int_{\mathcal{M}(\mathcal{A})} \left(\prod_{i=1}^{t} \Theta(x_{i})\right) d\Pi(\Theta)}{\int_{\mathcal{M}(\mathcal{A})} \left(\prod_{i=1}^{t-1} \Theta(x_{i})\right) d\Pi(\Theta)}.$$
(1)

For certain choices of prior, this integral expression becomes simple to compute, as is discussed in Section III-C.

This SPA, however, only uses zero-order information about the sequence; it does not take into consideration the different contexts that can precede a symbol. For instance, if in a binary sequence, the sequence (0, 0, 0) is always followed by a 1, a reasonable SPA should eventually be able to predict that pattern. To mitigate this, we could consider a fixed-length context preceding each symbol, as a *k*-order Markov SPA (Definition III.13) does.

However, any fixed context length of k will not capture patterns that depend on contexts longer than k, so it is desirable to have a context length that is allowed to grow unbounded. By Lemma B.1, the LZ78 context associated with a symbol is guaranteed to grow unbounded as the length of the input sequence tends to infinity. So, we modify the SPA from (1) by conditioning on the LZ78 context associated with the current symbol.

Construction III.4 (LZ78 Sequential Probability Assignment). Let Π be a prior distribution on $\mathcal{M}(\mathcal{A})$ with density f. We define the LZ78 SPA for prior Π as

$$q^{LZ78,f}(a|x^{t-1}) = q^f\left(a \mid \left\{x_i : 1 \le i \le t-1, z_c(x^{i-1}) = z_c(x^{t-1})\right\}\right),$$

where q^f is as defined in (1), $z_c(x^{t-1})$ is the context for x_t in the construction of a LZ78 prefix tree, and $\{x_i : \cdots\}$ represents the ordered subsequence of symbols in x^{t-1} that have the same LZ78 context as x_t .

This forms the LZ78 family of SPAs. In the subsequent sections, we will define the form of the LZ78 SPA for specific priors that result in a computationally-efficient form (1), and show that the log loss of this SPA approaches a scaled version of the LZ78 codelength. Then, we discuss the performance of this SPA with respect to log loss, proving that its loss is upper-bounded by the optimal log loss of a broad class of SPAs.

Remark III.5. For the definition of the LZ78 family of SPAs, we do not place any restrictions on the prior distribution. For subsequent theoretical results, however, we stipulate that the density associated with the prior is bounded from below, *i.e.*, $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$.

C. Special Cases of the LZ78 Sequential Probability Assignment

A canonical example of when the LZ78 SPA becomes tractable is when the prior Π is Dirichlet (γ, \ldots, γ) , for $0 < \gamma \leq 1$, which reduces $q^f(x_t|x^{t-1})$ to a simple perturbation of the empirical distribution:

Construction III.6 (Dirichlet SPA). If the prior defining q^f in (1) is Dirichlet (γ, \ldots, γ) , for positive γ , then, due to [15],

$$q^{f}(x_{t}|x^{t-1}) = \frac{N(x_{t}|x^{t-1}) + \gamma}{(t-1) + \gamma A}.$$

The corresponding LZ78 SPA evaluates to

$$q^{LZ78,f}(a|x^{t-1}) = \frac{N(a|x^{t-1}, z_c(x^{t-1})) + \gamma}{\sum_{b \in \mathcal{A}} N(b|x^{t-1}, z_c(x^{t-1})) + \gamma A}.$$

Remark III.7. As per, *e.g.*, [17], the choice $\gamma = \frac{1}{2}$ in Construction III.6 is essentially (to the leading term) minimax optimal with respect to the log loss incurred by the SPA on any individual sequence.

The structure of the LZ78-based universal predictor from [5], [6] is a special case the case of Construction III.6 with $\gamma = \frac{1}{A-1}$. The structure of this SPA makes it possible to directly show that the log loss incurred on any individual sequence approaches the LZ78 codelength, scaled by $\frac{1}{n}$.

Construction III.8. Let g be the density associated with the Dirichlet prior on $\mathcal{M}(\mathcal{A})$ with parameter $\gamma = \frac{1}{A-1}$.

The SPA $q^{LZ78, g}(x^n)$ is then

$$q^{\text{LZ78,g}}(x_t|x^{t-1}) = \frac{(A-1)N(x_t|x^{t-1}, z_c(x^{t-1})) + 1}{(A-1)\left(\sum_{a \in \mathcal{A}} N(a|x^{t-1}, z_c(x^{t-1}))\right) + A},$$

can be alternatively understood using the following variant of the LZ78 prefix tree:

- 1) The root node starts out with A branches, one for each possible first symbol.
- 2) When parsing a phrase, we traverse the tree until we reach a leaf. Upon reaching a leaf, we add A branches to the leaf (one for each symbol in \mathcal{A}).
- 3) We label each node with the number of leaves that are descendents of the node (including, when relevant, the node itself). Let us call this number $\mathcal{L}(z)$, where $z \in \mathbb{Z}$ is the phrase corresponding to the node of interest.
- 4) $q^{LZ78, g}(x_t|x^{t-1})$ is equal to the ratio of the label, \mathcal{L} , of the current node in the LZ78 tree (after traversing the tree according to the current symbol) to that of the parent node.

This is because every new phrase in the LZ78 parsing of a sequence removes one leaf from the tree and adds A leaves (by adding A branches to an additional leaf). So, for each phrase that a node is a part of, its label is incremented by A-1. Also, every node except for the root (which can never be the current node), starts off with a $\mathcal{L} = 1$, making the label of the current node equal to $(A-1)N(x_t|x^{t-1}, z_c(x^{t-1})) + 1$, *i.e.*, the numerator of $q^{LZ78, g}(x_t|x^{t-1})$. The label of the parent node is the sum of the labels of its children, *i.e.*, the denominator of $q^{LZ78, g}(x_t|x^{t-1})$.

For the example in Appendix A where x^n is parsed into 0, 1, 10, 01, 100, 11, the prefix tree would be:



Internal nodes, which correspond to phrases in the LZ78 parsing, are colored green, and leaves, which do not yet correspond to phrases, are colored blue.

For this SPA, there is a direct and exact connection between the log loss incurred on each phrase and the number of phrases in the LZ78 parsing thus far. In each phrase, the log loss incurred is, up to constant terms, the logarithm of the number of phrases that have been parsed thus far, as proven in Lemma B.2.

Using this, we can directly show that the log loss incurred by $q^{LZ78, g}$ is asymptotically equivalent to the $\frac{1}{n}$ -scaled LZ78 codelength. This is a crucial result for Section III-D, where we show that the same holds for any SPA in the LZ78 family.

Lemma III.9 (Log loss of Construction III.8). For any individual sequence and $q^{LZ78,g}$ from Construction III.8,

$$\max_{x^n} \left| \frac{1}{n} \log \frac{1}{q^{LZ78, g}(x^n)} - \frac{C(x^n) \log C(x^n)}{n} \right| = \epsilon(A, n).$$

where $\epsilon(A, n) \to 0$ as $n \to \infty$.

Proof sketch (full proof in Appendix B-B): An upper bound, $\max_{x^n} (\cdots) = o(1)$, can be achieved via direct computation. The lower bound, $\min_{x^n} (\cdots) = o(1)$, is more detailed and involves showing that the majority of the log loss is incurred in the last few phrases.

Note that, by [2], Lemma III.9 implies that $\frac{1}{n} \log \frac{1}{q^{1Z78, g(x^n)}}$ uniformly converges to $\frac{1}{n}$ times the LZ78 codelength.

D. Correspondence of LZ78 Sequential Probability Assignment Log Loss and LZ78 Codelength

In this section, we prove one critical result of this paper: the asymptotic correspondence between the $\frac{1}{n}$ -scaled LZ78 codelength and the log loss incurred by any SPA of the family Construction III.4. Specifically, we prove that the distance between the log loss and $\frac{C(x^n) \log C(x^n)}{n}$ approaches 0 as $n \to \infty$, uniformly over individual sequences. As, by [2], the same holds for the LZ78 codelength, the correspondence of the SPA log loss and the scaled codelength directly follows via the triangle inequality.

Theorem III.10. For any prior such that $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$,

$$\lim_{n \to \infty} \max_{x^n} \left| \frac{1}{n} \log \frac{1}{q^{LZ78, f}(x^n)} - \frac{C(x^n) \log C(x^n)}{n} \right| = 0.$$

Proof sketch (full proof in Appendix B-C): Lemma III.9 shows that this holds for the specific instance of the LZ78 SPA from Construction III.8, so this result reduces to showing that all SPAs in the LZ78 family have asymptotically-equivalent log losses.² Building off of a result from [32], we show that the absolute distance between the LZ78 SPA log loss and the empirical entropy of x^n , conditioned on LZ78 prefix, uniformly approaches 0. From there, the triangle inequality produces the desired result.

E. Classes of Sequential Probability Assignments and Associated Log Loss

In order to characterize the performance (in log loss) of the LZ78 family of SPAs, we will show that its log loss is upperbounded by the optimal log loss of any finite-state SPA. As a prerequisite, we must understand finite-state SPAs, their optimal log loss, and its relationship with other relevant quantities.

Definition III.11 (Finite-State SPA). A finite-state SPA is such that the probabilities assigned depend solely on the current state of an underlying finite-state mechanism. Concretely, q is a M-state SPA if \exists next-state function $g : [M] \times \mathcal{A} \rightarrow [M]$, prediction function $f : [M] \rightarrow \mathcal{M}(\mathcal{A})$, and initial state $s_1 \in [M]$ such that

 $\forall t \geq 1, \ q(\cdot | \boldsymbol{x}^{t-1}) = f(\boldsymbol{s}_t), \quad \text{and} \quad \boldsymbol{s}_{t+1} = g(\boldsymbol{s}_t, \boldsymbol{x}_t).$

The set of all *M*-state SPAs is denoted \mathcal{F}_M .

The optimal log loss of any finite-state SPA is defined as follows:

Definition III.12 (Optimal Finite-State Log Loss). The minimum log loss of a M-state SPA for sequence x is defined as

$$\lambda_M(\mathbf{x}) \triangleq \limsup_{n \to \infty} \lambda_M(x^n) \quad \text{for} \quad \lambda_M(x^n) \triangleq \min_{q \in \mathcal{F}_M} \frac{1}{n} \sum_{t=1}^n \log \frac{1}{q(x_t | x^{t-1})}.$$

The optimal finite-state log loss takes the number of states to infinity,

$$\lambda(\mathbf{x}) \triangleq \lim_{M \to \infty} \limsup_{n \to \infty} \lambda_M(x^n).$$

 $\lambda_M(\mathbf{x})$ is monotonically non-increasing in M and bounded below, so the outer limit is guaranteed to exist.

²*i.e.*, that the absolute distance in log loss between any two LZ78 SPAs approaches 0, uniformly over all individual sequences.

As the set of finite-state SPAs is quite broad, it is often simpler to consider the family of Markov SPAs, where $q(x_t|x^{t-1})$ only depends only on a fixed-length context x_{t-k}^{t-1} . In Section III-F, we will show that, although the set of finite-state SPAs is more broad than that of Markov SPAs, they are asymptotically equivalent for any individual sequence.

Definition III.13 (Markov SPA). An SPA q is Markov of order k if $\exists g : \mathcal{A}^k \to \mathcal{M}(\mathcal{A})$ such that $q(\cdot|x^{t-1}) = g\left(x_{t-k}^{t-1}\right)$, $\forall \mathbf{x} \text{ and } t \geq k+1$. The set of all k-order Markov SPAs is denoted \mathcal{M}_k .

Remark III.14. For a k-order Markov SPA, q_t , $t \le k$ is fully arbitrary. For instance, if evaluating a loss function, those q_t can be chosen to incur zero loss.

Remark III.15. If SPA q is Markov of order k, it is an A^k -state SPA. This can be seen by defining the state as the k-tuple consisting of the previous k symbols.

The definition of the optimal Markov SPA log loss is analogous to that of the optimal finite-state SPA log loss:

Definition III.16 (Optimal Markov Log Loss). For any sequence x, the optimal log loss of a k-order Markov SPA is

$$\mu_k(\mathbf{x}) \triangleq \limsup_{n \to \infty} \mu_k(x^n) \quad \text{for} \quad \mu_k(x^n) \triangleq \min_{q \in \mathcal{M}_k} \frac{1}{n} \sum_{t=1}^n \log \frac{1}{q(x_t | x^{t-1})}.$$

The optimal Markov SPA log loss is defined by taking the context length to ∞ :

$$\mu(\mathbf{x}) \triangleq \lim_{k \to \infty} \mu_k(\mathbf{x}) = \lim_{k \to \infty} \limsup_{n \to \infty} \mu_k(x^n)$$

As with $\lambda(\mathbf{x})$, the outer limit is guaranteed to exist.

1) Optimal Markov and Finite-State Log Loss in terms of Empirical Entropies: Essential to the proofs in Section III-F (and fundamental to the understanding of optimal SPAs) is the relationship between $\mu_k(x^n)$, $\lambda_m(x^n)$, and empirical entropies on individual sequence x^n . The specifics of these relationships, as well as the corresponding proofs, are detailed in Appendix B-D and summarized below.

- $\mu_0(x^n)$ is equal to the zero-order empirical entropy of x^n .
- $\mu_k(x^n)$ is, up to o(1) terms, equal to the empirical entropy of x^n , conditioned on the length-k context of each symbol.
- $\lambda_M^{g,s_1}(x^n)$, where g is a fixed state transition function and s_1 is a fixed initial state, is equal to the empirical entropy of x^n , conditioned on the current state.

2) *Finite-State Compressibility:* Also closely related to optimal SPAs is finite-state compressibility [2], as, in many cases, limits of compressibility and probability assignment log loss coincide. For instance, the entropy of an i.i.d. probability source is both the theoretical limit of compression and of the log loss for a probability assignment on that source. In addition, in Section III-D, we showed that the log loss of any LZ78 SPA from Construction III.4 is asymptotically equivalent to the scaled LZ78 codelength.

In Section III-F, we will show that a similar result holds for finite state compressibility; *i.e.*, that it is equal to the optimal finite-state SPA log loss (with a $\frac{1}{\log A}$ scaling factor). For the sake of that result being self-contained, we provide definitions of finite-state compressibility and some prerequisite concepts. For more detailed descriptions of these quantities, see [2].

Definition III.17 (Encoder). For an individual sequence x from alphabet A, an encoder is a mapping of input symbols $x_t \in A$ to output symbols $y_t \in B$, where B is the output alphabet. The elements of B have varying bitwidths, and B can include the empty sequence.

Definition III.18 (Information Lossless Finite-State Encoder). An *M*-state encoder consists of an initial state $s_1 \in [m]$, an encoding function $f : \mathcal{A} \times [M] \to \mathcal{B}$, and state-transition function $g : \mathcal{A} \times [M] \to [M]$ such that

$$y_t = f(x_t, s_t), \ s_{t+1} = g(x_t, s_t), \ \forall t \ge 1.$$

A finite-state encoder is **information lossless** if the initial state, output signal y^n , and set of states s^n uniquely determine the input signal x^n . Let the set of all information lossless *M*-state compressors be ρ_M .

Definition III.19 (Compression Ratio). The compression ratio of an encoder on an individual sequence is $\frac{L(y^n)}{L(x^n)}$, where $L(\cdot)$ represents the number of bits required to directly represent a sequence. We take the number of bits required to represent the input sequence, $L(x^n)$, to be $n \log A$.

Definition III.20 (Finite-State Compressibility). For any finite sequence x^n , the minimum M-state compression ratio is

$$\rho_M(x^n) \triangleq \min_{E \in \rho_M} \frac{L(y^n)}{L(x^n)} = \min_{E \in \rho_M} \frac{L(y^n)}{n \log A},$$

where y^n is understood to be the output produced by applying encoder E to sequence x^n .

Analogous to $\lambda_M(\mathbf{x})$ and $\lambda(\mathbf{x})$, the *M*-state compressibility and finite-state compressibility of \mathbf{x} are, respectively,

$$\rho_M(\mathbf{x}) \triangleq \limsup_{n \to \infty} \rho_M(x^n), \text{ and } \rho(\mathbf{x}) \triangleq \lim_{M \to \infty} \rho_M(\mathbf{x}) = \lim_{M \to \infty} \limsup_{n \to \infty} \rho_M(x^n).$$

F. Equivalence of Optimal Finite-State Log Loss, Optimal Markov Log Loss, and Finite-State Compressibility

One of our primary goals is to prove that the log loss of the LZ78 family of SPAs is asymptotically upper-bounded by the optimal finite-state log loss, for any individual sequence. To do so, we would like to utilize the relationship between the LZ78 SPA log loss and $\rho(\mathbf{x})$ established by Section III-D and [2]. To this extent, we consolidate a set of results that have been alluded to throughout the literature, as well as the viewpoints of individual sequence compressibility and optimal sequential probability assignment: for any individual sequence, $\lambda(\mathbf{x}) = \mu(\mathbf{x}) = \rho(\mathbf{x}) \log A$. Though not formally stated as a theorem, the bulk of the $\lambda(\mathbf{x}) = \mu(\mathbf{x})$ result is present in the analysis of [6], [8] ([6] presents this result in the context of "probability of error" loss, with [8] extending it to other bounded loss functions). In addition, much of the analysis that $\mu(\mathbf{x}) = \rho(\mathbf{x}) \log A$ is discussed in [2], and is also alluded to in [6], [7].

Theorem III.21. For any infinite individual sequence, the optimal finite-state log loss, optimal Markov SPA log loss, and finite-state compressibility are equivalent:

$$\lambda(\mathbf{x}) = \mu(\mathbf{x}) = \rho(\mathbf{x}) \log A.$$

Proof sketch (full proof in Appendix B-E): We first prove that $\lambda(\mathbf{x}) = \mu(\mathbf{x})$ via a lower and upper bound *i.e.*, $\lambda(\mathbf{x}) \leq \mu(\mathbf{x})$ and $\lambda(\mathbf{x}) \geq \mu(\mathbf{x})$. The upper bound, $\lambda(\mathbf{x}) \leq \mu(\mathbf{x})$, follows directly from Fact III.15. To achieve the lower bound, we first replace $\mu_k(x^n)$ and $\lambda_M^{g,s_1}(x^n)$ by their corresponding empirical entropies. Using the fact that conditioning reduces entropy, as well as the chain rule of entropy, we can show that $\mu_k(x^n) - \lambda_M^{g,s_1}(x^n)$ is upper-bounded by $\frac{\log M}{k+1}$, regardless of the choice of state transition function or initial state. From here, taking $k \to \infty$, followed by $M \to \infty$, completes the proof that $\lambda(\mathbf{x}) = \mu(\mathbf{x})$.

The result that $\rho(\mathbf{x}) \log A = \mu(\mathbf{x})$ follows from Theorem 3 of [2], along with an application of the chain rule of entropy and some minor further analysis.

IV. OPTIMALITY OF THE LZ78 FAMILY OF SPAS

Given the work thus far, it becomes simple to prove that, for any individual sequence, the limit supremum of the log loss of any LZ78 SPA is at most $\lambda(\mathbf{x})$. *i.e.*, in terms of log loss, the LZ78 family of SPAs either matches or outperforms any finite-state SPA.

Theorem IV.1 (Universality of LZ78 SPA). For prior distribution f such that $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$, $q^{LZ78,f}$ from Construction III.4 satisfies, for any individual sequence.

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q^{LZ78, f}(x^n)} \le \lambda(\mathbf{x}).$$

Proof.

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q^{LZ78, f}(x^n)} \stackrel{(a)}{=} \limsup_{n \to \infty} \frac{1}{n} C(x^n) \log C(x^n) \stackrel{(b)}{\leq} \rho(\mathbf{x}) \log A \stackrel{(c)}{=} \lambda(\mathbf{x})$$

where (a) is by Theorem III.10, (b) is stated in [2], and (c) is a result from Theorem III.21.

The inequality, in fact, can be strict (*i.e.*, the LZ78 SPA strictly outperforms any sequence of finite-state SPAs). In Section V-B, we define a class of sequences for which this is the case.

A. Results for Stationary and Ergodic Probability Sources

If, instead of an individual sequence, we consider a stationary stochastic process X, the expected log loss incurred by any SPA in the LZ78 family approaches the entropy rate of the source in the limit $n \to \infty$. Specifically, the following results hold, and follow without much effort from the corresponding results in the individual sequence setting:

- $\mathbb{E}\mu_0(X^n) \le H(X_1),$
- $\mathbb{E}\mu_k(X^n) \le H(X_{k+1}|X_k),$
- For any SPA such that the lim sup of the log loss is at most $\mu(\mathbf{x})$, *e.g.*, any SPA in the LZ78 family, the expected log loss approaches the entropy rate,
- If the process is also ergodic, then the above result holds almost surely rather than in expectation.

Details about these results can be found in Appendix C-A.

V. THE LZ78 SEQUENTIAL PROBABILITY ASSIGNMENT AS A PROBABILITY SOURCE

A. Motivation and Definition of LZ78 Probability Source

While LZ78 has been studied extensively in the context of compression, sequence modeling, and other universal schemes, it has not been studied as a probability source. Beyond intrinsic understanding, it is worthwhile to study this source due to its potential for lossy compression. As described in [20], a universal rate-distortion code can be achieved via a randomly generated codebook, where reconstruction codewords have log likelihood that scales with their LZ78 codelength. As will be further discussed in VI-B, the LZ78 probability source naturally generates sequences according to this distribution, so it can be a computationally-feasible way of realizing the theoretical results from [20].

There are two general techniques for defining a probability source based on the LZ78 SPA, both of which are statistically equivalent but have different computational properties.

The first directly uses the perspective of the $q^f(x^n)$ (where q^f is the SPA at a particular node of the LZ78 tree, as defined in Section III-B) as the density of a process that draws $\Theta \in \mathcal{M}(\mathcal{A})$ according to the given prior, and then generates a sequence i.i.d. according to Θ .

Construction V.1 (LZ78 Probability Source, Mixture Perspective). Given prior distribution Π with density f, we can generate samples from the corresponding LZ78 probability source, $Q_t^{LZ78,f}$, as follows:

- 1) Generate an infinite series of random variables, $\Theta_1, \Theta_2, \dots$, i.i.d. according to Π . Computationally, this step should be performed lazily, *i.e.*, only generating new values as they are needed for subsequent steps.
- 2) Grow an LZ78 prefix tree, assigning a Θ value generated from step (1) to each node and using the Θ at the current node of the tree to generate the source. Concretely, this is done by repeating the following steps, starting at the root node of the prefix tree:
 - a) If the current node of the LZ78 tree does not have an assigned Θ , select the next value generated in step (1) and assign it to the current node.
 - b) Generate the next output of $Q^{LZ78, f}$ as $X_t \sim \eta_t$, where η_t is the value of Θ assigned to the current node.
 - c) Traverse the LZ78 tree for the newly-drawn symbol X_t .

The second formulation of an LZ78 probability source directly uses the value of the LZ78 SPA at each current timestep.

Construction V.2 (LZ78 Probability Source, SPA Perspective). Given prior distribution Π with density f, we can also use the following procedure to generate samples from $Q_t^{\text{LZ78,f}}$:

- 1) Starting at the root of the LZ78 tree, repeat the following procedure:
 - a. Draw X_t according to the probability mass function $q^{LZ78,f}(\cdot|X^{t-1})$, where X^{t-1} is the realized sequence thus far.
 - b. Traverse the LZ78 tree for the newly-drawn symbol X_t .

This scheme also extends to any general strongly sequential SPA, including those that are not based on mixture distributions over a prior.

Remark V.3. If the prior distribution, Π , is Dirichlet, then the formulation of the LZ78 probability source from Construction V.2 is computationally efficient via results from Section III-C. For a general prior, however, $q^{LZ78,f}(\cdot|X^{t-1})$ is not simple to compute. In that case, the formulation of the source from Construction V.1 is far easier to evaluate and simulate.

Detailed theoretical results about this source, including its entropy rate, are deferred to a future work. For the purposes of this paper, we consider an extreme yet illustrative example of the source. In doing so, we will answer the question posed at a end of Section IV regarding existence of sequences for which the limit supremum of the LZ78 SPA log loss is strictly better (less) than $\mu(\mathbf{x})$.

B. Example: Bernoulli LZ78 Probability Source

We consider the binary source corresponding to $\Pi = \text{Ber}(1/2)$ (*i.e.*, Θ is 0 and 1 with equal probability). This means that each node of the LZ78 prefix tree only generates all ones or all zeros, and each new leaf has equal probability of having $\Theta = 1$ or $\Theta = 0$.

As a result, $Q_t^{LZ78,f}$ is uniform if the context of X_t is a leaf of the LZ78 tree; otherwise, each node of the LZ78 tree may only have one child, to which it must traverse each time. It can easily be verified that the sequence realized by this probability source has the following properties:

- 1) Each phrase in the LZ78 parsing of the realized sequence is equal to the previous phrase, with one new symbol at the end that is equally likely to be 0 or 1.
- 2) The k^{th} phrase, denoted C_k , has length $\ell(C_k) = k$.
- 3) As a result, the number of phrases in the realization X^n is $C(X^n) = O(\sqrt{n})$.

It is worthwhile to note that these properties hold, deterministically, for any sequence that can be realized from this source.

Any LZ78 SPA of the class in Construction III.4 satisfies $\limsup_{n\to\infty} \log \frac{1}{q^{\text{LZ78.f}}}(X^n) = 0$, for any possible realization of this source, whereas $\mu(\mathbf{X}) = 1$ (a.s.), as we prove in Appendix D-A.

VI. EXPERIMENTS

A. LZ78 as a Sequential Probability Assignment

In this section, we briefly explore the capabilities of LZ78 for sequence generation and classification. For the generation experiment, we "train" an LZ78 SPA (*i.e.*, building the prefix tree and storing the number of times each node was visited) on a provided set of training data. Then, we generate values based on $q^{LZ78,f}$ (continuing to traverse the prefix tree for the newly-generated symbols), with some simple tricks for improving the quality of the generated text. For the classification experiment, we train an LZ78 SPA for each distinct label, and classify test points based on the LZ78 SPA on which they achieve the smallest log loss.

In general, these methods will not produce better results than neural-network-based approaches, given the same amount of data. However, they generally use much less compute than neural networks (*e.g.*, they only perform a small number of mathematical operations per input datapoint, and do not require use of a GPU to run quickly). Direct comparison of LZ78-SPA-based generation and classification to neural networks is beyond the scope of the paper and will be explored in future work; the experiments contained here, however, provide evidence that the LZ78 SPA can be used for these tasks with some degree of success.

1) Text Generation: This experiment includes two phases: a "training" phase and a "generation" phase. During the training phase, an LZ78 prefix tree is formed using the available training sequences. If the dataset includes multiple distinct training sequences, we start at the root of the prefix tree for each sequence. We record the resulting prefix tree, as well as the values of $N(x^n, z)$, $\forall z \in \mathbb{Z}(x^n)$, where x^n represents the entire set of training data. For simplicity, each character is a separate symbol, and the alphabet consists of all lowercase and uppercase English letters, digits, and common punctuation marks. All other characters are omitted from the training data, for the sake of filtering out uncommon characters that unnecessarily increase the size of the alphabet.

Given the LZ78 prefix tree from the training phase, generation proceeds as follows:

- 1) We start at the root of the prefix tree, and optionally traverse the tree using a provided sequence of "seeding data." For this step, and the entirety of the generation procedure, no new leaves are added to the prefix tree, nor are the counts, $N(x^n, z)$, updated. We keep track of the currently-traversed node, which we all the state.
- 2) Loop:
 - a) Compute the sequential probability assignment (using the fixed counts, $N(x^n, z)$, from the training phase, and the current state), of the next symbol for all $a \in A$.
 - b) Denote the k symbols with the highest probabilities by \mathcal{K} . Draw a new symbol for the output sequence using the probability distribution:

$$\mathbb{P}(X=a) = \begin{cases} \frac{2^{\log\left(q^{LZ78}(a|\operatorname{state})\right)/T}}{\sum_{x\in\mathcal{K}} 2^{\log\left(q^{LZ78}(x|\operatorname{state})\right)/T}}, & a\in\mathcal{K}\\ 0, & a\notin\mathcal{K} \end{cases},$$

where T is a temperature parameter.

- c) Traverse the LZ78 prefix tree using the newly-drawn symbol.
- d) If the state is the root of the tree or a leaf, then we don't have any useful information to be derived from the LZ78 prefix (for a leaf, the sequential probability assignment is uniform, and, for the root, the LZ78 prefix is \emptyset . In that case, we take the last M characters of the generated sequence (where M is a hyperparameter), and repeat step (1). If we are still at the root or a leaf, repeat with the last M 1 symbols, *etc.* This is a heuristic similar to the back-shift parsing of the LZ-MS algorithm in [10].

For this experiment, we trained the LZ78 SPA, under Jeffrey's Prior (*i.e.*, a Dirichlet prior with parameter $\frac{1}{2}$), on the tiny-shakespeare dataset [33], which is 1 MB, the first eight partitions of the realnewslike segment of C4 [34], which is approximately 500 MB, and the first 500 MB of the tinystories dataset [35]. Training took 0.4 seconds for tiny-shakespeare and 6 minutes each for the C4 and tinystories subsets.

The results of the generation experiments are in Figures 1 to 3. For each experiment, M = 500, k = 5, and T = 0.1. Considering the LZ78 SPA is directly applied to text at a one-character-per-symbol level, without any pre-processing techniques like tokenization, the generated text is surprisingly high-quality. Both examples capture the general structure and tone of their training data and consist of plausible phrases (and occasionally, sentences). Higher-quality generated text will require more training data and perhaps more sophisticated techniques, which we will explore in future work.

This is the moon with the fairest charge thee stay; Which is not so. Provost: Art thou not That which withal; you go you to Baptista; or, but I am not Lucentio, Red the beasts, that Warwick, And those that runatice of his auture of our straight and will play the his profane eyes, came to see thy servant so die. LUCIO: But what lives in Signior Gremio: fools His will I may have auture of his auture of our common good time Unto the Tower, Give me thy hand as come enough And then he shall not rather with the Lord Stand be so longer see that are fond, as thou say the orace to speak brother, or oints? **BIONDELLO:** I may more straight and will play the his punish his convey much this leavine art thou that will not should be thus sir, there's face. Go you to Baptista; or, lo, here all abroad in the

Figure 1. 800 symbols generated via the LZ78 SPA, trained on the tiny-shakespeare dataset, seeded with the sequence "This."

This is a story about the version of Macron said he was "gration of the Tigers' hands of the department kept the world around us do well to start the second half.

The Wildcats last three or four days ago. In fact, I appreciate the opposition to END TO PUT I think the time to make the roster before being shot wide with the driver isn't a single speaking to the public.

There's a lot more spared. The ranking community is just one of the many leaving these players came close to that point.

Last year, the Steelers travel to West Virginia and two more as a president who said the right to cross Russia investigation is ongoing. To put this in countries including the United States. The plant for a special permission for some Democrats say the Red Cross and the small company culture in which a bad rap, and the former president of the Virginia Tech shootings. The report found that millennials are also included. Congo's early results have been produced and directed by James Baker. She was the wife of

Figure 2. 1000 symbols generated via the LZ78 SPA, trained on a subset of the realnewslike segment of C4, seeded with the sequence "This."

This is my boat," he said.

Anna and Ben felt sorry for the stars"

"Can we play with the ducks. They are nice. They were happy. They forget about the card. She picked it up and showed it to her mom.

"Look, Mommy A zoo with their mom. They saw many animals, like lions, monkeys, and elephants. But they are not careful. You were just curious and asked her mom what it meant. They thought it was so cool that he wanted to be friends with them.

The moral of the story is that it's important to be kind to others. And he also learned that it's important to take care of things that are not yours. You have to ask first. And you have to be polite and ask nicely inside. They heard a loud noise.

Anna and Ben are scared. They drop the tree and the fox were playing in the park. They were both happy and brave. He thought it was fun to see the dentist was not fun. It was dangerous and silly. They said they were sorry. They said they wanted to go home.

Mom hugs them and says, "I love you, bikes and ran to the

Figure 3. 1000 symbols generated via the LZ78 SPA, trained on a subset of the tinystories dataset, seeded with the sequence "This."

2) Image and Text Classification: We use the LZ78 SPA for classification as follows: first, we divide the training data according to the label, or class, of each sample. Then, considering each class independently, we concatenate the relevant samples and construct an LZ78 prefix tree. As with the text generation experiment, we start at the root of the appropriate tree for each training sample. This results in c different prefix trees, where c is the number of classes in the dataset.

To classify test samples, we compute the log loss of the sample on all c of the prefix trees from the training phrase (without adding new leaves or incrementing the counts, $N(a|x^n, z)$, at each node). The sample is classified according to the prefix tree with the smallest log loss over that sample.

Classification experiments were performed on the MNIST [36], Fashion-MNIST [37], IMDB [38], and Enron-Spam [39] datasets. The first two datasets consist of binary and grayscale 28×28 images,³ respectively. Both datasets have with 60,000 training examples and 10,000 test examples, and are divided into 10 classes. To produce a sequence that could be fed into the LZ78 SPA, the raw pixels of the images were concatenated in row-major order. For Fashion-MNIST, we uniformly quantized the 8-bit pixels to 2 bits, which resulted in a performance boost. The second two datasets are text datasets, and are processed exactly like the training data in Section VI-A1. The IMDB dataset consists of 50,000 "highly polar" movie reviews, and the Enron-Spam dataset consists of approximately 33,000 spam and non-spam emails. Both datasets are evenly divided between training and test segments.

The results of these classification experiments are in Table I. As in Section VI-A1, we used the LZ78 SPA under a Dirichlet prior with parameter 0.1. To achieve an accuracy boost at the cost of run time, we formed the prefix tree for each class by looping through the training set 20 times for the image datasets and 5 times for the text datasets. Training is parallelized across the classes but otherwise unoptimized.

3) Discussion: Given the same amount of data, neural networks generally outperform the LZ78-based methods discussed here in terms of result quality. They, however, can be prohibitively expensive, requiring orders of magnitude more compute

³MNIST consists of handwritten digits and Fashion-MNIST consists of basic articles of clothing.

 Table I

 Results of classification experiments using the LZ78 SPA.

Dataset	MNIST	Fashion-MNIST	IMBD	Spam Emails
Accuracy (%)	75.36	72.16	75.62	98.12
Training Time (s)	14	15	16	14

depending on the complexity of the network. Though a thorough investigation comparing LZ-based generation and classification to neural networks will be the focus of a future work, we expect a neural network, constrained to use the same amount of computational resources as the LZ78 SPA, will perform worse than the results listed here.

In addition, it will be worthwhile to compare the classification results to Ziv-Merhav Cross Parsing [24], which shares some similarities to the classification setup here. As per [25]–[27], Ziv-Merhav Cross Parsing has enjoyed success in several classification tasks.

B. LZ78 as a Probability Source

1) Compression via LZ78 Probability Source: As per recent results from [20], the LZ78 probability source from Construction V.1 or Construction V.2 can be practically useful in lossy and lossless compression. [20] states that a universal lossy compressor can be constructed via a codebook of samples generated by a distribution proportional to $2^{-LZ(\hat{x}^n)}$, where $LZ(\hat{x}^n)$ is the LZ78 codelength of the reconstruction vector \hat{x}^n .

By Theorem III.10, for any prior bounded away from zero, the log loss incurred by $q^{LZ78, f}$ asymptotically approaches the LZ78 codelength, uniformly over all individual sequences. In addition, by construction, the probability that sequence x^n is drawn from $Q^{LZ78,f}$ from Construction V.2 is equal to $q^{LZ78, f}(x^n)$. Therefore, it is reasonable to expect a codebook generated via $Q^{LZ78,f}$ to have similar universality properties to the codebook from [20]. Though a detailed examination of the compression properties of $Q^{LZ78,f}$ is beyond the scope of this work, we provide some promising empirical results.

For the purposes of this paper, we consider some simple yet illustrative examples: three short, highly-compressible sequences that illustrate the potential of Q^{LZ} for sequence compression. Though we only consider lossless compression, it is possible to extend this experiment to lossy compression, as discussed in [20]. Specifically, we consider: an all-zero sequence, which has entropy of 0, a sequence generated from the Bernoulli LZ78 probability source of Section V-B, which has an entropy rate of 0, and an i.i.d. sequence of Ber(0.01), which has an entropy rate of 0.08.

On these sequences, we perform the following experiment:

- 1) We first generate a sequence to compress of length k_{max} , which is 140 for the two zero-entropy-rate sequences, and 50 for the Bernoulli sequence.⁴
- 2) Looping over k from 1 to k_{max} , inclusive:
 - a) We generate length-k sequences from $Q^{LZ78,f}$, where f is the Dirichlet prior with parameter 0.1,⁵ until we find one that matches the first k symbols of the sequence from (1). The total number of sequences generated is denoted n_k .
 - b) The compression ratio for this subsequence is estimated as $\frac{\log n_k}{k}$: it takes $\log n_k$ bits to represent the number of sequences to generate, assuming the encoder and decoder have a shared seed, and the original binary sequence is represented by k bits.

We repeat this experiment for 200 trials, for each sequence being compressed.

The compression ratios are plotted with respect to k in Figure 4. For comparison, LZ78 has a compression ratio of around 0.5 at k = 140 for the two zero-entropy-rate sequences, and compression ratios ranging from 0.7 to 0.9 for the length-50 Bernoulli sequences.

2) Off-the-shelf Compressibility of the Bernoulli LZ78 Source: As the entropy rate of the Bernoulli LZ78 Source from Section V-B is 0, yet $\mu(\mathbf{X})$ is almost surely 1 for \mathbf{X} generated from the source, it is of interest to explore how real-world compressors perform on a realization of this probability source.

⁴As the codebook is drawn with probability approximately proportional to $2^{-LZ(\hat{X}^n)}$, sequences with a longer codelength are slower to compress because more samples must be drawn before the sequence can be reconstructed.

⁵Empirically, we found that this prior works best for compressing such short, low-entropy sequences.



Figure 4. Compression ratios of Q^{LZ} codebook compression for three simple sequences.

The context length that is relevant for compressing this source grows indefinitely, so it is particularly well-suited to LZ78 compression, which naturally handles growing context lengths. As we see, off-the-shelf LZ77-based compressors may or may not perform well, depending on the particular implementation.

In Figure 5, we compress different-length realizations of the Bernoulli LZ78 source using off-the-shelf compressors: ZSTD and GZIP. For ZSTD, we consider level 19, which is the recommended setting for maximal compression at the cost of increased compute, and level 9, which is a moderate tradeoff between compression ratio and compute. ZSTD does fairly well, scaling approximately with the LZ78 codelength. Surprisingly, level 9 outperforms level 19. The compression ratio of GZIP, however, suffers for longer sequences. As the context length of GZIP is fixed, it can at best achieve the finite-state compressibility as the sequence length tends towards infinity. By Theorem III.21, this is equal to $\mu(\mathbf{X})$, which is almost surely 1 for this probability source.



Figure 5. Compression ratio of industry-standard for compressing different-length realizations of the Bernoulli LZ78 probability source, along with the compression ratio of LZ78.

VII. CONCLUSION

We defined a universal class of sequential probability assignments based on the LZ78 sequential parsing algorithm [2]. The sequential probability assignment conditions on the LZ78 context associated with each symbol in the input sequence, and then applies a Bayesian mixture. Under a Dirichlet prior, the sequential probability assignment becomes an additive perturbation of the empirical distribution (conditioned on LZ78 context), and, with a specific choice of Dirichlet prior, becomes the SPA from [4]–[6]. We then proved that the log loss of any such LZ78 SPA converges to $\frac{1}{n}$ times the LZ78 codelength, uniformly over all individual sequences. From there, we were well-situated to prove the universality of any SPA from this family, in the sense that, for any individual sequence, it achieves at most the log loss of the best finite-state SPA. As a prerequisite to this, we consolidated a group of results from throughout the literature: that the optimal log loss over Markovian SPAs, the optimal log loss over finite-state SPAs, and a scaled version of the finite-state compressibility are all equal. Inspired by the LZ78 class of SPAs, we defined two equivalent formulations of a probability source that samples from an LZ78 SPA at each timestep. Finally, we used the LZ78 SPA for text generation, image classification, and text classification, showing promise to compete with existing approaches in a compute-constrained environment. We also performed preliminary experiments using the LZ78 probability source for text compression, as per [20].

In future work, we will explore the theoretical properties of the LZ78 probability source, including but not limited to its entropy rate. We will also thoroughly compare the capabilities of the LZ78 SPA to existing approaches in amount of data required, compute, and result quality. As an example, we will compare against the Ziv-Merhav cross-parsing [24] approach to classification. We may improve the performance of the LZ78 SPA by incorporating ideas from Active-LeZi [30], the LZ-based classifier from [10], mixture of experts models, *etc.* In addition, we will explore the capabilities of the LZ78

SPA and probability source for compression, via arithmetic coding [3] and the analysis in [20], respectively. All of these directions are currently under investigation.

ACKNOWLEDGMENTS

Discussions with Amir Dembo, Divija Hasteer, and Andrea Montanari are acknowledged with thanks.

APPENDIX A

EXAMPLE: LZ78 PARSING OF A SEQUENCE

We will demonstrate the formation of the LZ78 prefix tree via an example on a binary alphabet.

Consider the sequence

$$x^n = 01100110011.$$

The LZ78 prefix tree begins as a singular root node. We start at the beginning of the sequence and add the first symbol, 0, as a branch to the root node. 0 is then the first phrase. We then do the same thing with the next symbol, 1, which becomes the second phrase. After encoding the first two phrases, the tree is as follows:



So far, we have parsed x^n as 0, 1 and still have to encode 01100110011.

The next symbol is 1, which is already present as a branch off of the root. So, we traverse from the root to the node 1 and move onto the next symbol, 0, which can be added as a branch off of the node 1. After adding the new leaf, we say that the third phrase is 10.



By the process of LZ78 parsing, x^n is divided into the phrases 0, 1, 10, 01, 100, 11, forming the tree:



APPENDIX B PROOFS: THE LZ78 FAMILY OF SEQUENTIAL PROBABILITY ASSIGNMENTS

A. LZ78 Compression Algorithm

Lemma B.1. For any individual sequence \mathbf{x} , the length of the k^{th} phrase, denoted ℓ_k , grows unbounded. i.e., $\ell_k \to \infty$.

Proof. For contradiction, assume that $\lim_{k\to\infty} \ell_k \neq \infty$. This means that $\exists M < \infty$ s.t., $\forall k' > 0$, $\exists k > k'$ where $\ell_k \leq M$. As a consequence, there are infinitely many phrases such that $\ell_k \leq M$ (otherwise, we could set k' to be the last phrase with $\ell_k \leq M$). This is impossible because there are at most $\sum_{i=1}^{M} A^i \leq M A^M$ phrases with length $\leq M$.

B. Special Cases of the LZ78 Sequential Probability Assignment

The following theorems concern properties of the log loss of the particular LZ78-based SPA in Construction III.8.

Lemma B.2. For any full phrase in the LZ78 parsing of x^n , i.e., $\alpha \triangleq x_{t_0+1}^{t_1}$ s.t. $z(x^{t_1}) = \alpha$ and $z_c(x^{t_1}) = \emptyset$, the log loss incurred is

$$\log \frac{1}{q^{LZ78, g}(x_{t_0+1}^{t_1}|x^{t_0})} \le \log((A-1)C(x^{t_0}) + A),$$

with equality for all phrases α in the LZ78 parsing, except perhaps the last one.

Proof. Consider one full phrase that starts at t_0 , and denote the nodes of the prefix tree visited during that phrase z_0, z_1, \ldots, z_m . The first node, z_0 is always the root, and z_m is a leaf unless α is the last phrase in the parsing of x^n .

The log loss incurred by this phrase is:

$$\log \frac{1}{q^{\text{LZ78, g}}(x_{t_0+1}^{t_1}|x^{t_0})} = \log \left(\frac{\mathcal{L}(z_0)}{\mathcal{L}(z_1)} \cdot \frac{\mathcal{L}(z_1)}{\mathcal{L}(z_2)} \cdots \frac{\mathcal{L}(z_{m-1})}{\mathcal{L}(z_m)}\right) = \log \frac{\mathcal{L}(z_0)}{\mathcal{L}(z_m)}.$$

 $\mathcal{L}(z_m) \ge 1$, with equality if z_m is a leaf itself, and $\mathcal{L}(z_0)$, the number of leaves in the whole tree, is $(A-1)C(x^{t_0}) + A$. This is because the tree starts with A leaves, and each phrase removes one leaf (a node that was once a leaf now has children) and adds A new leaves (by construction).

Plugging these values in,

$$\log \frac{1}{q^{\text{LZ78, g}}(x_{t_0+1}^{t_1}|x^{t_0})} \le \log \left((A-1)C(x^{t_0}) + A \right),$$

with equality if z_m is a leaf, which must hold except for the last phrase of the LZ78 parsing.

Lemma III.9 (Log loss of Construction III.8). For any individual sequence and $q^{LZ78,g}$ from Construction III.8,

$$\max_{x^n} \left| \frac{1}{n} \log \frac{1}{q^{\text{LZ78, g}}(x^n)} - \frac{C(x^n) \log C(x^n)}{n} \right| = \epsilon(A, n),$$

where $\epsilon(A, n) \to 0$ as $n \to \infty$. By [2], this means that $\frac{1}{n} \log \frac{1}{q^{1Z/8, g(x^n)}}$ uniformly converges to $\frac{1}{n}$ times the LZ78 codelength.

Proof. We will first prove an upper bound $\max_{x^n} \left(\frac{1}{n} \log \frac{1}{q^{1\mathbb{Z78, g}(x^n)}} - \frac{C(x^n) \log C(x^n)}{n}\right) \leq \epsilon_1(A, n) = o(1)$, followed by a lower bound, $\min_{x^n} \left(\frac{1}{n} \log \frac{1}{q^{1\mathbb{Z78, g}(x^n)}} - \frac{C(x^n) \log C(x^n)}{n}\right) \geq -\epsilon_2(A, n) = o(1).$

Upper Bound: As a consequence of Lemma B.2, the ℓ^{th} phrase has scaled log loss $\leq \frac{1}{n} \log((A-1)\ell + A)$, with equality for all but potentially the last phrase.

$$\frac{1}{n} \sum_{\ell=1}^{C(x^n)-1} \log((A-1)\ell + A) \le \frac{1}{n} \log \frac{1}{q^{LZ78, g}(x^n)} \le \frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log((A-1)\ell + A).$$
(2)

The upper bound of (2) evaluates to

$$\begin{split} \frac{1}{n}\log\frac{1}{q^{\text{LZ78, g}}(x^n)} &\leq \frac{1}{n}\sum_{\ell=1}^{C(x^n)}\log\big((A-1)\ell + A\big) \leq \frac{1}{n}\sum_{\ell=1}^{C(x^n)}\log\big((A-1)(\ell+2)\big) \\ &= C(x^n)\frac{A-1}{n} + \frac{1}{n}\sum_{\ell=1}^{C(x^n)}\log(\ell+2) \leq C(x^n)\frac{A-1}{n} + \frac{C(x^n)\log C(x^n)}{n} + C_1\frac{C(x^n)}{n}, \end{split}$$

where C_1 is a constant such that $\log(\alpha + 2) \le \log(\alpha) + C_1$, $\forall \alpha \ge 1$. The number of phrases is uniformly $O\left(\frac{1}{\log n}\right)$ by [2], so $\max_{x^n} \frac{C(x^n)}{n} = C_2(A) \frac{1}{\log n}$, where $C_2(A)$ is a constant that only depends on the size of the alphabet.

$$\max_{x^n} \left(\frac{1}{n} \log \frac{1}{q^{\text{LZ78, g}}(x^n)} - \frac{C(x^n) \log C(x^n)}{n} \right) = \frac{C_3(A)}{\log n}$$

where $C_3(A)$ is a constant the only depends on the alphabet size.

Lower Bound: The lower bound of (2) simplifies to

$$\frac{1}{n}\log\frac{1}{q^{LZ78, g}(x^n)} \ge \frac{1}{n}\sum_{\ell=1}^{C(x^n)-1}\log((A-1)\ell + A) \ge \frac{1}{n}\sum_{\ell=1}^{C(x^n)-1}\log(\ell)$$
$$= \frac{1}{n}\sum_{\ell=1}^{C(x^n)}\log(\ell) - \frac{1}{n}\log C(x^n) = \frac{1}{n}\sum_{\ell=1}^{C(x^n)}\log(\ell) - C_2(A)\frac{\log(n/\log n)}{n}$$

where $C_2(A)$ is as in the upper bound. We want to show that $\min_{x^n} \left(\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) - \frac{1}{n} C(x^n) \log C(x^n)\right) = o(1)$, *i.e.*:

$$\forall \epsilon > 0, \ \exists N > 0 \ \text{s.t.} \ \forall n > N, \ \min_{x^n} \left(\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) - \frac{1}{n} C(x^n) \log C(x^n) \right) > -\epsilon.$$

We introduce a parameter ξ (which we will explicitly set later, independent of the individual sequence x^n), and consider the sum $\xi C(x^n)$ to $C(x^n)$:

$$\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) \ge \frac{1}{n} \sum_{\ell=\xi C(x^n)}^{C(x^n)} \log(\ell) \ge \frac{1}{n} (1-\xi)C(x^n)(\log\xi + \log C(x^n))$$
$$= \frac{1}{n} (1-\xi)C(x^n)\log C(x^n) + (1-\xi)(\log\xi)C_2(A)\frac{1}{\log n}$$
$$\triangleq \frac{1}{n}C(x^n)\log C(x^n) - \frac{\xi}{n}C(x^n)\log C(x^n) - \frac{C_4(A,\xi)}{\log(n)}.$$

As $C(x^n) \leq C_2(A) \frac{n}{\log n}$, it can be directly shown that $\frac{C(x^n) \log C(x^n)}{n} < 2C_2(A)$, $\forall n \geq 2$. So, choosing $\xi = \frac{\epsilon}{4C_2(A)}$,

$$\min_{x^n} \left(\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) - \frac{1}{n} C(x^n) \log C(x^n) \right) > -\frac{C(x^n) \log C(x^n)}{n} \frac{\epsilon}{4C_2(A)} - \frac{C_4(A,\epsilon)}{\log n} > -\frac{\epsilon}{2} - \frac{C_4(A,\epsilon)}{\log n}.$$

As $\frac{C_4(A,\epsilon)}{\log n}$ vanishes, $\exists N > 0$ such that, $\forall n > N$, $\frac{C_4(A,\epsilon)}{\log n}$ has magnitude less than $\frac{\epsilon}{2}$. So, for all such n,

$$\min_{x^n} \left(\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) - \frac{1}{n} C(x^n) \log C(x^n) \right) > -\frac{\epsilon}{2} - \frac{\epsilon}{2} = -\epsilon.$$

$$\therefore, \min_{x^n} \left(\frac{1}{n} \sum_{\ell=1}^{C(x^n)} \log(\ell) - \frac{1}{n} C(x^n) \log C(x^n) \right) - \epsilon_2(A, n), \text{ where } \epsilon_2(A, n) \to 0 \text{ as } n \to \infty.$$

Putting the lower and upper bound together achieves the desired result via the squeeze theorem.

C. Correspondence of LZ78 Sequential Probability Assignment Log Loss and LZ78 Codelength

We wish to show that the sequential probability assignment log loss incurred by any SPA in the family Construction III.4⁶ approaches the $\frac{1}{n}$ -scaled LZ78 codelength, uniformly over all individual sequences. As [2] proves that the distance between the scaled LZ78 codelength and $\frac{C(x^n) \log C(x^n)}{n}$ uniformly converges to 0, it suffices to show that the distance between the log loss and $\frac{C(x^n) \log C(x^n)}{n}$ uniformly approaches 0 as well.

⁶with a prior bounded away from 0

From Lemma III.9, we know that this result holds for the specific instance of the LZ78 SPA described in Construction III.8. So, we will show that the log loss achieved by Construction III.4 for any two priors with a density bounded away from zero is asymptotically equivalent, uniformly over all individual sequences.

To do so, we make use of the following result from [32]:

Theorem B.3 ([32], equation (50)). For any prior bounded away from 0 (i.e., $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$),

$$\max_{x^n} \frac{1}{n} \sum_{t=1}^n \log \frac{1}{q^f(x_t | x^{t-1})} - \frac{1}{n} \hat{H}(x^n) \le C_1(A) \frac{\log(n)}{n} + \frac{C_2(A)}{n}$$

where $\hat{H}(x^n)$ is the empirical entropy of x^n , and $C_1(A)$ and $C_2(A)$ are constants that only depend on the size of the alphabet and the choice of prior.

Using this result, we can show that the asymptotic log loss achieved by any SPA in the LZ78 family is the same: Lemma B.4. For any prior such that $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$,

$$\max_{x^n} \left| \frac{1}{n} \log \frac{1}{q^{LZ78, f}(x^n)} - \frac{1}{n} \sum_{z \in \mathcal{Z}(x^n)} \hat{H} \left(\{ x_t : z_c(x^t) = z \} \right) \right| = o(1).$$

Proof. Let $y_z^{m_z}$ be the subsequence of x^n consisting of the symbols with an LZ78 context of z, *i.e.*, $\{x_t : z_c(x^t) = z\}$.⁷ m_z is the length of this subsequence. By construction, the log loss of $q^{LZ78, f}$ can be divided into the subsequences corresponding to each LZ78 context:

$$\log \frac{1}{q^{\text{LZ78, f}}(x^n)} = \sum_{z \in \mathcal{Z}(x^n)} \log \frac{1}{q^f(y_z^{m_z})}.$$

The scaled log loss of $q^f(y^m)$ is lower-bounded by the empirical entropy, as the mixture distribution is upper-bounded by the maximum likelihood of y^m over i.i.d. Ber(Θ) laws, so

$$\log \frac{1}{q^f(y^m)} \le \log \frac{1}{\max_{\Theta} \prod_{i=1}^m \Theta(y_i)} = \hat{H}(y^m).$$

So, by Theorem B.3,

$$\max_{y^m} \left| \frac{1}{m} \log \frac{1}{q^f(y^m)} - \frac{1}{m} \hat{H}(y^m) \right| \leq \alpha \log m,$$

where α is a constant that only depends on f and the size of the alphabet. By the triangle inequality,

$$\max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{\text{LZ78, f}}(x^n)} - \sum_{z \in \mathcal{Z}(x^n)} \hat{H}(y_z^{m_z}) \right| \le \max_{x^n} \frac{1}{n} \sum_{z \in \mathcal{Z}(x^n)} \alpha \log m_z.$$

Multiplying and dividing by $|\mathcal{Z}(x^n)| = C(x^n)$, we can apply Jensen's inequality to get

$$\max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{\text{LZ78, f}}(x^n)} - \sum_{z \in \mathcal{Z}(x^n)} \hat{H}(y_z^{m_z}) \right| \leq \max_{x^n} \frac{\alpha C(x^n)}{n} \sum_{z \in \mathcal{Z}(x^n)} \frac{1}{C(x^n)} \log m_z \leq \max_{x^n} \frac{\alpha C(x^n)}{n} \log \left(\frac{\sum_{z \in \mathcal{Z}(x^n)} m_z}{C(x^n)} \right) \\
= \max_{x^n} \alpha \frac{C(x^n)}{n} \log \frac{n}{C(x^n)} = o(1),$$

as, by [2], $\max_{x^n} \frac{C(x^n)}{n} = o(1)$.

Putting this result together with Lemma III.9,

Theorem III.10. For any prior such that $\inf_{\theta \in \mathcal{M}(\mathcal{A})} f(\theta) > 0$,

$$\lim_{n \to \infty} \max_{x^n} \left| \frac{1}{n} \log \frac{1}{q^{LZ78, f}(x^n)} - \frac{C(x^n) \log C(x^n)}{n} \right| = 0.$$

⁷As in Construction III.4, $\{x_t : \cdots\}$ refers to the ordered subsequence of symbols with a given LZ78 context.

Proof. Denote the SPA corresponding to Construction III.8 as $q^{LZ78,g}$, where g is the PDF of the Dirichlet $(\frac{1}{A-1}, \dots, \frac{1}{A-1})$ prior. Also, for brevity, denote the asymptotic LZ78 codelength by $C(x^n) \log C(x^n)$, by $\ell_{LZ78}(x^n)$, and the quantity $\sum_{z \in \mathcal{Z}(x^n)} \hat{H}(y_z^{m_z})$ from Theorem III.10 by $H^{LZ78}(x^n)$.

By the triangle inequality and Lemma III.9,

$$\begin{split} \max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{LZ78,f}(x^n)} - \ell_{\text{LZ78}}(x^n) \right| &\leq \max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{LZ78,g}(x^n)} - \ell_{\text{LZ78}}(x^n) \right| + \max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{LZ78,g}(x^n)} - \log \frac{1}{q^{LZ78,f}(x^n)} \right| \\ &\leq o(1) + \max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{\text{LZ78,f}}(x^n)} - H^{\text{LZ78}}(x^n) \right| + \max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{\text{LZ78,g}}(x^n)} - H^{\text{LZ78}}(x^n) \right| . \end{split}$$

By Lemma B.4, the final two terms are o(1) as well, so

$$\max_{x^n} \frac{1}{n} \left| \log \frac{1}{q^{LZ78, f}(x^n)} - \ell_{\text{LZ78}}(x^n) \right| = o(1) \text{ as } n \to \infty.$$

D. Optimal Markov and Finite-State Log Loss in terms of Empirical Entropies

1) Empirical Distributions: In order to precisely define the empirical entropies mentioned in Section III-E1, we define some empirical distributions over individual sequence x^n . In addition, for finite-state SPAs, we define empirical distributions over the list of states, s^n .

Definition B.5 (Zero-order empirical distribution). X, the random variable following the zero-order empirical distribution of x^n , has law $\mathbb{P}(X = a) = \frac{N(a|x^n)}{n}$.

Definition B.6 (k-order empirical distribution). The k-order empirical distribution of x^n is defined as the law

$$\mathbb{P}(X^{k} = a^{k}) = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1} \left\{ x_{i}^{i+k-1} = a^{k} \right\},\$$

where indices greater than n "wrap around" to the beginning of the sequence. This wrapping is known as the **circular** convention.

Remark B.7. From Definition B.6, a conditional distribution can also be defined:

$$\mathbb{P}(X_k = a_k | X^{k-1} = a^{k-1}) = \frac{1}{|\{t : x_t^{t+k-2} = a^{k-1}\}|} \sum_{i=1}^n \mathbf{1} \left\{ x_i^{i+k-1} = a^k \right\}.$$

For a fixed a^{k-1} , this is equivalent to the zero-order empirical distribution of the subsequence $\{x_t : x_{t-k}^{t-1} = a^{k-1}\}$, where x_{t-k}^{t-1} is evaluated using the circular convention.

Definition B.8 (Finite-state empirical distribution). For finite-state SPAs, we can define the empirical distribution of the states s^n exactly as we defined the distribution of X. The joint empirical distribution of (x^n, s^n) is defined as

$$\mathbb{P}(X = a, S = s) = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1} \{ x_i = a, s_i = s \}.$$

The k-order joint empirical distribution of (x^n, s^n) is defined analogously as in Definition B.6, as is $\mathbb{P}(X|S)$.

For any individual sequence x^n and an associated set of states s^n , the k-order empirical distribution of (x^n, s^n) satisfies the following property:

Lemma B.9. Let (X^k, S^k) follow the joint k-order empirical distribution of (x^n, s^n) . Then, $(X_\ell, S_\ell) \stackrel{d}{=} (X, S), \forall \ell \in [k]$, where (X, S) is the zero-order joint empirical distribution of (x^n, s^n) .

Proof. The distribution of (X^k, S^k) is

$$\mathbb{P}\left(X^{k} = a^{k}, S^{k} = s^{k}\right) = \frac{1}{n} \# \left\{x_{i}^{i+k-1} = a^{k}, s_{i}^{i+k-1} = s^{k}\right\}_{i \in [n]},$$

where we follow the circular convention.

Then, the distribution of (X_{ℓ}, S_{ℓ}) is defined by

$$\begin{split} \mathbb{P}(X_{\ell} = a, S_{\ell} = s) &= \sum_{\substack{a^{k} \in \mathcal{A}^{k}: a_{\ell} = a \\ s^{k} \in [M]^{k}: s_{\ell} = s}} \mathbb{P}\left(X^{k} = a^{k}, S^{k} = s^{k}\right) \\ &= \frac{1}{n} \sum_{\substack{a^{k} \in \mathcal{A}^{k}: a_{\ell} = a \\ s^{k} \in [M]^{k}: s_{\ell} = s}} \#\left\{x_{i}^{i+k-1} = a^{k}, s_{i}^{i+k-1} = s^{k}\right\}_{i \in [n]} \\ &= \frac{1}{n} \#\left\{x_{i+\ell-1} = a, s_{i+\ell-1} = s\right\}_{i \in [n]} = \frac{1}{n} N\left((a, s)|(x^{n}, s^{n})\right) = \mathbb{P}(X = a, S = s), \end{split}$$

where, the second-to-last step is a result of the circular convention.

Corollary B.10. Via a similar proof to that of Lemma B.9, we can show that $(X_{\ell}^{\ell+r-1}, S_{\ell}^{\ell+r-1}) \stackrel{d}{=} (X^r, S^r), \forall \ell, r \in [k].$

2) Equivalence of Log Losses and Empirical Entropies: We can now show the equivalence of $\mu_k(\mathbf{x})$ and $\lambda_M(\mathbf{x})$ to conditional entropies of the corresponding empirical distributions, the specifics of which are discussed in the following lemmas.

Lemma B.11 (Equivalence of Zero-Order Markov Loss to Empirical Entropy). For all individual sequences x^n , the optimal zero-order Markov log loss is equal to the empirical entropy. i.e., $\mu_0(x^n) = H(X)$, where X follows the zero-order empirical distribution of x^n .

Proof. The zero-order optimal log loss is

$$\mu_0(x^n) = \min_{q \in \mathcal{M}(\mathcal{A})} \frac{1}{n} \sum_{t=1}^n \log \frac{1}{q(x_t)} \stackrel{(a)}{=} \min_{q \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \frac{N(a|x^n)}{n} \log \frac{1}{q(a)} = \min_{q \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \mathbb{P}(X=a) \log \frac{1}{q(a)}$$
$$= H(X) + \min_{q \in \mathcal{M}(\mathcal{A})} D(X||Y \sim q) \stackrel{(b)}{=} H(X),$$

where D(X||Y) represents relative entropy. (a) follows from rearranging the sum, and (b) is a result of the fact that relative entropy is a non-negative quantity, with a minimum of 0 when the two distributions are identical.

In order to extrapolate this to k-order Markov SPA log loss, we make use of the following property: the optimal k-order Markov log loss can be achieved by dividing the input sequence into subsequences for every possible length-k context and then applying a probability assignment that achieves the optimal zero-order Markov log loss to each subsequence.

Lemma B.12 (Relationship between zero-order and k-order Markov log loss). For any sequence y,

$$m \cdot \mu_k(y^m) = \sum_{z \in \mathcal{A}^k} \left| \{k+1 \le t \le n : y_{t-k}^{t-1} = z\} \right| \mu_0 \left(\{y_t : k+1 \le t \le n, y_{t-k}^{t-1} = z\} \right).$$

Proof. As a k-order Markov SPA is allowed to attain a log loss of zero over the first k symbols,

$$m\mu_k(y^m) = \min_{q \in \mathcal{M}_k} \sum_{t=k+1}^m \log \frac{1}{q(y_t | y_{t-k}^{t-1})} = \sum_{z \in \mathcal{A}^k} \min_{q_z \in \mathcal{M}(\mathcal{A})} \log \frac{1}{q_z \left(\{y_t : y_{t-k}^{t-1} = z\} \right)}$$
$$= \sum_{z \in \mathcal{A}^k} \left| \{y_t : y_{t-k}^{t-1} = z\} \right| \mu_0 \left(\{y_t : y_{t-k}^{t-1} = z\} \right).$$

Lemma B.13 (Equivalence of k-Order Markov Loss to Conditional Entropy). $\forall k \ge 1$ and sequence x^n ,

$$H(X_{k+1}|X^k) - \epsilon(k, n) \le \mu_k(x^n) \le H(X_{k+1}|X^k),$$

where X^{k+1} follows the (k+1)-order empirical distribution of x^n and $\lim_{n\to\infty} \epsilon(k,n) = 0$.

Proof. We first prove the upper bound, $\mu_k(x^n) \leq H(X_{k+1}|X^k)$, followed by the lower bound, $H(X_{k+1}|X^k) - \epsilon(k,n)$.

1

Upper bound: By Lemma B.12,

$$\mu_k(x^n) = \sum_{z \in \mathcal{A}^k} \frac{\left| \{x_t : x_{t-k}^{t-1} = z\} \right|}{n} \mu_0\left(\{x_t : x_{t-k}^{t-1} = z\} \right),$$

where the circular convention is not used. As applying the circular convention can only increase each term of the summation, $\mu_k(x^n)$ can be upper-bounded by applying the circular convention:

$$\begin{split} \mu_k(x^n) &\leq \sum_{z \in \mathcal{A}^k} \frac{\left| \{x_t : x_{t-k}^{t-1} = z\} \right|}{n} \mu_0\left(\{y_t : y_{t-k}^{t-1} = z\} \right) \quad \text{(with circular convention)} \\ &= \sum_{z \in \mathcal{A}^k} \mathbb{P}(X^k = z) \mu_0\left(\{x_t : x_{t-k}^{t-1} = z\} \right) \\ &= \sum_{z \in \mathcal{A}^k} \mathbb{P}(X^k = z) H(X_{k+1} | X^k = z) = H(X_{k+1} | X^k). \end{split}$$

Lower bound: First, define \tilde{X}^{k+1} according to the following empirical distribution:

$$\mathbb{P}\left(\tilde{X}^{k+1} = a^{k+1}\right) = \frac{1}{n-k} \sum_{i=1}^{n-k} \mathbf{1}\left\{x_i^{i+k} = a^{k+1}\right\}.$$

This is similar to the (k+1)-order emprical distribution of x^n , but we only consider the first n-k length-(k+1) sequences instead of using the circular convention.

By Lemma B.12 and analysis identical to that in the proof of the upper bound,

$$\mu_{k}(x^{n}) = \frac{n-k}{n} \sum_{z \in \mathcal{A}^{k}} \frac{\left| \{x_{t} : x_{t-k}^{t-1} = z\} \right|}{n-k} \mu_{0} \left(\{x_{t} : x_{t-k}^{t-1} = z\} \right) \quad \text{(without circular convention)}$$
$$= \frac{n-k}{n} \sum_{z \in \mathcal{A}^{k}} \mathbb{P} \left(\tilde{X}^{k} = z \right) H(\tilde{X}_{k+1} | X^{k} = z) = \frac{n-k}{n} H(\tilde{X}_{k+1} | \tilde{X}^{k}).$$

 $H(\tilde{X}_{k+1}|\tilde{X}^k)$ is bounded and $\frac{k}{n} \to 0$ as $n \to \infty$, so the second term is o(1) as $n \to \infty$ and k is fixed. Therefore, it is sufficient to show that $H(\tilde{X}_{k+1}|\tilde{X}^k) = H(X_{k+1}|X^k) - \xi(k,n)$, where $\lim_{n\to\infty} \xi(k,n) = 0$.

Equivalently, we show that $\lim_{n\to\infty} \left| H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \right| = 0.$

By the chain rule of entropy and the triangle inequality,

$$\left| H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \right| \le \left| H(\tilde{X}^{k+1}) - H(X^{k+1}) \right| + \left| H(\tilde{X}^k) - H(X^k) \right|.$$

Entropy is uniformly continuous with respect to the probability mass function and the ℓ_1 metric,⁸ as each term of the summation $H(X) = \sum_{a \in \mathcal{A}} p_a \log \frac{1}{p_a}$ is continuous and bounded over a compact domain.

By the definition of uniform continuity,

$$\forall \epsilon > 0, \ \exists \delta_{\epsilon} > 0 \ \text{s.t.} \ \forall P, Q \in \mathcal{M}(\mathcal{A}), \ \|P - Q\|_1 < \delta_{\epsilon} \implies |H_P(X) - H_Q(X)| < \epsilon.$$

To apply uniform continuity to show that $\lim_{n\to\infty} \left| H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \right| = 0$, we must verify that $\left\| \mathbb{P}(\tilde{X}^{k+1}) - \mathbb{P}(X^{k+1}) \right\|_1 \to 0$ and $\left\| \mathbb{P}(\tilde{X}^k) - \mathbb{P}(X^k) \right\|_1 \to 0$ as $n \to \infty$.

By the definitions of the empirical distributions for X^{k+1} and \tilde{X}^{k+1} , $\forall a^{k+1} \in \mathcal{A}^{k+1}$,

$$\begin{split} \mathbb{P}(X^{k+1} = a^{k+1}) &= \frac{1}{n} \# \left\{ x_i^{i+k} = a^{k+1} \right\}_{i \in [n]} = \frac{1}{n} \# \left\{ x_i^{i+k} = a^{k+1} \right\}_{i \in [n-k]} + \frac{1}{n} \# \left\{ x_i^{i+k} = a^{k+1} \right\}_{n-k < i \le n} \\ &= \frac{n-k}{n} \mathbb{P}(\tilde{X}^{k+1} = a^{k+1}) + \frac{1}{n} \# \left\{ x_i^{i+k} = a^{k+1} \right\}_{n-k < i \le n} . \end{split}$$

⁸The ℓ_1 metric for probability mass functions P, Q is taken to be $||P - Q||_1 = \sum_{a \in \mathcal{A}} |P(a) - Q(a)|$.

As
$$\#\{x_i^{i+k} = a^{k+1}\}_{n-k < i \le n} \le |\{i : n-k < i \le n\}| = k,$$

$$\mathbb{P}(\tilde{X}^{k+1} = a^{k+1}) - \frac{k}{n} \le \mathbb{P}(X^{k+1} = a^{k+1}) \le \mathbb{P}(\tilde{X}^{k+1} = a^{k+1}) + \frac{k}{n}$$

Via an identical argument, the exact same relation holds for $\mathbb{P}(X^k = a^k)$.

We can now directly show that $\lim_{n\to\infty} \left| H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \right| = 0$. Choose arbitrarily-small $\epsilon > 0$. As entropy is uniformly continuous, $\exists \delta_1 > 0$ and $\delta_2 > 0$ such that

$$\begin{aligned} \left\| \mathbb{P}(X^{k+1}) - \mathbb{P}(\tilde{X}^{k+1}) \right\|_1 < \delta_1 \implies \left| H(\tilde{X}^{k+1}) - H(X^{k+1}) \right| < \epsilon/2, \\ \left\| \mathbb{P}(X^k) - \mathbb{P}(\tilde{X}^k) \right\|_1 < \delta_2 \implies \left| H(\tilde{X}^k) - H(X^k) \right| < \epsilon/2. \end{aligned}$$

Let $N = \left\lceil \frac{A^{k+1}k}{\min(\delta_1, \delta_2)} \right\rceil$. Then, $\forall n > N$, $\left\| \mathbb{P}(X^{k+1}) - \mathbb{P}(\tilde{X}^k) \right\|$

$$\mathbb{P}(X^{k+1}) - \mathbb{P}(\tilde{X}^{k+1}) \Big\|_1 \le \frac{k}{n} A^{k+1} < \delta_1, \text{ and } \Big\| \mathbb{P}(X^k) - \mathbb{P}(\tilde{X}^k) \Big\|_1 \le \frac{k}{n} A^k < \delta_2.$$

Therefore, $\forall n > N$,

$$H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \Big| \le \epsilon/2 + \epsilon/2 = \epsilon.$$

As ϵ is arbitrary, $\lim_{n\to\infty} \left| H(X_{k+1}|X^k) - H(\tilde{X}_{k+1}|\tilde{X}^k) \right| = 0.$

To draw a similar connection between the optimal finite state-log loss and the empirical entropy of x^n given the corresponding states, we analyze the behavior of SPAs in \mathcal{F}_M^{g,s_1} , which denotes the set of *M*-state SPAs with fixed state transition function g and initial state s_1 . Define the optimal loss over this class of SPAs as

$$\lambda_M^{g,s_1}(x^n) \triangleq \min_{q^{g,s_1,f} \in \mathcal{F}_M^{g,s_1}} \frac{1}{n} \log \frac{1}{q^{g,s_1,f}(x^n)}.$$

Lemma B.14 (Equivalence of Finite-State Log Loss to Conditional Entropy). \forall sequences x^n , state transition functions g, and initial states s_1 ,

$$\lambda_M^{g,s_1}(x^n) = H(X|S),$$

where (X, S) follow the joint empirical distribution of (x^n, s^n) , where s^n is a function of x^n , g and s_1 .

Proof. By the definition of $\lambda_M^{g,s_1}(x^n)$,

$$\lambda_M^{g,s_1}(x^n) = \min_{q^{g,s_1,f} \in \mathcal{F}_M^{g,s_1}} \frac{1}{n} \log \frac{1}{q^{g,s_1}(x^n)} = \min_{f:[M] \to \mathcal{M}(\mathcal{A})} \frac{1}{n} \sum_{i=1}^n \log \frac{1}{f(s_i)(x_i)},$$

where s_i is the *i*th state, determined by x^i , g and s_1 . Rearranging the summation,

$$\lambda_M^{g,s_1}(x^n) = \min_{f:[M] \to \mathcal{M}(\mathcal{A})} \frac{1}{n} \sum_{(a,s) \in \mathcal{A} \times [M]} N\left((a,s)|(x^n,s^n)\right) \log \frac{1}{f(s)(a)}$$
$$= \min_{f:[M] \to \mathcal{M}(\mathcal{A})} \sum_{(a,s) \in \mathcal{A} \times [M]} \mathbb{P}(X = a, S = s) \log \frac{1}{f(s)(a)}$$
$$= \sum_{s \in [M]} \mathbb{P}(S = s) \min_{f_s \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \mathbb{P}(X = a|S = s) \log \frac{1}{f_s(a)}.$$

As in Lemma B.11, we write this expression as the sum of a condition entropy and a sum of relative entropies.

$$\lambda_M^{g,s_1}(x^n) = H(X|S) + \sum_{s \in [M]} \mathbb{P}(S=s) \min_{f_s \in \mathcal{M}(\mathcal{A})} D\left(\mathbb{P}_{X|S}(\cdot|S=s)||f_s\right).$$

 $D\left(\mathbb{P}_{X|S}(\cdot|S=s)||f_s\right)$ achieves the minimum of 0 when $f_s = \mathbb{P}(X|S=s)$, so $\lambda_M^{g,s_1}(x^n) = H(X|S)$.

E. Equivalence of Optimal Finite-State Log Loss and Markov Log Loss, and Finite-State Compressibility

The proof that, for any individual sequence, $\lambda(\mathbf{x}) = \mu(\mathbf{x}) = \rho(\mathbf{x}) \log A$, is divided into three parts. First, we prove that $\lambda(\mathbf{x}) = \mu(\mathbf{x})$ by proving that $\lambda(\mathbf{x})$ is both upper- and lower-bounded by $\mu(\mathbf{x})$. Then, we directly prove that $\mu(\mathbf{x}) = \rho(\mathbf{x}) \log A$.

Lemma B.15 (Upper bound of $\lambda(\mathbf{x})$ by $\mu(\mathbf{x})$). For all individual sequences,

$$\lambda(\mathbf{x}) \leq \mu(\mathbf{x})$$

Proof. By Fact III.15, as any k-order Markov SPA is also an A^k -state SPA, $\mathcal{M}_k \subseteq \mathcal{F}_{A^k}$, so $\lambda_{A^k}(x^n) \leq \mu_k(x^n)$. Taking $\limsup_{n \to \infty}$ on both sides, $\lambda_{A^k}(\mathbf{x}) \leq \mu_k(\mathbf{x})$. So, as $\lambda_M(\mathbf{x})$ is monotonically non-increasing in M, $\lambda(\mathbf{x}) \leq \mu_k(\mathbf{x})$, $\forall k \geq 0$. Taking the limit as $k \to \infty$, we have $\lambda(\mathbf{x}) \leq \mu(\mathbf{x})$.

The proof of the upper bound, $\lambda(\mathbf{x}) \ge \mu(\mathbf{x})$, is primarily based on the following claim:

Claim B.16. \forall finite sequences x^n , number of states M, and Markov order k,

$$\mu_k(x^n) - \lambda_M(x^n) \le \frac{\log M}{k+1}.$$

Proof. By Lemma B.13, Lemma B.14, and Lemma B.9,

$$\mu_k(x^n) - \lambda_M^{g,s_1}(x^n) \le H(X_{k+1}|X^k) - H(X|S) = H(X_{k+1}|X^k) - H(X_{k+1}|S_{k+1})$$

where (X^{k+1}, S^{k+1}) is the (k+1)-order joint empirical distribution of the sequence and corresponding states.

We will now apply rules of conditional entropy such that we can take advantage of the deterministic finite state dynamics and the chain rule of entropy.

As conditioning reduces entropy,

$$\mu_k(x^n) - \lambda_M^{g,s_1}(x^n) \le \frac{1}{k+1} \sum_{j=-1}^{k-1} \left(H(X_{k+1}|X_{k-j}^k) - H(X_{k+1}|S_{k+1}, X_{k-j}^k, S_{k-j}) \right),$$

because the right-hand side is an average where each term is $\geq \mu_k(x^n) - \lambda_M^{g,s_1}(x^n)$ (we condition on fewer variables than in $H(X_{k+1}|X^k)$ for the first component of each term, and we condition on more variables than H(X|S) for the second component).

Given S_{k-j} and X_{k-j}^k , we deterministically know S_{k+1} via applying the state-transition function g. So, $H(X_{k+1}|S_{k+1}, X_{k-j}^k, S_{k-j})$ is equivalent to $H(X_{k+1}|X_{k-j}^k, S_{k-j})$. Expanding the summation and applying Corollary B.10,

$$\mu_k(x^n) - \lambda_M^{g,s_1}(x^n) \le \frac{1}{k+1} \bigg[\left(H(X_1) + H(X_2|X_1) \dots + H(X_{k+1}|X^k) \right) \\ - \left(H(X_1|S_1) + H(X_2|X_1,S_1) + \dots + H(X_{k+1}|X^k,S_1) \right) \bigg].$$

By pattern-matching with the chain rule of entropy,

$$\mu_k(x^n) - \lambda_M^{g,s_1}(x^n) \le \frac{1}{k+1} \left(H(X^{k+1}) - H(X^{k+1}|S_1) \right) = \frac{1}{k+1} I(X^{k+1};S_1) \le \frac{1}{k+1} H(S_1) \le \frac{\log M}{k+1},$$

where the second and third steps follow directly from the definition of mutual information.

Lemma B.17 (Lower bound of $\lambda(\mathbf{x})$ by $\mu(\mathbf{x})$). For all individual sequences,

$$\lambda(\mathbf{x}) \ge \mu(\mathbf{x})$$

Proof. By Claim B.16,

$$\limsup_{n \to \infty} \mu_k(x^n) \le \limsup_{n \to \infty} \lambda_M(x^n) + \frac{\log M}{k+1} \implies \mu_k(\mathbf{x}) \le \lambda_M(\mathbf{x}) + \frac{\log M}{k+1}, \, \forall \mathbf{x}, M, k.$$

First, fix M and take the limit as $k \to \infty$ to get

$$\mu(\mathbf{x}) \leq \lambda_M(\mathbf{x}), \,\forall M.$$

Then, we obtain the desired result by taking $M \to \infty$.

$$\mu(\mathbf{x}) \le \lambda(\mathbf{x}).$$

The proof that $\rho(\mathbf{x}) \log A = \mu(\mathbf{x})$ follows from Theorem 3 of [2], which states that $\rho(\mathbf{x}) = \hat{H}(\mathbf{x}) \log A$,⁹ where $\hat{H}(\mathbf{x})$ is defined as follows:

Definition B.18. As in the proof for the lower bound in Lemma B.13, let \tilde{X}^{k+1} follow empirical distribution

$$\mathbb{P}\left(\tilde{X}^{k+1} = a^{k+1}\right) = \frac{1}{n-k} \sum_{i=1}^{n-k} \mathbf{1}\left\{x_i^{i+k} = a^{k+1}\right\}.$$

Here, we only consider the first n-k length-(k+1) sequences instead of using the circular convention. $\hat{H}(\mathbf{x})$ is defined as

$$\hat{H}(\mathbf{x}) \triangleq \lim_{k \to \infty} \hat{H}_k(x^n), \text{ where } \hat{H}_k(x^n) \triangleq \limsup_{n \to \infty} \hat{H}_k(x^n) \triangleq \limsup_{n \to \infty} \frac{1}{k} H(\tilde{X}^k)).$$

Lemma B.19 (Equivalence of $\rho(\mathbf{x})$ and $\mu(\mathbf{x})$). For all individual sequences,

$$\mu(\mathbf{x}) = \rho(\mathbf{x}) \log A.$$

Proof. Let X^k be the empirical distribution from Definition B.6, *i.e.*, using the circular convention. As part of the proof of the lower bound in Lemma B.13, we showed that $\lim_{n\to\infty} |H(X^k) - H(\tilde{X}^k)| = 0$, so $\hat{H}_k(\mathbf{x}) = \lim_{n\to\infty} \sup_{n\to\infty} \frac{1}{k} H(X^k)$.

By the chain rule of entropy and Lemma B.13,

$$\hat{H}_k(\mathbf{x}) = \frac{1}{k} \lim_{n \to \infty} \left(H(X_1) + H(X_2|X_1) + \dots + H(X_k|X^{k-1}) \right) = \frac{1}{k} \sum_{\ell=0}^{k-1} \mu_\ell(\mathbf{x}).$$

We would like to show that $\lim_{k\to\infty} \hat{H}_k(\mathbf{x}) = \mu(\mathbf{x})$, *i.e.*, that, $\forall \epsilon > 0$, $\exists K > 0$, s.t., $\forall k > K$, $|\hat{H}_k(\mathbf{x}) - \mu(\mathbf{x})| < \epsilon$.

As $\lim_{k\to\infty} \mu_k(\mathbf{x}) = \mu(\mathbf{x}), \exists L \text{ s.t., } \forall \ell > L, |\mu_\ell(\mathbf{x}) - \mu(\mathbf{x})| < \frac{\epsilon}{2}$. Choose $K > \frac{2L \log A}{\epsilon}$. Then, $\forall k > K$,

$$\begin{aligned} \left| \hat{H}_{k}(\mathbf{x}) - \mu(\mathbf{x}) \right| &= \left| \frac{1}{k} \sum_{\ell=0}^{k-1} \mu_{\ell}(\mathbf{x}) - \mu(\mathbf{x}) \right| \leq \frac{1}{k} \sum_{\ell=0}^{L} \left| \mu_{\ell}(\mathbf{x}) - \mu(\mathbf{x}) \right| + \frac{1}{k} \sum_{\ell=L}^{k-1} \left| \mu_{\ell}(\mathbf{x}) - \mu(\mathbf{x}) \right| \\ &< \frac{1}{k} \sum_{\ell=0}^{L} \left| \mu_{\ell}(\mathbf{x}) - \mu(\mathbf{x}) \right| + \frac{\epsilon}{2} < \epsilon, \end{aligned}$$

where the final inequality follows from the fact that $0 \le \mu_{\ell}(\mathbf{x}) \le \log A$ and the same holds for $\mu(\mathbf{x})$.

$$\therefore, \hat{H}_k(\mathbf{x}) \to \mu(\mathbf{x}) \text{ as } k \to \infty. \text{ And, as } \rho(\mathbf{x}) \log A = \hat{H}(\mathbf{x}), \ \rho(\mathbf{x}) \log A = \mu(\mathbf{x}).$$

Theorem III.21. For any infinite individual sequence, the optimal finite-state log loss, optimal Markov SPA log loss, and finite-state compressibility are equivalent:

$$\lambda(\mathbf{x}) = \mu(\mathbf{x}) = \rho(\mathbf{x}) \log A.$$

Proof. This is encompassed in Lemma B.15, Lemma B.17, and Lemma B.19.

⁹The definition of $\hat{H}(\mathbf{x})$ here is a factor of log A off from the definition in [2] in order to be more consistent with the work in Section III-E1.

APPENDIX C PROOFS: OPTIMALITY OF THE LZ78 FAMILY OF SPAS

A. Results for Stationary and Ergodic Probability Sources

Here, we detail how much of the work on sequential probability assignments for individual sequences extends to sequential probability assignments for stationary stochastic processes.

First, the correspondence between the optimal k-order Markov loss and the corresponding empirical entropy, in the individual sequence setting, translates over to the following result:

Lemma C.1. For any stationary stochastic process X,

- (a) $\mathbb{E}\mu_0(X^n) \leq H(X_1)$, and
- (b) $\mathbb{E}\mu_k(X^n) \le H(X_{k+1}|X_k).$

Proof. (a) The expectation of $\mu_0(X^n)$ is

$$\mathbb{E}\mu_0(X^n) = \mathbb{E}\left[\frac{1}{n}\min_{q_t \in \mu_0} \sum_{t=1}^n \log \frac{1}{q(X^t)}\right] \stackrel{(i)}{=} \mathbb{E}\left[\min_{q \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \frac{N(a|X^n)}{n} \log \frac{1}{q(a)}\right] \\ \stackrel{(ii)}{\leq} \min_{q \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \mathbb{E}\left[\frac{N(a|X^n)}{n}\right] \log \frac{1}{q(a)},$$

where (i) is because q is a zero-order Markov model and (ii) follows from Jensen's inequality. We can apply stationarity of **X** to evaluate

$$\mathbb{E}\left[\frac{N(a|X^n)}{n}\right] = \sum_{t=1}^n \frac{\mathbb{P}(X_t = a)}{n} = \sum_{t=1}^n \frac{\mathbb{P}(X_1 = a)}{n} = \mathbb{P}(X_1 = a)$$

So, applying logic from the proof of Lemma B.11,

$$\mathbb{E}\mu_0(X^n) \le \min_{q \in \mathcal{M}(\mathcal{A})} \sum_{a \in \mathcal{A}} \mathbb{P}(X_1 = a) \log \frac{1}{q(a)} = H(X_1).$$

(b) We have defined M_k such that $q_t \in M_k$ can attain zero loss for the first k samples (as its behavior for those samples is entirely unconstrained). So,

$$\mathbb{E}\mu_k(X^n) = \mathbb{E}\left[\frac{1}{n} \min_{q_t \in \mathcal{M}_k} \sum_{t=k+1}^n \log \frac{1}{q(X_t | X^{t-1})}\right] \le \mathbb{E}\left[\frac{1}{n-k} \min_{q_t \in \mathcal{M}_k} \sum_{t=k+1}^n \log \frac{1}{q(X_t | X^{t-1}_{t-k})}\right].$$

As in part (a), we apply Jensen's inequality and stationarity to say

$$\mathbb{E}\mu_{k}(X^{n}) \stackrel{(i)}{\leq} \min_{q \in \mathcal{M}_{k}} \sum_{a^{k+1} \in \mathcal{A}^{k+1}} \log \frac{1}{q(a_{k+1}|a^{k})} \mathbb{E} \frac{|\{i : X_{i}^{i+k} = a^{k+1}\}|}{n-k} \\
\stackrel{(ii)}{=} \min_{q \in \mathcal{M}_{k}} \sum_{a^{k+1} \in \mathcal{A}^{k+1}} \log \frac{1}{q(a_{k+1}|a^{k})} \mathbb{P} \left(X^{k+1} = a^{k+1}\right) \\
= \min_{q \in \mathcal{M}_{k}} \sum_{a^{k} \in \mathcal{A}^{k}} \mathbb{P}(X^{k} = a^{k}) \sum_{a_{k+1} \in \mathcal{A}} \mathbb{P} \left(X_{k+1} = a_{k+1}|X^{k} = a^{k}\right) \log \frac{1}{q(a_{k+1}|a_{k})} \\
= \sum_{a^{k} \in \mathcal{A}^{k}} \mathbb{P} \left(X^{k} = a^{k}\right) \min_{q_{a^{k}} \in \mathcal{M}(\mathcal{A})} \sum_{a_{k+1} \in \mathcal{A}} \mathbb{P}(X_{k+1} = a_{k+1}|X^{k} = a^{k}) \log \frac{1}{q_{a^{k}}(a_{k+1})} \\
= \sum_{a^{k} \in \mathcal{A}^{k}} \mathbb{P} \left(X^{k} = a^{k}\right) H(X_{k+1}|X^{k} = a^{k}) = H(X_{k+1}|X^{k}).$$
(3)

where (i) is by Jensen's inequality and (ii) is by stationarity.

Using these results, we can now show that any SPA such that the limit supremum of the log loss is at most $\mu(\mathbf{x})$, for all individual sequences, will have an expected log loss equal to the entropy rate of the process. In particular, this holds for the LZ78 family of SPAs by Section IV.

Theorem C.2. Suppose \mathbf{X} is a stationary process and the SPA q satisfies

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q(x^n)} \le \mu(\mathbf{x}),$$

for all individual sequences \mathbf{x} . Then, if $\mathbb{H}(\mathbf{X})$ is the entropy rate of the stochastic process,

$$\lim_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \log \frac{1}{q(X^n)}\right] = \mathbb{H}(\mathbf{X})$$

Proof. We will split this proof into two parts:

$$\liminf_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \log \frac{1}{q(X^n)}\right] \stackrel{(a)}{\geq} \mathbb{H}(\mathbf{X}); \quad \limsup_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \log \frac{1}{q(X^n)}\right] \stackrel{(b)}{\leq} \mathbb{H}(\mathbf{X}),$$

which, together, imply the result via the squeeze theorem.

(a) $\forall n > 0$, let p^n be the joint PDF of X^n . Then,

$$\mathbb{E}\left[\frac{1}{n}\log\frac{1}{q(X^n)}\right] = \mathbb{E}\left[\frac{1}{n}\log\left(\frac{1}{q(X^n)}\cdot\frac{p^n(X^n)}{p^n(X^n)}\right)\right] = \frac{1}{n}H(X^n) + \frac{1}{n}D(p^n||q) \ge \frac{1}{n}H(X^n),$$

as relative entropy is a non-negative quantity. Taking $\liminf_{n\to\infty}$ on both sides,

$$\liminf_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \log \frac{1}{q(X^n)}\right] \ge \liminf_{n \to \infty} \frac{1}{n} H(X^n) = \mathbb{H}(\mathbf{X}).$$

(b) By the assumption

 $\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q(x^n)} \leq \mu(\mathbf{x}), \, \forall \text{ individual sequences } \mathbf{x},$

 $\forall \epsilon > 0, \ \exists N > 0 \ \text{such that}, \ \forall n > N,$

$$\frac{1}{n}\log\frac{1}{q(x^n)} \le \mu(\mathbf{x}) + \epsilon, \,\forall \mathbf{x}$$

As $\mu(\mathbf{x}) \leq \mu_k(\mathbf{x}), \forall k \geq 0$ and individual sequence \mathbf{x} ,

$$\frac{1}{n}\log\frac{1}{q(x^n)} \le \mu_k(\mathbf{x}) + \epsilon, \, \forall n > N, k \ge 0, \mathbf{x}$$

Plugging this fact into $\mathbb{E}\left[\frac{1}{n}\log\frac{1}{q(X^n)}\right]$ and applying the second result of Lemma C.1,

$$\mathbb{E}\left[\frac{1}{n}\log\frac{1}{q(X^n)}\right] \le \mathbb{E}\left[\mu_k(\mathbf{X}) + \epsilon\right] \le H(X_{k+1}|X^k) + \epsilon, \, \forall k \ge 0, n > N.$$

Taking the limit as $k \to \infty$ on both sides,

$$\mathbb{E}\left[\frac{1}{n}\log\frac{1}{q(X^n)}\right] \le \mathbb{H}(\mathbf{X}) + \epsilon, \, \forall n > N,$$

where we applied strong stationarity to say that $\lim_{k\to\infty} H(X_{k+1}|X^k) = \mathbb{H}(\mathbf{X})$. As ϵ is arbitrary, we can apply the definition of a limit supremum to say

$$\limsup_{n \to \infty} \mathbb{E}\left[\frac{1}{n} \log \frac{1}{q(X^n)}\right] \le \mathbb{H}(\mathbf{X}).$$

Theorem C.3. If, additionally, the process is ergodic, then the result holds almost surely rather than in expectation:

$$\frac{1}{n}\log\frac{1}{q(X^n)} \stackrel{a.s.}{\to} \mathbb{H}(\mathbf{X}).$$

Proof. We will again split the proof into that of two inequalities:

(a) $\liminf_{n \to \infty} \frac{1}{n} \log \frac{1}{q(X^n)} \ge \mathbb{H}(\mathbf{X})$ (a.s.).

 $\forall n > 0$, let p^n be the joint PDF of X^n . Then,

$$\frac{1}{n}\log\frac{1}{q(X^n)} = \frac{1}{n}\log\left(\frac{1}{q(X^n)} \cdot \frac{p^n(X^n)}{p^n(X^n)}\right) = \frac{1}{n}\log\frac{1}{p^n(X^n)} + \frac{1}{n}\log\frac{p^n(X^n)}{q(X^n)}$$

By the Shannon-McMillan-Breiman theorem [40]

$$\lim_{n \to \infty} \frac{1}{n} \log \frac{1}{p^n(X^n)} = \mathbb{H}(\mathbf{X}) \quad (a.s.)$$

In addition, by Lemma 2 of [41], $\liminf_{n\to\infty} \frac{1}{n} \log \frac{p^n(X^n)}{q(X^n)}$ is almost surely non-negative, so $\liminf_{n\to\infty} \frac{1}{n} \log \frac{1}{q(X^n)} \ge \mathbb{H}(\mathbf{X}) \quad (a.s.).$

(b) $\limsup_{n\to\infty} \frac{1}{n} \log \frac{1}{q(X^n)} \leq \mathbb{H}(\mathbf{X})$ (a.s.).

We first show the following:

Claim C.4. For any stationary and ergodic source, the following holds with probability 1:

$$\lim_{n \to \infty} \mu_k(X^n) = H(X_{k+1}|X^k).$$

Proof of claim. By Birkhoff's Ergodic Theorem [42] and the continuous mapping theorem,

$$\frac{|\{i:X_i^{i+k}=a^{k+1}\}|)}{n} \stackrel{a.s.}{\rightarrow} \mathbb{P}(X^{k+1}=a^{k+1}).$$

Then, almost surely,

$$\lim_{n \to \infty} \mu_k(X^n) = \lim_{n \to \infty} \min_{\hat{q} \in \mathcal{M}_k} \sum_{a^{k+1} \in \mathcal{A}^{k+1}} \frac{|\{i : X_i^{i+k} = a^{k+1}\}|)}{n} \log \frac{1}{\hat{q}(a_{k+1}|a^k)}$$
$$= \min_{\hat{q} \in \mathcal{M}_k} \sum_{a^{k+1} \in \mathcal{A}^{k+1}} \mathbb{P}(X^{k+1} = a^{k+1}) \log \frac{1}{\hat{q}(a_{k+1}|a^k)}.$$

We are now in an identical position as line 2 of (3), and can therefore follow the rest of (3) to conclude that

$$\lim_{n \to \infty} \mu_k(X^n) = H(X_{k+1}|X^k) \quad (a.s.).$$

By the same logic as part (b) of Theorem C.2, $\forall \epsilon > 0$, $\exists N \in \mathbb{N}$ s.t., $\forall n > N$ and k > 0,

$$\frac{1}{n}\log\frac{1}{q(X^n)} \le \mu_k(\mathbf{X}) + \epsilon.$$

By the claim,

$$\frac{1}{n}\log\frac{1}{q(X^n)} \le \mu_k(\mathbf{X}) + \epsilon \le H(X_{k+1}|X^k) + \epsilon \quad (a.s.), \quad \forall n > N.$$

As ϵ is arbitrary,

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q(X^n)} \le H(X_{k+1} | X^k) \quad (a.s.).$$

Taking the limit as $k \to \infty$ and applying strong stationarity,

$$\limsup_{n \to \infty} \frac{1}{n} \log \frac{1}{q(X^n)} \le \mathbb{H}(\mathbf{X}) \quad (a.s.)$$

Appendix D

PROOFS: THE LZ78 SEQUENTIAL PROBABILITY ASSIGNMENT AS A PROBABILITY SOURCE

A. The Bernoulli LZ78 Probability Source

Lemma D.1. The entropy rate of the LZ78 probability source with prior $\Pi = Ber(1/2)$ has entropy rate 0.

Proof. Let X be generated from the LZ78 probability source with a Ber(1/2) prior. Then.

$$H(\mathbf{X}) = \lim_{n \to \infty} \frac{1}{n} H(X^n) = \lim_{n \to \infty} \frac{1}{n} \mathbb{E} \log \frac{1}{q^{LZ78, f}(X^n)} = \lim_{n \to \infty} \frac{1}{n} \mathbb{E} \sum_{k=1}^{C(X^n)} \log \frac{1}{q^{LZ78, f}(C_k)}.$$

a (TTD)

As each phrase is deterministic except for the final symbol, which is equally likely to be 0 or 1, a log loss of 1 is incurred on each phrase. In addition, $C(X^n) = O(\sqrt{n})$, so $H(\mathbf{X}) = \lim_{n \to \infty} \frac{C(X^n)}{n} = 0$.

Lemma D.2. The LZ78 SPA of Construction III.4, for any prior density g bounded away from zero, will achieve am asymptotic log loss of 0 deterministically on any sequence from the LZ78 probability source with a Ber(1/2) prior.

Proof. The log loss incurred by SPA $q^{LZ78,g}$ is

$$\frac{1}{n}\log\frac{1}{q^{LZ78,g}(X^n)} = \frac{1}{n}\sum_{z\in\mathcal{Z}(X^n)}\log\frac{1}{q^g(\{X_t:z_c(X^{t-1})=z\})}.$$

Define $y_z^{m_z} \triangleq \{X_t : z_c(X^{t-1}) = z\}$. As each node of the LZ78 tree can only have one child for any realization of the Bernoulli LZ78 source, $y_z^{m_z}$ is either all 0 or all 1. Using this fact, $q^g(y_z^{m_z})$ directly evaluates to

$$\begin{split} q^{g}(y_{z}^{m_{z}}) &= \int_{0}^{1} g(q) q^{N(1|y_{z}^{m_{z}})} (1-q)^{N(0|y_{z}^{m_{z}})} dq = \begin{cases} \int_{0}^{1} g(q) q^{m_{z}} dq, & y_{z}^{m_{z}} \text{ is all } 1\\ \int_{0}^{1} g(q) (1-q)^{m_{z}} dq, & y_{z}^{m_{z}} \text{ is all } 0 \end{cases} \\ &\geq \int_{0}^{1} \left(\inf_{p \in [0,1]} g(p) \right) q^{m_{z}} dq = \frac{\left(\inf_{p \in [0,1]} g(p) \right)}{m_{z} + 1}. \end{split}$$

For simplicity of notation, denote $\left(\inf_{p\in[0,1]}g(p)\right)$ by α . Then, the log loss can be bounded by

$$\frac{1}{n}\log\frac{1}{q^{LZ78,g}(X^n)} = \frac{1}{n}\sum_{z\in\mathcal{Z}(X^n)}\log\frac{1}{q^g(\{X_t:z_c(X^{t-1})=z\})} \ge \frac{1}{n}\sum_{z\in\mathcal{Z}(X^n)}\left(\log\frac{1}{\alpha} + \log(m_z+1)\right).$$

As each context $z \in \mathcal{Z}(X^n)$ must have been a phrase in the LZ78 parsing of X^n ,

$$\frac{1}{n}\log\frac{1}{q^{LZ78,g}(X^n)} \ge \frac{1}{n}\sum_{k=1}^{C(X^n)} \left(\log\frac{1}{\alpha} + \log\left(m_{C_k} + 1\right)\right) \stackrel{(i)}{\ge} \frac{1}{n} \left(C(X^n)\log\frac{1}{\alpha} + C(X^n)\log(C(X^n) + 1)\right)$$
$$\stackrel{(ii)}{=} \frac{O(\sqrt{n})}{n} \left(\log\frac{1}{\alpha} + \log(O(\sqrt{n}))\right) \stackrel{(iii)}{=} o(1),$$

where (i) follows from the fact that each context may only appear once per phrase, (ii) is because $C(X^n) = O(\sqrt{n})$, and (iii) is valid because $\alpha > 0$ by assumption, so $\log \frac{1}{\alpha}$ is finite.

Lemma D.3. Almost surely, **X** generated from the LZ78 probability source with a Ber(1/2) prior satisfies $\mu(\mathbf{X}) = 1$.

Proof. To show that $\mu(\mathbf{X}) = 1$ (a.s.), we show that, for any fixed context length $k \in \mathbb{N}$, $\mu_k(\mathbf{X}) = 1$, almost surely.

Consider a realization, X^n , of the LZ78 source, and denote the final complete phrase by Y^m . This phrase, considered in isolation, is $\stackrel{\text{i.i.d.}}{\sim}$ Ber(1/2). By Lemma B.13, the strong law of large numbers, and the continuous mapping theorem $\mu_k(Y^m) \stackrel{a.s.}{\to} h_2(1/2) = 1$ as $m \to \infty$, where h_2 is the binary entropy function.

This result can be extended to the full sequence, X^n , via the following result:

Claim D.4. Suppose that $\mu_k(u^m) \to 1$ for individual binary sequence u. Then, for v^n defined as

$$u_1; u_1, u_2; u_1, u_2, u_3; \ldots; u_1, u_2, \ldots, u_m; u_1, \ldots, u_\ell$$

where $n = \frac{m(m+1)}{2} + \ell$, it also holds that $\mu_k(v^n) \to 1$.

Proof of claim. First, $\mu_k(v^n) \leq 1$, as $\mu_k(v^n)$ is equal to the emprical entropy associated with binary sequence v^n , which is upper-bounded by 1. So, it suffices to show that $\lim_{n\to\infty} \mu_k(v^n) \geq 1$. Specifically, we must show that, $\forall \epsilon > 0$, $\exists N > 0$ s.t., $\forall n > N$, $\mu_k(v^n) \geq 1 - \epsilon$.

 $\mu_k(u^m) \to 1$, so by definition, $\exists M > 0$ s.t., $\forall m > M$, $\mu_k(u^m) > 1 - \epsilon/2$. We then choose N such that fewer than $\frac{\epsilon}{2}N$ symbols are in phrases of length $\leq M$.¹⁰ Then, for n > N,

$$\mu_k(v^n) = \min_{q \in \mathcal{M}_k} \frac{1}{n} \left(\sum_{z \in \mathcal{Z}(v^n): |z| \le M} \log \frac{1}{q(z)} + \sum_{z \in \mathcal{Z}(v^n): |z| > M} \log \frac{1}{q(z)} \right)$$

$$\stackrel{(i)}{>} \frac{1}{n} \left(\sum_{z \in \mathcal{Z}(v^n): |z| \le M} |z| \mu_k(z) + \sum_{z \in \mathcal{Z}(v^n): |z| > M} |z| \mu_k(z) \right) \stackrel{(ii)}{>} \frac{1}{n} \left(1 - \frac{\epsilon}{2} \right) \sum_{z \in \mathcal{Z}(v^n): |z| \le N} |z|$$

$$\stackrel{(iii)}{\geq} \left(1 - \frac{\epsilon}{2} \right)^2 > 1 - \epsilon,$$

where (i) is by Jensen's inequality, (ii) follows from the fact that all phrases in the second summation have length > N, and (iii) follows from the definition of M. \therefore , $\lim_{n\to\infty} \mu_k(v^n) \ge 1$, meaning $\lim_{n\to\infty} \mu_k(v^n) = 1$.

Therefore, as $\lim_{m\to\infty} \mu_k(Y^m) = 1$ with probability 1, $\lim_{n\to\infty} \mu_k(X^n) = 1$ almost surely as well. So, by definition, $\mu_k(\mathbf{X}) = 1$ (a.s.), and therefore $\mu(\mathbf{X}) = 1$ (a.s.).

REFERENCES

- [1] J. Ziv and A. Lempel, "A universal algorithm for sequential data compression," *IEEE Transactions on Information Theory*, vol. 23, no. 3, pp. 337–343, 1977.
- [2] —, "Compression of individual sequences via variable-rate coding," IEEE Transactions on Information Theory, vol. 24, no. 5, pp. 530–536, 1978.

[3] J. Rissanen and G. G. Langdon, "Arithmetic coding," IBM Journal of Research and Development, vol. 23, no. 2, pp. 149–162, 1979.

- [4] G. Langdon, "A note on the ziv lempel model for compressing individual sequences (corresp.)," *IEEE Transactions on Information Theory*, vol. 29, no. 2, pp. 284–287, 1983.
- [5] M. Feder, "Gambling using a finite state machine," IEEE Transactions on Information Theory, vol. 37, no. 5, pp. 1459–1465, 1991.
- [6] M. Feder, N. Merhav, and M. Gutman, "Universal prediction of individual sequences," *IEEE Transactions on Information Theory*, vol. 38, no. 4, pp. 1258–1270, 1992.
- [7] M. Weinberger, N. Merhav, and M. Feder, "Optimal sequential probability assignment for individual sequences," *IEEE Transactions on Information Theory*, vol. 40, no. 2, pp. 384–396, 1994.
- [8] N. Merhav and M. Feder, "Universal schemes for sequential decision from individual data sequences," *IEEE Transactions on Information Theory*, vol. 39, no. 4, pp. 1280–1292, 1993.
- [9] J. Ziv, "Universal decoding for finite-state channels," IEEE Transactions on Information Theory, vol. 31, no. 4, pp. 453-460, 1985.
- [10] R. Begleiter, R. El-Yaniv, and G. Yona, "On prediction using variable order markov models," *Journal of Artificial Intelligence Research*, vol. 22, p. 385–421, Dec. 2004. [Online]. Available: http://dx.doi.org/10.1613/jair.1491
- [11] F. Willems, Y. Shtarkov, and T. Tjalkens, "The context-tree weighting method: basic properties," *IEEE Transactions on Information Theory*, vol. 41, no. 3, pp. 653–664, 1995.
- [12] T. Weissman, E. Ordentlich, M. J. Weinberger, A. Somekh-Baruch, and N. Merhav, "Universal filtering via prediction," *IEEE Transactions on Information Theory*, vol. 53, no. 4, pp. 1253–1264, 2007.
- [13] N. Merhav, "On jacob ziv's individual-sequence approach to information theory," 2024. [Online]. Available: https://arxiv.org/abs/2406.02904
- [14] E. Gilbert, "Codes based on inaccurate source probabilities," *IEEE Trans. Inf. Theor.*, vol. 17, no. 3, p. 304–314, Sep. 2006. [Online]. Available: https://doi.org/10.1109/TIT.1971.1054638

¹⁰The only phrases that have length $\leq M$ are the first M phrases, which comprise $\frac{M(M+1)}{2}$ symbols, and potentially the last phrase. As a result, the condition is satisfied by $N \geq \left\lceil \frac{M(M+1)+2M}{\epsilon} \right\rceil$.

- [15] T. Cover, "Admissibility properties or gilbert's encoding for unknown source probabilities (corresp.)," *IEEE Transactions on Information Theory*, vol. 18, no. 1, pp. 216–217, 1972.
- [16] R. Krichevsky and V. Trofimov, "The performance of universal encoding," *IEEE Transactions on Information Theory*, vol. 27, no. 2, pp. 199–207, 1981.
- [17] N. Merhav and M. Feder, "Universal prediction," IEEE Transactions on Information Theory, vol. 44, no. 6, pp. 2124–2147, 1998.
- [18] A. Ingber and M. Feder, "Non-asymptotic design of finite state universal predictors for individual sequences," in *Data Compression Conference* (*DCC'06*), 2006, pp. 3–12.
- [19] E. Yang and J. Kieffer, "Simple universal lossy data compression schemes derived from the Lempel-Ziv algorithm," *IEEE Transactions on Information Theory*, vol. 42, no. 1, pp. 239–245, 1996.
- [20] N. Merhav, "A universal random coding ensemble for sample-wise lossy compression," 2022. [Online]. Available: https://arxiv.org/abs/2212.12208
- [21] —, "Lossy compression of individual sequences revisited: Fundamental limits of finite-state encoders," *Entropy*, vol. 26, no. 2, 2024. [Online]. Available: https://www.mdpi.com/1099-4300/26/2/116
- [22] P. Jacquet and W. Szpankowski, "On the limiting distribution of lempel-ziv'78 redundancy for memoryless sources," *IEEE Transactions on Information Theory*, vol. 60, no. 11, pp. 6917–6930, 2014.
- [23] —, "Analysis of lempel-ziv'78 for markov sources," in AofA2020 31st International Conference on Probabilistic, Combinatorial and Asymptotic Methods for the Analysis of Algorithms, Klagenfurt, Austria, Jun. 2020. [Online]. Available: https://hal.science/hal-03139593
- [24] J. Ziv and N. Merhav, "A measure of relative entropy between individual sequences with application to universal classification," *IEEE Transactions on Information Theory*, vol. 39, no. 4, pp. 1270–1279, 1993.
- [25] D. P. Coutinho, A. L. Fred, and M. A. Figueiredo, "One-lead ECG-based personal identification using Ziv-Merhav cross parsing," in 2010 20th International Conference on Pattern Recognition, 2010, pp. 3858–3861.
- [26] S. Helmer, "Measuring the structural similarity of semistructured documents using entropy," in Very Large Data Bases Conference, 2007. [Online]. Available: https://api.semanticscholar.org/CorpusID:15615555
- [27] D. Pratas, R. M. Silva, and A. J. Pinho, "Comparison of compression-based measures with application to the evolution of primate genomes," *Entropy*, vol. 20, no. 6, 2018. [Online]. Available: https://www.mdpi.com/1099-4300/20/6/393
- [28] D. Benedetto, E. Caglioti, and V. Loreto, "Language trees and zipping," *Physical Review Letters*, vol. 88, no. 4, Jan. 2002. [Online]. Available: http://dx.doi.org/10.1103/PhysRevLett.88.048702
- [29] A. Bhattacharya and S. K. Das, "LeZi-update: an information-theoretic framework for personal mobility tracking in PCS networks," Wirel. Netw., vol. 8, no. 2/3, p. 121–135, Mar. 2002. [Online]. Available: https://doi.org/10.1023/A:1013759724438
- [30] K. Gopalratnam and D. J. Cook, "Online sequential prediction via incremental parsing: The active LeZi algorithm," *IEEE Intelligent Systems*, vol. 22, no. 1, pp. 52–58, 2007.
- [31] G. Delétang, A. Ruoss, P.-A. Duquenne, E. Catt, T. Genewein, C. Mattern, J. Grau-Moya, L. K. Wenliang, M. Aitchison, L. Orseau, M. Hutter, and J. Veness, "Language modeling is compression," 2024. [Online]. Available: https://arxiv.org/abs/2309.10668
- [32] Y. M. Shtar'kov, "Universal sequential coding of individual messages," Problemy Peredachi Informatsii, vol. 23, no. 3, pp. 3–17, 1987.
- [33] A. Karpathy, "char-RNN," https://github.com/karpathy/char-rnn, 2015.
- [34] J. Dodge, M. Sap, A. Marasović, W. Agnew, G. Ilharco, D. Groeneveld, M. Mitchell, and M. Gardner, "Documenting large webtext corpora: A case study on the colossal clean crawled corpus," 2021. [Online]. Available: https://arxiv.org/abs/2104.08758
- [35] R. Eldan and Y. Li, "TinyStories: How small can language models be and still speak coherent English?" 2023. [Online]. Available: https://arxiv.org/abs/2305.07759
- [36] L. Deng, "The MNIST database of handwritten digit images for machine learning research," *IEEE Signal Processing Magazine*, vol. 29, no. 6, pp. 141–142, 2012.
- [37] H. Xiao, K. Rasul, and R. Vollgraf, "Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms," 2017. [Online]. Available: https://arxiv.org/abs/1708.07747
- [38] A. L. Maas, R. E. Daly, P. T. Pham, D. Huang, A. Y. Ng, and C. Potts, "Learning word vectors for sentiment analysis," in *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*. Portland, Oregon, USA: Association for Computational Linguistics, June 2011, pp. 142–150. [Online]. Available: http://www.aclweb.org/anthology/P11-1015
- [39] V. Metsis, I. Androutsopoulos, and G. Paliouras, "Spam filtering with naive Bayes which naive Bayes?" 01 2006.
- [40] L. Breiman, "The individual ergodic theorem of information theory," *The Annals of Mathematical Statistics*, vol. 28, no. 3, pp. 809 811, 1957. [Online]. Available: https://doi.org/10.1214/aoms/1177706899
- [41] P. Algoet, "Universal schemes for prediction, gambling and portfolio selection," *The Annals of Probability*, vol. 20, no. 2, pp. 901 941, 1992. [Online]. Available: https://doi.org/10.1214/aop/1176989811
- [42] K. E. Petersen, Ergodic Theory, ser. Cambridge Studies in Advanced Mathematics. Cambridge University Press, 1983.