

Multi-Level Steiner Trees


Reyan Ahmed

University of Arizona, Tucson, United States

Patrizio Angelini

Universität Tübingen, Tübingen, Germany  0000-0002-7602-1524

Faryad Darabi Sahneh

University of Arizona, Tucson, United States  0000-0003-2521-4331

Alon Efrat

University of Arizona, Tucson, United States

David Glickenstein

University of Arizona, Tucson, United States


Martin Gronemann

Universität zu Köln, Cologne, Germany

Niklas Heinsohn

Universität Tübingen, Tübingen, Germany

Stephen G. Kobourov

University of Arizona, Tucson, United States  0000-0002-0477-2724

Richard Spence

University of Arizona, Tucson, United States

rspence@email.arizona.edu

Joseph Watkins

University of Arizona, Tucson, United States

Alexander Wolff

Universität Würzburg, Würzburg, Germany  0000-0001-5872-718X

Abstract

In the classical Steiner tree problem, one is given an undirected, connected graph $G = (V, E)$ with non-negative edge costs and a set of *terminals* $T \subseteq V$. The objective is to find a minimum-cost edge set $E' \subseteq E$ that spans the terminals. The problem is APX-hard; the best known approximation algorithm has a ratio of $\rho = \ln(4) + \varepsilon < 1.39$. In this paper, we study a natural generalization, the *multi-level Steiner tree* (MLST) problem: given a nested sequence of terminals $T_1 \subset \dots \subset T_k \subseteq V$, compute nested edge sets $E_1 \subseteq \dots \subseteq E_k \subseteq E$ that span the corresponding terminal sets with minimum total cost.

The MLST problem and variants thereof have been studied under names such as Quality-of-Service Multicast tree, Grade-of-Service Steiner tree, and Multi-Tier tree. Several approximation results are known. We first present two natural heuristics with approximation factor $O(k)$. Based on these, we introduce a composite algorithm that requires 2^k Steiner tree computations. We determine its approximation ratio by solving a linear program. We then present a method that guarantees the same approximation ratio and needs at most $2k$ Steiner tree computations. We compare five algorithms experimentally on several classes of graphs using four types of graph generators. We also implemented an integer linear program for MLST to provide ground truth. Our combined algorithm outperforms the others both in theory and in practice when the number of levels is small ($k \leq 22$), which works well for applications such as designing multi-level infrastructure or network visualization.



© Reyan Ahmed, Patrizio Angelini, Faryad Darabi Sahneh, Alon Efrat, David Glickenstein, Martin Gronemann, Niklas Heinsohn, Stephen Kobourov, Richard Carlton Spence, Joe Watkins, Alexander Wolff;

licensed under Creative Commons License CC-BY

17th International Symposium on Experimental Algorithms (SEA 2018).

Editor: Gianlorenzo D'Angelo; Article No. 15; pp. 15:1–15:14



Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany