

# Relay: A New IR for Machine Learning Frameworks

(Extended Abstract)

Anonymous Author(s)

## Abstract

Machine learning powers diverse services in industry including search, translation, recommendation systems, security, and more. The scale and importance of these models require that they be efficient, expressive, and portable across an array of heterogeneous hardware devices. These constraints are often at odds; in order to simultaneously accommodate them we propose a new high-level intermediate representation called Relay. Relay is a purely functional, statically typed IR designed to balance efficient compilation, expressiveness, and portability. We present a prototype of Relay and highlight its important design decisions. Our prototype is part of the open source NNVM compiler framework, which powers Amazon’s deep learning framework MxNet.

**Keywords** intermediate representation, machine learning, compilers, differentiable programming

## 1 Introduction

Machine Learning (ML) has dramatically reshaped computer vision, natural language processing, robotics, and computational biology and is gaining traction in new areas such as program synthesis. Deep learning (DL) in particular has driven progress in these areas, and is now powering diverse services in industry including search, translation, recommendation systems, security, and more. These models are not only being deployed in the cloud, but also on mobile phones in major services such as Google’s Android keyboard and Apple’s FaceID.

The ease with which researchers can design, train, and deploy these models controls the pace of research. One clear trend is getting the most out of diverse, heterogeneous hardware accelerators, visible today in the form of specialized GPU and TPU-like accelerators. Yet, even with these powerful tools, today’s systems are struggling to satisfy the demand for machine learning workloads. We believe that satisfying this demand requires new programming models for such specialized accelerators to remove the expressivity and control restrictions that currently limit what data scientists can easily deploy.

Deep learning models have become so pervasive and profitable that large companies are now investing significant resources into optimizing both training and inference across CPU, GPU, distributed, and parallel execution. To reduce

costs and accelerate workloads, these companies are exploring optimizations at the hardware level and have begun deploying custom accelerators to decrease learning cost and latency. Powerful new GPU and TPU-like accelerators have provided impressive benefits, spurring further demand for new accelerators and optimizations. However, as the landscape becomes more complex and diverse, *the corresponding programming models have not kept pace*, thus increasingly making development effort a key bottleneck.

Neural networks (NN) rely on computations that are differentiable; i.e., computations where it is possible to compute a mathematical derivative. In order to guarantee this property for users’ networks, existing frameworks have limited networks’ computational expressivity. Frameworks like TensorFlow represent differentiable computation using static graphs: dataflow graphs with a fixed topology. These graphs are easy to optimize but require users to construct programs in a deeply embedded domain-specific language (DSL) without high-level abstractions like functions.

A more expressive style popularized by imperative frameworks like Chainer, PyTorch, and Gluon allows the construction of graphs with dynamic topologies that can depend on runtime data and support differentiation of most imperative computations. This expressivity is great for the user, but limits how well PyTorch can optimize user-defined graphs. PyTorch’s model requires a Python interpreter, making deployment to new accelerators and FPGAs extremely challenging.

This work proposes Relay, a new high-level intermediate representation (IR) designed to balance efficient compilation, expressiveness, and portability. Static graphs are easy to optimize but lack the expressivity found in higher-level languages; dynamic graphs provide this missing expressivity but introduce new compilation and execution challenges, especially on heterogeneous hardware. We design Relay not from the perspective of a computation graph, but as a programming language for differentiable computation. This PL perspective allows us to exploit decades of research in functional programming, type systems, synthesis, rewrite systems, and classic compiler techniques. We believe this will reduce the cost of targeting new accelerators and enable more optimizations to improve training and inference time, energy consumption, and space usage while simultaneously opening up new research directions.

We are implementing Relay as part of the Neural Net VM (NNVM) compiler framework. NNVM is a component of the

Tensor VM (TVM) end-to-end deep learning stack that powers MxNet, a popular deep learning framework supported by multiple companies and universities, including Amazon, Microsoft, and Intel.

## 2 Background

Current designs for high-level Deep Learning (DL) IRs, including those in NNVM, are heavily inspired by dataflow programming and the related computation graph abstractions made popular by previous frameworks.

TensorFlow [1] is an evolution of previous work at Google, such as DistBelief[4]. These frameworks have evolved out of dataflow programming paradigms where the abstractions are just operators with input and output connections.

TensorFlow's motivating design principles are a simple dataflow graph of primitive operators. This representation is sufficient for many of the previous state of the art models, and provides a simple implementation of reverse mode automatic differentiation [2]. Because TensorFlow can be viewed as a deeply embedded DSL (eDSL) the result of executing the user's Python script provides the entire program as a unified graph, making it possible to schedule, optimize and more. Furthermore, because the graph only exposes high level nodes, it is possible for it to be portable for heterogeneous devices given a set of operators for a device.

Unfortunately, this programming model has limitations. Because the topology is fixed before execution, TensorFlow does not lend itself well to certain applications. As an example, building models where the shape of the computation graph is dependent on the input is not supported in unmodified TensorFlow. While there does exist a library to help mitigate this particular problem (see [5]), this pattern suggests that should new dependencies be discovered in the future, similar libraries would also have to be written to address each one.

Imperative frameworks such Chainer, PyTorch, Gluon, and Tensorflow-eager-mode alleviate this problem by stepping away from the style of TensorFlow where the user program builds a graph statically, and then executes it. Instead they embed primitives in Python that construct dynamic data flow graphs based on Python's control flow and let the Python interpreter drive execution.

We believe that previous work in higher-order differentiation for functional frameworks, and in general [6][7], can be extended to mitigate many of these challenges. Our goal is to draw from this work and integrate the ideas into existing software stacks for deep learning, in particular NNVM and TVM.

Early work in these frameworks was focused on enabling users to efficiently execute operators backed by kernels on accelerated hardware. However, since that time, the overhead of applying such models has grown, leading to various approaches to address the compilation challenges.

## 3 Language

Relay is a statically typed, purely functional, differentiable IR. Relay is intended to replace NNVM's computation graph, rather than to be a low-level IR intended for writing high-performance kernels. We allow for primitive operators implemented either in external languages like C/C++ or in lower-level IRs like TVM or tensor comprehensions. Our new IR is designed to serve as a convenient way to implement new differentiable programming languages and deep probabilistic programming languages in the style of Edward and Pyro.

As we discussed in Section 2, most popular machine learning frameworks construct computation graphs that represent the user's program. From the programming languages perspective, this data structure is immediately recognizable as a modified form of an abstract syntax tree (AST).

Programming languages research has a long history of transforming and optimizing programs expressed as various ASTs. We consider the transformations and analyses that have been performed as computation graphs as program transforms and program analyses. While other DL frameworks also adopt this perspective, their graph-based approaches have made it difficult to bring the full arsenal of traditional compiler and programming languages techniques to bear.

Static typing enables direct compilation of models into embedded hardware and accelerators, which has been demonstrated in prior work done in the TVM stack [3]. Having an IR like Relay enables the deployment of richer dynamic models for applications such as natural language processing. By taking this point of view, we can leverage decades of programming language research to help us express and understand these deep learning models not as a restricted data flow language, but as a full programming language.

Relay is still under active development so we present it in the style of a tutorial, with a fully formal presentation forthcoming.

Relay is a simple functional language containing first-class functions, conditionals, primitive operations, and primitive values including floating point, integers, booleans, and tensors. Relay's IR has two main design contributions: the addition of functions and a rich type system that can capture the relationship of tensor operations.

In order to support higher-order (in the function sense) differentiable programs, we need to be able to support computing gradients over arbitrary functions. We accomplish this by introducing a higher-order, higher-order (in both senses) reverse mode operator[6]. This operator allows us to compute  $n$ th-order derivatives of higher order programs, opening up the ability to differentiate over arbitrary control structures encoded with functions.

Inspired in part by DLVM [8], a neural network DSL that supports a CFG-style IR for deep learning programs which

introduces a type system for tensors that is based on constant tensor shape and types, Relay supports a rich type system that includes dependent typing for tensor shapes, thereby allowing function type signatures to specify the relationship between arguments (such as attributes or other tensors) and the resulting tensor shapes. Relay's control flow is explicit; its current version does not support differentiation over conditionals and loops.

## 4 Conclusion

We describe our in progress work on Relay: a new IR for compiling machine learning models. Relay is implemented within NNVM and designed to address the key challenges engineers face today in deep learning compilation pipelines. In our talk we will show preliminary results demonstrating that Relay provides expressivity, efficiency, and portability. We hope to demonstrate that the effort for designing and implementing optimizations for this new IR is lower than that for NNVM's previous computation graph. In the presentation, we will expand on this foundation to demonstrate HGrad, a prototype differentiable source language that uses Relay as its backend.

## References

- [1] Martin Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. 2016. TensorFlow: A system for large-scale machine learning. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)*. 265–283. <https://www.usenix.org/system/files/conference/osdi16/osdi16-abadi.pdf>
- [2] Atilim Gunes Baydin, Barak A. Pearlmutter, and Alexey Andreyevich Radul. 2015. Automatic differentiation in machine learning: a survey. *CoRR* abs/1502.05767 (2015). arXiv:1502.05767 <http://arxiv.org/abs/1502.05767>
- [3] Tianqi Chen, Thierry Moreau, Ziheng Jiang, Haichen Shen, Eddie Yan, Leyuan Wang, Yuwei Hu, Luis Ceze, Carlos Guestrin, and Arvind Krishnamurthy. 2018. TVM: End-to-End Compilation Stack for Deep Learning. In *SysML 2018*. <https://arxiv.org/abs/1802.04799>
- [4] Jeffrey Dean, Greg S. Corrado, Rajat Monga, Kai Chen, Matthieu Devin, Quoc V. Le, Mark Z. Mao, Marc'Antonio Aurelio Ranzato, Andrew Senior, Paul Tucker, Ke Yang, and Andrew Y. Ng. 2012. Large Scale Distributed Deep Networks. In *NIPS*. [https://research.google.com/archive/large\\_deep\\_networks\\_nips2012.html](https://research.google.com/archive/large_deep_networks_nips2012.html)
- [5] Moshe Looks, Marcello Herreshoff, and DeLesley Hutchins. 2017. Announcing TensorFlow Fold: Deep Learning With Dynamic Computation Graphs. <https://research.googleblog.com/2017/02/announcing-tensorflow-fold-deep.html>. (7 February 2017).
- [6] Barak A. Pearlmutter and Jeffrey Mark Siskind. 2008. Reverse-mode AD in a Functional Framework: Lambda the Ultimate Backpropagator. *ACM Trans. Program. Lang. Syst.* 30, 2, Article 7 (March 2008), 36 pages. <https://doi.org/10.1145/1330017.1330018>
- [7] Mu Wang and Alex Pothén. 2017. An Overview of High Order Reverse Mode. (2017). <https://openreview.net/pdf?id=Hkmj6tzRZ>
- [8] Richard Wei, Vikram S. Adve, and Lane Schwartz. 2017. DLVM: A modern compiler infrastructure for deep learning systems. *CoRR* abs/1711.03016 (2017). arXiv:1711.03016 <http://arxiv.org/abs/1711.03016>