

```
# DocString
/**
 * If <code>value</code> is "true", then <code>>true</code> is returned. If <code>value</code>
is "false", then <code>>false</code> is returned. Otherwise, <code>default</code> is returned.
<p>Case of value is unimportant.
 */
# Signature
public static boolean toBoolean(String value,boolean dEFAULT){
```

Generation

```
# Generated Code
public static boolean toBoolean(String value, boolean dEFAULT) {
    if (value.equalsIgnoreCase("true")) {
        return true;
    } else if (value.equalsIgnoreCase("false")) {
        return false;
    } else {
        return dEFAULT;
    }
}

-----

# Error Message
Exception in thread "main" java.lang.NullPointerException: Cannot invoke
"String.equalsIgnoreCase(String)" because "<parameter1>" is null
    at org.apache.log4j.helpers.OptionConverter.toBoolean(OptionConverter.java:129)
    at
org.apache.log4j.helpers.OptionConverter_toBoolean.main(OptionConverter_toBoolean.java:9)
```

Search + Generation

```
# Reference Code
private Boolean toBoolean(String value, Boolean defaultValue) {
    if (StrKit.isBlank(value))
        return defaultValue;
    value = value.trim().toLowerCase();
    if ("1".equals(value) || "true".equals(value))
        return Boolean.TRUE;
    else if ("0".equals(value) || "false".equals(value))
        return Boolean.FALSE;
    throw new ActionException(400, renderManager.getRenderFactory().getErrorRender(400), "Can
not parse the parameter \"" + value + "\" to Boolean value.");
}

-----

# Generated Code
public static boolean toBoolean(String value, boolean dEFAULT) {
    if (value == null || value.isEmpty()) {
        return dEFAULT;
    }
    value = value.toLowerCase();
    if ("true".equals(value)) {
        return true;
    } else if ("false".equals(value)) {
        return true;
    } else {
        return dEFAULT;
    }
}

-----

# Error Message
Test case 2 failed: input='FalsE', expected=false, actual=true
```

Search + Generation + Repair

```
public static boolean toBoolean(String value, boolean dEFAULT) {
    if (value == null || value.isEmpty()) {
        return dEFAULT;
    }
    value = value.toLowerCase();
    if ("true".equals(value)) {
        return true;
    } else if ("false".equals(value)) {
        return false;
    } else {
        return dEFAULT;
    }
}
```