

Title A	Abstract A	Title B	Abstract B	Ground-truth	Vicuna-13b	GPT-3.5 turbo	LitFM-13b
Observation of higher-order exceptional points in pseudo-Hermitian radio-frequency circuits	Exceptional points (EP) in non-Hermitian systems have been widely investigated due to their enhanced sensitivity in comparison to standard systems. In this letter, we report the observation of higher-order pseudo-Hermitian degeneracies in an electronic platform comprised of three inductively coupled gain-loss-loss LC resonators. Theoretical analysis demonstrates that the proposed system can realize third-order EP with asymmetric coupling between adjacent inductors and an arbitrary scaling factor between two loss resonators. When capacitive perturbation is introduced on the middle resonator, the perturbed eigenfrequencies follow a cube-root dependence on the perturbation parameter; in this case, the sensitivity is significantly greater than conventional wireless readout methods. Our work enriches the explorations of higher-order EP on electronic platforms and provides a new degree of design freedom for the non-Hermitian-EP-enhanced wireless sensing system.	Generalized Parity-Time Symmetry Condition for Enhanced Sensor Telemetry	Wireless sensors based on micro-machined tunable resonators are important in a variety of applications, ranging from medical diagnosis to industrial and environmental monitoring.The sensitivity of these devices is, however, often limited by their low quality (Q) factor.Here, we introduce the concept of isospectral parity time reciprocal scaling (PTX) symmetry and show that it can be used to build a new family of radiofrequency wireless microsensors exhibiting ultrasensitive responses and ultrahigh resolution, which are well beyond the limitations of conventional passive sensors. We show theoretically, and demonstrate experimentally using microelectromechanical based wireless pressure sensors, that PTXsymmetric electronic systems share the same eigenfrequencies as their parity time (PT)-symmetric counterparts, but crucially have different circuit profiles and eigenmodes. This simplifies the electronic circuit design and enables further enhancements to the extrinsic Q factor of the sensors.	Recently, it has been proposed that a PT-symmetry -based wireless sensing system can improve the resolution of the readout spectrum	Recently, Paper A observed higher-order exceptional points in pseudo-Hermitian radio-frequency circuits , which showed enhanced sensitivity in wireless sensing systems	Inspired by the concept of isospectral parity-time reciprocal scaling (PTX) symmetry , as discussed in [Paper B], we extend these ideas to demonstrate higher-order exceptional points in pseudo-Hermitian circuits	Recently, several studies have shown that the PT-symmetric systems possess unique properties such as unidirectional transmission , high resolution , and robustness against fabrication errors.
A Data-Driven Statistical-Stochastic Surrogate Modeling Strategy for Complex Nonlinear Non-stationary Dynamics	We propose a statistical-stochastic surrogate modeling approach to predict the response of the mean and variance statistics under various initial conditions and external forcing perturbations. The proposed modeling framework extends the purely statistical modeling approach that is practically limited to the homogeneous statistical regime for high-dimensional state variables. The new closure system allows one to overcome several practical issues that emerge in the non-homogeneous statistical regimes. First, the proposed ensemble modeling that couples the mean statistics and stochastic fluctuations naturally produces positive-definite covariance matrix estimation, which is a challenging issue that hampers the purely statistical modeling approaches. Second, the proposed closure model, which embeds a non-Markovian neural-network model for the unresolved fluxes such that the variance of the dynamics is consistent, overcomes the inherent instability of the stochastic fluctuation dynamics. Effectively, the proposed framework extends the classical stochastic parametric modeling paradigm for the unresolved dynamics to a semi-parametric parameterization with a residual Long-Short-Term-Memory neural network architecture. Third, based on empirical information metric, we provide an efficient and effective training procedure by fitting a loss function that measures the differences between response statistics. Supporting numerical examples are provided with the Lorenz-96 model, a system of ODEs that admits the characteristic of chaotic dynamics with both homogeneous and inhomogeneous statistical regimes. In the latter case, we will see the effectiveness of the statistical prediction even though the resolved Fourier modes corresponding to the leading mean energy and variance spectra do not coincide.	Machine Learning-Based Statistical Closure Models for Turbulent Dynamical Systems	We propose a Machine Learning (ML) non-Markovian closure modeling framework for accurate predictions of statistical responses of turbulent dynamical systems subjected to external forcings. One of the difficulties in this statistical closure problem is the lack of training data, which is a configuration that is not desirable in supervised learning with neural network models. In this study with the 40-dimensional Lorenz-96 model, the shortage of data (in temporal) is due to the stationarity of the statistics beyond the decorrelation time, thus, the only informative content in the training data is on short-time transient statistics. We adopted a unified closure framework on various truncation regimes, including and excluding the detailed dynamical equations for the variances. The closure frameworks employ a Long-Short-Term-Memory architecture to represent the higher-order unresolved statistical feedbacks with careful consideration to account for the intrinsic instability yet producing stable long-time predictions. We found that this unified agnostic ML approach performs well under various truncation scenarios. Numerically, the ML closure model can accurately predict the long-time statistical responses subjected to various time-dependent external forces that are not (and maximum forcing amplitudes that are relatively larger than those) in the training dataset.	Following the work in <code>\cite{qi2022machine}</code> , we will consider the class of residual network with vanilla LSTM architecture.	In contrast to previous works [1, 2], our proposed statistical-stochastic surrogate modeling strategy effectively addresses the challenges associated with non-homogeneous statistical regimes , as demonstrated through supporting numerical examples with the Lorenz-96 model [3]	Building on the previous work, who proposed a machine learning-based closure modeling framework for turbulent dynamical systems, our study extends the statistical-stochastic surrogate modeling approach to address non-homogeneous statistical regimes and improve covariance matrix estimation.	Following the same strategy as in <code>\cite{qi2022machine}</code> , we adopt a vanilla LSTM architecture to approximate the unresolved dynamics
PtyLab: a cross-platform, open-source inverse modeling toolbox for conventional and Fourier ptychography	Conventional (CP) and Fourier (FP) ptychography have emerged as versatile quantitative phase imaging techniques. While the main application cases for each technique are different, namely lens-less short wavelength imaging for CP and lens-based visible light imaging for FP, both methods share a common algorithmic ground. CP and FP have in part independently evolved to include experimentally robust forward models and inversion techniques. This separation has resulted in a plethora of algorithmic extensions, some of which have not crossed the boundary from one modality to the other. Here, we present an open source, cross-platform software, called PtyLab, enabling both CP and FP data analysis in a unified framework. With this framework, we aim to facilitate and accelerate cross-pollination between the two techniques. Moreover, the availability in Matlab, Python, and Julia will set a low barrier to enter each field.	Using Automatic Differentiation as a General Framework for Ptychographic Reconstruction	Coherent diffraction imaging methods enable imaging beyond lens-imposed resolution limits. In these methods, the object can be recovered by minimizing an error metric that quantifies the difference between diffraction patterns as observed, and those calculated from a present guess of the object. Efficient minimization methods require analytical calculation of the derivatives of the error metric, which is not always straightforward. This limits our ability to explore variations of basic imaging approaches. In this paper, we propose to substitute analytical derivative expressions with the automatic differentiation method, whereby we can achieve object reconstruction by specifying only the physics-based experimental forward model. We demonstrate the generality of the proposed method through straightforward object reconstruction for a variety of complex ptychographic experimental models.	Another line of research has investigated the capabilities opened up by modern automatic differentiation (AD) and machine learning (ML) toolboxes <code>\cite{Kandel2019}</code> .	Recent development in the field of ptychography is the introduction of PtyLab .	PtyLab builds on the automatic differentiation methods for ptychographic reconstruction introduced by [1].	Another example of a more recent development is the use of automatic differentiation and machine learning as a general framework for ptychographic reconstruction~ <code>\cite{Kandel2019}</code>
Model discovery in the sparse sampling regime	To improve the physical understanding and the predictions of complex dynamic systems, such as ocean dynamics and weather predictions, it is of paramount interest to identify interpretable models from coarsely and off-grid sampled observations. In this work, we investigate how deep learning can improve model discovery of partial differential equations when the spacing between sensors is large and the samples are not placed on a grid. We show how leveraging physics informed neural network interpolation and automatic differentiation, allow to better fit the data and its spatiotemporal derivatives, compared to more classic spline interpolation and numerical differentiation techniques. As a result, deep learning-based model discovery allows to recover the underlying equations, even when sensors are placed further apart than the data's characteristic length scale and in the presence of high noise levels. We illustrate our claims on both synthetic and experimental data sets where combinations of physical processes such as (non)-linear advection, reaction, and diffusion are correctly identified.	SciPy1.0-Fundamental Algorithms for Scientific Computing in Python	SciPy is an open source scientific computing library for the Python programming language. SciPy 1.0 was released in late 2017, about 16 years after the original version 0.1 release. SciPy has become a de facto standard for leveraging scientific algorithms in the Python programming language, with more than 600 unique code contributors, thousands of dependent packages, over 100,000 dependent repositories, and millions of downloads per year. This includes usage of SciPy in almost half of all machine learning projects on GitHub, and usage by high profile projects including LIGO gravitational wave analysis and creation of the first-ever image of a black hole (M87). The library includes functionality spanning clustering, Fourier transforms, integration, interpolation, file I/O, linear algebra, image processing, orthogonal distance regression, minimization algorithms, signal processing, sparse matrix handling, computational geometry, and statistics. In this work, we provide an overview of the capabilities and development practices of the SciPy library and highlight some recent technical developments.	We would also like to thank the authors and contributors of Scipy <code>\cite{scipy}</code> for making our work possible through their open-source software .	We cannot generate a citation sentence because there is no relationship or connection between the two papers	To address the challenges of interpolation and numerical differentiation in the sparse sampling regime, we utilize the SciPy library's advanced interpolation capabilities .	We have implemented the methodology described above in Python using the scipy library ~ <code>\cite{scipy}</code>