

Title	Ground-truth	Vicuna-13b	GPT-3.5 turbo	LitFM-13b
Adversarial Attacks on Deep Learning Based Power Allocation in a Massive MIMO Network	<p>Deep learning (DL) is becoming popular as a new tool for many applications in wireless communication systems. However, for many classification tasks (e.g., modulation classification) it has been shown that DL-based wireless systems are susceptible to adversarial examples; adversarial examples are well-crafted malicious inputs to the neural network (NN) with the objective to cause erroneous outputs. In this paper, we extend this to regression problems and show that adversarial attacks can break DL-based power allocation in the downlink of a massive multiple-input-multiple-output (maMIMO) network. Specifically, we extend the fast gradient sign method (FGSM), momentum iterative FGSM, and projected gradient descent adversarial attacks in the context of power allocation in a maMIMO system. We benchmark the performance of these attacks and show that with a small perturbation in the input of the NN, the white-box attacks can result in infeasible solutions up to 86%. Furthermore, we investigate the performance of black-box attacks. All the evaluations conducted in this work are based on an open dataset and NN models, which are publicly available.</p>	<p>Deep learning (DL) has emerged as a powerful tool for optimizing power allocation in wireless communication systems, particularly in the context of complex and dynamic environments. However, the vulnerability of DL models to adversarial attacks poses significant challenges to their reliability and security. This paper investigates the impact of adversarial attacks on DL-based power allocation strategies in wireless communication networks. We explore how carefully crafted perturbations can degrade the performance of DL models, leading to suboptimal or even detrimental power allocation decisions. Our study analyzes various types of adversarial attacks, including white-box and black-box attacks, and evaluates their effects on both the accuracy and robustness of DL models in different scenarios. We also discuss potential defense mechanisms to mitigate these attacks and improve the resilience of DL-based power allocation systems. The findings underscore the need for incorporating security considerations into the design of DL algorithms for wireless networks, ensuring that they can operate reliably even in the presence of adversarial threats.</p>	<p>Deep learning (DL) has emerged as a powerful tool for optimizing power allocation in massive multiple-input multiple-output (MIMO) networks, significantly improving network efficiency and performance. However, the deployment of DL models in real-world wireless communication systems presents vulnerabilities to adversarial attacks, which can lead to suboptimal or even catastrophic power allocation decisions. In this paper, we investigate the susceptibility of DL-based power allocation algorithms in massive MIMO networks to adversarial attacks. We explore various attack strategies and demonstrate their effectiveness in disrupting the performance of these algorithms. Our analysis includes both white-box and black-box attack scenarios, highlighting the potential risks posed by adversarially crafted inputs. To mitigate these risks, we propose a set of defense mechanisms designed to enhance the robustness of DL-based power allocation models. Through extensive simulations, we demonstrate that these defenses can significantly reduce the impact of adversarial attacks, ensuring more reliable and secure power allocation in massive MIMO networks. Our findings underscore the importance of considering adversarial threats in the design and deployment of DL-based solutions in wireless communication systems.</p>	<p>Deep learning (DL) is becoming popular as a new tool for many applications in wireless communication systems. However, it is known that DL models are highly sensitive to adversarial attacks. In this paper, we investigate the impact of adversarial attacks on DL-based power allocation in a massive multiple-input-multiple-output (MIMO) network. Firstly, we introduce two types of adversarial attacks, namely white-box attack and black-box attack, and then we formulate them as optimization problems. Secondly, we develop efficient algorithms to solve the formulated problems. Thirdly, we conduct simulations to evaluate the effectiveness of our proposed attacks. Our results indicate that both white-box and black-box attacks can effectively degrade the performance of DL-based power allocation in a massive MIMO network.</p>
Universal Sparse Superposition Codes with Spatial Coupling and GAMP Decoding	<p>Sparse superposition codes, or sparse regression codes, constitute a new class of codes which was first introduced for communication over the additive white Gaussian noise (AWGN) channel. It has been shown that such codes are capacity-achieving over the AWGN channel under optimal maximum-likelihood decoding as well as under various efficient iterative decoding schemes equipped with power allocation or spatially coupled constructions. Here, we generalize the analysis of these codes to a much broader setting that includes all memoryless channels. We show, for a large class of memoryless channels, that spatial coupling allows an efficient decoder, based on the generalized approximate message-passing (GAMP) algorithm, to reach the potential (or Bayes optimal) threshold of the underlying (or uncoupled) code ensemble. Moreover, we argue that spatially coupled sparse superposition codes universally achieve capacity under GAMP decoding by showing, through analytical computations, that the error floor vanishes and the potential threshold tends to capacity as one of the code parameter goes to infinity. Furthermore, we provide a closed form formula for the algorithmic threshold of the underlying code ensemble in terms of a Fisher information. Relating an algorithmic threshold to a Fisher information has theoretical as well as practical importance. Our proof relies on the state evolution analysis and uses the potential method developed in the theory of low-density parity-check (LDPC) codes and compressed sensing.</p>	<p>Sparse superposition codes have gained significant attention in recent years due to their ability to achieve near-optimal performance while maintaining low complexity. These codes are characterized by having a small number of nonzero coefficients, making them well-suited for applications where memory efficiency and computational resources are limited. In this paper, we propose a novel approach to construct universal sparse superposition codes that can be used in various communication scenarios. Our method relies on spatial coupling techniques and generalized approximate message passing (GAMP) decoding to achieve high error correction capabilities. We demonstrate the effectiveness of our proposed codes through simulations and compare them against existing state-of-the-art methods. The results show that our codes outperform other approaches in terms of both performance and complexity, making them an attractive option for practical applications.</p>	<p>Sparse superposition codes (SSC) have emerged as a powerful technique in the realm of communication systems, offering near-optimal performance in various channels. This paper explores the integration of universal sparse superposition codes with spatial coupling and the Generalized Approximate Message Passing (GAMP) algorithm for decoding. Spatial coupling, a technique known to enhance the robustness and efficiency of codes, is combined with SSC to achieve better performance over a wide range of channel conditions. The GAMP decoding algorithm is utilized to decode the spatially coupled SSC, leveraging its computational efficiency and ability to handle large-scale systems. Through both theoretical analysis and simulation, we demonstrate that the proposed system achieves reliable communication at rates approaching the channel capacity, while maintaining computational feasibility. The results suggest that the integration of spatial coupling with SSC, decoded via GAMP, offers a promising approach for future communication systems, particularly in scenarios demanding high reliability and efficiency.</p>	<p>Sparse superposition codes, or sparse regression codes, constitute a new class of codes which was first introduced for communication over the additive white Gaussian noise channel. These codes are now known to be universal, i.e., they achieve capacity over any memoryless channel under generalized approximate message-passing (GAMP) decoding. However, the GAMP decoder has never been explicitly designed for sparse superposition codes. In this work, we propose a novel GAMP decoder for sparse superposition codes, and we analyze its behavior on several channels. Our numerical simulations indicate that the GAMP decoder achieves near-capacity performance on the AWGN channel, while it reach the Bayes optimal on the binary erasure channel. We also demonstrate that the GAMP decoder exhibits a vanishing error floor when the number of nonzero coefficients increases. Finally, we discuss the impact of the choice of the encoding matrix on the performance of the GAMP decoder.</p>
Hybrid Combining Based on Constant Phase Shifters and Active/Inactive Switches	<p>In this paper, we propose a new hybrid analog and digital combining architecture for millimeter wave (mmWave) multi-user multiple-input multiple-output (MU-MIMO) systems. The proposed structure employs antenna subset selection per radio frequency (RF) chain based on active/inactive switches and uses constant phase shifters (CPS) to control the phases of signals in the RF circuit. In this scheme, for each RF chain, a subset of receive antennas that contribute more to the desired signal power than the interference power is chosen for signal combining in the analog domain, whereas other receive antennas are excluded from signal combining, thereby enhancing sum-rates. Simultaneously, the proposed structure reduces power consumption in the RF circuit by exclusively activating switches that correspond to the antennas selected for each RF chain. We also develop three low-complexity algorithms for per-RF chain antenna subset selection. Finally, through numerical simulation, we show that the proposed structure provides higher spectral efficiency and higher energy efficiency than conventional hybrid analog and digital combining schemes for mmWave MU-MIMO systems.</p>	<p>In this paper, we propose a new hybrid analog and digital combining architecture for millimeter wave (mmWave) multi-antenna systems. The proposed architecture employs constant phase shifters and active/inactive switches to achieve efficient power combination while maintaining low complexity. Simulation results demonstrate that our proposed method outperforms existing techniques in terms of both performance and complexity. This work paves the way for practical implementation of high-gain mmWave MIMO systems with reduced hardware requirements.</p>	<p>In this paper, we propose a novel hybrid combining architecture that integrates constant phase shifters with active and inactive switches for millimeter wave (mmWave) multi-user multiple input single output (MISO) systems. This architecture aims to enhance the performance of mmWave communication by leveraging the benefits of both analog and digital combining techniques. The proposed system optimizes beamforming and signal reception through a strategic combination of phase shifting and switching, which improves overall system efficiency and signal quality. Simulation results demonstrate the effectiveness of the hybrid approach in achieving significant gains in signal-to-noise ratio (SNR) and overall system capacity, making it a promising solution for advanced mmWave communication networks.</p>	<p>In this paper, we propose a new hybrid analog and digital combining architecture for millimeter wave (mmWave) multi-user multiple input single output (MISO) systems. The proposed architecture consists of two parts: an active part that uses constant phase shifters to combine the signals from different users at the transmitter side; and an inactive part that uses switches to selectively turn off some of the antennas at the receiver side. We first derive the optimal power allocation strategy based on the maximum ratio transmission (MRT) principle. Then, we analyze the performance of the proposed architecture by deriving closed form expressions for the achievable rate and outage probability. Simulation results show that our proposed architecture can achieve significant gains over conventional architectures with only one type of combining scheme. Moreover, it achieves similar or better performance than the state-of-the-art hybrid analog and digital combining schemes while requiring fewer hardware components.</p>