Quantum Cryptography and Meta-Complexity

Taiga Hiroka¹ and Tomoyuki Morimae¹

¹Yukawa Institute for Theoretical Physics, Kyoto University, Kyoto, Japan {taiga.hiroka,tomoyuki.morimae}@yukawa.kyoto-u.ac.jp

Abstract

In classical cryptography, one-way functions (OWFs) are the minimal assumption, while it is not the case in quantum cryptography. Several new primitives have been introduced such as pseudorandom unitaries (PRUs), pseudorandom function-like state generators (PRFSGs), pseudorandom state generators (PRSGs), one-way state generators (OWSGs), one-way puzzles (OWPuzzs), and EFI pairs. They seem to be weaker than OWFs, but still imply many useful applications such as private-key quantum money schemes, secret-key encryption, message authentication codes, digital signatures, commitments, and multiparty computations. Now that the possibility of quantum cryptography without OWFs has opened up, the most important goal in the field is to build a foundation of it. In this paper, we, for the first time, characterize quantum cryptographic primitives with meta-complexity. We show that one-way puzzles (OWPuzzs) exist if and only if GapK is weakly-quantum-average-hard. GapK is a promise problem to decide whether a given bit string has a small Kolmogorov complexity or not. Weakly-quantum-averagehard means that an instance is sampled from a QPT samplable distribution, and for any QPT adversary the probability that it makes mistake is larger than 1*/*poly. We also show that if quantum PRGs exist then GapK is strongly-quantum-average-hard. Here, strongly-quantum-average-hardis a stronger version of weakly-quantum-average-hard where the probability that the adversary makes mistake is larger than 1*/*2 − 1*/*poly. Finally, we show that if GapK is weakly-classical-average-hard, then inefficient-verifier proofs of quantumness (IV-PoQ) exist. Weakly-classical-average-hard is the same as weakly-quantumaverage-hard except that the adversary is PPT. IV-PoQ are a generalization of proofs of quantumness (PoQ) that capture sampling-based and search-based quantum advantage, and an important application of OWpuzzs. This is the fist time that quantum advantage is based on meta-complexity. (Note: There are two concurrent works, [\[KT24b,](#page-29-0) [CGGH24\]](#page-27-0).)

Contents

1 Introduction

In classical cryptography, the existence of one-way functions (OWFs) is the minimal assumption [\[IL89\]](#page-28-0), because they are existentially equivalent to many primitives, such as pseudorandom generators (PRGs) [\[HILL99\]](#page-28-1), pseudorandom functions (PRFs) [\[GGM86\]](#page-28-2), secret-key encryption (SKE) [\[GM84\]](#page-28-3), message authentication codes (MAC) [\[GGM84\]](#page-28-4), digital signatures [\[Rom90\]](#page-29-1), and commitments [\[Nao90\]](#page-29-2). Moreover, almost all primitives (including public-key encryption and multiparty computations) imply OWFs.

On the other hand, in quantum cryptography, OWFs are not necessarily the minimum assumption [\[Kre21,](#page-28-5) [MY22,](#page-29-3) [AQY22\]](#page-26-0). Several new primitives have been introduced such as pseudorandom unitaries (PRUs) [\[JLS18\]](#page-28-6), pseudorandom function-like state generators (PRFSGs) [\[AQY22,](#page-26-0) [AGQY22\]](#page-26-1), pseudorandom state generators (PRSGs) [\[JLS18\]](#page-28-6), one-way state generators (OWSGs) [\[MY22\]](#page-29-3), one-way puzzles (OWPuzzs) [\[KT24a\]](#page-29-4), and EFI pairs [\[BCQ23\]](#page-27-1). Although they could be weaker than OWFs [\[Kre21,](#page-28-5) [KQST23,](#page-28-7) [LMW24\]](#page-29-5), they still imply many useful applications such as private-key quantum money schemes [\[JLS18\]](#page-28-6), SKE [\[AQY22\]](#page-26-0), MAC [\[AQY22\]](#page-26-0), digital signatures [\[MY22\]](#page-29-3), commitments [\[MY22,](#page-29-3) [AQY22,](#page-26-0) [Yan22\]](#page-30-1), and multiparty computations [\[MY22,](#page-29-3) [AQY22,](#page-26-0) [BCKM21,](#page-26-2) [GLSV21\]](#page-28-8).

Now that the possibility of the "OWFs-free" quantum cryptographic world (so-called Microcrypt) has opened up, the most important goal in the field is to build a foundation of Microcrypt. In classical cryptography, OWFs are founded in several ways and levels. Although basing OWFs on $P \neq NP$ or its average version is still open, OWFs have many instantiations based on concrete hardness assumptions, such as the hardness of discrete logarithm [\[DH76\]](#page-27-2) or lattice problems [A jt 96], and abstracted assumptions such as cryptographic group actions [\[Cou06,](#page-27-3) [JQSY19,](#page-28-9) [ADMP20,](#page-26-4) [BY91\]](#page-27-4). Moreover, recent active studies have succeeded to base OWFs on meta-complexity (for example [\[LP20,](#page-29-6) [IRS21\]](#page-28-10)).

On the other hand, for the foundation of Microcrypt, currently what we know is only that all Microcrypt primitives can be generically constructed at least from OWFs [\[MH24,](#page-29-7) [JLS18,](#page-28-6) [AQY22,](#page-26-0) [MY22,](#page-29-3) [MY24a,](#page-29-8) [KT24a\]](#page-29-4). In particular, we do not know whether they can be based on some worst-case or average-case complexity assumptions, hardness assumptions of concrete mathematical problems, or some meta-complexity assumptions that do not imply OWFs.[1](#page-2-2)

1.1 Our Results

The goal of the present paper is to base Microcrypt primitives on meta-complexity. As far as we know, this is the first time that quantum cryptographic primitives are characterized by meta-complexity.[2](#page-2-3) In the following, we explain each result. Our results are also summarized in Figure [1.](#page-5-0)

One-way puzzles. Our first result is a characterization of OWPuzzs with average-hardness of GapK.

Theorem 1.1. *OWPuzzs exist if and only if GapK is weakly-quantum-average-hard.*

OWPuzzs [\[KT24a\]](#page-29-4) are a quantum analogue of OWFs, and one of the most fundamental primitives in quantum cryptography. A OWPuzz is a pair (Samp*,*Ver) of two algorithms. Samp is a quantum polynomialtime (QPT) algorithm that, on input the security parameter $1ⁿ$, outputs two classical bit strings, ans and puzz. Ver is an unbounded algorithm that, on input (puzz*,* ans′), outputs ⊤*/*⊥. Correctness requires that Ver accepts (puzz, ans) \leftarrow Samp(1ⁿ) with high probability. Security requires that no QPT adversary that receives puzz can output ans' such that (puzz, ans') is accepted by Ver with high probability. OWPuzzs

¹There are two concurrent works [\[KT24b,](#page-29-0) [CGGH24\]](#page-27-0) that tackle this open problem. See Section [1.3.](#page-7-0)

²There is a concurrent work [\[CGGH24\]](#page-27-0). See Section [1.3.](#page-7-0)

are implied by almost all primitives including PRUs, PRFSGs, PRSGs, OWSGs, SKE, MAC, private-key quantum money schemes, etc. [\[MY24a,](#page-29-8) [MY22,](#page-29-3) [KT24a,](#page-29-4) [BJ24\]](#page-27-5). OWPuzzs imply EFI pairs, commitments, multiparty computations, and quantum advantage [\[KT24a,](#page-29-4) [GLSV21,](#page-28-8) [BCKM21,](#page-26-2) [MSY24\]](#page-29-9).

GapK [\[IRS21\]](#page-28-10) is a promise problem to decide whether a given classical bit string *x* has a small Kolmogorov complexity or not. Roughly speaking, a Kolmogorov complexity [\[Sol64,](#page-29-10) [Kol68,](#page-28-11) [Cha69\]](#page-27-6) of a bit string *x* is the length of the shortest program that outputs *x*. (For more details, see for example [\[LV19\]](#page-29-11).) Weakly-quantum-average-hard means that an instance *x* is sampled from a QPT samplable distribution, and for any QPT adversary the probability that it makes mistake is larger than 1*/*poly. (Here, the probability is taken over the sampling of the instance and the algorithm of the adversary.)

Quantum PRGs. Having characterized OWPuzzs, the next question is whether we can do the same for other Microcrypt primitives. In paricular, OWPuzzs are a search-type primitive, and hence it is interesting to ask whether we can characterize decision-type primitives with meta-complexity. Our second result is a meta-complexity lower-bound for quantum PRGs (QPRGs).

Theorem 1.2. *If QPRGs exist, then GapK is strongly-quantum-average-hard.*

A QPRG is a QPT algorithm that takes the security parameter 1^n as input and outputs a classical bit string. Its output probability distribution is statistically far but computationally indistinguishable from a uniform distribution. Strongly-quantum-average-hard is a stronger version of weakly-quantum-average-hard where the probability that a QPT adversary makes mistake is larger than $1/2 - 1/poly$. QPRGs are a special case of QEFID and EFI. An EFI [\[BCQ23\]](#page-27-1) is a QPT algorithm that outputs two quantum states that are statistically far but computationally indistinguishable. QEFID are a variant of EFI where the outputs are bit strings. We left the problem of characterizing EFI and QEFID with meta-complexity open. Another open problem is whether we can establish a meta-complexity upperbound for QPRGs.

Quantum advantage. Quantum advantage is another important application of OWPuzzs [\[MSY24\]](#page-29-9). We can base quantum advantage on meta-complexity. As far as we know, this is the first time that quantum advantage is based on meta-complexity.

Theorem 1.3. *If GapK is weakly-classical-average-hard, then IV-PoQ exist.*

Weakly-classical-average-hard is equivalent to weakly-quantum-average-hard except that the adversary is PPT. (Note that the instance sampling algorithm is still QPT.) Inefficient-verifier proofs of quantumness $(IV-PoQ)$ [\[MY24b\]](#page-29-12) are a generalization of proofs of quantumness (PoQ) [\[BCM](#page-27-7)⁺21] and capture various notions of quantum advantage such as sampling-based quantum advantage [\[BFNV19,](#page-27-8) [AA11,](#page-26-5) [TD04,](#page-30-2) [BJS11,](#page-27-9) [BMS16,](#page-27-10) [FKM](#page-27-11)⁺18] and searching-based one $[AC17, AG19, Aar10, ACC⁺23, Sho94, YZ24]$ $[AC17, AG19, Aar10, ACC⁺23, Sho94, YZ24]$. An IV-PoQ is an interactive protocol over a classical channel between a verifier and a QPT prover. During the interaction phase, the verifier is PPT, but after the interaction, the verifier becomes unbounded. If the QPT prover honestly runs the protocol, the unbounded verifier accepts with high probability, but for any PPT prover, the unbounded verifier does not accept except for a small probability. It was shown recently [\[MSY24\]](#page-29-9) that IV-PoQ are existentially equivalent to classically-secure OWPuzzs. This in particular means that OWPuzzs imply IV-PoQ. Our result, for the first time, bases quantum advantage on meta-complexity. It is an open problem whether any meta-complexity lower bound for quantum advantage can be established.

Quantum probability estimation. Theorem [1.1](#page-2-4) shows that average-hardness of GapK implies OWPuzzs. However, technically, we do not directly construct OWPuzzs from the hardness of GapK. We introduce a new problem, which we call quantum probability estimation (QPE), and show the following two results from which GapK⇒OWPuzzs is obtained.

Theorem 1.4. *If GapK is weakly-quantum-average-hard, then QPE is quantum-average-hard.*

Theorem 1.5. *If QPE is quantum-average-hard, then OWPuzzs exist.*

QPE is, roughly speaking, the task of computing $Pr[x \leftarrow \mathcal{Q}(1^n)]$ within a multiplicative-error given *x* and a classical description of a QPT algorithm Q that outputs *n*-bit strings on input 1^n . Its quantum-averagehardness means that an instance $x \in \{0,1\}^n$ is sampled by $\mathcal{Q}(1^n)$, and for any QPT adversary the probability that it outputs a correct estimate is less than $1 - 1/\text{poly}(n)$.

The problem QPE, and the assumption of its average-hardess themselves seem to be of independent interest, and will be useful in other applications.^{[3](#page-4-1)}

1.2 Technical Overview

In this subsection, we provide high-level overview of our proofs.

OWPuzzs from weakly-quantum-average-hardness of GapK. GapK[s_1 , s_2] is the following promise problem: Given a bit string x, decide $K(x) \leq s_1$ or $K(x) \geq s_2$, where $K(x)$ is the Kolmogorov complexity of *x*, i.e., the length of the shortest program that a universal Turing machine outputs *x*. Weakly-quantumaverage-hardness means that an instance *x* is sampled from a QPT samplable distribution, and for any QPT adversary, the probability that it makes mistake is larger than 1*/*poly. (Here, the probability is taken over the sampling of the instance and the algorithm of the adversary.) More precisely, we require that there exist an integer $k > 0$ and a QPT algorithm Q (that takes 1^n as input and outputs *n*-bit strings) such that, for any QPT adversary A,

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}] + \Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}] \ge \frac{1}{n^k} \tag{1}
$$

for all sufficiently large $n \in \mathbb{N}$, where \mathcal{L}_{Yes} (resp. \mathcal{L}_{No}) is the set of yes (resp. no) instances of GapK[s_1, s_2].^{[4](#page-4-2)}

We do not directly show the existence of OWPuzzs from weakly-quantum-average-hardness of GapK. We introduce another problem, which we call quantum probability estimation (QPE), and assume its quantumaverage-hardness. We first show that weakly-quantum-average-hardness of GapK implies quantum-averagehardness of QPE, and then we show that quantum-average-hardness of QPE implies OWPuzzs.

A QPE is a problem of computing $Pr[x \leftarrow Q(1^n)]$ within a multiplicative error given x and a classical description of a QPT algorithm Q . Its quantum-average-hardness means that x is sampled from $Q(1^n)$ and for any QPT adversary, the probability that it outputs a correct estimate is smaller than 1− 1*/*poly(*n*). More precisely, we require that there exist a real $c > 1$, an integer $q > 0$, and a QPT algorithm Q (that takes 1^n as input and outputs *n*-bit strings) such that, for any QPT algorithm Estimate,

$$
\Pr_{\leftarrow \mathcal{Q}(1^n)} \left[\frac{1}{c} \Pr[x \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(x) \le c \Pr[x \leftarrow \mathcal{Q}(1^n)] \right] \le 1 - \frac{1}{n^q} \tag{2}
$$

 x

³In fact, in a concurrent paper [\[KT24b\]](#page-29-0), Khurana and Tomer showed that hardness of QPE is implied by the assumption previously studied in the field of sampling-based quantum advantage (plus $P^{+P} \not\subseteq (io)BQP/qpoly$).

⁴A bit string *x* is a yes (no) instance if $K(x) \leq s_1$ ($K(x) \geq s_2$).

Figure 1: A summary of results. Black lines are known results or trivial implications. Red lines are new in our work. The concurrent work [\[KT24b\]](#page-29-0) showed QPE⇔OWPuzzs. The concurrent work [\[CGGH24\]](#page-27-0) showed OWPuzzs⇒wGapK, wGapK⇒QPE, and QPE⇒OWPuzzs. "qs" stands for quantumly-secure, and "cs" stands for classically-secure. "nu" stands for non-uniform. sGapK means strongly-quantum-averagehardness of GapK. wGapK means weakly-quantum-average-hardness of GapK. cwGapK means weaklyclassical-average-hardness of GapK. Quantum advantage assumption is the combination of so-called "#**P**hardness assumption" (computing some functions within multiplicative errors is #**P**-hard on average) and so-called "anti-concentration" [\[AA11,](#page-26-5) [BMS16\]](#page-27-10).)

for all sufficiently large $n \in \mathbb{N}$.

Let us first explain how to construct OWPuzzs from quantum-average-hardness of QPE. Let Q be the instance sampling QPT algorithm for quantum-average-hardness of QPE. [\[CGG24\]](#page-27-12) showed the equivalence between OWPuzzs and distributional OWPuzzs, which means that if OWPuzzs do not exist, then distributional OWPuzzs do not exist as well. If distributional OWPuzzs do not exist, then there exists a QPT extrapolation algorithm Ext that, given $(x_1, ..., x_{i-1}) \leftarrow Q(1^n)$, can sample x_i , such that the statistical distance between $(x_1,...,x_i)_{(x_1,...,x_i)\leftarrow\mathcal{Q}(1^n)}$ and $(x_1,...,x_{i-1},\mathsf{Ext}(x_1,...,x_{i-1}))_{(x_1,...,x_{i-1})\leftarrow\mathcal{Q}(1^n)}$ is small for all $i\in[n-1]$. Then, by repeatedly running Ext, we can compute an approximation of $Pr[(x_1, ..., x_n) \leftarrow Q(1^n)]$. This means that quantum-average-hardness of QPE does not hold.

Next, let us explain how quantum-average-hardness of QPE is derived from weakly-quantum-average-hardness of GapK.^{[5](#page-6-0)} Assume that quantum-average-hardness of QPE does not hold. Then, there is a QPT algorithm Estimate that can estimate output probability of any QPT distribution. We construct a QPT algorithm A that solves GapK as follows: Let Q be a QPT algorithm that samples the instance of GapK. Given $x \leftarrow Q(1^n)$, run Estimate (x) and output yes if the approximation of $Pr[x \leftarrow Q(1^n)]$ is larger than a certain threshold. Intuitively, $K(x)$ is small (resp. large) if $Pr[x \leftarrow Q(1^n)]$ is large (resp. small) with high probability over $x \leftarrow Q(1^n)^6$ $x \leftarrow Q(1^n)^6$, and therefore A can correctly decide whether $K(x)$ is small or large.

Strongly-quantum-average-hardness of GapK from QPRGs. Next let us explain how to show stronglyquantum-average-hardness of GapK from the existence of QPRGs. Strongly-quantum-average-hardness is the same as weakly-quantum-average-hardness explained above except that the probability that the adversary makes a mistake is larger than $1/2 - 1/poly$. A QPRG is a QPT algorithm Gen that takes the security parameter 1ⁿ as input and outputs *n*-bit strings whose distribution is statistically far but computationally indistinguishable from the uniform distribution over $\{0, 1\}^n$. Our key observation is that if the output distribution of Gen(1^n) is exponentially statistically far^{[7](#page-6-2)} from the uniform distribution over $\{0,1\}^n$, then the Kolmogorov complexity $K(x)$ of x is small with high probability over $x \leftarrow$ Gen (1^n) . In that case, it is easy to show strongly-quantum-average-hardness of GapK as follows. Let Q be a QPT algorithm that outputs $x \leftarrow$ Gen(1ⁿ) with probability 1/2 and a uniformly random *n*-bit string x with probability 1/2. If there is a QPT algorithm that can decide if $K(x)$ is large or small with probability larger than $1/2 + 1/\text{poly}(n)$ over the distribution $x \leftarrow Q(1^n)$, then we can construct a QPT algorithm that can distinguish the distribution of Gen(1^n) from the uniform distribution over $\{0, 1\}^n$, which breaks the QPRG.

However, in general, a QPRG does not satisfy such an exponentially-statistically-far property. Fortunately, we can show that if QPRGs exist, then QPRGs with the exponentially-statistically-far property exist by the parallel repetition and the padding argument.

Weakly-quantum-average-hardness of GapK from OWPuzzs. This is obtained by showing that nonuniform QPRGs (nuQPRGs) imply weakly-quantum-average-hardness of GapK, because nuQPRGs exist if and only if OWPuzzs exist [\[KT24a,](#page-29-4) [CGG24\]](#page-27-12).

⁵This was essentially shown in [\[IRS21\]](#page-28-10), but we slightly improved the parameters for our purpose.

⁶If $Pr[x \leftarrow Q(1^n)]$ is large, *x* can be taken from the support of $Q(1^n)$, which allows a shorter program to output *x*. On the other hand, because there are at most 2^{s+1} strings $x \in \{0,1\}^n$ that satisfy $K(x) < s$, the probability that $\mathcal{Q}(1^n)$ outputs *x* such that both $K(x) < s$ and $Pr[x \leftarrow Q(1^n)] < \alpha$ is at most $2^{s+1}\alpha$. Therefore, if $Pr[x \leftarrow Q(1^n)]$ is sufficiently small, then $K(x)$ must be large with high probability over $x \leftarrow \mathcal{Q}(1^n)$.

⁷We say that a family $\{D_n\}_{n\in\mathbb{N}}$ of distributions where D_n is a distribution over $\{0,1\}^n$ is exponentially statistically far from a family $\{E_n\}_{n\in\mathbb{N}}$ of distributions where E_n is a distribution over $\{0,1\}^n$, if for some real $0<\tau<1$, $\mathsf{SD}((x)_{x\leftarrow D_n}, (x)_{x\leftarrow E_n})>$ $1 - 2^{-n^T}$ for all sufficiently large $n \in \mathbb{N}$.

nuQPRGs are a non-uniform version of QPRGs: A nuQPRG is a QPT algorithm Gen that takes the security parameter 1^n and an advice bit string μ of $\log(n)$ length as input, and outputs *n*-bit strings. It satisfies that for a $\mu^* \in [n]$, the distribution Gen $(1^n, \mu^*)$ is statistically far but computationally indistinguishable from the uniform distribution over $\{0, 1\}^n$.

The proof of showing weakly-quantum-average-hardness of GapK from nuQPRGs is similar to that of strongly-quantum-average-hardness of GapK from QPRGs. As we have already explained above, in the proof of showing strongly-quantum-average-hardness of GapK from QPRGs, we define a QPT algorithm Q that outputs $x \leftarrow$ Gen(1ⁿ) with 1/2 and outputs random *n*-bit string with probability 1/2, and show that Q works as an instance sampling algorithm for which GapK is strongly-quantum-average-hard. In order to show weaklyquantum-average-hardness of GapK from nuQPRGs, a difference is that Q additionally samples an advice string $\mu \leftarrow [n]$ and outputs $x \leftarrow$ Gen $(1^n, \mu)$ with probability $1/2$ and a random *n*-bit string with probability 1/2. Because the good advice μ^* is obtained with probability 1/n, weakly-quantum-average-hardness of GapK is satisfied.

IV-PoQ from weakly-classical-average-hardness of GapK. From the result of [\[MSY24\]](#page-29-9), IV-PoQ exist if and only if the QAS/OWF condition holds. Therefore we show that if weakly-classical-average-hardness of GapK is satisfied, then the QAS/OWF condition is satisfied.

Informally, if the QAS/OWF condition is satisfied, then quantum advantage samplers (QASs) exist or OWFs exist. Here a QAS is QPT algorithm that outputs classical bit strings whose distribution cannot be sampled with any PPT algorithm. For contradiction, assume that the QAS/OWF condition is not satisfied, which roughly means that both QASs and OWFs do not exist. Let Q be a QPT algorithm that samples the instance x of GapK. Because QASs do not exist, there exists a PPT algorithm S that approximately samples Q. Moreover, because OWFs do not exist, we can construct a PPT algorithm Estimate that estimates $Pr[x \leftarrow S(1^n)] \approx Pr[x \leftarrow Q(1^n)]$. As we have explained above, if we can estimate the value of $Pr[x \leftarrow Q(1^n)]$ then we can solve GapK.

As is shown in [\[MSY24\]](#page-29-9), classically-secure OWPuzzs exist if and only if IV-PoQ exist. Therefore, readers might think that we can directly show that weakly-classical-average-hardness of GapK implies classically-secure OWPuzzs (and hence IV-PoQ) by replacing all QPT adversaries with PPT ones in the proof of OWPuzzs from weakly-quantum-average-hardness of GapK. However, we do not know how to do that, because we do not know whether classically-secure OWPuzzs are equivalent to classically-secure distributional OWPuzzs unlike the quantumly-secure case [\[CGG24\]](#page-27-12).

1.3 Concurrent Works

There are two concurrent works, [\[KT24b,](#page-29-0) [CGGH24\]](#page-27-0). We explain relations between our results and these concurrent works.

Relation to [\[KT24b\]](#page-29-0). During the preparation of the first version of this manuscript, Khurana and Tomer uploaded [\[KT24b\]](#page-29-0). They introduce two hardness assumptions, Assumption 1 and Assumption 2. Assumption 1 is an assumption often studied in the field of quantum advantage to derive sampling-based quantum advantage. They show that Assumption 1 plus a mild complexity assumption, $P^{p} \not\subset (io) BQP/qpoly$, imply Assumption 2. They then show that Assumption 2 is equivalent to the existence of OWPuzzs.

Their Assumption 2 is the same as our assumption, Assumption [3.4,](#page-12-3) the average-hardness of QPE. Moreover, their proof of "Assumption 2 \Rightarrow OWPuzzs" is similar to our proof of "Assumption [3.4](#page-12-3) \Rightarrow OWPuzzs".

In addition, their Assumption 2 allows quantum advice for adversaries. In this paper we do not explicitly consider quantum advice, but we believe that our proofs can be straightforwardly extended to the case with quantum advice.

Relation to [\[CGGH24\]](#page-27-0). After uploading the first version of this paper on arXiv, Cavalar, Goldin, Gray, and Hall sent us their manuscript (that was later uploaded [\[CGGH24\]](#page-27-0)). In the first version of our paper, we showed only the direction of wGapK⇒OWPuzzs, while their manuscript shows the both directions wGapK⇔OWPuzzs. When they contacted us, we had shown QPRGs⇒sGapK, and planned to add the result to the revised version. We later realized that with almost the same proof, this also means nuOPRGs \Rightarrow wGapK, which means OWPuzzs⇒wGapK. Our proof for OWPuzzs⇒wGapK is different from theirs.

2 Preliminaries

2.1 Basic Notations

We use the standard notations of cryptography and quantum information. *n* is the security parameter. negl is a negligible function. [*n*] denotes the set $\{1, 2, ..., n\}$. QPT stands for quantum polynomial time, and PPT stands for classical polynomial time. For an algorithm (or a Turing machine) $A, y \leftarrow A(x)$ means that A runs on input *x* and outputs *y*. SD(*D, E*) is the statistical distance between two distributions *D* and *E*.

2.2 One-Way Puzzles

We review the definition of OWPuzzs.

Definition 2.1 (One-Way Puzzles (OWPuzzs) [\[KT24a\]](#page-29-4)). *A one-way puzzle is a pair* (Samp*,*Ver) *of algorithms with the following syntax:*

- Samp $(1^n) \rightarrow$ (ans, puzz): It is a QPT algorithm that, on input 1^n , outputs two classical bit strings (ans*,* puzz)*.*
- $\text{Ver}(\text{ans}', \text{puzz}) \rightarrow \top/\bot$: It is an unbounded algorithm that, on input (ans', puzz), outputs \top/\bot .

We require the following correctness and security.

Correctness:

$$
\Pr_{(\text{ans}, \text{puzz}) \leftarrow \text{Samp}(1^n)}[\top \leftarrow \text{Ver}(\text{ans}, \text{puzz})] \ge 1 - \text{negl}(n). \tag{3}
$$

Security: *For any uniform QPT adversary* A*,*

$$
\Pr_{(\text{ans}, \text{puzz}) \leftarrow \text{Samp}(1^n)}[\top \leftarrow \text{Ver}(\mathcal{A}(1^n, \text{puzz}), \text{puzz})] \le \text{negl}(n). \tag{4}
$$

[\[CGG24\]](#page-27-12) introduced distributional OWPuzzs, and show their equivalence to OWPuzzs. The following lemma comes from the equivalence. We will use the lemma later.

Lemma 2.2 ([\[CGG24\]](#page-27-12)). *Suppose that (resp. infinitely-often) OWPuzzs do not exist. Then, for any QPT algorithm* Q *that on input* 1 *ⁿ outputs n-bit strings, and for any constant t >* 0*, there exists a uniform QPT algorithm* Ext *that outputs a single bit such that*

$$
\text{SD}\left((y_1, \dots, y_i)_{(y_1, \dots, y_i) \leftarrow \mathcal{Q}(1^n)}, (y_1, \dots, y_{i-1}, \text{Ext}(1^n, i, y_1, \dots, y_{i-1}))_{(y_1, \dots, y_{i-1}) \leftarrow \mathcal{Q}(1^n)}\right) \le \frac{1}{n^t} \tag{5}
$$

for all $i \in [n]$ *and infinitely many* $n \in \mathbb{N}$ *(resp. all sufficiently large* $n \in \mathbb{N}$ *). Here* y_i *is the ith bit of* $y \in \{0,1\}^n$, and $(y_1,...,y_i) \leftarrow Q(1^n)$ is the marginal distribution over the first *i* bits of the output of $Q(1^n)$.

2.3 Quantum PRGs

We review the definitions of quantum PRGs (QPRGs).

Definition 2.3 (Quantum PRGs (QPRGs)). *A QPRG is a QPT algorithm* Gen(1*ⁿ*) *that takes a security parameter* 1^n *as input, and outputs a classical bit string* $x \in \{0,1\}^n$ *satisfying the following properties:*

Statistically far:

$$
SD((x)_{x \leftarrow Gen(1^n)}, (x)_{x \leftarrow \{0,1\}^n}) \ge 1 - neg(n). \tag{6}
$$

Computationally indistinguishable: *For any QPT algorithm* A*,*

$$
\left|\Pr_{x \leftarrow \mathsf{Gen}(1^n)}[1 \leftarrow \mathcal{A}(1^n, x)] - \Pr_{x \leftarrow \{0,1\}^n}[1 \leftarrow \mathcal{A}(1^n, x)]\right| \le \mathsf{negl}(n). \tag{7}
$$

We will later use the following lemma. Its proof is given by the standard padding argument. We give its proof in Appendix [A.](#page-30-0)

Lemma 2.4. *Suppose that there exists a QPRG* Gen. *Then, for any real* $0 < \tau < 1$ *, there exists a QPRG* Gen[∗] *that satisfies the following properties.*

Exponentially statistically far:

$$
SD((x)_{x \leftarrow Gen^*(1^n)}, (x)_{x \leftarrow \{0,1\}^n}) \ge 1 - 2^{-n^{\tau}}
$$
\n(8)

for all sufficiently large $n \in \mathbb{N}$ *.*

Computationally indistinguishable: *For any QPT algorithm* A*,*

$$
\left| \Pr_{x \leftarrow \mathsf{Gen}^*(1^n)}[1 \leftarrow \mathcal{A}(1^n, x)] - \Pr_{x \leftarrow \{0, 1\}^n}[1 \leftarrow \mathcal{A}(1^n, x)] \right| \le \mathsf{negl}(n). \tag{9}
$$

We also introduce a non-uniform version of QPRGs.

Definition 2.5 (non-uniform QPRGs (nuQPRGs)). *A non-uniform QPRG is a QPT algorithm* Gen(1*ⁿ , µ*) *that takes a security parameter* 1^n *and* $\mu \in [n]$ *as input, and outputs a classical bit string* $x \in \{0,1\}^n$ *. We require that there exists* $\mu^* \in [n]$ *such that the following two conditions hold:*

Statistically far:

$$
SD((x)_{x \leftarrow Gen(1^n, \mu^*)}, (x)_{x \leftarrow \{0, 1\}^n}) \ge 1 - negl(n). \tag{10}
$$

Computationally indistinguishable: *For any QPT algorithm* A*,*

$$
\left|\Pr_{x \leftarrow \mathsf{Gen}(1^n,\mu^*)} [1 \leftarrow \mathcal{A}(1^n,x)] - \Pr_{x \leftarrow \{0,1\}^n} [1 \leftarrow \mathcal{A}(1^n,x)]\right| \le \mathsf{negl}(n). \tag{11}
$$

It is known that OWPuzzs are existentially equivalent to nuQPRGs.

Theorem 2.6 ([\[KT24a,](#page-29-4) [CGG24\]](#page-27-12)). *OWPuzzs exist if and only if nuQPRGs exist.*

We will use the following lemma. We omit its proof because it is the same as that of Lemma [2.4.](#page-9-1)

Lemma 2.7. *Suppose that there exists a nuQPRG* Gen*. Then, for any real* 0 *< τ <* 1*, there exists another* $nuQPRG$ Gen^{*} such that there exists $\mu^* \in [n]$ with the following properties:

Exponentially statistically far:

$$
SD((x)_{x \leftarrow Gen^*(1^n, \mu^*)}, (x)_{x \leftarrow \{0,1\}^n}) \ge 1 - 2^{-n^{\tau}}
$$
\n(12)

for all sufficiently large $n \in \mathbb{N}$ *.*

Computationally indistinguishable: *For any QPT algorithm* A*,*

$$
\left|\Pr_{x \leftarrow \mathsf{Gen}^*(1^n,\mu^*)} [1 \leftarrow \mathcal{A}(1^n,x)] - \Pr_{x \leftarrow \{0,1\}^n} [1 \leftarrow \mathcal{A}(1^n,x)]\right| \le \mathsf{negl}(n). \tag{13}
$$

2.4 One-Way Functions

Definition 2.8 (OWFs on Σ **[\[MSY24\]](#page-29-9)**). Let $\Sigma \subseteq \mathbb{N}$ be a set. A function $f : \{0,1\}^* \to \{0,1\}^*$ that *is computable in classical deterministic polynomial-time is a classically-secure (resp. quantumly-secure) OWF on* Σ *if there exists an efficiently-computable polynomial m such that for any PPT (resp. QPT) adversary* A *and any polynomial p there exists n* [∗] ∈ N *such that*

$$
\Pr[f(x') = f(x) : x \leftarrow \{0, 1\}^{m(n)}, x' \leftarrow \mathcal{A}(1^{m(n)}, f(x)) \le \frac{1}{p(n)} \tag{14}
$$

holds for all $n \geq n^*$ *in* Σ *.*

2.5 QAS/OWF Condition

Definition 2.9 (The QAS/OWF Condition [\[MSY24\]](#page-29-9)). *The QAS/OWF condition holds if there exist a polynomial p, a QPT algorithm* Q *that takes* 1 *ⁿ as input and outputs a classical string, and a function* $f: \{0,1\}^* \to \{0,1\}^*$ that is computable in classical deterministic polynomial-time such that for any PPT *algorithm* S*, the following holds: if we define*

$$
\Sigma_{\mathcal{S}} := \left\{ n \in \mathbb{N} : SD(\mathcal{Q}(1^n), \mathcal{S}(1^n)) \le \frac{1}{p(n)} \right\},\tag{15}
$$

then f is a classically-secure OWF on Σ *s*.

We will use the following lemma.

Lemma 2.10 ([\[MSY24\]](#page-29-9)). *If the QAS/OWF condition is not satisfied, then the following statement is satisfied: for any QPT algorithm* Q *that takes* 1^n *as input and outputs a classical string and for any real* $k > 0$ *, there exists a PPT algorithm* S *such that for any efficiently-computable polynomial m and any family* ${f_n: \{0,1\}^m$ \rightarrow ${0,1\}^*\}$ _{*n*∈N} *of functions that are computable in classical deterministic polynomialtime, there exists a PPT algorithm* R *such that*

$$
SD(Q(1^n), S(1^n)) \le \frac{1}{n^k}
$$
\n(16)

and

$$
\text{SD}\left(\{x, f_n(x)\}_{x \leftarrow \{0,1\}^{m(n)}}, \{\mathcal{R}(1^{m(n)}, f_n(x)), f_n(x)\}_{x \leftarrow \{0,1\}^{m(n)}}\right) \le \frac{1}{n^k} \tag{17}
$$

for infinitely many $n \in \mathbb{N}$.

2.6 IV-PoQ

Definition 2.11 (Inefficient-Verifier Proofs of Quantumness (IV-PoQ) [\[MY24b\]](#page-29-12)). *An IV-PoQ is a tuple* (P, V_1, V_2) *of interactive algorithms.* P *(prover) is QPT,* V_1 *(first verifier) is PPT, and* V_2 *(second verifier) is unbounded. The protocol is divided into two phases. In the first phase,* P *and* V_1 *take the security parameter* 1 *ⁿ as input and interact with each other over a classical channel. Let τ be the transcript, i.e., the sequence of all classical messages exchanged between* P *and* V_1 . In the second phase, V_2 takes 1^n and τ as input and *outputs* ⊤ *(accept) or* ⊥ *(reject). We require the following two properties for some functions c and s such that* $c(n) - s(n) \geq 1/\text{poly}(n)$.

• *c***-completeness:**

$$
\Pr[\top \leftarrow \mathcal{V}_2(1^n, \tau) : \tau \leftarrow \langle \mathcal{P}, \mathcal{V}_1 \rangle(1^n)] \ge c(n) \tag{18}
$$

holds for all sufficiently large $n \in \mathbb{N}$.

• *s***-soundness:** *For any PPT prover* P ∗ *,*

$$
\Pr[\top \leftarrow \mathcal{V}_2(1^n, \tau) : \tau \leftarrow \langle \mathcal{P}^*, \mathcal{V}_1 \rangle(1^n)] \le s(n) \tag{19}
$$

holds for all sufficiently large $n \in \mathbb{N}$.

Theorem 2.12 ([\[MSY24\]](#page-29-9)). *IV-PoQ exist if and only if the QAS/OWF condition is satisfied.*

2.7 Kolmogorov Complexity

We also review some basics of Kolmogorov complexity. For details, see for example [\[LV19\]](#page-29-11). Throughout this paper, we consider a fixed deterministic universal Turing machine *U*.

Definition 2.13 (Kolmogorov Complexity). *The Kolmogorov complexity* K(*x*) *for a string x is defined as*

$$
K(x) := \min_{d \in \{0,1\}^*} \{|d| : x \leftarrow U(d)\}.
$$
 (20)

Definition 2.14 (GapK). *Let* s_1 : \mathbb{N} → \mathbb{N} *and* s_2 : \mathbb{N} → \mathbb{N} *be functions such that* $s_2(n) - s_1(n) > w(\log(n))$ *.* $\mathsf{GapK}[s_1, s_2] \coloneqq (\mathcal{L}_{\mathsf{Yes}}, \mathcal{L}_{\mathsf{No}}) \subseteq \{0, 1\}^*$ is a promise problem whose yes instances are strings x such that $K(x) \leq s_1(|x|)$ *and no instances are strings x such that* $K(x) \geq s_2(|x|)$ *.*

3 Assumptions

In this section, we introduce assumptions.

3.1 Average-Hardness of GapK

We introduce three assumptions on average-hardness of GapK. We first introduce strongly-quantum-averagehardness of GapK as follows.

Assumption 3.1 (Strongly-Quantum-Average-Hardness of GapK[s_1 , s_2]). Let $s_1 : \mathbb{N} \to \mathbb{N}$ and $s_2 : \mathbb{N} \to \mathbb{N}$ N *be polynomial-time-computable functions with* $s_2(n) - s_1(n) > w(\log(n))$ *. There exist an integer k* > 0 *and a QPT algorithm* Q *that outputs n-bit strings on input* 1 *n such that for any QPT algorithm* A*,*

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}] + \Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}] \ge \frac{1}{2} - \frac{1}{n^k} \tag{21}
$$

for all sufficiently large $n \in \mathbb{N}$ *, where* \mathcal{L}_{Yes} *(resp.* \mathcal{L}_{No} *) is the set of yes (resp. no) instances of* $\text{GapK}[s_1, s_2]$ *.*

We next introduce a weaker version as follows where the failure probability is larger than 1*/poly*, not 1*/*2 − 1*/poly*.

Assumption 3.2 (Weakly-Quantum-Average-Hardness of GapK[s_1, s_2]). Let $s_1 : \mathbb{N} \to \mathbb{N}$ and $s_2 : \mathbb{N} \to \mathbb{N}$ *be polynomial-time-computable functions with* $s_2(n) - s_1(n) > w(\log(n))$ *. There exist an integer* $k > 1$ *and a QPT algorithm* Q *that outputs n-bit strings on input* 1 *n such that for any QPT algorithm* A*,*

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}] + \Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}] \ge \frac{1}{n^k} \tag{22}
$$

for all sufficiently large $n \in \mathbb{N}$ *, where* \mathcal{L}_{Yes} *(resp.* \mathcal{L}_{No} *) is the set of yes (resp. no) instances of* GapK[s_1, s_2]*.*

We finally introduce a classical-average-hardness version which is equivalent to Assumption [3.2](#page-12-4) except that the adversary A is PPT, not QPT. (Note that the instance sampling algorithm is still QPT.)

Assumption 3.3 (Weakly-Classical-Average-Hardness of GapK $[s_1, s_2]$ **).** Let $s_1 : \mathbb{N} \to \mathbb{N}$ and $s_2 : \mathbb{N} \to \mathbb{N}$ *be polynomial-time-computable functions with* $s_2(n) - s_1(n) \geq w(\log(n))$ *. There exist an integer* $k > 1$ *and a QPT algorithm* Q *that outputs n-bit strings on input* 1 *n such that for any PPT algorithm* A*,*

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}] + \Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}] \ge \frac{1}{n^k} \tag{23}
$$

for all sufficiently large $n \in \mathbb{N}$ *, where* \mathcal{L}_{Yes} *(resp.* \mathcal{L}_{No} *) is the set of yes (resp. no) instances of* GapK[s_1, s_2]*.*

3.2 Average-Hardness of QPE

We introduce two types of average-hardness of QPE as follows. Assumption [3.4](#page-12-3) is defined against QPT adversaries, while Assumption [3.5](#page-12-5) is defined against PPT adversaries.

Assumption 3.4 (Quantum-Average-Hardness of Quantum Probability Estimation). *There exist a real* $c > 1$, an integer $q > 0$, and a QPT algorithm Q that outputs *n*-bit strings on input 1^n such that, for any *QPT algorithm* Estimate*, we have*

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)} \left[\frac{1}{c} \Pr[x \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(x) \le c \Pr[x \leftarrow \mathcal{Q}(1^n)] \right] \le 1 - \frac{1}{n^q} \tag{24}
$$

for all sufficiently large $n \in \mathbb{N}$ *.*

Assumption 3.5 (Classical-Average-Hardness of Quantum Probability Estimation). *There exist a real* $c > 1$, an integer $q > 0$, and a QPT algorithm Q that outputs *n*-bit strings on input 1^n such that, for any *PPT algorithm* Estimate*, we have*

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)} \left[\frac{1}{c} \Pr[x \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(x) \le c \Pr[x \leftarrow \mathcal{Q}(1^n)] \right] \le 1 - \frac{1}{n^q} \tag{25}
$$

for all sufficiently large $n \in \mathbb{N}$.

4 Results on OWPuzzs and QPRGs

We show the following theorem.

Theorem 4.1. *The following three are equivalent:*

- *OWPuzzs exist.*
- *There exists a real* $0 < \epsilon < 1$ *and a polynomial-time-computable function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.2](#page-12-4) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *.*
- *Assumption [3.4](#page-12-3) holds.*

Theorem [4.1](#page-13-6) follows from the following three Lemmata [4.2](#page-13-1) to [4.4.](#page-13-5)^{[8](#page-13-7)}

Lemma 4.2 ([\[IRS21\]](#page-28-10)). Suppose that there exists a real $0 < \epsilon < 1$ and a polynomial-time-computable *function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.2](#page-12-4) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *. Then, Assumption [3.4](#page-12-3) holds.*

Lemma 4.3. *Assumption [3.4](#page-12-3) implies the existence of OWPuzzs.*

Lemma 4.4. *If OWPuzzs exist, then for all real* $0 < \epsilon < 1$ *, there exists a polynomial-time-computable function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.2](#page-12-4) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *.*

Lemma [4.4](#page-13-5) is obtained by a slight modification of the following theorem.

Theorem 4.5. *If QPRGs exist, then for all real* $0 < \epsilon < 1$ *, there exists a polynomial-time-computable function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.1](#page-12-6) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *.*

In the following subsections, we show them.

4.1 Proof of Lemma [4.2](#page-13-1)

In this subsection, we show Lemma [4.2.](#page-13-1) The proof was essentially given in [\[IRS21\]](#page-28-10), but here we re-provide a proof with stronger parameters, because it is convenient to show Lemma [4.3](#page-13-3) (and also for the convenience of readers).

⁸Lemma [4.2](#page-13-1) was essentially shown in [\[IRS21\]](#page-28-10). Here, we show a slightly stronger version for our purpose.

Proof of Lemma [4.2.](#page-13-1) In the following, for the notational simplicity, we often omit |*y*| of $s(|y|)$ and $\Delta(|y|)$, and just write *s* and ∆, respectively. For contradiction, we assume that Assumption [3.4](#page-12-3) does not follow, and construct a QPT algorithm A that breaks Assumption [3.2.](#page-12-4) For an arbitrary constant $k > 0$, there exists a constant $q > 0$ such that

$$
\frac{1}{n^q} + 2^{-\Delta/3} \le \frac{1}{n^k} \tag{26}
$$

for all sufficiently large $n \in \mathbb{N}$. Because we assume that Assumption [3.4](#page-12-3) does not hold, for any $q > 0$ and for any QPT algorithm Q there exists a QPT algorithm Estimate such that

$$
\Pr_{y \leftarrow \mathcal{Q}(1^n)} \left[\frac{99}{100} \Pr[y \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(y) \le \frac{100}{99} \Pr[y \leftarrow \mathcal{Q}(1^n)] \right] > 1 - \frac{1}{n^q} \tag{27}
$$

for infinitely many $n \in \mathbb{N}$.

Our QPT algorithm A that solves $\text{GapK}[s - \Delta, s]$ is constructed as follows: It receives an instance *y* ← $\mathcal{Q}(1^n)$ and runs Estimate (y) . A outputs yes indicating $y \in \mathcal{L}_{\mathsf{yes}}$ if Estimate $(y) \geq 2^{-s + \Delta/2}$, and outputs no otherwise indicating $y \in \mathcal{L}_{\text{no}}$.

We use the following Claims [4.6](#page-14-0) and [4.7,](#page-14-1) which we will prove later.

Claim 4.6. For all sufficiently large $n \in \mathbb{N}$,

$$
\Pr_{y \leftarrow \mathcal{Q}(1^n)} \left[\Pr[y \leftarrow \mathcal{Q}(1^n)] < \frac{100}{99} \cdot 2^{-s + \Delta/2} \land K(y) \le s - \Delta \right] \le 2^{-\Delta/3}.\tag{28}
$$

Claim 4.7. We have

$$
\Pr_{y \leftarrow \mathcal{Q}(1^n)} \left[\Pr[y \leftarrow \mathcal{Q}(1^n)] \ge \frac{99}{100} \cdot 2^{-s + \Delta/2} \wedge K(y) \ge s \right] = 0 \tag{29}
$$

for all sufficiently large $n \in \mathbb{N}$.

Now, we have

$$
\Pr_{y \leftarrow Q(1^n)}[\text{no} \leftarrow \mathcal{A}(y) \land y \in \mathcal{L}_{\text{Yes}}] + \Pr_{y \leftarrow Q(1^n)}[\text{yes} \leftarrow \mathcal{A}(y) \land y \in \mathcal{L}_{\text{No}}] \tag{30}
$$
\n
$$
= \Pr_{y \leftarrow Q(1^n)}[\text{Estimate}(y) < 2^{-s + \Delta/2} \land K(y) \le s - \Delta] + \Pr_{y \leftarrow Q(1^n)}[\text{Estimate}(y) \ge 2^{-s + \Delta/2} \land K(y) \ge s] \tag{31}
$$

$$
\langle \frac{1}{n^q} + \Pr_{y \leftarrow \mathcal{Q}(1^n)} \left[\Pr[y \leftarrow \mathcal{Q}(1^n)] < \frac{100}{99} \cdot 2^{-s + \Delta/2} \land K(y) \le s - \Delta \right] \tag{32}
$$

$$
+\Pr_{y \leftarrow \mathcal{Q}(1^n)}\left[\Pr[y \leftarrow \mathcal{Q}(1^n)] \ge \frac{99}{100} \cdot 2^{-s + \Delta/2} \wedge K(y) \ge s\right] \tag{33}
$$

$$
\leq \frac{1}{n^q} + 2^{-\Delta/3} \tag{34}
$$

$$
\leq \frac{1}{n^k},\tag{35}
$$

for infinitely many $n \in \mathbb{N}$, where, in the first inequality, we have used Equation [\(27\)](#page-14-2), that is, $\frac{99}{100} \Pr[y \leftarrow Q(1^n)] \le$ Estimate(y) $\leq \frac{100}{99} \Pr[y \leftarrow Q(1^n)]$ with probability at least $1 - \frac{1}{n^q}$ and, in the second inequality, we have used Claims [4.6](#page-14-0) and [4.7.](#page-14-1)

Proof of Claim [4.6.](#page-14-0) Let

$$
\mathsf{Low} := \left\{ y \in \{0, 1\}^n : K(y) \le s - \Delta \text{ and } \Pr[y \leftarrow \mathcal{Q}(1^n)] < \frac{100}{99} 2^{-s + \Delta/2} \right\}. \tag{36}
$$

Because the number of string $y \in \{0,1\}^n$ such that $K(y) \leq s - \Delta$ is at most $2^{s-\Delta+1}$, we have

$$
|\mathsf{Low}| \le 2^{s - \Delta + 1}.\tag{37}
$$

Therefore, we have

$$
\Pr_{y \leftarrow \mathcal{Q}(1^n)}[y \in \text{Low}] = \sum_{y \in \text{Low}} \Pr[y \leftarrow \mathcal{Q}(1^n)] \tag{38}
$$

$$
\leq \sum_{y \in \text{Low}} \frac{100}{99} 2^{-s + \Delta/2} \tag{39}
$$

$$
\leq 2^{s-\Delta+1} \cdot \frac{100}{99} 2^{-s+\Delta/2} \tag{40}
$$

$$
\leq 2^{-\Delta/3} \tag{41}
$$

for all sufficiently large $n \in \mathbb{N}$, which shows the claim.

Proof of Claim [4.7.](#page-14-1) Let

$$
\text{High} := \left\{ y \in \{0, 1\}^n : \Pr[y \leftarrow \mathcal{Q}(1^n)] \ge \frac{99}{100} 2^{-s + \Delta/2} \right\}. \tag{42}
$$

Then, we have $|H$ igh $| \leq \frac{100}{99} 2^{s-\Delta/2}$. There exists a Turing machine M that generates any $y \in H$ igh by specifying the code of $Q, n, \frac{99}{100}2^{-s+\Delta/2}$ $Q, n, \frac{99}{100}2^{-s+\Delta/2}$ $Q, n, \frac{99}{100}2^{-s+\Delta/2}$ and the index *i* of $y \in$ High⁹. The code of Q and M are described by constant bits, *n* and $\frac{100}{99}2^{-s+\Delta/2}$ are described by $O(\log(n))$ bits, and the index *i* of $y \in$ High is described by $(s - \Delta/2 + 1)$ -bits. Therefore, the Kolmogorov complexity of $y \in$ High is at most

$$
O(1) + O(\log(n)) + s - \Delta/2 + 1 \le s - w(\log(n))
$$
\n(43)

for all sufficiently large $n \in \mathbb{N}$. Hence Equation [\(29\)](#page-14-3) is obtained for all sufficiently large $n \in \mathbb{N}$.

 \Box \Box

 \Box

4.2 Proof of Lemma [4.3](#page-13-3)

Proof of Lemma [4.3.](#page-13-3) We show Lemma [4.3](#page-13-3) by showing its contraposition. More precisely, assume that OWPuzzs do not exist. Then, for an arbitrary QPT algorithm Q and arbitrary two constants $c > 1$ and $q > 0$, we construct a QPT algorithm Estimate such that for infinitely many $n \in \mathbb{N}$,

$$
\Pr_{y \leftarrow \mathcal{Q}(1^n)} \left[\frac{1}{c} \Pr[y \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(y) \le c \Pr[y \leftarrow \mathcal{Q}(1^n)] \right] \ge 1 - \frac{1}{n^q}.\tag{44}
$$

⁹An inefficient Turing machine $y \leftarrow M(Q, n, \frac{99}{100}2^{-s+\Delta/2}, i)$ works as follows: For all $y \in \{0, 1\}^n$, M computes $Pr[y \leftarrow Q(1^n)]$ and adds $y \in$ High if $Pr[y \leftarrow Q(1^n)] \ge \frac{99}{100} 2^{-s + \Delta/2}$. M outputs the *i*-th string that belongs to High.

In the following, we often omit 1^n of $\mathcal{Q}(1^n)$. From the assumption that OWPuzzs do not exist and Lemma [2.2,](#page-8-3) there exists a QPT algorithm Ext such that

SD
$$
\left((y_1, ..., y_i)_{(y_1, ..., y_i) \leftarrow Q}, (y_1, ..., y_{i-1}, \text{Ext}(i, y_1, ..., y_{i-1}))_{(y_1, ..., y_{i-1}) \leftarrow Q} \right) \le \frac{1}{n^{50q}}
$$
 (45)

for all $i \in [n]$ and infinitely many $n \in \mathbb{N}$.

We construct Estimate by using the Ext as follows.

Construction of Estimate**:**

- 1. Receive (y_1, \ldots, y_n) as input.
- 2. For each $i \in [n]$, run as follows:
	- Run $b \leftarrow \text{Ext}(i, y_1 \cdots y_{i-1})$ for $n^{100} n^{100q}$ times. Let Count $y_1 \cdots y_{i-1}(b)$ be the number of times that $\text{Ext}(i, y_1 \cdots y_{i-1})$ outputs *b*.
	- Set

$$
\widetilde{p}[y_i] := \frac{\text{Count}_{y_1 \cdots y_{i-1}}(y_i)}{n^{100} n^{100q}}.
$$
\n(46)

3. Output the value of $\prod_{i=1}^{n} \tilde{p}[y_i]$.

In the following, we prove that

$$
\frac{1}{c}\Pr[y \leftarrow \mathcal{Q}] \le \prod_{i=1}^{n} \widetilde{p}[y_i] \le c \cdot \Pr[y \leftarrow \mathcal{Q}] \tag{47}
$$

with high probability over $y \leftarrow \mathcal{D}_n$.

For showing Lemma [4.3,](#page-13-3) we use the following Claims [4.8](#page-16-0) to [4.10,](#page-16-1) which we prove later. Here, $Pr[(y_1, ..., y_{i-1}) \leftarrow Q] = 1$ if *i* = 1.

Claim 4.8. For any real $a > 0$, we have

$$
\Pr_{y \leftarrow Q} \left[\frac{1}{2a} \le \frac{\Pr[(y_1, \dots, y_{i-1}y_i) \leftarrow Q]}{\Pr[(y_1, \dots, y_{i-1}) \leftarrow Q]} \text{ for all } i \in [n] \right] \ge 1 - \frac{n}{a}
$$
\n
$$
(48)
$$

for all $n \in \mathbb{N}$.

Claim 4.9. For any real $b > 0$, we have

$$
\Pr_{y \leftarrow \mathcal{Q}} \left[\left| \Pr[y_i \leftarrow \mathsf{Ext}(i, y_1, ..., y_{i-1})] - \frac{\Pr[(y_1, ..., y_{i-1}y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]} \right| \le b n^{-50q} \text{ for all } i \in [n] \right] \ge 1 - \frac{n}{b} \tag{49}
$$

for infinitely many $n \in \mathbb{N}$.

Claim 4.10. For any real $d > 0$, we have

$$
\Pr\left[|\tilde{p}[y_i] - \Pr[y_i \leftarrow \text{Ext}(i, y_1, ..., y_{i-1})]| \le \frac{1}{d} \text{ for all } i \in [n]\right] \ge 1 - 2n \exp\left\{\frac{-2n^{100 + 100q}}{d^2}\right\} \tag{50}
$$

for all $n \in \mathbb{N}$, where the probability is taken over Estimate(*y*) for computing $\tilde{p}[y_i]$.

We use the claims above by setting $a = n^{q+2}$, $b = n^{q+4}$ and $d = n^{q+4}$. From Claims [4.9](#page-16-2) and [4.10,](#page-16-1) with probability at least $1 - 2n^{-q-3}$, we have

$$
\left| \widetilde{p}[y_i] - \frac{\Pr[(y_1, ..., y_{i-1}y_i) \leftarrow Q]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow Q]} \right| \le 1/d + bn^{-50q} \le 2n^{-q-4}
$$
\n(51)

for all $i \in [n]$. This implies that

$$
\widetilde{p}[y_i] \le \frac{\Pr[(y_1, ..., y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]} \left(1 + 2n^{-q-4} \frac{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_i) \leftarrow \mathcal{Q}]} \right)\right)
$$
\n(52)

with probability at least $1 - 2n^{-q-3}$. Furthermore, from Claim [4.8,](#page-16-0) with probability at least $1 - n^{-q-1}$, we have

$$
\frac{\Pr[(y_1, ..., y_{i-1}) \leftarrow Q]}{\Pr[(y_1, ..., y_{i-1}y_i) \leftarrow Q]} \le 2a = 2n^{q+2}
$$
\n(53)

for all $i \in [n]$. Therefore, with probability at least $1 - 3n^{-q-1}$, we have

$$
\widetilde{p}[y_i] \le \frac{\Pr[(y_1, \ldots, y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \ldots, y_{i-1}) \leftarrow \mathcal{Q}]} \left(1 + \frac{4}{n^2}\right).
$$
\n(54)

Therefore, with probability at least $1 - 3n^{-q-1}$, we have

$$
\prod_{i\in[n]}\widetilde{p}[y_i] \le \prod_{i\in[n]}\left(\frac{\Pr[(y_1,\ldots,y_i)\leftarrow\mathcal{Q}]}{\Pr[(y_1,\ldots,y_{i-1})\leftarrow\mathcal{Q}]} \left(1+\frac{4}{n^2}\right)\right)\tag{55}
$$

$$
= \Pr[(y_1, \ldots, y_n) \leftarrow \mathcal{Q}] \left(1 + \frac{4}{n^2}\right)^n \tag{56}
$$

for infinitely many $n \in \mathbb{N}$.^{[10](#page-17-0)} For any constant $c > 1$, there exists an $n_0 \in \mathbb{N}$ such that

$$
\left(1 + \frac{4}{n^2}\right)^n \le c \tag{57}
$$

for all $n \geq n_0$. Therefore, we have

$$
\prod_{i \in [n]} \widetilde{p}[y_i] \le c \cdot \Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] \tag{58}
$$

for infinitely many $n \in \mathbb{N}$.

In the same way, we can prove that, with probability at least $1 - 3n^{-q-1}$,

$$
\frac{1}{c}\Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] \le \prod_{i \in [n]} \widetilde{p}[y_i]
$$
\n(59)

for infinitely many $n \in \mathbb{N}$ as follows. From Claims [4.9](#page-16-2) and [4.10,](#page-16-1) with probability at least $1 - 2n^{-q-3}$, we have

$$
\frac{\Pr[(y_1, ..., y_i) \leftarrow Q]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow Q]} \left(1 - 2n^{-q-4} \frac{\Pr[(y_1, ..., y_{i-1}) \leftarrow Q]}{\Pr[(y_1, ..., y_i) \leftarrow Q]}\right)\n\leq \tilde{p}[y_i]
$$
\n(60)

¹⁰Remember that Claim [4.9](#page-16-2) satisfied only for infinitely many $n \in \mathbb{N}$.

for infinitely many $n \in \mathbb{N}$ and for all $i \in [n]$. Furthermore, from Claim [4.8,](#page-16-0) with probability at least $1 - n^{-q-1}$, we have

$$
-2n^{q+2} = -2a \le -\frac{\Pr[(y_1, \dots, y_{i-1}) \leftarrow \mathcal{Q}]}{\Pr[(y_1 \cdots y_{i-1} y_i) \leftarrow \mathcal{Q}]}.
$$
(61)

Therefore, with probability at least $1 - 3n^{-q-1}$, we have

$$
\frac{\Pr[(y_1, ..., y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]} \left(1 - \frac{4}{n^2}\right) \le \widetilde{p}[y_i].\tag{62}
$$

Hence, with probability at least $1 - 3n^{-q-1}$, we have

$$
\prod_{i \in [n]} \widetilde{p}[y_i] \ge \prod_{i \in [n]} \left(\frac{\Pr[(y_1, \ldots, y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \ldots, y_{i-1}) \leftarrow \mathcal{Q}]} \left(1 - \frac{4}{n^2} \right) \right) \tag{63}
$$

$$
= \Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] \left(1 - \frac{4}{n^2}\right)^n \tag{64}
$$

for infinitely many $n \in \mathbb{N}$. For any constant $c > 1$, there exists an $n_1 \in \mathbb{N}$ such that

$$
\frac{1}{c} \le \left(1 - \frac{4}{n^2}\right)^n\tag{65}
$$

for all $n \geq n_1$. Therefore, we have, with probability at least $1 - 3n^{-q-1}$

$$
\frac{1}{c}\Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] \le \prod_{i \in [n]} \widetilde{p}[y_i]
$$
\n(66)

for infinitely many $n \in \mathbb{N}$. By combining Equation [\(58\)](#page-17-1) and Equation [\(66\)](#page-18-0), we have that

$$
\frac{1}{c}\Pr[(y_1,\ldots,y_n)\leftarrow \mathcal{Q}] \leq \prod_{i\in[n]}\widetilde{p}[y_i] \leq c\Pr[(y_1,\ldots,y_n)\leftarrow \mathcal{Q}] \tag{67}
$$

with probability at least $1 - 6n^{-q-1}$ (which is larger than $1 - \frac{1}{n^q}$ for sufficiently large $n \in \mathbb{N}$) for infinitely many $n \in \mathbb{N}$, which shows the lemma.

Proof of Claim [4.8.](#page-16-0) This is shown by a standard probabilistic argument. Let

Good :=
$$
\left\{ y \in \{0, 1\}^n : \frac{\Pr[(y_1, ..., y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]} \ge \frac{1}{2a} \text{ for all } i \in [n] \right\},\right\}
$$
 (68)

and let

$$
\text{Bad}_{i} := \left\{ y \in \{0, 1\}^{n} : \frac{\Pr[(y_1, ..., y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, ..., y_{i-1}) \leftarrow \mathcal{Q}]} < \frac{1}{2a} \right\}. \tag{69}
$$

Because

$$
\sum_{y \in \text{Good}} \Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] \ge 1 - \sum_{i \in [n]} \sum_{y \in \text{Bad}_i} \Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}],\tag{70}
$$

it is sufficient to show

$$
\sum_{y \in \text{Bad}_i} \Pr[(y_1, ..., y_n) \leftarrow \mathcal{Q}] < 1/a \tag{71}
$$

for all $i \in [n]$. We have

$$
\sum_{y \in \text{Bad}_i} \Pr[(y_1, \dots, y_n) \leftarrow \mathcal{Q}] = \sum_{y \in \text{Bad}_i} \left(\prod_{j \in [n]} \frac{\Pr[(y_1, \dots, y_j) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \dots, y_{j-1}) \leftarrow \mathcal{Q}]} \right) \right)
$$
(72)

$$
= \sum_{y \in \text{Bad}_i} \left(\prod_{j \in [n] \setminus i} \frac{\Pr[(y_1, \dots, y_j) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \dots, y_{j-1}) \leftarrow \mathcal{Q}]} \right) \cdot \frac{\Pr[(y_1, \dots, y_{i-1}y_i) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \dots, y_{i-1}) \leftarrow \mathcal{Q}]} \tag{73}
$$

$$
\langle \sum_{y \in \text{Bad}_i} \left(\prod_{j \in [n] \setminus i} \frac{\Pr[(y_1 \cdots y_j) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \dots, y_{j-1}) \leftarrow \mathcal{Q}]} \right) \cdot \frac{1}{2a} \tag{74}
$$

$$
\langle \sum_{y \in \{0,1\}^n} \left(\prod_{j \in [n] \setminus i} \frac{\Pr[(y_1, ..., y_j) \leftarrow Q]}{\Pr[(y_1, ..., y_{j-1}) \leftarrow Q]} \right) \cdot \frac{1}{2a} \tag{75}
$$

$$
=\frac{1}{a}.\tag{76}
$$

In the last equation, we have used that

$$
\sum_{y_1,\dots,y_n \in \{0,1\}^n} \left(\prod_{j \in [n] \setminus i} \frac{\Pr[(y_1,\dots,y_j) \leftarrow \mathcal{Q}]}{\Pr[(y_1,\dots,y_{j-1}) \leftarrow \mathcal{Q}]} \right) \right) \tag{77}
$$

$$
= \sum_{y_1,\dots,y_n \in \{0,1\}^n} \frac{\Pr[(y_1,\dots,y_{i-1}) \leftarrow Q]}{\Pr[(y_1,\dots,y_i) \leftarrow Q]} \Pr[(y_1,\dots,y_n) \leftarrow Q] \tag{78}
$$

$$
= \sum_{y_1,\dots,y_n \in \{0,1\}^n} \Pr[(y_1,\dots,y_{i-1}) \leftarrow \mathcal{Q}] \Pr[(y_{i+1},\dots,y_n) \leftarrow \mathcal{Q} | (y_1,\dots,y_i) \leftarrow \mathcal{Q}] \tag{79}
$$

$$
= \sum_{y_1,\dots,y_i \in \{0,1\}^i} \Pr[(y_1,\dots,y_{i-1}) \leftarrow \mathcal{Q}] \tag{80}
$$

$$
=\sum_{y_i \in \{0,1\}} 1\tag{81}
$$

$$
=2.\t(82)
$$

 \Box

Proof of Claim [4.9.](#page-16-2) From the definition of Ext, we have

SD
$$
\left((y_1, ..., y_i)_{(y_1, ..., y_i) \leftarrow Q}, (y_1, ..., y_{i-1}, \text{Ext}(i, y_1, ..., y_{i-1}))_{(y_1, ..., y_{i-1}) \leftarrow Q} \right) \le \frac{1}{n^{50q}}
$$
 (83)

for all $i \in [n]$. This implies that

$$
\sum_{y_1,\dots,y_{i-1}\in\{0,1\}^{i-1}} |\Pr[(y_1,\dots,y_{i-1},1)\leftarrow \mathcal{Q}] - \Pr[(y_1,\dots,y_{i-1})\leftarrow \mathcal{Q}] \Pr[1\leftarrow \text{Ext}(i,y_1,\dots,y_{i-1})]| \quad (84)
$$

$$
= \sum_{y_1,\dots,y_{i-1}\in\{0,1\}^{i-1}} \Pr[(y_1,\dots,y_{i-1}) \leftarrow Q] \cdot \left| \frac{\Pr[(y_1,\dots,y_{i-1},1) \leftarrow Q]}{\Pr[(y_1,\dots,y_{i-1}) \leftarrow Q]} - \Pr[1 \leftarrow \text{Ext}(i,y_1,\dots,y_{i-1})] \right| \right|
$$
\n(85)

$$
= \mathbb{E}_{(y_1,\dots,y_{i-1})\leftarrow \mathcal{Q}}\left[\left|\frac{\Pr[(y_1,\dots,y_{i-1},1)\leftarrow \mathcal{Q}]}{\Pr[(y_1,\dots,y_{i-1})\leftarrow \mathcal{Q}]} - \Pr[1\leftarrow \text{Ext}(i,y_1,\dots,y_{i-1})]\right|\right| \le n^{-50q}
$$
(86)

for all $i \in [n]$. From Markov inequality, for each $i \in [n]$, we have

$$
\Pr_{(y_1,\dots,y_{i-1})\leftarrow Q} \left[\left| \frac{\Pr[(y_1,\dots,y_{i-1},1)\leftarrow Q]}{\Pr[(y_1,\dots,y_{i-1})\leftarrow Q]} - \Pr[1\leftarrow \text{Ext}(i,y_1,\dots,y_{i-1})] \right| \ge bn^{-50q} \right] \le \frac{1}{b}.\tag{87}
$$

Therefore,

$$
\left| \frac{\Pr[(y_1, \ldots, y_{i-1}, 1) \leftarrow \mathcal{Q}]}{\Pr[(y_1, \ldots, y_{i-1}) \leftarrow \mathcal{Q}]} - \Pr[1 \leftarrow \text{Ext}(i, y_1, \ldots, y_{i-1})] \right| \right| \tag{88}
$$

$$
= \left| \frac{\Pr[y_1, \dots, y_{i-1}, 0 \leftarrow \mathcal{Q}]}{\Pr[y_1, \dots, y_{i-1} \leftarrow \mathcal{Q}]} - \Pr[0 \leftarrow \text{Ext}(i, y_1, \dots, y_{i-1})] \right| < b n^{-50q} \tag{89}
$$

 \Box

is satisfied for all $i \in [n]$ with probability at least $1 - \frac{n}{b}$ $\frac{n}{b}$.

Proof of Claim [4.10.](#page-16-1) From the Hoeffding inequality, for each $i \in [n]$,

$$
\Pr_{\widetilde{p}[y_i] \leftarrow \text{Estimate}(y)} \left[|\widetilde{p}[y_i] - \Pr[y_i \leftarrow \text{Ext}(i, y_1, ..., y_{i-1})]| > \frac{1}{d} \right] \le 2 \exp\left(\frac{-2n^{100+100q}}{d^2}\right). \tag{90}
$$

Union bound implies that

$$
\Pr_{\{\widetilde{p}[y_i]\}_{i\in[n]}\leftarrow \text{Estimate}(y)}\left[|\widetilde{p}[y_i] - \Pr[y_i \leftarrow \text{Ext}(i, y_1, \dots, y_{i-1})]\right] > 1/d \text{ for some } i \in [n]\right] \le 2n \exp\left(\frac{-2n^{100+100q}}{d^2}\right). \tag{91}
$$

4.3 Proof of Theorem [4.5](#page-13-4)

Proof of Theorem [4.5.](#page-13-4) Assume that a QPRG exists. Our goal is to show that, for any real $0 < \epsilon < 1$, there exist an integer $k > 0$ and a QPT algorithm Q such that for any QPT algorithm A ,

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}] + \Pr_{x \leftarrow \mathcal{Q}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}] \ge \frac{1}{2} - \frac{1}{n^k} \tag{92}
$$

for all sufficiently large $n \in \mathbb{N}$. Here \mathcal{L}_{Yes} (resp. \mathcal{L}_{No}) is the set of yes (resp. no) instances of GapK[n $n^{\epsilon}, n - \Delta$. Let $\tau \coloneqq \frac{1+\epsilon}{2}$ $\frac{1+\epsilon}{2}$ so that $\epsilon < \tau < 1$. From Lemma [2.4,](#page-9-1) for any real $0 < \epsilon < \tau < 1$, there exists a QPRG Gen such that

$$
SD((x)_{x \leftarrow Gen(1^n)}, (x)_{x \leftarrow \{0,1\}^n}) \ge 1 - 2^{-n^{\tau}}
$$
\n(93)

 $\overline{1}$

for all sufficiently large $n \in \mathbb{N}$. Let Q be a QPT algorithm such that, on input 1^n , it samples $y \leftarrow \{0, 1\}^n$ with probability $1/2$ and $x \leftarrow$ Gen (1^n) with probability $1/2$. We claim that thus defined Q is the desired sampling algorithm. For contradiction, assume that, for any integer $k > 0$, there exists a QPT algorithm A such that

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)}[(\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}) \lor (\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}) \lor (x \notin \mathcal{L}_{\text{yes}} \cup \mathcal{L}_{\text{no}})] > \frac{1}{2} + \frac{1}{n^k} \tag{94}
$$

for infinitely many $n \in \mathbb{N}$. Then, we construct a QPT adversary β that breaks the QPRG Gen as follows: B receives *x*, and runs yes/no $\leftarrow \mathcal{A}(x)$. B outputs 1 if yes $\leftarrow \mathcal{A}(x)$ and outputs 0 otherwise. We use the following Claims [4.11](#page-21-0) and [4.12.](#page-21-1)

Claim 4.11. For any $\Delta(n) = w(\log(n))$, we have

$$
\Pr_{x \leftarrow \{0,1\}^n} [K(x) > n - \Delta] \ge 1 - 2^{-\Delta + 1}.\tag{95}
$$

Claim 4.12. For an arbitrary real $G > 0$, we have

$$
\Pr_{x \leftarrow \text{Gen}(1^n)}[K(x) < n - n^{\tau} + \log(1/G) + O(\log(n))] \ge 1 - \left(G + 2^{-n^{\tau}}\right) \tag{96}
$$

for infinitely many $n \in \mathbb{N}$.

Claims [4.11](#page-21-0) and [4.12](#page-21-1) will be shown later. We use Claim 4.12 by setting $G = 2^{-n^e}$. Hence, we have

$$
1 - 2 \cdot 2^{-n^{\epsilon}} \le \Pr_{x \leftarrow \text{Gen}(1^n)} [K(x) < n - n^{\tau} + n^{\epsilon} + O(\log(n))]
$$
\n(97)

$$
\leq \Pr_{x \leftarrow \text{Gen}(1^n)} [K(x) < n - 3n^{\epsilon} + n^{\epsilon} + O(\log(n))] \tag{98}
$$

$$
\leq \Pr_{x \leftarrow \text{Gen}(1^n)} [K(x) < n - n^{\epsilon}] \tag{99}
$$

for infinitely many $n \in \mathbb{N}$. From Claims [4.11](#page-21-0) and [4.12](#page-21-1) and Equation [\(94\)](#page-21-2), we have

$$
\frac{1}{2} + \frac{1}{n^k} < \Pr_{x \leftarrow \mathcal{Q}(1^n)} \left[(\text{yes} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{Yes}}) \lor (\text{no} \leftarrow \mathcal{A}(x) \land x \in \mathcal{L}_{\text{No}}) \lor (x \notin \mathcal{L}_{\text{yes}} \cup \mathcal{L}_{\text{no}}) \right] \tag{100}
$$

$$
\langle \frac{1}{2} \left(\Pr_{x \leftarrow \text{Gen}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x)] + \Pr_{x \leftarrow \{0,1\}^n}[\text{no} \leftarrow \mathcal{A}(x)] + 2 \cdot 2^{-n^{\epsilon}} + 2^{-\Delta + 1} \right) \tag{101}
$$

$$
\leq \frac{1}{2} \left(\Pr_{x \leftarrow \text{Gen}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x)] + 1 - \Pr_{x \leftarrow \{0,1\}^n}[\text{yes} \leftarrow \mathcal{A}(x)] + 2 \cdot 2^{-n^{\epsilon}} + 2^{-\Delta + 1} \right) \right) \tag{102}
$$

for infinitely many $n \in \mathbb{N}$. This implies that

$$
\frac{2}{n^k} - 2 \cdot 2^{-n^{\epsilon}} - 2^{-\Delta + 1} < \Pr_{x \leftarrow \text{Gen}(1^n)}[\text{yes} \leftarrow \mathcal{A}(x)] - \Pr_{x \leftarrow \{0,1\}^n}[\text{yes} \leftarrow \mathcal{A}(x)]. \tag{103}
$$

This implies that, for some polynomial *q*,

$$
\left| \Pr_{x \leftarrow \text{Gen}(1^n)}[1 \leftarrow \mathcal{B}(1^n, x)] - \Pr_{x \leftarrow \{0, 1\}^n}[1 \leftarrow \mathcal{B}(1^n, x)] \right| \ge \frac{1}{q(n)} \right| \tag{104}
$$

for infinitely many $n \in \mathbb{N}$. This is the contradiction.

Proof of Claim 4.11. The number of string $y \in \{0,1\}^n$ such that $K(y) \leq n - \Delta$ is at most $2^{n-\Delta+1}$. Therefore, we have

$$
\Pr_{x \leftarrow \{0,1\}^n} [K(x) \le n - \Delta] \le \frac{2^{n - \Delta + 1}}{2^n} = 2^{-\Delta + 1}.
$$
\n(105)

 \Box

Proof of Claim [4.12.](#page-21-1) We define the following sets.

$$
A := \{x \in \{0, 1\}^n : \Pr[x \leftarrow \text{Gen}(1^n)] < 2^{-n}\}\tag{106}
$$

$$
B := \{ x \in \{0, 1\}^n : 2^{-n} \le \Pr[x \leftarrow \text{Gen}(1^n)] < G \cdot 2^{-n + n^{\tau}} \} \tag{107}
$$

$$
C := \{ x \in \{0, 1\}^n : G \cdot 2^{-n + n^{\tau}} \le \Pr[x \leftarrow \text{Gen}(1^n)] \le 1 \}. \tag{108}
$$

From Equation (93) , we have

$$
1 - 2^{-n^{T}} \le \sum_{x \in A} (\Pr[x \leftarrow \{0, 1\}^{n}] - \Pr[x \leftarrow \text{Gen}(1^{n})]) \tag{109}
$$

$$
=\sum_{x\in A} (2^{-n}-\Pr[x\leftarrow \text{Gen}(1^n)])\tag{110}
$$

$$
\leq 2^{-n}|A|.\tag{111}
$$

This implies that

$$
|B| + |C| \le 2^{n-n^{\tau}}.
$$
\n(112)

Furthermore, we have

$$
1 - 2^{-n^{T}} \le \sum_{x \in B} (\Pr[x \leftarrow \text{Gen}(1^{n})] - 2^{-n}) + \sum_{x \in C} (\Pr[x \leftarrow \text{Gen}(1^{n})] - 2^{-n}) \tag{113}
$$

$$
\leq \sum_{x \in B} G \cdot 2^{-n+n^{\tau}} + \sum_{x \in C} \Pr[x \leftarrow \text{Gen}(1^n)] \tag{114}
$$

$$
\leq |B|G \cdot 2^{-n+n^{\tau}} + \sum_{x \in C} \Pr[x \leftarrow \text{Gen}(1^n)]. \tag{115}
$$

This and Equation [\(112\)](#page-22-0) implies that

$$
1 - G - 2^{-n^{\tau}} \le \sum_{x \in C} \Pr[x \leftarrow \text{Gen}(1^n)]. \tag{116}
$$

Now, the remaining part is to show that

$$
K(x) < n - n^{\tau} + \log(1/G) + O(\log(n))\tag{117}
$$

for all $x \in C$. There exists a Turing machine M such that it generates $x \in C$ by taking as input the Gen, *n*, 1 $\frac{1}{G} \cdot 2^{n-n^{\tau}}$ and the index *i* of $x \in C$. ^{[11](#page-23-4)} Therefore, $K(x)$ is upper bounded by

$$
O(1) + O(\log(n)) + \log\left(\frac{1}{G} \cdot 2^{n - n^{\tau}}\right) \le n - n^{\tau} + \log(1/G) + O(\log(n))\tag{118}
$$

for all sufficiently large $n \in \mathbb{N}$.

 \Box

 \Box

4.4 Proof of Lemma [4.4](#page-13-5)

We can show Lemma [4.4](#page-13-5) in the almost same way as Theorem [4.5](#page-13-4) by considering nuQPRGs instead of QPRGs. Therefore, instead of re-providing the proof, we briefly explain the difference.

In the proof of Theorem [4.5,](#page-13-4) we consider QPRGs $Gen(1^n)$ given in Lemma [2.4](#page-9-1) and construct a QPT algorithm Q such that, on input 1^n , it outputs $y \leftarrow$ Gen (1^n) with probability $1/2$ and $y \leftarrow \{0, 1\}^n$ with probability 1/2. We showed the strongly quantum hardness of GapK over $x \leftarrow Q$ by using the fact that *K*(*x*) is sufficiently small with overwhelming probability over the distribution $x \leftarrow$ Gen(1^{*n*})</sub> when Gen(1^{*n*}) is exponentially far from the uniform distribution.

For the proof of Lemma [4.4,](#page-13-5) we consider nuQPRGs $Gen(1^n, \mu)$ given in Lemma [2.7](#page-10-2) instead of considering QPRGs. Then, we construct a QPT algorithm Q that, on input 1^n , samples $\mu^* \leftarrow [n]$, and outputs $y \leftarrow$ Gen($1^n, \mu^*$) with probability $1/2$ and $y \leftarrow \{0, 1\}^n$ with probability $1/2$. Now, we have $K(x)$ is sufficiently small with overwhelming probability over the distribution $x \leftarrow$ Gen $(1^n, \mu^*)$. Furthermore, such μ^* is sampled with probability $1/n$. Therefore, we can show the weakly-quantum-average-hardness of GapK over $x \leftarrow Q$.

5 Results on IV-PoQ

Theorem 5.1. *If there exists a real* $0 < \epsilon < 1$ *and a polynomial-time-computable function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.3](#page-12-7) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *, then the QAS/OWF condition holds.*

This theorem is obtained from the following lemmas.^{[12](#page-23-5)}

Lemma 5.2 ([\[IRS21\]](#page-28-10)). Suppose that there exists a real $0 < \epsilon < 1$ and a polynomial-time-computable *function* $\Delta(n) = w(\log(n))$ *such that Assumption* [3.3](#page-12-7) *holds with* $s_1 = n - n^{\epsilon}$ *and* $s_2 = n - \Delta$ *. Then, Assumption [3.5](#page-12-5) holds.*

Lemma 5.3. *Assumption [3.5](#page-12-5) implies the QAS/OWF condition.*

5.1 Proof of Lemma [5.3](#page-23-2)

Proof of Lemma [5.3.](#page-23-2) For contradiction, suppose that the QAS/OWF condition is not satisfied. Our goal is to show that for any real $c > 1$, integer $q > 0$, and QPT algorithm Q , there exists a PPT algorithm Estimate

^{*n*}A Turing machine *y* ← *M* (Gen, *n*, $\frac{1}{G}2^{n-n^{\tau}}$, *i*) works as follows: For all *y* ∈ {0, 1}^{*n*}, *M* computes Pr[*y* ← Gen(1^{*n*})] and adds *y* ∈ High if $Pr[y \leftarrow Gen(1^n)] \ge G \cdot 2^{-n+n^{\tau}}$. *M* outputs the *i*-th string that belongs to High.

 $12A$ proof of Lemma [5.2](#page-23-6) is almost the same as that of Lemma [4.2,](#page-13-1) which is a slighly stonger version of $[IRS21]$, and therefore we omit its proof.

such that

$$
\Pr_{x \leftarrow \mathcal{Q}(1^n)} \left[\frac{1}{c} \Pr[x \leftarrow \mathcal{Q}(1^n)] \le \text{Estimate}(x) \le c \Pr[x \leftarrow \mathcal{Q}(1^n)] \right] \ge 1 - \frac{1}{n^q} \tag{119}
$$

for infinitely many $n \in \mathbb{N}$.

From the assumption that the QAS/OWF condition is not satisfied and Lemma [2.10,](#page-11-2) for any real $k > 0$, there exists a PPT algorithm S such that

$$
SD((x)_{x \leftarrow \mathcal{Q}(1^n)}, \mathcal{S}(1^n; r)_{r \leftarrow \{0,1\}^{t(n)}}) \le \frac{1}{n^k}
$$
\n(120)

for infinitely many $n \in \mathbb{N}$. Here $t(n)$ is the length of the random seed of $\mathcal{S}(1^n)$. Let Σ be the set of such n . For each $n \in \mathbb{N}$, define a function $f_n: \{0,1\}^{m(n)} \to \{0,1\}^*$ as follows:

- 1. Receive $(r, i) \in \{0, 1\}^{t(n)} \times [n-1]$ as input.^{[13](#page-24-0)}
- 2. Compute $x = \mathcal{S}(1^n; r)$.
- 3. Output *i* and the first *i* bits, x_1, \ldots, x_i , of x .

From Lemma [2.10,](#page-11-2) there exists a PPT algorithm R such that

$$
\text{SD}\left(\left\{(r,i), f_n(r,i)\right\}_{r \leftarrow \{0,1\}^{t(n)}, i \leftarrow [n-1]}, \left\{\mathcal{R}(1^{m(n)}, f_n(r,i)), f_n(r,i)\right\}_{r \leftarrow \{0,1\}^{t(n)}, i \leftarrow [n-1]}\right) \le \frac{1}{n^k} \tag{121}
$$

for all $n \in \Sigma$.

Now, we define the following PPT algorithm, Ext, as follows:

- 1. Receive 1^n , $i \in [n-1]$, and $(y_1, ..., y_i) \in \{0, 1\}^i$ as input.
- 2. Run $(r', i') \leftarrow \mathcal{R}(1^{m(n)}, i, y_1, ..., y_i)$.
- 3. Run $x = \mathcal{S}(1^n; r')$, and output x_{i+1} .

We claim that Ext satisfies

$$
SD((x_1, ..., x_{i+1}) \leftarrow \mathcal{S}(1^n), (x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i))_{x_1, ..., x_i \leftarrow \mathcal{S}(1^n)}) < \frac{1}{n^{k-1}} \tag{122}
$$

¹³Actually, the integer *i* is encoded into a bit string. If the input bit string corresponds to an integer that is outside of $[n-1]$, f_n outputs just 0.

for all $i \in [n-1]$ and all $n \in \Sigma$. This is shown as follows.

$$
\frac{1}{n^k} \geq \text{SD}\left(\{(r,i), f_n(r,i)\}_{r \leftarrow \{0,1\}^{t(n)}, i \leftarrow [n-1]}, \{\mathcal{R}(1^{m(n)}, f_n(r,i)), f_n(r,i)\}_{r \leftarrow \{0,1\}^{t(n)}, i \leftarrow [n-1]}\right) \tag{123}
$$

$$
= SD\left(\{(r,i),(i,x_1,...,x_i)\}_{i \leftarrow [n-1], r \leftarrow \{0,1\}^{t(n)},(x_1,...,x_i) = S(1^n;r)},\right.\right.\tag{124}
$$

$$
\{\mathcal{R}(1^{m(n)}, (i, x_1, ..., x_i)), (i, x_1, ..., x_i)\}_{i \leftarrow [n-1], r \leftarrow \{0,1\}^{t(n)}, (x_1, ..., x_i) = \mathcal{S}(1^n; r)\}\
$$
\n
$$
\geq \text{SD}\left(\{(r, i), (i, x_1, ..., x_i), x_{i+1}\}_{i \leftarrow [n-1], r \leftarrow \{0,1\}^{t(n)}, (x_1, ..., x_i) = \mathcal{S}(1^n; r)\right)}\tag{126}
$$

$$
\geq SD\left(\{(r,i),(i,x_1,...,x_i),x_{i+1}\}_{i\leftarrow [n-1],r\leftarrow \{0,1\}^{t(n)},(x_1,...,x_i)=\mathcal{S}(1^n;r)},\right.\tag{126}
$$
\n
$$
\left(\mathcal{P}(1^{m(n)}\ (i,x_1,...,x_i))\ (i,x_1,...,x_i)\ \mathbf{Ext}(1^n\ i,x_1,...,x_i)\right)
$$

$$
\{\mathcal{R}(1^{m(n)}, (i, x_1, \ldots, x_i)), (i, x_1, \ldots, x_i), \text{Ext}(1^n, i, x_1, \ldots, x_i)\}_{i \leftarrow [n-1], r \leftarrow \{0, 1\}^{t(n)}, (x_1, \ldots, x_i) = \mathcal{S}(1^n; r)\}\tag{127}
$$

$$
\geq SD\left(\{i, x_1, ..., x_i, x_{i+1}\}_{i \leftarrow [n-1], (x_1, ..., x_i, x_{i+1})\leftarrow \mathcal{S}(1^n)},\right.\right.\tag{128}
$$

$$
\{i, x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i)\}_{i \leftarrow [n-1], (x_1, ..., x_i) \leftarrow \mathcal{S}(1^n)}\bigg)
$$
\n(129)

$$
\geq \frac{1}{n-1} \sum_{i=1}^{n} SD\left(\{x_1, ..., x_i, x_{i+1}\}_{(x_1, ..., x_i, x_{i+1}) \leftarrow \mathcal{S}(1^n)},\right.\tag{130}
$$

$$
\{x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i)\}_{(x_1, ..., x_i) \leftarrow \mathcal{S}(1^n)}\bigg). \tag{131}
$$

Then we claim that

$$
SD((x_1, ..., x_{i+1}) \leftarrow \mathcal{Q}(1^n), (x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i))_{x_1, ..., x_i \leftarrow \mathcal{Q}(1^n)}) < \frac{1}{n^{k-2}} \tag{132}
$$

for all $i \in [n-1]$ and all $n \in \Sigma$. This is shown as follows from the triangle inequality, Equation [\(122\)](#page-24-1), and Equation [\(120\)](#page-24-2).

$$
SD((x_1, ..., x_{i+1}) \leftarrow Q(1^n), (x_1, ..., x_i, Ext(1^n, i, x_1, ..., x_i))_{x_1, ..., x_i} \leftarrow Q(1^n))
$$
\n(133)

$$
\langle SD((x_1, ..., x_{i+1}) \leftarrow \mathcal{Q}(1^n), (x_1, ..., x_{i+1}) \leftarrow \mathcal{S}(1^n))
$$
\n(134)

$$
+\text{SD}((x_1,...,x_{i+1}) \leftarrow \mathcal{S}(1^n), (x_1,...,x_i, \text{Ext}(1^n, i, x_1,...,x_i))_{x_1,...,x_i \leftarrow \mathcal{S}(1^n)})
$$
(135)

$$
+\text{SD}((x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i))_{x_1, ..., x_i \leftarrow \mathcal{S}(1^n)}, (x_1, ..., x_i, \text{Ext}(1^n, i, x_1, ..., x_i))_{x_1, ..., x_i \leftarrow \mathcal{Q}(1^n)})
$$
\n(136)

$$
\leq \frac{1}{n^k} + \frac{1}{n^{k-1}} + \frac{1}{n^k} \tag{137}
$$

$$
\leq \frac{1}{n^{k-2}}.\tag{138}
$$

By using Ext, we construct a PPT algorithm Estimate as follows:

- 1. Receive $(y_1, ..., y_n) \in \{0, 1\}^n$ as input.
- 2. For each $i \in [n]$, run as follows:
	- Run $b \leftarrow \text{Ext}(i, y_1 \cdots y_{i-1})$ for $n^{100} n^{100q}$ times. Let Count $y_1 \cdots y_{i-1}(b)$ be the number of times that $\text{Ext}(i, y_1 \cdots y_{i-1})$ outputs *b*.
	- Set

$$
\widetilde{p}[y_i] \coloneqq \frac{\text{Count}_{y_1 \cdots y_{i-1}}(y_i)}{n^{100} n^{100q}}.
$$
\n(139)

3. Output the value of $\prod_{i=1}^{n} \tilde{p}[y_i]$.

The analysis of Estimate is almost the same as Lemma [4.3,](#page-13-3) and therefore we omit it.

Acknowledgements. TH is supported by JSPS research fellowship and by JSPS KAKENHI No. JP22J21864. TM is supported by JST CREST JPMJCR23I3, JST Moonshot R&D JPMJMS2061-5-1-1, JST FOREST, MEXT QLEAP, the Grant-in Aid for Transformative Research Areas (A) 21H05183, and the Grant-in-Aid for Scientific Research (A) No.22H00522.

References

- [AA11] Scott Aaronson and Alex Arkhipov. The computational complexity of linear optics. In Lance Fortnow and Salil P. Vadhan, editors, *43rd ACM STOC*, pages 333–342. ACM Press, June 2011. (Cited on page [2,](#page-3-0) [4.](#page-5-1))
- [Aar10] Scott Aaronson. BQP and the polynomial hierarchy. In Leonard J. Schulman, editor, *42nd ACM STOC*, pages 141–150. ACM Press, June 2010. (Cited on page [2.](#page-3-0))
- [AC17] Scott Aaronson and Lijie Chen. Complexity-theoretic foundations of quantum supremacy experiments. CCC'17: Proceedings of the 32nd Computational Complexity Conference, 2017. (Cited on page [2.](#page-3-0))
- [ACC⁺23] Atul Singh Arora, Andrea Coladangelo, Matthew Coudron, Alexandru Gheorghiu, Uttam Singh, and Hendrik Waldner. Quantum depth in the random oracle model. In Barna Saha and Rocco A. Servedio, editors, *55th ACM STOC*, pages 1111–1124. ACM Press, June 2023. (Cited on page [2.](#page-3-0))
- [ADMP20] Navid Alamati, Luca De Feo, Hart Montgomery, and Sikhar Patranabis. Cryptographic group actions and applications. In Shiho Moriai and Huaxiong Wang, editors, *ASIACRYPT 2020, Part II*, volume 12492 of *LNCS*, pages 411–439. Springer, Cham, December 2020. (Cited on page [1.](#page-2-5))
- [AG19] Scott Aaronson and Sam Gunn. On the classical hardness of spoofing linear cross-entropy benchmarking. *arXiv:1910.12085*, 2019. (Cited on page [2.](#page-3-0))
- [AGQY22] Prabhanjan Ananth, Aditya Gulati, Luowen Qian, and Henry Yuen. Pseudorandom (functionlike) quantum state generators: New definitions and applications. In Eike Kiltz and Vinod Vaikuntanathan, editors, *TCC 2022, Part I*, volume 13747 of *LNCS*, pages 237–265. Springer, Cham, November 2022. (Cited on page [1.](#page-2-5))
- [Ajt96] Miklós Ajtai. Generating hard instances of lattice problems (extended abstract). In *28th ACM STOC*, pages 99–108. ACM Press, May 1996. (Cited on page [1.](#page-2-5))
- [AQY22] Prabhanjan Ananth, Luowen Qian, and Henry Yuen. Cryptography from pseudorandom quantum states. In Yevgeniy Dodis and Thomas Shrimpton, editors, *CRYPTO 2022, Part I*, volume 13507 of *LNCS*, pages 208–236. Springer, Cham, August 2022. (Cited on page [1.](#page-2-5))
- [BCKM21] James Bartusek, Andrea Coladangelo, Dakshita Khurana, and Fermi Ma. One-way functions imply secure computation in a quantum world. In Tal Malkin and Chris Peikert, editors, *CRYPTO 2021, Part I*, volume 12825 of *LNCS*, pages 467–496, Virtual Event, August 2021. Springer, Cham. (Cited on page [1,](#page-2-5) [2.](#page-3-0))
- [BCM+21] Zvika Brakerski, Paul Christiano, Urmila Mahadev, Umesh Vazirani, and Thomas Vidick. A cryptographic test of quantumness and certifiable randomness from a single quantum device. *Journal of the ACM*, 68(5):31:1–31:47, 2021. (Cited on page [2.](#page-3-0))
- [BCQ23] Zvika Brakerski, Ran Canetti, and Luowen Qian. On the computational hardness needed for quantum cryptography. In Yael Tauman Kalai, editor, *14th Innovations in Theoretical Computer Science Conference, ITCS 2023, January 10-13, 2023, MIT, Cambridge, Massachusetts, USA*, volume 251 of *LIPIcs*, pages 24:1–24:21. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2023. (Cited on page [1,](#page-2-5) [2.](#page-3-0))
- [BFNV19] Adam Bouland, Bill Fefferman, Chinmay Nirkhe, and Umesh Vazirani. On the complexity and verification of quantum random circuit sampling. *Nature Physics*, 15:159–163, 2019. (Cited on page [2.](#page-3-0))
- [BJ24] Rishabh Batra and Rahul Jain. Commitments are equivalent to statistically-verifiable one-way state generators, 2024. (Cited on page [2.](#page-3-0))
- [BJS11] Michael J. Bremner, Richard Jozsa, and Dan J. Shepherd. Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 467:459–472, 2011. (Cited on page [2.](#page-3-0))
- [BMS16] Michael J. Bremner, Ashley Montanaro, and Dan J. Shepherd. Average-case complexity versus approximate simulation of commuting quantum computations. *Physical Review Letters*, 117:080501, 2016. (Cited on page [2,](#page-3-0) [4.](#page-5-1))
- [BY91] Gilles Brassard and Moti Yung. One-way group actions. In Alfred J. Menezes and Scott A. Vanstone, editors, *CRYPTO'90*, volume 537 of *LNCS*, pages 94–107. Springer, Berlin, Heidelberg, August 1991. (Cited on page [1.](#page-2-5))
- [CGG24] Kai-Min Chung, Eli Goldin, and Matthew Gray. On central primitives for quantum cryptography with classical communication. In Leonid Reyzin and Douglas Stebila, editors, *CRYPTO 2024, Part VII*, volume 14926 of *LNCS*, pages 215–248. Springer, Cham, August 2024. (Cited on page [4,](#page-5-1) [5,](#page-6-3) [6,](#page-7-1) [7,](#page-8-4) [8,](#page-9-2) [9.](#page-10-3))
- [CGGH24] Bruno P. Cavalar, Eli Goldin, Matthew Gray, and Peter Hall. A meta-complexity characterization of quantum cryptography, 2024. (Cited on page , [1,](#page-2-5) [4,](#page-5-1) [6,](#page-7-1) [7.](#page-8-4))
- [Cha69] Gregory J. Chaitin. On the simplicity and speed of programs for computing infinite sets of natural numbers. *J. ACM*, 16(3):407–422, July 1969. (Cited on page [2.](#page-3-0))
- [Cou06] Jean-Marc Couveignes. Hard homogeneous spaces. Cryptology ePrint Archive, Paper 2006/291, 2006. (Cited on page [1.](#page-2-5))
- [DH76] Whitfield Diffie and Martin E. Hellman. New directions in cryptography. *IEEE Transactions on Information Theory*, 22(6):644–654, 1976. (Cited on page [1.](#page-2-5))
- [FKM+18] Keisuke Fujii, Hirotada Kobayashi, Tomoyuki Morimae, Harumichi Nishimura, Seiichiro Tani, and Shuhei Tamate. Impossibility of classically simulating one-clean-qubit model with multiplicative error. *Physical Review Letters*, 120:200502, 2018. (Cited on page [2.](#page-3-0))
- [GGM84] Oded Goldreich, Shafi Goldwasser, and Silvio Micali. On the cryptographic applications of random functions. In G. R. Blakley and David Chaum, editors, *CRYPTO'84*, volume 196 of *LNCS*, pages 276–288. Springer, Berlin, Heidelberg, August 1984. (Cited on page [1.](#page-2-5))
- [GGM86] Oded Goldreich, Shafi Goldwasser, and Silvio Micali. How to construct random functions. *Journal of the ACM*, 33(4):792–807, 1986. (Cited on page [1.](#page-2-5))
- [GLSV21] Alex B. Grilo, Huijia Lin, Fang Song, and Vinod Vaikuntanathan. Oblivious transfer is in MiniQCrypt. In Anne Canteaut and François-Xavier Standaert, editors, *EUROCRYPT 2021,* Part II, volume 12697 of *LNCS*, pages 531–561. Springer, Cham, October 2021. (Cited on page [1,](#page-2-5) [2.](#page-3-0))
- [GM84] Shafi Goldwasser and Silvio Micali. Probabilistic encryption. *J. Comput. Syst. Sci.*, 28:270–299, 1984. (Cited on page [1.](#page-2-5))
- [HILL99] Johan Håstad, Russell Impagliazzo, Leonid A. Levin, and Michael Luby. A pseudorandom generator from any one-way function. *SIAM Journal on Computing*, 28(4):1364–1396, 1999. (Cited on page [1.](#page-2-5))
- [IL89] Russell Impagliazzo and Michael Luby. One-way functions are essential for complexity based cryptography (extended abstract). In *30th FOCS*, pages 230–235. IEEE Computer Society Press, October / November 1989. (Cited on page [1.](#page-2-5))
- [IRS21] Rahul Ilango, Hanlin Ren, and Rahul Santhanam. Hardness on any samplable distribution suffices: New characterizations of one-way functions by meta-complexity. *Electron. Colloquium Comput. Complex.*, TR21-082, 2021. (Cited on page [1,](#page-2-5) [2,](#page-3-0) [5,](#page-6-3) [12,](#page-13-8) [22.](#page-23-7))
- [JLS18] Zhengfeng Ji, Yi-Kai Liu, and Fang Song. Pseudorandom quantum states. In Hovav Shacham and Alexandra Boldyreva, editors, *CRYPTO 2018, Part III*, volume 10993 of *LNCS*, pages 126–152. Springer, Cham, August 2018. (Cited on page [1.](#page-2-5))
- [JQSY19] Zhengfeng Ji, Youming Qiao, Fang Song, and Aaram Yun. General linear group action on tensors: A candidate for post-quantum cryptography. In Dennis Hofheinz and Alon Rosen, editors, *TCC 2019, Part I*, volume 11891 of *LNCS*, pages 251–281. Springer, Cham, December 2019. (Cited on page [1.](#page-2-5))
- [Kol68] Andrey Kolmogorov. Three approaches to the quantitative definition of information. *International Journal of Computer Mathematics*, 2:157–168, 1968. (Cited on page [2.](#page-3-0))
- [KQST23] William Kretschmer, Luowen Qian, Makrand Sinha, and Avishay Tal. Quantum cryptography in algorithmica. In Barna Saha and Rocco A. Servedio, editors, *55th ACM STOC*, pages 1589–1602. ACM Press, June 2023. (Cited on page [1.](#page-2-5))
- [Kre21] William Kretschmer. Quantum Pseudorandomness and Classical Complexity. In Min-Hsiu Hsieh, editor, *16th Conference on the Theory of Quantum Computation, Communication and Cryptography (TQC 2021)*, volume 197 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 2:1–2:20, Dagstuhl, Germany, 2021. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. (Cited on page [1.](#page-2-5))
- [KT24a] Dakshita Khurana and Kabir Tomer. Commitments from quantum one-wayness. In Bojan Mohar, Igor Shinkar, and Ryan O'Donnell, editors, *56th ACM STOC*, pages 968–978. ACM Press, June 2024. (Cited on page [1,](#page-2-5) [2,](#page-3-0) [4,](#page-5-1) [5,](#page-6-3) [7,](#page-8-4) [9.](#page-10-3))
- [KT24b] Dakshita Khurana and Kabir Tomer. Founding quantum cryptography on quantum advantage, or, towards cryptography from #P-hardness. Cryptology ePrint Archive, Paper 2024/1490, 2024. (Cited on page, $1, 3, 4, 6$ $1, 3, 4, 6$ $1, 3, 4, 6$ $1, 3, 4, 6$ $1, 3, 4, 6$ $1, 3, 4, 6$.)
- [LMW24] Alex Lombardi, Fermi Ma, and John Wright. A one-query lower bound for unitary synthesis and breaking quantum cryptography. In Bojan Mohar, Igor Shinkar, and Ryan O'Donnell, editors, *56th ACM STOC*, pages 979–990. ACM Press, June 2024. (Cited on page [1.](#page-2-5))
- [LP20] Yanyi Liu and Rafael Pass. On one-way functions and kolmogorov complexity. In *61st FOCS*, pages 1243–1254. IEEE Computer Society Press, November 2020. (Cited on page [1.](#page-2-5))
- [LV19] Ming Li and Paul Vitányi. *An Introduction to Kolmogorov Complexity and Its Applications*. Texts in Computer Science. Springer Cham, 4th edition, 2019. (Cited on page [2,](#page-3-0) [10.](#page-11-3))
- [MH24] Fermi Ma and Hsin-Yuan Huang. How to construct random unitaries. Cryptology ePrint Archive, Paper 2024/1652, 2024. (Cited on page [1.](#page-2-5))
- [MSY24] Tomoyuki Morimae, Yuki Shirakawa, and Takashi Yamakawa. Cryptographic characterization of quantum advantage. arXiv:2410.00499, 2024. (Cited on page [2,](#page-3-0) [4,](#page-5-1) [6,](#page-7-1) [9,](#page-10-3) [10.](#page-11-3))
- [MY22] Tomoyuki Morimae and Takashi Yamakawa. Quantum commitments and signatures without one-way functions. In Yevgeniy Dodis and Thomas Shrimpton, editors, *CRYPTO 2022, Part I*, volume 13507 of *LNCS*, pages 269–295. Springer, Cham, August 2022. (Cited on page [1,](#page-2-5) [2.](#page-3-0))
- [MY24a] Tomoyuki Morimae and Takashi Yamakawa. One-wayness in quantum cryptography. In Frédéric Magniez and Alex Bredariol Grilo, editors, *19th Conference on the Theory of Quantum Computation, Communication and Cryptography, TQC 2024, September 9-13, 2024, Okinawa, Japan*, volume 310 of *LIPIcs*, pages 4:1–4:21. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2024. (Cited on page [1,](#page-2-5) [2.](#page-3-0))
- [MY24b] Tomoyuki Morimae and Takashi Yamakawa. Quantum advantage from one-way functions. In Leonid Reyzin and Douglas Stebila, editors, *CRYPTO 2024, Part V*, volume 14924 of *LNCS*, pages 359–392. Springer, Cham, August 2024. (Cited on page [2,](#page-3-0) [10.](#page-11-3))
- [Nao90] Moni Naor. Bit commitment using pseudo-randomness. In Gilles Brassard, editor, *CRYPTO'89*, volume 435 of *LNCS*, pages 128–136. Springer, New York, August 1990. (Cited on page [1.](#page-2-5))
- [Rom90] John Rompel. One-way functions are necessary and sufficient for secure signatures. In *22nd ACM STOC*, pages 387–394. ACM Press, May 1990. (Cited on page [1.](#page-2-5))
- [Sho94] Peter W. Shor. Algorithms for quantum computation: Discrete logarithms and factoring. In *35th FOCS*, pages 124–134. IEEE Computer Society Press, November 1994. (Cited on page [2.](#page-3-0))
- [Sol64] Ray R. Solomonoff. A formal theory of inductive inference. part i. *Information and Control*, 7:1–22, 1964. (Cited on page [2.](#page-3-0))
- [TD04] B. M. Terhal and D. P. DiVincenzo. Adaptive quantum computation, constant-depth circuits and arthur-merlin games. *Quant. Inf. Comput.*, 4(2):134–145, 2004. (Cited on page [2.](#page-3-0))
- [Yan22] Jun Yan. General properties of quantum bit commitments (extended abstract). In Shweta Agrawal and Dongdai Lin, editors, *ASIACRYPT 2022, Part IV*, volume 13794 of *LNCS*, pages 628–657. Springer, Cham, December 2022. (Cited on page [1.](#page-2-5))
- [YZ24] Takashi Yamakawa and Mark Zhandry. Verifiable quantum advantage without structure. *J. ACM*, 71(3), jun 2024. (Cited on page [2.](#page-3-0))

A Proof of Lemma [2.4](#page-9-1)

Proof of Lemma [2.4.](#page-9-1) Suppose that QEFID with uniform distribution exists. Then, there exists Gen such that

$$
SD((x)_{x \leftarrow Gen(1^n)}, (x)_{x \leftarrow \{0,1\}^n}) \ge \frac{1}{n}
$$
\n(140)

for all sufficiently large $n \in \mathbb{N}$.

For an arbitrary real $0 < \tau < 1$, we consider the following Gen^{*}.

The description of Gen[∗] (1*ⁿ*)**:**

- Let $A = n^{\frac{1-\tau}{2}}$ and $B = n^{\frac{1+\tau}{2}}$.
- Run $x_i \leftarrow$ Gen(1^A) for all $i \in [B]$.
- Output $\{x_i\}_{i \in [B]}$.

We have

$$
\text{SD}\left((\{x_i\}_{i\in[B]})_{\{x_i\}_{i\in[B]}\leftarrow \text{Gen}^*(1^n)}, X_{X\leftarrow \{0,1\}^n} \right) \geq 1 - \exp\left(-B\cdot \text{SD}\left(x_{x\leftarrow \text{Gen}(1^A)}, x_{x\leftarrow \{0,1\}^A} \right) \right) \right. \right. \tag{141}
$$

$$
\geq 1 - \exp\left(-\frac{B}{A}\right) = 1 - \exp(-n^{\tau}) > 1 - 2^{-n^{\tau}}.
$$
 (142)

Furthermore, computationally indistinguishability of Gen[∗] follows from a standard argument. \Box