Quantifying User Coherence: A Unified Framework for Cross-Domain Recommendation Analysis

Michaël Soumm^{*1}, Alexandre Fournier-Montgieux^{*1}, Adrian Popescu¹, Bertrand Delezoide²

¹Université Paris-Saclay, CEA, List, F-91120, Palaiseau, France ²Amanda, 34 Avenue Des Champs Elysées, F-75008, Paris, France

Abstract

The effectiveness of Recommender Systems (RS) is closely tied to the quality and distinctiveness of user profiles, yet despite many advancements in raw performance, the sensitivity of RS to user profile quality remains under-researched. This paper introduces novel information-theoretic measures for understanding recommender systems: a "surprise" measure quantifying users' deviations from popular choices, and a "conditional surprise" measure capturing user interaction coherence. We evaluate 7 recommendation algorithms across 9 datasets, revealing the relationships between our measures and standard performance metrics. Using a rigorous statistical framework, our analysis quantifies how much user profile density and information measures impact algorithm performance across domains. By segmenting users based on these measures, we achieve improved performance with reduced data and show that simpler algorithms can match complex ones for low-coherence users. Additionally, we employ our measures to analyze how well different recommendation algorithms maintain the coherence and diversity of user preferences in their predictions, providing insights into algorithm behavior. This work advances the theoretical understanding of user behavior and practical heuristics for personalized recommendation systems, promoting more efficient and adaptive architectures.

1 Introduction

In the context of the rapid development of digital connectivity and the explosion in the amount of information, recommender systems (RS) have emerged as essential tools, offering personalized suggestions adapted to individual preferences and behaviors (Nilashi et al. 2013; Pavlidis 2019). These systems play an essential role in filtering and personalizing content across various domains, from e-commerce to entertainment and news consumption (Nilashi et al. 2013; Konstan 2004).

RS can be categorized into three main types: contentbased (CB), knowledge-based (KB), and in our study scope, collaborative filtering (CF) approaches (Burke 2000). Content-based systems use machine learning to classify items likely to interest users based on available characteristics of previously consumed items (e.g. the genre of a film), while knowledge-based approaches aim to extract semantic



Figure 1: Performance in Recall@20 of different RS, averaged over datasets, w.r. to our proposed **Conditional Surprise** (CS(u)) measure, standardized between 0 and 1, with a moving average smoothing. All RS performance collapse for high values of CS(u).

representations to find products meeting user requirements (Burke 2000; Jannach et al. 2010). On the other hand, collaborative filtering has gained significant attention due to its ability to aggregate user preferences and make recommendations based on similarities in user behavior patterns (Konstan 2004). We concentrate on CF approaches because they have dominated the research landscape in recent years (Lops et al. 2019; Zhang et al. 2019; Batmaz et al. 2019) and require minimal information, analyzing only user-item interactions without the need for additional content or knowledge-based features (Ekstrand et al. 2011; Afoudi et al. 2018).

Selecting the right measures is essential to ensure that RS delivers recommendations that are not only accurate but also align well with users' overall preferences and consumption patterns, ultimately enhancing user satisfaction. Despite the emergence of many new measures like diversity and novelty (Kaminskas and Bridge 2016) that describe predicted items, the field lacks measures that accurately model the diversity of the user consumptions. We propose two coherence measures, **Surprise** and **Conditional Surprise**, that quantify different aspects of coherence and can be applied to both user interactions and model predictions. The former de-

^{*}These authors contributed equally.

scribes how surprising (uncommon) a user's consumptions' are, while the latter describes their internal coherence, independently of their uncommonness. We provide theoretical interpretations and properties of these measures and use them to improve our understanding of the performance of RS. Figure 1 illustrates the impact of our Conditional Surprise measure on the performance of various recommendation algorithms across multiple datasets. The graph clearly demonstrates that as the Conditional Surprise increases (indicating less coherent user behavior), the performance of all recommender systems drastically declines. This relationship holds true across different algorithms and datasets, highlighting the impact of user coherence in recommendation tasks and the potential utility of our proposed measure for understanding and improving recommender system performance. Specifically, we address three questions in this regard:

- Can we develop a framework that describes user behavior and how it impacts the effectiveness of different recommendation algorithms? We demonstrate that our measures capture nuanced user behavior patterns, revealing significant correlations between user coherence and algorithm performance across various domains.
- Can this framework allow for meaningful recommendation effectiveness comparisons across domains and algorithms? Our proposed measures provide a common basis for evaluating recommender systems across diverse contexts, allowing us to compare RS performance across multiple scenarios.
- 3. How can we leverage the proposed measures to enhance overall recommender system performance and adaptability? Our analysis demonstrates that these measures can be used to optimize various aspects of recommender systems, from prediction quality and algorithm selection to coherence preservation, leading to more effective and efficient recommendations.

2 Related Work

RS have evolved significantly over the past decade (Wu et al. 2012; Roy et al. 2022). However, recent studies still highlight persistent and major challenges within the field. More specifically, offline evaluation (Sun 2023, 2024) and replicability (Dong et al. 2023) issues motivate the need for more rigorous evaluation approaches.

The data processing pipline can also have an important impact on performance. Meng et al. (2020) examined data splitting strategies and their impact on evaluation outcomes while Ji et al. (2020) addressed data leakage in offline evaluation, highlighting the issue of evaluating on too few sets (Fan et al. 2024).

Several frameworks and analyses have thus been developed to enhance evaluation rigor and standardization. Sun et al. (2020) and Salah et al. (2020) focus on reproducible evaluation. More recently, new comprehensive frameworks like Elliot (Anelli et al. 2021) and ReChorus2.0 (Li et al. 2024) now provide standardized evaluation tools. While these frameworks offer valuable resources for consistent evaluation, they primarily focus on traditional performance metrics.

While traditional metrics focus primarily on accuracy, recent research has emphasized the importance of considering additional factors to provide a more comprehensive evaluation (Kuanr and Mohapatra 2021). In the context of collaborative filtering, the accuracy is usually measured through Recall@K, Precision@K, or NDCG@K, among others, which describe the RS's capacity to recover the user's interactions that were hidden in test-time. These metrics have been widely used (Silveira et al. 2019), but leave out other recommendation aspects that are in the users' interests, some of which have been tackled over the years. More precisely, Konstan and Riedl (2012) introduced user satisfaction in evaluations. Kaminskas and Bridge (2016) examined diversity, serendipity, and coverage metrics. The use of satisfaction metrics was democratized to evaluate model prediction in the following works (Silveira et al. 2019; Alhijawi, Awajan, and Fraihat 2022). Additional works highlighted the importance of considering these newer metrics in order to better match users' behavior and find better recommendations (Kim, Choi, and Li 2021; Ping, Li, and Zhu 2024). Using relevant metrics enables the analysis of group disparity in the behavior of the recommendation system. Recent work thus used these metrics to analyze such disparity in given user or item segments (Dong et al. 2023; Diricic et al. 2023).

In addition, concerns about domain-specific evaluation methodologies have emerged, highlighting the need for more nuanced and versatile evaluation approaches. Latifi et al. (2022) proposed metrics for session-based recommendations in streaming contexts, revealing that traditional static metrics often fail to adequately assess the performance of recommender systems in dynamic, session-based environments. Dietz et al. (2023) studied the influence of data characteristics on point-of-interest recommendation algorithms, demonstrating that factors such as geographical distribution and temporal patterns significantly impact algorithm performance. Their findings underscored the importance of considering domain-specific features in evaluation methodologies. Building on these insights, Sun (2024) questioned the cross-domain applicability of current evaluation practices, arguing that metrics and evaluation protocols optimized for one domain may not translate effectively to others. They highlighted the need for more generalizable evaluation frameworks that can account for domain-specific nuances while still enabling meaningful cross-domain comparisons.

Recent research advocates for improvements in fundamental aspects of recommender system evaluation, such as data handling, performance metrics, and cross-domain applicability (Fan et al. 2024; Shevchenko et al. 2024). Additionally, emerging works highlight new concerns, including the need to create RS tasks more aligned with real-world applications (Sun 2024) and to develop a better understanding of users' true intents (Kleinberg et al. 2022).

Collectively, these studies depict a field in transition, showing the need for better evaluation practices to match the increasing sophistication and real-world impact of recommender systems.

3 Proposed Approach

3.1 Notations and Problem Formulation

We denote the set of users as \mathcal{U} and the set of items as \mathcal{I} . Let $n = |\mathcal{U}|$ be the number of users and $m = |\mathcal{I}|$ the number of items. We place ourselves in a binary setting where each user $u \in \mathcal{U}$ can either interact $(x_{ui} = 1)$ or not interact $(x_{ui} = 0)$ with an item $i \in \mathcal{I}$, leading to the binary interaction matrix $X \in \{0, 1\}^{n \times m}$. We identify each user to its item set so that "u" refers equivalently to a user id and to their item set.

A set of test users \mathcal{U}_{test} is randomly sampled. For each test user, their last interaction is isolated as the test target $x_{ui_{test}}$. All other interactions are part of the training set. The goal of a recommender system is to learn a function $f: \mathcal{U} \times \mathcal{I} \rightarrow \mathbb{R}$ that assigns a score f(u, i) to each user-item pair (u, i), indicating the likelihood of user u interacting with item i. The system's performance is evaluated by its ability to rank the test item i_{test} highly among all items not in the user's training set.

3.2 Coherence measures

We aim to understand and quantify individual user behavior in recommender systems. Traditional approaches often simplify users into entries in a user-item matrix, and this modeling choice can overlook important nuances in user preferences and consumption patterns. By modeling individual user behavior more comprehensively, we can gain insights into why certain recommendations succeed or fail, and potentially tailor our approaches to different types of users.

In this context, we define coherence as "the degree to which a user's interactions form a consistent and predictable pattern". A highly coherent user would have a set of interactions that align well with each other and with common consumption patterns. In contrast, a less coherent user might have more diverse interactions.

Specifically, we want to measure how the performance of recommender algorithms is impacted by how surprising or unpredictable a user's behavior is. To model surprise, one natural way is to first assign probabilities to items. In previous works (Kaminskas and Bridge 2016), the probabilities used to compute existing measures describe the prediction distribution. However, this approach is limited as it focuses on the model's output rather than the inherent characteristics of user behavior. Here, we adopt another view and consider the item probability as their frequency among the users:

$$p_i^* = \frac{|\{x_{ui} = 1\}|}{n} \tag{1}$$

This quantity is insufficient since a user can interact with very rare items but still have a very coherent set of items (e.g. niche movies from the same director). Therefore, we consider the second-order statistics:

$$p_{i,j}^* = \frac{\left| \{ x_{ui} = x_{uj} = 1, u \in \mathcal{U} \} \right|}{n} \quad \text{and} \quad p_{i|j}^* = \frac{p_{i,j}^*}{p_j^*} \quad (2)$$

The probability $p_{i|j}^*$ represents how much a user is likely to interact with *i* when they also interacted with *j*.

Then, we can define the **Surprise** of an item as $-\log(p_i^*)$

and the **Conditional Surprise** $-\log(p_{i|j}^*)$. The first intuitive measures to study are the mean empirical binary crossentropies:

$$\widetilde{S}(u) = -\frac{1}{m} \sum_{i=1}^{m} \log(p_i^*) x_{ui}$$
(3)

$$\widetilde{CS}(u) = -\frac{1}{m^2} \sum_{i=1}^{m} \sum_{j=1}^{m} \log(p_{i|j}^*) x_{ui} x_{uj}$$
(4)

However, these existing definitions have an important limitation in that they are non-decreasing when a new item is added to a user's set, regardless of the item's characteristics. This behavior is counter-intuitive, as we would expect the overall surprise to potentially decrease if a highly predictable or common item is added to the user's profile. Thus, we define our user coherence measures, called **Mean Surprise** and **Mean Conditional Surprise**:

$$S(u) = -\frac{1}{|u|} \sum_{i \in u} \log(p_i^*) \tag{5}$$

$$CS(u) = -\frac{1}{|u|^2} \sum_{i \in u} \sum_{j \in u} \log(p_{i|j}^*)$$
(6)

where $|\cdot|$ is the L^1 norm. To show the relevance of our measures, we also compute their Oracle versions on the test items. In our leave-one-out setup, they simplify to $S(i_{test}) = -\log(p_{i_{test}})$ and $CS(i_{test}) = -\frac{1}{|u|} \sum_{j \in u} \log(p_{i_{test}|j}).$

3.3 Interpretation and Properties

The quantities in Equations 5 and 6 have a similar form as in Equations3 and 4, but provide a dynamic rescaling dependent on the user. This ensures that the measures are comparable across users with different numbers of interactions, providing a fair basis for comparison. Unlike the previous formulations, these measures can decrease when a user interacts with a common item, better reflecting intuitive notions of surprise and coherence. The Mean Surprise S(u) describes at the first order how much a user's consumption deviates from the popular items, on a scale from the *unsurprising* users to the *surprising* users. The Mean Conditional Surprise CS(u) indicates whether the co-occurrences in the user's consumption set are far from frequent co-occurrences, capturing the internal consistency of a user's choices, on a scale from the *coherent* users to the *incoherent* users.

In RS data, user behavior and item consumption detection can be quite noisy (Amatriain, Pujol, and Oliver 2009). We can verify how our measures behave on average:

Proposition 1. Let π_u be the distribution from which u is drawn, and $\pi_u^{\geq 1}$ be the distribution of u conditioned on $|u| \geq 1$. Let $S^*(u) = \mathbb{E}_{\pi_u^{\geq 1}}[\widetilde{S}(u)]$ and $CS^*(u) = \mathbb{E}_{\pi_u^{\geq 1}}[\widetilde{CS}(u)]$. Then:

$$\frac{m}{\mathbb{E}_{\pi_{u}^{\geq 1}}[|u|]} \le \frac{\mathbb{E}_{\pi_{u}^{\geq 1}}[S(u)]}{S^{*}(u)} \le \mathbb{E}_{\pi_{u}^{\geq 1}}\left[\frac{m}{|u|}\right]$$
(7)

$$\frac{m^2}{\mathbb{E}_{\pi_u^{\ge 1}}[|u|^2]} \le \frac{\mathbb{E}_{\pi_u^{\ge 1}}[CS(u)]}{CS^*(u)} \le \mathbb{E}_{\pi_u^{\ge 1}}\left[\frac{m^2}{|u|^2}\right]$$
(8)

Proof. See appendix.

In particular, we see that the lower bound for the scaling depends only on the expected value of the number of items. The upper bound, however, can get bigger than $m/\mathbb{E}_{\pi_u^{\geq 1}}[|u|]$, due to the Jensen inequality. However, there is no way of simply bounding it without additional hypotheses. Since |u| is the number of items consumed by u, we can model it as a Poisson variable with parameter λ (see appendix). We have the following bound:

Proposition 2. If X is a Poisson variable of parameter $\lambda > 0$, we have:

$$\mathbb{E}_{\geq 1}\left[\frac{1}{X}\right] \leq \frac{2}{\mathbb{E}_{\geq 1}[X]} \tag{9}$$

Proof. See appendix.

Empirically, we find a tighter upper bound for Equation 9 with a numerator equal to 1.37 instead of 2. This upper bound is met for $\lambda_{sup} \approx 2.9$. For smaller and larger values of λ , the numerator quickly drops to 1. This means that for surprising users, on average, the empirical estimation should not be too far from $S^*(u) \times m/\mathbb{E}_{\pi_w^{\geq 1}}[|u|]$, which is indeed the classical estimator expectancy re-scaled by the mean proportion of items that a user will consume. The same bound effects apply to CS(u).

3.4 User Coherence Segmentation

We study how different recommendation algorithms react to different users. For each training dataset \mathcal{D} , we calculate S(u) and CS(u) for each user u. In particular, we have an estimate of the measures for the test users, using their train interactions. This allows us to segment the dataset into bins based on the value of the coherence measures. As we will see, the conditional surprise metric plays an important role in explaining user performance, so we mainly use CS(u)for our user segmentation. We denote by $\mathcal{D}[\alpha, \beta]$ the dataset comprised of users with a CS(u) between the α th and the β th percentiles. For example, $\mathcal{D}[0, 0.1]$ is the set of *coherent* users, i.e., users with a Mean Conditional Surprise in the first decile.

3.5 Regression Model as an Analytical tool

To accurately quantify the impact of our measures on RS performance, we employ logistic regression (Angrist and Pischke 2009), a statistical method for modeling the relation between attributes and binary outcomes, as proposed by Soumm (2024). The logistic regression model is defined as:

$$\ln \frac{\mathbb{P}[y=1|X]}{\mathbb{P}[y=0|X]} = \beta_0 + \beta_1 X_1 + \dots + \beta_k X_k$$
(10)

where y is the binary target variable, $X_1, ..., X_k$ are the explanatory variables, and $\beta_0, ..., \beta_k$ are the fitted coefficients. This model is denoted in a condensed form as $Y \sim \sigma(X_1 +$ $\dots + X_k$). The model provides coefficient estimates ($\hat{\beta}$ values) for each variable, from which we compute average marginal effects (AME), quantifying how changes in each variable affect the outcome probability while holding other variables constant (Angrist and Pischke 2009). The choice of the considered variables is motivated by modeling considerations and regression quality metrics such as McFadden R^2 (Allison 2014) and the AIC (Akaike 1998). To capture the interactions between variables, we use product terms. For example, the notation $X \times Y$ expands to X + Y + XY, including the main effects and their interaction. This allows for the modeling of complex relationships while retaining individual variable effects.

When X is a variable estimating X^* with a certain variance σ^2 , the plain regression on X becomes imprecise, as the regression data becomes noisy. We the SIMEX (Simulation-Extrapolation) method (Cook and Stefanski 1994), which simulates many regressions with the added noise σ^2 , and extrapolates to the case of no noise, providing more robust coefficient estimates.

4 Experimental Setup

4.1 Datasets

We perform our analysis on 9 datasets of various sizes and domains:

- MovieLens 1M and MovieLens 10M (Harper and Konstan 2016): movie ratings recommendation datasets, commonly used for benchmarking recommendation algorithms;
- Netflix Small and Netflix (Bennett et al. 2007): two versions of the Netflix Prize dataset, consisting of movie ratings;
- Amazon Music, Amazon Office, and Amazon Toys (Lakkaraju et al. 2013): part of the Amazon product reviews collection, focusing on different product categories;
- **Tradesy** (Lakkaraju et al. 2013): interactions on the Tradesy platform, which specializes in the resale of designer fashion;
- **Vis2Rec** (Soumm et al. 2023): tourism recommendation dataset, with visits identified from photos.

We used different sizes from the same dataset, and datasets from the same domain but different sources, specifically to study the effects of dataset size and domain. This allows us to analyze recommender systems across a wide range of real-world applications.

4.2 Data Processing

Following standard practices (Meng et al. 2020), we binarize non-binary ratings, which are all in [1,5], by setting $x_{ui} = \mathbb{1}(r_{ui} > 3)$. A 5-code is extracted from the datasets, i.e. a subset of users and items with at least 5 interactions, by sequentially filtering out users and items with less than



Figure 2: Distribution of the measures across datasets. S denotes the Surprise measure, and CS the Conditional Surprise measure. CS shows remarkable stability across all datasets.

Dataset	Items	Users	Inter.	Density
ML 1M	3.1K	6K	562K	$3 \cdot 10^{-2}$
ML 10M	9.4K	69K	5.7M	$9 \cdot 10^{-3}$
Netflix Small	2.7K	8.3K	320K	$1 \cdot 10^{-2}$
Netflix	18K	463K	59.9M	$7 \cdot 10^{-4}$
Vis2Rec	9.3K	9.1K	200K	$2 \cdot 10^{-3}$
Tradesy	12K	6.6K	73K	$9 \cdot 10^{-4}$
Amazon Music	11K	8.6K	87K	$9 \cdot 10^{-4}$
Amazon Office	62K	20K	468K	$4 \cdot 10^{-4}$
Amazon Toys	143K	61K	1.2M	$1 \cdot 10^{-4}$

Table 1: Description of the datasets after processing

5 interactions until convergence. This pre-processing makes the datasets more compact, leading to a size distribution described in Table 1.

We sample 10'000 test users from each dataset, isolate their last interaction as the test set, and the second-to-last interaction as a validation set. For datasets with less than 10'000 users, all users are considered test users.

For each dataset, the Mean Surprise and Conditional Surprise are computed for each user. This allows us to easily create the segments $\mathcal{D}[\alpha, \beta]$ for multiple values of α and β , both in the train and test set. Since most algorithms cannot handle users that are not in the train set, we ensure that test users always appear in the train set. However, some items of the test set may not always be present in the train set, which makes the task more complicated. All relevant code is provided in the appendix.

4.3 Recommender Algorithms

We benchmark 7 recommendation algorithms:

- MostPop is the baseline algorithm that recommends the most popular items to every user;
- **UserKNN** is a neighborhood-based approach that relies on a similarity between pairs of users.
- **ItemKNN** is a neighborhood-based approach that relies on a similarity between pairs of items;
- **WMF** is a weighted matrix factorization approach that learns user and item embeddings with gradient descent, minimizing a reconstruction loss;

- **EASE** (Steck 2019) is a matrix factorization approach that computes an item-item weight matrix with a closed-form formula;
- LightGCN (Shenbin et al. 2020) is an approach that learns user and item embeddings by aggregating information from the user-item interaction graph using a light graph convolution;
- **RecVAE** (Shenbin et al. 2020) is a variational autoencoder approach inspired by β -VAE (Higgins et al. 2017) and denoising-VAE (Im et al. 2016).

These algorithms have been chosen to represent a wide range of possible usages, depending on how well they scale with the number of users, the number of items, training times, or flexibility.

4.4 Training

In the leave-one-out protocol, as there is only 1 relevant test item per user, the two reference metrics Recall@K and Precision@K (Herlocker et al. 2004) are equivalent, up to a constant, since they are proportional to the number of relevant items. Therefore, we only use Recall@K, which corresponds in this case to a binary variable 0/1. For each experiment (i.e. algorithm trained on a dataset or a dataset segment), we perform a hyperparameter search using optuna with 50 rounds maximizing the Recall@20 on the validation set.

The models are trained on 256 AMD EPYC 9554 64-Core CPUs and 1.4TB of RAM for the algorithms that run on CPU, while others are run on a single NVIDIA A100 GPU with 40GB of VRAM.

5 Results and Analysis

5.1 Experimental Properties of the Measures

Measure Distribution. Figure 2 presents the distribution of our proposed measures across the datasets. A key observation is that the distribution of S(u) characterizes the domain: the movie-related datasets exhibit comparable Mean Surprise values. This suggests a uniformity in user behavior patterns within the movie recommendation domain, even if they come from different sources and collection processes. In contrast, all e-commerce datasets demonstrate higher S(u) values, indicating higher diversity in user consumptions. Vis2Rec, designed for tourism recommendation, falls



Figure 3: Overall algorithms performance across datasets, measured in Recall@20 with confidence intervals at 95%.



Figure 4: Comparison of S(u) and S(u) against |u| on the Netflix dataset, with a regression fo S(u) on |u|. Similar graphs are produced for other datasets and for CS(u) (see appendix).

between the movie and e-commerce clusters, highlighting its distinct nature.

Interestingly, despite the variations in the distribution of S(u) across domains, we observe consistency in the distribution of CS(u) across all datasets. This suggests that the CS(u) measure is a good candidate for a domain-agnostic coherence measure.

Comparison with naive measures. We start by verifying that our measures behave better than existing ones, such as the mean-cross entropies $\tilde{S}(u)$ and CS(u) defined in Eq. (3) and (4). We graphically inspect the relationship between candidate measures and |u|. Figure 4 shows that S(u) linearly increases with the number of items, whereas S(u)tends to stabilize as |u| increases. A closer inspection reveals that $(S(u) - \hat{\mathbb{E}}_u[S(u)])$ still increases with |u|, but with a constant asymptotic behavior. This is consistent with the idea that users with fewer consumptions can either overconsume very popular items or, on the contrary, exhibit specific preferences. In contrast, users with more items, on average, consume a mix of popular and specific items, converging to a single limit distribution. Similar findings are found for CS(u): as the number of items in a user's set increases, the internal coherence of the interactions converges to a single behavior.

Dataset	Coefficient	R^2
ML 1M	0.58	0.79
ML 10M	0.55	0.86
Netflix Small	0.49	0.67
Netflix	0.6	0.84
Vis2Rec	-0.12	0.02
Tradesy	-0.66	0.28
Amazon Music	-0.66	0.43
Amazon Office	-0.68	0.44
Amazon Toys	-0.66	0.51

Table 2: Linear dependence between the information measures across datasets

Correlation between measures Table 2 presents the linear dependence between CS(u) and S(u) across the tested datasets. As before, we see a clear distinction between the different domains. For movie datasets, we observe positive correlation coefficients ranging from 0.49 to 0.6, suggesting that in this domain, unsurprising users also happen to be coherent. The higher R^2 value for these datasets indicates that this relationship is quite significant and consistent.

In contrast, e-commerce datasets demonstrate strong negative correlations, with coefficients consistently between -0.66 and -0.68. This negative relationship implies that in online shopping contexts, the coherent users are also the most surprising ones. The moderate R^2 values suggest that while this inverse relationship is significant, it's not as deterministic as in the movie domain.

The Vis2Rec dataset stands out with a weak negative correlation (-0.12) and a very low R^2 . This implies that for this dataset, there is only a very weak link between surprise and coherence.

These findings help us understand the data-specific challenges in each domain by revealing the unique relationships between user surprise and coherence. These domain-specific patterns underscore the importance of tailoring recommendation strategies to the unique characteristics of user behavior in each field, rather than applying a one-size-fits-all approach across different domains.

5.2 Overall Performance

The overall results are presented in Figure 3. All combinations of datasets and algorithms have been benchmarked except UserKNN on Netflix. Due to the amount of users, the



Figure 5: Average marginal effect of the variables on the performance. Each value corresponds to the causal variation in Recall@20 when the variable goes up by 1 standard deviation.

Dataset	u	$S(i_{test})$	$CS(i_{test})$	R^2
ML 1M	-0.02	0.02	-0.22	0.34
ML 10M	-0.02	0.06	-0.26	0.50
Netflix Small	0.02	-0.00	-0.19	0.53
Netflix	-0.05	-0.04	0.02	0.14
Vis2Rec	0.05	-0.02	-0.17	0.4
Tradesy	0.03	-0.03	-0.05	0.32
Amazon Music	0.04	-0.05	-0.08	0.33
Amazon Office	0.02	-0.01	-0.03	0.31
Amazon Toys	0.05	-0.03	-0.09	0.35

Table 3: Marginal effects of the variables for equation 11. All values are significant at *p*-value < .05. For e.g. on ML 1M, the increase of 1 std. in $CS(i_{test})$ causes the Recall@20 to decrease of 22 points on average.

method saturates the 1.4 TB of RAM available for experiments.

Figure 3 shows two global trends. First, there are substantial performance differences between movie datasets and ecommerce datasets. This can be explained by the density of their associated consumptions (see Table 1), which is much higher for movie datasets. Second, performances are better when the dataset size increases: the performances of the algorithms are overall better on ML 10M and Netflix than, respectively, on ML 1M and Netflix Small. This is not trivial since increasing the size not only increases the number of samples (users) but also the number of items, which theoretically makes the task harder.

EASE provides the best performances on almost all datasets. WMF is second everywhere except for the biggest sets, where RecVAE, leverages better the amount of data at its disposal, as expected from a deep approach. However RecVAE and ItemKNN are more sensitive to the number of items and users. In particular, RecVAE performs better when the number of items is below the number of users. Conversely, ItemKNN performs better when the number of users is below the number of items.

5.3 Validating Coherence Measures

For each dataset, we demonstrate the usefulness of our coherence measures by performing a logistic regression of the binary Recall@20 metric denoted Rec(u) on the oracle test information measures and the profile density, controlling for the used algorithm:

$$Rec(u) \sim \sigma(algo + |u| \times S(i_{test}) \times CS(i_{test}))$$
 (11)

We compute the average marginal effects (AME) of the variables and the McFadden's R^2 of the model, reporting the values in Table 3. The regressions have overall very high R^2 values, which shows the power of our regression¹. We additionally noticed that the marginal effects of the measures, in particular CS(u), are as important as the algorithm's. The mostly negative coefficients highlight the sensitivity of the algorithms to the coherence of the test item with respect to the input items.

5.4 Impact on Performance

We now directly estimate how our measures computed on the train set impact RS performance. Figure 1 shows the relation of the Recall@20 to CS(u). This graph reveals several important insights:

- There is a clear negative correlation between CS(u) and recommendation performance for all algorithms.
- The performance gap between different algorithms is most pronounced for coherent users, i.e. for users with low CS(u) values.
- As CS(u) increases, the performance of all algorithms converges to a similarly low level.

Notably, the convergence of algorithm performance for high CS(u) values suggests that for highly incoherent users, the choice of algorithm becomes less important. This observation has significant implications for recommender system

 $^{^1 {\}rm For}$ logistic regression, McFadden $R^2 > 0.2$ is considered an excellent fit (Allison 2014)

	IKNN	LGCN	WMF	RVAE	EASE
Vanilla	0.0	33.8	47.4	46.0	53.0
Spec.	3.2	39.3	49.2	47.8	56.0

Table 4: Recall@20 on the coherent users of Netflix, for the Vanilla models and the specialized ones, trained on a small coherent subset.

design and deployment. It indicates that most gains in overall performance primarily come from improvements in recommendations for coherent users. For incoherent users, even sophisticated algorithms struggle to outperform simpler approaches.

To get the true marginal effect independent of other variables, we estimate the model:

$$Rec(u) \sim \sigma(|u| \times S(u) \times CS(u))$$
 (12)

We perform one regression on each dataset and algorithm pair. We model the variability in $\log(p_i)$ and $\log(p_{i|j})$ for a given user by using SIMEX with a variance estimated on each user set of interactions. Empirically, this yields to a model with much more statistically significant effects, and with a larger effect norm.

The AME for the regression of each dataset and algorithm are reported in Figure 5, showing that the most important effects come from profile density and CS(u). The AME of |u| is non-significant or negative for movie sets while being positive for e-commerce. This can be explained by the difference in consumption density between movie and e-commerce datasets. Since e-commerce profiles are more sparse, each new item adds useful information for RS. On the other hand, adding items to already dense profiles only adds complexity.

The S(u) measure is the less impactful variable, meaning RS adapt (to some degree) to users with niche tastes. Mean Surprise still holds a negative effect on e-commerce sets. This could be explained by the fact that these datasets have a higher mean S(u). When a user deviates from the popular items, they would buy very rare items, which are not well-modeled by the algorithm.

Mean Conditional Surprise CS(u) greatly impacts the performance negatively in most scenarios. This highlights the importance of the measure in quantifying the difficulty of a user. The distinction between e-commerce and movie datasets is not as clear as for the previous graphs, showing the cross-domain applicability of the measure.

5.5 Coherence Reproduction

While Recall@K and other discrete metrics are broadly used to evaluate RS, the exclusive use of discrete performance metrics is adapted to the field. A good recommendation system might not exactly recommend the test target, as long as its predictions are coherent with the user behavior. Thus, we compare in Figure 6 the distribution of CS(u) for a given train set (ML 10M) and for the prediction sets given by EASE and RecVAE for each user. While RecVAE achieves a lower recall score compared to EASE, it more closely reproduces the CS(u) distribution of the training set. This ob-



Figure 6: Distributions of CS(u) for ML 10M (Train) set and predictions of both RecVAE and EASE

servation suggests that RecVAE may be better at capturing the underlying coherence patterns of user behavior, even if it doesn't always predict the exact test items. This dual approach to evaluation offers several advantages: it provides a more comprehensive view of recommendation quality, facilitates the identification of algorithms that better maintain user behavior patterns, and may reveal strengths overlooked by traditional metrics. This approach encourages the development of more nuanced recommendation strategies. Detailed results for all datasets and algorithms are available in the appendix.

5.6 Specialized Models for Coherent Users

Since we showed that CS(u) explains most of RS performance, and since it is well-behaved across datasets, it is a good candidate to segment datasets using the protocol described in Section 3.4. From our experiments, we found that the best segmenting strategy was to evaluate on the coherent test users set $\mathcal{D}[0, 0.1]$. We train models on $\mathcal{D}[0, \beta]$ for Netflix, with $\beta \in \{0.1, 0.2, 0.3\}$ independently chosen for each algorithm, and evaluate them on the coherent users. Table 4 shows that despite training on at most 30% for the training set, specialized models achieve better performances on coherent users than models trained on the whole dataset. This is probably due to a reduction in the distribution shift between the train and the test set.

6 Conclusion

We introduced two information measures for analyzing recommender systems across diverse domains. Our study shows that these measures effectively capture nuanced user behavior patterns that are consistent across different recommendation contexts. These measures provide a domainagnostic framework for quantifying user coherence, offering insights into the relationship between user behavior and recommendation difficulty. By revealing how user coherence impacts algorithm performance, our approach enables a more nuanced understanding of recommender system dynamics. This work shows the importance of coherence user modeling in recommender systems, potentially leading to adaptive architectures that can better align with diverse user behaviors across various domains.

References

Afoudi; et al. 2018. Collaborative Filtering Recommender System. *Advances in intelligent systems and computing*.

Akaike, H. 1998. Information theory and an extension of the maximum likelihood principle. In *Selected papers of hirotugu akaike*, 199–213. Springer.

Alhijawi, B.; Awajan, A.; and Fraihat, S. 2022. Survey on the Objectives of Recommender Systems: Measures, Solutions, Evaluation Methodology, and New Perspectives. *ACM Computing Surveys*.

Allison, P. D. 2014. Measures of Fit for Logistic Regression.

Amatriain, X.; Pujol, J. M.; and Oliver, N. 2009. I Like It... I Like It Not: Evaluating User Ratings Noise in Recommender Systems. In Houben, G.-J.; McCalla, G.; Pianesi, F.; and Zancanaro, M., eds., *User Modeling, Adaptation, and Personalization*, 247–258. Berlin, Heidelberg: Springer Berlin Heidelberg. ISBN 978-3-642-02247-0.

Anelli, V. W.; Bellogín, A.; Ferrara, A.; Malitesta, D.; Merra, F. A.; Pomo, C.; Donini, F. M.; and Noia, T. D. 2021. Elliot: A Comprehensive and Rigorous Framework for Reproducible Recommender Systems Evaluation.

Angrist, J. D.; and Pischke, J.-S. 2009. *Mostly Harmless Econometrics: An Empiricist's Companion*. Princeton University Press. ISBN 9780691120348.

Batmaz, Z.; Yurekli, A.; Bilge, A.; and Kaleli, C. 2019. A review on deep learning for recommender systems: challenges and remedies. *Artificial Intelligence Review*, 52: 1–37.

Bennett; et al. 2007. The netflix prize. In *Proceedings of KDD cup and workshop*, volume 2007, 35.

Burke, R. 2000. Knowledge-Based Recommender Systems. *Encyclopedia of library and information systems*, 69.

Cam, L. L. 1960. An approximation theorem for the Poisson binomial distribution. *Pacific Journal of Mathematics*, 10(4): 1181 – 1197.

Cook, J. R.; and Stefanski, L. A. 1994. Simulation-Extrapolation Estimation in Parametric Measurement Error Models. *Journal of the American Statistical Association*, 89(428): 1314–1328. Publisher: ASA Website _eprint: https://doi.org/10.1080/01621459.1994.10476871.

Dietz; et al. 2023. Understanding the Influence of Data Characteristics on the Performance of Point-of-Interest Recommendation Algorithms. *arXiv.org*.

Diricic, T.; Kowald, D.; Lacic, E.; and Lex, E. 2023. Beyond-accuracy: a review on diversity, serendipity, and fairness in recommender systems based on graph neural networks. *Frontiers in big data*.

Dong; et al. 2023. When Newer is Not Better: Does Deep Learning Really Benefit Recommendation From Implicit Feedback?

Ekstrand; et al. 2011. Collaborative Filtering Recommender Systems. *Found. Trends Hum. Comput. Interact.*

Fan, Y.; Ji, Y.; Zhang, J.; and Sun, A. 2024. Our Model Achieves Excellent Performance on MovieLens: What Does It Mean? *ACM transactions on office information systems*.

Harper, F. M.; and Konstan, J. 2016. The MovieLens Datasets: History and Context. *TIIS*.

Herlocker, J. L.; Konstan, J. A.; Terveen, L. G.; and Riedl, J. T. 2004. Evaluating collaborative filtering recommender systems. *ACM Trans. Inf. Syst.*, 22(1): 5–53.

Higgins, I.; Matthey, L.; Pal, A.; Burgess, C.; Glorot, X.; Botvinick, M.; Mohamed, S.; and Lerchner, A. 2017. beta-VAE: Learning Basic Visual Concepts with a Constrained Variational Framework. In *International Conference on Learning Representations*.

Im, D. J.; Ahn, S.; Memisevic, R.; and Bengio, Y. 2016. Denoising Criterion for Variational Auto-Encoding Framework. arXiv:1511.06406.

Jannach, D.; Zanker, M.; Felfernig, A.; and Friedrich, G. 2010. *Knowledge-based recommendation*, 81–123. Cambridge University Press.

Ji, Y.; Sun, A.; Zhang, J.; and Li, C. 2020. A Critical Study on Data Leakage in Recommender System Offline Evaluation. *ACM Transactions on Information Systems*.

Kaminskas, M.; and Bridge, D. 2016. Diversity, Serendipity, Novelty, and Coverage. ACM Trans. Interact. Intell. Syst.

Kim, J.-K.; Choi, I.; and Li, Q. 2021. Customer Satisfaction of Recommender System: Examining Accuracy and Diversity in Several Types of Recommendation Approaches. *Sustainability*.

Kleinberg, J.; Mullainathan, S.; Raghavan, M.; Kleinberg, J.; Mullainathan, S.; and Raghavan, M. 2022. The Challenge of Understanding What Users Want.

Konstan, J. 2004. Introduction to recommender systems: Algorithms and Evaluation. *TOIS*.

Konstan, J. A.; and Riedl, J. 2012. Recommender systems: from algorithms to user experience. *User Modeling and User-adapted Interaction*.

Kuanr, M.; and Mohapatra, P. 2021. Assessment Methods for Evaluation of Recommender Systems: A Survey. *Foundations of Computing and Decision Sciences*.

Lakkaraju; et al. 2013. What's in a Name? Understanding the Interplay between Titles, Content, and Communities in Social Media. *ICWSM*.

Latifi; et al. 2022. Streaming Session-Based Recommendation: When Graph Neural Networks meet the Neighborhood. *ACM Conference on Recommender Systems*.

Li, J.; Li, H.; He, Z.; Ma, W.; Sun, P.; Zhang, M.; and Ma, S. 2024. ReChorus2.0: A Modular and Task-Flexible Recommendation Library. *arXiv.org*.

Lops, P.; Jannach, D.; Musto, C.; Bogers, T.; and Koolen, M. 2019. Trends in content-based recommendation. *User Modeling and User-Adapted Interaction*.

Meng, Z.; McCreadie, R.; Macdonald, C.; and Ounis, I. 2020. Exploring Data Splitting Strategies for the Evaluation of Recommendation Models.

Nilashi, M.; Bagherifard, K.; Ibrahim, O.; Alizadeh, H.; Nojeem, L. A.; and Roozegar, N. 2013. Collaborative filtering recommender systems. *Research Journal of Applied Sciences, Engineering and Technology*, 5: 4168–4182.

Pavlidis, G. 2019. Recommender systems, cultural heritage applications, and the way forward. *Journal of Cultural Heritage*.

Ping, Y.; Li, Y.; and Zhu, J. 2024. Beyond accuracy measures: the effect of diversity, novelty and serendipity in recommender systems on user engagement. *Electronic Commerce Research*.

Roy, D.; Dutta, M.; Roy, D.; and Dutta, M. 2022. A systematic review and research perspective on recommender systems.

Salah, A.; Truong, Q.-T.; Lauw, H. W.; and Mueller, A. 2020. Cornac: A Comparative Framework for Multimodal Recommender Systems. *J. Mach. Learn. Res.*

Shenbin, I.; Alekseev, A.; Tutubalina, E.; Malykh, V.; and Nikolenko, S. I. 2020. RecVAE: A New Variational Autoencoder for Top-N Recommendations with Implicit Feedback. In *Proceedings of the 13th International Conference on Web Search and Data Mining*, WSDM '20. ACM.

Shevchenko, V.; Belousov, N.; Vasilev, A.; Zholobov, V.; Sosedka, A.; Semenova, N.; Volodkevich, A.; Savchenko, A.; and Zaytsev, A. 2024. From Variability to Stability: Advancing RecSys Benchmarking Practices. *arXiv.org*.

Silveira, T.; Zhang, M.; Lin, X.; Liu, Y.; and Ma, S. 2019. How good your recommender system is? A survey on evaluations in recommendation. *International Journal of Machine Learning and Cybernetics*.

Soumm; et al. 2023. Vis2Rec: A Large-Scale Visual Dataset for Visit Recommendation. *IEEE Workshop/Winter Conference on Applications of Computer Vision*.

Soumm, M. 2024. Causal Inference Tools for a Better Evaluation of Machine Learning. arXiv:2410.01392.

Steck, H. 2019. Embarrassingly Shallow Autoencoders for Sparse Data. In *The World Wide Web Conference*, WWW '19. ACM.

Sun, A. 2023. On Challenges of Evaluating Recommender Systems in an Offline Setting.

Sun, A. 2024. Beyond Collaborative Filtering: A Relook at Task Formulation in Recommender Systems. *arXiv.org*.

Sun, Z.; Yu, D.; Fang, H.; Yang, J.; Qu, X.; Zhang, J.; and Geng, C. 2020. Are We Evaluating Rigorously? Benchmarking Recommendation for Reproducible Evaluation and Fair Comparison. *ACM Conference on Recommender Systems*.

Wu; et al. 2012. Evaluating recommender systems. *International Conference on Digital Information Management*.

Zhang, S.; Yao, L.; Sun, A.; and Tay, Y. 2019. Deep learning based recommender system: A survey and new perspectives. *ACM computing surveys (CSUR)*, 52(1): 1–38.

A Properties of the Measures

A.1 Orthogonality of the measures

Since $\log(p_{i|i}) = 0$, effectively, the pairs (i, i) do not intervene in the definition of SC(u). In fact, if we denote by PS(u) the **Mean Pair Surprise** by replacing $p_{i|j}$ by $p_{i,j}$ in the definition of CS(u), then we have:

$$CS(u) = PS(u) - S(u)$$
(13)

Effectively, we remove the effect of the surprise at the first order from the surprise of the pairs.

A.2 **Proof of Proposition 1**

Let $p_{ui} = \mathbb{P}(x_{ui} = 1 ||u| > 0)$. First, consider that:

$$\mathbb{E}_{\pi_{u}^{\geq 1}}[\widetilde{S}(u)] = \frac{1}{m} \sum_{i=1}^{m} \log(p_{i}^{*}) \mathbb{E}_{\pi_{u}^{\geq 1}}[x_{ui}]$$
$$= \frac{1}{m} \sum_{i=1}^{m} \log(p_{i}^{*}) p_{ui}$$

since x_{ui} is a Bernoulli variable. Then for any user u with |u| > 0:

$$\mathbb{E}_{\pi_{u}^{\geq 1}}[S(u)] = -\sum_{i}^{m} \log(p_{i}^{*}) \mathbb{E}_{\pi_{u}^{\geq 1}} \left[\frac{x_{ui}}{|u|} \right]$$
$$= -\sum_{i}^{m} \log(p_{i}^{*}) \mathbb{E}_{x_{ui}} \left[\mathbb{E}_{\pi_{u}^{\geq 1}} \left[\frac{x_{ui}}{|u|} \middle| x_{ui} \right] \right]$$
$$= -\sum_{i}^{m} \log(p_{i}^{*}) p_{ui} \mathbb{E}_{\pi_{u}^{\geq 1}} \left[\frac{x_{ui}}{|u|} \middle| x_{ui} = 1 \right]$$
$$= -\sum_{i}^{m} \log(p_{i}^{*}) p_{ui} \mathbb{E}_{\pi_{u}^{\geq 1}} \left[\frac{1}{|u|} \middle| x_{ui} = 1 \right]$$

where the second line is a consequence of the law of iterated expectations. Then, since $x \mapsto 1/x$ is convex on \mathbb{R}^*_+ , by Jensen inequality:

$$\begin{split} \mathbb{E}_{\pi_u^{\geq 1}}[S(u)] &\geq -\sum_i^m \log(p_i^*) p_{ui} \frac{1}{\mathbb{E}_{\pi_u^{\geq 1}}[|u|]} \\ &\geq \mathbb{E}_{\pi_u^{\geq 1}}[\widetilde{S}(u)] \frac{m}{\mathbb{E}_{\pi_u^{\geq 1}}[|u|]} \end{split}$$

which directly gives the left-hand side of Proposition 1. The right-hand-side follows from the fact that $|u| = \sum_i x_{ui}$. So, for any random events ω_0, ω_1 that only differ in $x_{ui}(\omega_0) = 0$ and $x_{ui}(\omega_1) = 1$, we have $\frac{1}{|u|}(\omega_0) \ge \frac{1}{|u|}(\omega_1)$. Taking the expected value from both sides gives:

$$\mathbb{E}_{\pi_{u}^{\geq 1}}[S(u)] \leq -\sum_{i}^{m} \log(p_{i}^{*})p_{ui}\mathbb{E}_{\pi_{u}^{\geq 1}}\left[\frac{1}{|u|}\right]$$
$$\leq -\mathbb{E}_{\pi_{u}^{\geq 1}}\left[\frac{1}{|u|}\right]\sum_{i}^{m} \log(p_{i}^{*})p_{ui}$$
$$\leq \mathbb{E}_{\pi_{u}^{\geq 1}}\left[\frac{m}{|u|}\right]\mathbb{E}_{\pi_{u}^{\geq 1}}[\widetilde{S}(u)] \quad \Box$$

For CS(u), the convexity of $x \mapsto 1/x^2$ on \mathbb{R}^*_+ and the fact that $\mathbb{E}_{\pi_u^{\geq 1}}\left[\frac{1}{|u|^2}|x_{ui}=1\right] \leq \mathbb{E}_{\pi_u^{\geq 1}}\left[\frac{1}{|u|^2}\right]$ proves the bounds.



Figure 7: Monte-Carlo estimation of $\mathbb{E}_{X \ge 1}[X]\mathbb{E}_{X \ge 1}\left[\frac{1}{X}\right]$



Figure 8: Monte Carlo estimation of $\mathbb{E}_{X \ge 1}[X^2]\mathbb{E}_{X \ge 1}\left[\frac{1}{X^2}\right]$

A.3 Discussion about the Poisson model for |u|

The Poison distribution, also known as "the law of rare events", is an adapted model to count the frequency of events that occur rarely. In particular, in recommendation data, users consume only a small fraction of the possible items, giving a motivation for Poisson modelization. Moreover, if we choose a finer description of the user's choices, for example, assigning known oracle probability p_{ui} of observing the item *i* in the user's *u* set, then π_u becomes, by definition, a multivariate Bernoulli distribution. Therefore, $|u| = \sum x_{ui}$ is, by definition, a Poisson-Binomial variable, which is well-approximated by a Poisson distribution of parameter $\lambda = \sum p_{ui}$, in virtue of Le Cam's theorem (Cam 1960).

A.4 Proof of Proposition 2

If X is a poison variable of parameter $\lambda > 0$, then :

$$\forall k \in \mathbb{N}, \mathbb{P}[X = k] = \frac{e^{-\lambda}\lambda^k}{k!}$$

which yields:

$$\forall k \in \mathbb{N}, \mathbb{P}[X = k | X > 0] = \frac{\mathbb{P}[X > 0 | X = k] \mathbb{P}[X = k]}{1 - \mathbb{P}[X = 0]}$$
$$= \frac{\mathbb{1}(k > 0)}{1 - e^{-\lambda}} \mathbb{P}[X = k]$$
$$= \mathbb{1}(k > 0) \frac{e^{-\lambda} \lambda^k}{(1 - e^{-\lambda})k!}$$

Then, we can consider the fact that we have:

$$\forall k \in \mathbb{N}^*, \frac{1}{k} \le \frac{2}{k+1}$$

Taking the expectancy conditioned on X > 0 (i.e. $X \ge 1$) gives us:

$$\mathbb{E}_{X \ge 1} \left[\frac{1}{X} \right] \le \mathbb{E}_{X \ge 1} \left[\frac{2}{X+1} \right]$$

$$\le 2 \sum_{k=1}^{\infty} \frac{\mathbb{P}[X=k|X>0]}{k+1}$$

$$\le 2 \sum_{k=1}^{\infty} \frac{e^{-\lambda}}{1-e^{-\lambda}} \frac{\lambda^k}{(k+1)k!}$$

$$\le \frac{2e^{-\lambda}}{1-e^{-\lambda}} \frac{1}{\lambda} \sum_{k=1}^{\infty} \frac{\lambda^{k+1}}{(k+1)!}$$

$$\le \frac{2e^{-\lambda}}{1-e^{-\lambda}} \frac{1}{\lambda} (e^{\lambda} - 1 - \lambda)$$

$$\le \frac{2(1-e^{-\lambda})}{\lambda}$$

$$\le \frac{2}{\mathbb{E}_{\ge 1}[X]} \square$$

To get a similar bound for CS(u), i.e bounding $\mathbb{E}_{X \ge 1}[X^2]\mathbb{E}_{X \ge 1}\left[\frac{1}{X^2}\right]$ we first find a constant K such that :

$$\forall k \in \mathbb{N}^*, \frac{1}{k^2} \le \frac{K}{(k+1)(k+2)} \\ 0 \le (1-\frac{1}{K})k^2 - \frac{3}{K}k - \frac{2}{K}$$

The biggest root of the RHS is given by $\frac{3+\sqrt{1+8K}}{2K-2}$, which is smaller than 1 for $K \ge 6$. The rest of the proof follows the same calculations as for S(u).

A.5 Empirical Bounds

We empirically estimate an upper bound for $\mathbb{E}_{X \ge 1}[X]\mathbb{E}_{X \ge 1}\left[\frac{1}{X}\right]$ and $\mathbb{E}_{X \ge 1}[X^2]\mathbb{E}_{X \ge 1}\left[\frac{1}{X^2}\right]$ for a Poisson variable by varying λ . The results are presented in Figures 7 and 8.

B Data Processing and Training

B.1 Data Processing

We found that in most implementations of recommender data pre-processing, the data was filtered by first removing

Algorithm 1: k-core extraction

Input: A DataFrame df in format ['user'; 'item']
Parameters: An integer k

Output: A k-core for df

- 1: Let $n_1 = df.groupby('user').len().min()$
- 2: Let $n_2 = df.groupby('item').len().min()$
- 3: while $\max(n_1, n_2) > k$ do
- 4: df \leftarrow df.groupby('user').filter(len(x) $\geq k$)
- 5: df \leftarrow df.groupby('item').filter(len(x) $\geq k$)
- 6: $n_1 \leftarrow df.groupby('user').len().min()$
- 7: $n_2 \leftarrow df.groupby('item').len().min()$

```
8: end while
```

9: return df



Figure 9: S(u) and $\tilde{S}(u)$ vs |u| on the Netflix Small dataset, along with the linear fit of S(u) on |u|

the items that were consumed by less than k users, then removing the users that consumed less than k items. This is a problem since with this ordering, the remaining items could be consumed less than k times. Thus, the k-core is extracted using the algorithm 1.

B.2 Optimal Hyperparameters

The optimal hyperparameters found by optuna on 50 runs for each combination of dataset and algorithm, optimizing on the Recall@20 of the validation set, are presented in Table 5.

C Results

C.1 Experimental Properties of S(u) and CS(u)

We show a non zero relationship between S(u) or CS(u), and |u|, in Figure 9 and 10. As we see, the relationship is much less clear than for $\widetilde{S}(u)$ or $\widetilde{CS}(u)$, which are almost perfectly linear or quadratic. Graphs 11 and 12 show the standard deviation dependence of S(u) and CS(u) on |u|, where the deviation is the standard deviation of the surprises (and conditional surprises) values used to compute the sums S(u) and CS(u). As |u| increases, the standard deviation values stabilize, slightly increasing with with |u|. As we see,



Figure 10: CS(u) and CS(u) vs |u| on the Netflix Small dataset, along with the linear fit of CS(u) on |u|



Figure 11: std(S(u))vs |u| on the Netflix Small dataset, along with the linear fit

users with few items can consume either very low-variance items or, on the contrary, have a very erratic behavior.

C.2 Impact on Performance

All regression are run in R, using the glm function, with a binomial law with logit link. The simex package is used to incorporate the variance of the variables, and margins to get the marginal effects.

The choice of the regression to make, in particular which dependencies between variables (such as $S(u) \times CS(u)$), was motivated primarily by the model with the lowest AIC score. Consistently, the model with all the product variables met our criterion.

We also found an important aspect in modeling these logit regressions was to put a threshold on the variable |u|. In accordance with what we stated in the main paper for the impact of our measures on performances, this can be justified by the fact that up until a certain point, adding more items to the item set of a user can only help us to cover all their tastes. Once all the interests of a user are well represented in their item set, then we expect |u| to have less importance. Indeed, thresholding |u| led to models with a lower AIC but also removed the heteroscedasticity of the residuals, i.e., the dependence between the variance of the errors and the predictor variables.



Figure 12: std(CS(u)) vs |u| on the Netflix Small dataset, along with the linear fit.



Figure 13: Correlation between S(u) and $S(\hat{u})$; and CS(u)and $CS(\hat{u})$, where \hat{u} is the predicted item set for u.

C.3 Coherence Reproduction

As mentioned in the Coherence Reproduction section of the main paper, Figure 13 shows the correlation between the information measures of the user u, and the information measures evaluated on their predicted set \hat{u} . As we see, most algorithms (except MostPop), generate predictions that are more correlated with the Mean Surprise level of the known set of the user. One notable exception is ItemKNN, which quite poorly reproduces the Mean Surprise level of the movie datasets. This can be linked to the overall poor performance of ItemKNN on these datasets, with scores of recall way smaller than those of MostPop. For the Conditional Surprise, we find that Deep Learning methods, such as LightGCN and RecVAE, have a stronger correlation between the input and the predictions than more traditional methods (especially for datasets with a lot of users). For these methods, the predictions are computed in a highly nonlinear fashion, which could enable more complex interaction modelization.

Dataset	UserKNN	ItemKNN	WMF	LightGCN	RecVAE	EASE
ML 1M	k: 926 centered: 1 sim: cosine	k: 170 centered: 0 sim: cosine	b: 9.50e-01 batch_size: 16000 k: 518 lambda_u: 4.92e-03 lambda_v: 2.30e-04	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 919 latent_dim: 254 n_epochs: 100	lamb: 200
ML 10M	k: 705 centered: 1 sim: pearson	k: 594 centered: 1 sim: cosine	b: 9.07e-01 batch_size: 16000 k: 878 lambda_u: 3.54e-02 lambda_v: 5.54e-02	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 611 latent_dim: 541 n_epochs: 100	lamb: 147
Netflix S.	k: 930 centered: 1 sim: cosine	k: 610 centered: 1 sim: cosine	b: 9.52e-01 batch_size: 16000 k: 689 lambda_u: 3.91e-02 lambda_v: 4.08e-03	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 349 latent_dim: 696 n_epochs: 100	lamb: 787
Netflix	NaN	k: 841 centered: 0 sim: cosine	b: 7.20e-01 batch_size: 16000 k: 705 lambda_u: 8.36e-03 lambda_v: 2.79e-04	batch_size: 16000 emb_size: 32 epochs: 200 num_layers: 1	batch_size: 1024 hidden_dim: 778 latent_dim: 164 n_epochs: 100	lamb: 298
Vis2Rec	k: 547 centered: 0 sim: pearson	k: 814 centered: 1 sim: cosine	b: 9.25e-01 batch_size: 16000 k: 702 lambda_u: 1.81e-02 lambda_v: 3.32e-03	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 589 latent_dim: 614 n_epochs: 100	lamb: 63
Tradesy	k: 9 centered: 0 sim: cosine	k: 773 centered: 1 sim: pearson	b: 9.2e-01 batch_size: 16000 k: 485 lambda_u: 1.02e-02 lambda_v: 1.02e-04	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1025 hidden_dim: 325 latent_dim: 464 n_epochs: 101	lamb: 86
A. Music	k: 25 centered: 0 sim: cosine	k: 568 centered: 1 sim: pearson	b: 7.76e-01 batch_size: 16000 k: 588 lambda_u: 4.96e-02 lambda_v: 1.65e-04	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 217 latent_dim: 336 n_epochs: 100	lamb: 31
A. Office	k: 53 centered: 1 sim: pearson	k: 837 centered: 1 sim: cosine	b: 3.91e-02 batch_size: 16000 k: 985 lambda_u: 8.93e-01 lambda_v: 4.51e-02	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 479 latent_dim: 585 n_epochs: 100	lamb: 49
A. Toys	k: 159 centered: 0 sim: pearson	k: 524 centered: 0 sim: cosine	b: 2.34e-02 batch_size: 16000 k: 1000 lambda_u: 1.15e-02 lambda_v: 2.06e-04	batch_size: 16000 emb_size: 64 epochs: 1000 num_layers: 3	batch_size: 1024 hidden_dim: 660 latent_dim: 492 n_epochs: 100	lamb: 35

Table 5: Optimal hyperparameters on each dataset with each algorithm, optimizing the Recall@20 in the leave-one-out setup.