



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
hp visualize j6000 UNIX workstation

SPECfp2000 = 433  
SPECfp\_base2000 = 400

SPEC license #: 3 Tested by: HP TCL Fort Collins CO Test date: Oct-2000 Hardware Avail: Jun-2000 Software Avail: Sep-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	470	340	348	460
171.swim	3100	408	761	402	771
172.mgrid	1800	390	462	390	462
173.applu	2100	373	563	373	563
177.mesa	1400	467	300	414	338
178.galgel	2900	510	569	488	594
179.art	2600	621	419	570	456
183.quake	1300	375	347	283	459
187.facerec	1900	735	258	692	275
188.amp	2200	584	376	533	413
189.lucas	2000	541	370	541	370
191.fma3d	2100	696	302	696	302
200.sixtrack	1100	385	286	342	322
301.apsi	2600	497	523	497	523

### Hardware

CPU: 552 MHz PA-8600  
 CPU MHz: 552  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 2  
 Parallel: --  
 Primary Cache: 500KBI+1MBD (on chip)  
 Secondary Cache: none  
 L3 Cache: none  
 Other Cache: None  
 Memory: 8GB  
 Disk Subsystem: 1x9Gbyte 10000RPM + 1x9Gbyte LVD 10000RPM  
 Other Hardware: --

### Software

Operating System: HP-UX B.11.0  
 Compiler: HP-UX f90 20000928 (181730) B.11.01.25  
 HP92453-01 A.11.01.21505.GP HP C Compiler  
 HP-UX f77 971027 (162928) B.11.00.01  
 File System: HP-UX VxFS  
 System State: Multi-user

## Notes/Tuning Information

Portability flags:

cc: -Ae  
178.galgel: +source=fixed

Base flags:

f90: +O3 +Onofltacc -Wl,-a,archive -Wl,+FPD  
cc: +Oall +Odataprefetch -Wl,-a,archive +I/+P

Peak flags:

Peak flags = base flags for: 172.mgrid, 173.applu, 189.lucas, 191.fma3d and 301.apsi  
 168.wupwise: f77 +DA2.0 +DS2.0 +O4 +Odataprefetch +Onofltacc -Wl,+FPD -Wl,-a,archive  
 171.swim: +O3 +Ocacheypadcommon +Oloop\_unroll -Wl,+FPD -Wl,-a,archive  
 177.mesa: +I/+P +Oall +Odataprefetch +Opromote\_indirect\_calls -Wl,+FPD -Wl,-a,archive  
 178.galgel: +Oall +fastallocatable-Wl,+FPD -Wl,-a,archive -llapack  
 RM\_SOURCES = lapack.f90  
 179.art: +Oall +Odataprefetch +I/+P +Onofltacc +Optrs\_strongly\_typed -Wl,+FPD -Wl,-a,archive  
 183.quake: +Oall +Odataprefetch +Optrs\_strongly\_typed -Wl,+FPD -Wl,-a,archive



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
hp visualize j6000 UNIX workstation

SPECfp2000 = 433  
SPECfp\_base2000 = 400

SPEC license #: 3 Tested by: HP TCL Fort Collins CO Test date: Oct-2000 Hardware Avail: Jun-2000 Software Avail: Sep-2000

## Notes/Tuning Information (Continued)

```
187.facerec: +O2 +Ofastaccess +fastallocatable -Wl,+FPD
             -Wl,-a,archive -Wl,/opt/langtools/lib/fastmem.o
188.ampp:    +Oall +Odataprefetch +Optrs_strongly_typed +I/+P -Wl,+FPD -Wl,-a,archive
200.sixtrack: +Oall +fastallocatable +Onodataprefetch -Wl,+FPD
             -Wl,-a,archive -Wl,/opt/langtools/lib/fastmem.o
```

### Kernel tunables:

```
vps_pagesize=4096, vps_ceiling=4096, dbc_min_pct=25, dbc_max_pct=25
2nd processor disabled at boot - co cpu 1 OFF
```