



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.4 GHz, Pentium 4 processor)

SPECfp2000 = 538

SPECfp_base2000 = 529

SPEC license #: 13 Tested by: Intel Corporation Test date: Nov-2000 Hardware Avail: Nov-2000 Software Avail: Nov-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	223	719	222	719	
171.swim	3100	249	1243	249	1244	
172.mgrid	1800	340	530	311	579	
173.applu	2100	333	630	333	630	
177.mesa	1400	269	520	273	513	
178.galgel	2900	556	522	556	521	
179.art	2600	506	513	492	528	
183.quake	1300	181	720	165	789	
187.facerec	1900	445	427	441	431	
188.amp	2200	619	356	614	358	
189.lucas	2000	270	740	270	740	
191.fma3d	2100	517	406	517	406	
200.sixtrack	1100	458	240	453	243	
301.apsi	2600	632	411	632	411	

Hardware

CPU: Pentium 4 processor (1.4 GHz, 400 MHz bus)
CPU MHz: 1400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K micro-ops I + 8KB D
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256MB (2 128MB PC800 RDRAM non-ECC modules)
Disk Subsystem: IBM DTLA-307030 ATA-100
Other Hardware: Creative Labs Annihilator 2

Software

Operating System: Windows 2000(Build 2195)
Compiler: Intel C/C++ Compiler 5.0,
Intel FORTRAN Compiler 5.0,
Microsoft Visual C++ 6.0 (for libraries),
Other software: Microquill SmartHeap V5.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 +FDO
177.mesa: -Qipo -QxW -Oa -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO shlw32M.lib
183.quake: -Qipo -QxW -Qrcd -Oa +FDO shlw32M.lib
187.facerec: -Qipo -QxW -O3 +FDO shlw32M.lib
188.amp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.4 GHz, Pentium 4 processor)

SPECfp2000 = 538

SPECfp_base2000 = 529

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Nov-2000 | Hardware Avail: Nov-2000 | Software Avail: Nov-2000

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO
 301.apsi: -Qipo -QxW -O3 +FDO
 Library ordering for 187.facerec (include SmartHeap correctly with default libs):
 LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlW32M.lib
 LIBC.lib libirc.lib OLDNAMES.lib
 shlW32M.lib is the SmartHeap library V5.0 from Microquill: <http://www.microquill.com>
 Tested systems can be used with Shin-G ATX case, Delta Inc. power supply
 Product description located as of 11/2000:
http://developer.intel.com/design/motherbd/gb/gb_ds.htm
 Motherboard is available through Intel OEM Distribution Channel. See
<http://channel.intel.com/business/ibp/boards/d850gb.htm> for more information
 The system bus runs at 400 MHz