



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Dell**  
Precision WorkStation 420 (1.0 GHz PIII)

SPECfp2000 = **340**  
SPECfp\_base2000 = **329**

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: Nov-2000 Hardware Avail: Sep-2000 Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	100 200 300 400 500 600					
168.wupwise	1600	385	416	385	416	[Bar chart showing ratio 416]					
171.swim	3100	629	493	629	493	[Bar chart showing ratio 493]					
172.mgrid	1800	658	274	699	258	[Bar chart showing ratio 258]					
173.applu	2100	749	280	749	280	[Bar chart showing ratio 280]					
177.mesa	1400	259	541	261	535	[Bar chart showing ratio 535]					
178.galgel	2900	866	335	808	359	[Bar chart showing ratio 359]					
179.art	2600	634	410	606	429	[Bar chart showing ratio 429]					
183.quake	1300	522	249	414	314	[Bar chart showing ratio 314]					
187.facerec	1900	618	307	556	342	[Bar chart showing ratio 342]					
188.amp	2200	747	294	729	302	[Bar chart showing ratio 302]					
189.lucas	2000	573	349	577	347	[Bar chart showing ratio 347]					
191.fma3d	2100	706	297	706	297	[Bar chart showing ratio 297]					
200.sixtrack	1100	646	170	630	175	[Bar chart showing ratio 175]					
301.apsi	2600	700	371	670	388	[Bar chart showing ratio 388]					

### Hardware

CPU: Pentium III  
 CPU MHz: 1000  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1, 2  
 Parallel: No  
 Primary Cache: 16KB(I) + 16KB(D) on chip  
 Secondary Cache: 256KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 2 x 128MB PC800 RDRAM  
 Disk Subsystem: 1 x 18GB Quantum Atlas 10K U160  
 Other Hardware:

### Software

Operating System: Windows NT 4.0 (SP5)  
 Compiler: Intel C and Fortran Compiler 5.0 for Windows NT  
 Microsoft Visual C++ 6.0 (for libraries)  
 MicroQuill SmartHeap Library 5.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxK -Qipo -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxK -O3 +FDO
171.swim: -Qipo -QxK -O3 +FDO
172.mgrid: -Qipo -QaxK -O3 +FDO
173.applu: -Qipo -QxK -O3 +FDO
177.mesa: -Qipo -QxK -O3 -Oa +FDO shlw32M.lib
178.galgel: -Qipo -QxK -O3 +FDO shlw32M.lib
179.art: -Qipo -QxK -O3 -Oa +FDO shlw32M.lib
183.quake: -Qipo -QxK -Qrcd -Oa +FDO shlw32M.lib
187.facerec: -Qipo -QxK -O3 +FDO shlw32M.lib
188.amp: -Qipo -QxK -O3 -Oa +FDO
189.lucas: -Qipo -QxK -O3 +FDO shlw32M.lib
191.fma3d: -Qipo -QxK -O3 +FDO
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell Precision WorkStation 420 (1.0 GHz PIII)	SPECfp2000 =	340
	SPECfp_base2000 =	329

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Nov-2000 | Hardware Avail: Sep-2000 | Software Avail: Oct-2000

## Notes/Tuning Information (Continued)

```
200.sixtrack: -Qipo -QxK +FDO
301.apsi:     -Qipo -QxK +FDO
Library ordering for 178.galgel, 187.facerec and 189.lucus (include
SmartHeap correctly with default libs): LIBS=libIEPCF90.lib libintrins.lib
libF90.lib libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
```