



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2400 64X 500MHz R14k

SPECfp_rate2000 = 228

SPECfp_rate_base2000 = 212

SPEC license #: 4 | Tested by: SGI | Test date: Aug-2001 | Hardware Avail: Jul-2001 | Software Avail: Aug-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	64	582	204	64	534	222
171.swim	64	1812	127	64	1808	127
172.mgrid	64	1125	119	64	1123	119
173.applu	64	1047	149	64	949	164
177.mesa	64	430	242	64	399	260
178.galgel	64	259	833	64	228	943
179.art	64	239	809	64	238	811
183.equake	64	770	125	64	761	127
187.facerec	64	479	294	64	478	295
188.amp	64	467	349	64	469	348
189.lucas	64	1186	125	64	1189	125
191.fma3d	64	1382	113	64	1120	139
200.sixtrack	64	516	158	64	505	162
301.apsi	64	1153	167	64	754	256

Hardware

CPU: R14000
CPU MHz: 500
FPU: Integrated
CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
CPU(s) orderable: 2-64
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 64 GB
Disk Subsystem: 1 x 18 GB FC, 3 x 18 GB FC (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.13m
Compiler: MIPSpro 7.3.1.2m C, Fortran90
SCSL 1.3 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):
PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2
Portability Flags:
178.galgel: -fixedform
Peak optimization flags:
note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000
-INLINE:aggressive=on -OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5
171.swim: -Ofast=ip27 -LNO:cs2=8m -CG:ld_latency=10
172.mgrid: -Ofast=ip27 -LNO:fusion=2
173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2 -CG:ld_latency=3
177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0:cs2=8m -CG:ld_latency=6 (FEEDBACK)
178.galgel: -Ofast=ip27 -LNO:ou_max=7 -CG:ld_latency=3 -lscs (FEEDBACK)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2400 64X 500MHz R14k

SPECfp_rate2000 = 228
SPECfp_rate_base2000 = 212

SPEC license #: 4 | Tested by: SGI | Test date: Aug-2001 | Hardware Avail: Jul-2001 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

```

.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -LNO:prefetch=0 -IPA:min_hot=15 -CG:ld_latency=3 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -LNO:fusion=2
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 -CG:ld_latency=7 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -CG:ld_latency=2
.
  -OPT:goto=off:unroll_size=160:unroll_times_max=4 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
  setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
  systune -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
  systune -i ; r12k_bdiag = 0x4000000 ;
  limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):
 rm -rf /tmp/SPEC2000/FBDIR_peak/\$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/\$baseexe
 The first disk mentioned in the Disk Subsystem is the system disk. A striped XFS filesystem was created using the rest of the disks and the benchmark was run on this.