



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire 12K

SPECint\_rate2000 = 119  
SPECint\_rate\_base2000 = 105

SPEC license #: 6 Tested by: Sun Microsystems Test date: Mar-2003 Hardware Avail: Mar-2003 Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	320	81.3	16	265	98.2
175.vpr	16	293	88.7	16	276	94.2
176.gcc	16	200	102	16	169	121
181.mcf	16	360	92.8	16	295	113
186.crafty	16	157	118	16	134	139
197.parser	16	339	98.7	16	295	113
252.eon	16	178	136	16	171	141
253.perlbnk	16	306	109	16	278	120
254.gap	16	277	73.6	16	231	88.3
255.vortex	16	220	161	16	197	179
256.bzip2	16	238	117	16	223	125
300.twolf	16	495	113	16	459	121

### Hardware

CPU: UltraSPARC III Cu  
CPU MHz: 1200  
FPU: Integrated  
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip  
CPU(s) orderable: 4-52  
Parallel: No  
Primary Cache: 32KBI+64KBD on chip  
Secondary Cache: 8MB(I+D) off chip  
L3 Cache: None  
Other Cache: None  
Memory: 128GB 16-way interleaved  
Disk Subsystem: 1 x 36GB (System Disk)  
Sun StorEdge T3, 9 x 18GB striped  
Other Hardware: None

### Software

Operating System: Solaris 9 12/02  
Compiler: Sun ONE Studio 8 (pre-FCS build 3/9)  
Sun Performance Library 8 (pre-FCS build 3/9)  
File System: ufs with ufs logging  
System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

```
C: cc
CXX: CC
F90: f90
F77: f90
```

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

```
164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
          -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
175.vpr: -fast -xalias_level=std -xipo=2
          -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
```



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire 12K

SPECint\_rate2000 = 119  
SPECint\_rate\_base2000 = 105

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Mar-2003 | Hardware Avail: Mar-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

```

Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind