



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 2000 (1.2GHz)

SPECfp\_rate2000 = 13.0

SPECfp\_rate\_base2000 = 11.1

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	179	10.4	1	167	11.1
171.swim	1	299	12.0	1	117	30.8
172.mgrid	1	255	8.19	1	255	8.19
173.applu	1	282	8.65	1	220	11.1
177.mesa	1	201	8.10	1	191	8.52
178.galgel	1	146	23.1	1	122	27.5
179.art	1	26.0	116	1	23.5	128
183.quake	1	83.5	18.1	1	80.4	18.7
187.facerec	1	161	13.7	1	161	13.7
188.amp	1	367	6.95	1	338	7.56
189.lucas	1	378	6.14	1	279	8.31
191.fma3d	1	431	5.65	1	384	6.34
200.sixtrack	1	270	4.73	1	242	5.26
301.apsi	1	402	7.51	1	401	7.52

### Hardware

CPU: UltraSPARC III Cu  
CPU MHz: 1200  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1-2  
Parallel: No  
Primary Cache: 32KBI+64KBD on chip  
Secondary Cache: 8MB(I+D) off chip  
L3 Cache: None  
Other Cache: None  
Memory: 2GB 4-way interleaved  
Disk Subsystem: 1 x 73GB 10K RPM FC-AL Disk, Sun Option X6805A  
Other Hardware: None

### Software

Operating System: Solaris 9 12/02  
Compiler: Sun ONE Studio 8 (pre-FCS build 3/09)  
Sun Performance Library 8 (pre-FCS build 3/09)  
File System: ufs with ufs logging  
System State: Multi-User

## Notes/Tuning Information

### Compiler invocation:

C: cc  
CXX: CC  
F90: f90  
F77: f90

### Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
F90: -fast -xipo=2 with ONESTEP=yes and feedback

### Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6  
-Qoption iropt -Atile:skewp,-Ainline:cs=700  
(no feedback)



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 2000 (1.2GHz)

SPECfp\_rate2000 = 13.0

SPECfp\_rate\_base2000 = 11.1

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

```

172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
          -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ammp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

System Settings:

2nd cpu physically removed from system