



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 630 Model 6C4 (1200 MHz, 1 CPU)

SPECfp2000 = --

SPECfp_base2000 = 852

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: Feb-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	126	1265		
171.swim	3100	300	1034		
172.mgrid	1800	304	591		
173.aplu	2100	297	706		
177.mesa	1400	278	503		
178.galgel	2900	125	2313		
179.art	2600	208	1247		
183.quake	1300	137	950		
187.facerec	1900	191	996		
188.amp	2200	332	663		
189.lucas	2000	241	829		
191.fma3d	2100	318	659		
200.sixtrack	1100	212	519		
301.apsi	2600	344	756		

Hardware

CPU: POWER4+
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip, 1 chip/SCM
CPU(s) orderable: 1,2,4 (order by # cores)
Parallel: No
Primary Cache: 64KBI+32KBD (on chip) per core
Secondary Cache: 1536KB unified (on chip) per chip
L3 Cache: 8MB ECC shared per processor card (1 processor card in SUT)
Other Cache: None
Memory: 8 GB
Disk Subsystem: 1x36GB SCSI
Other Hardware: None

Software

Operating System: SLES 8 for pSeries w/2.4.19 kernel
Compiler: IBM VisualAge C++ Version 6.0 for Linux on pSeries
IBM XL Fortran Version 8.1 for Linux on pSeries
File System: ext2
System State: Multi-user

Notes/Tuning Information

cfg file: ppc32-linux-ibm-ref-o5.cfg

Compiled 32-bit applications

CC = /opt/ibmcmp/vac/6.0/bin/xlc
CXX = /opt/ibmcmp/vacpp/6.0/bin/xlC
FC = /opt/ibmcmp/xlf/8.1/bin/xlf90
F77 = /opt/ibmcmp/xlf/8.1/bin/xlf90

SCM: Acronym for "Single-chip module"
SUT: Acronym for "System under test"

SLES: SuSE Linux Enterprise Server

1 processor was deconfigured through the configuration menu.



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 630 Model 6C4 (1200 MHz, 1 CPU)

SPECfp2000 = --

SPECfp_base2000 = 852

SPEC license #: 11 | Tested by: IBM, Austin, Tx | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: Feb-2003

Notes/Tuning Information (Continued)

Floating point optimization flags

FP: -O5

Floating point portability flags

wupwise: -qfixed
swim: -qfixed
mgrid: -qfixed
applu: -qfixed
mesa: none
galgel: -qfixed -qsuffix=f=f90
facerec: -qsuffix=f=f90
lucas: -qsuffix=f=f90
fma3d: -qsuffix=f=f90
sixtrack: -qfixed
apsi: -qfixed