



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp_rate2000 = 11.7

SPECfp_rate_base2000 = 10.8

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	169	11.0	1	152	12.2
171.swim	1	205	17.5	1	178	20.2
172.mgrid	1	208	10.0	1	206	10.2
173.applu	1	262	9.30	1	237	10.3
177.mesa	1	144	11.3	1	140	11.6
178.galgel	1	222	15.1	1	175	19.2
179.art	1	213	14.2	1	200	15.1
183.equake	1	164	9.21	1	133	11.4
187.facerec	1	180	12.2	1	171	12.9
188.amp	1	247	10.3	1	242	10.5
189.lucas	1	163	14.3	1	161	14.4
191.fma3d	1	230	10.6	1	230	10.6
200.sixtrack	1	314	4.07	1	288	4.43
301.apsi	1	306	9.87	1	286	10.6

Hardware

CPU: AMD Opteron 140, 1.4 GHz
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB PC2700 DDR ECC Reg SDRAM CL2.5
 Disk Subsystem: IDE 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition
 Compiler: Intel C/C++ 7.0 build 20021212Z and Intel Fortran 7.0 build 20021212Z
 Compaq Visual Fortran Compiler Version 6.6 (Update B)
 Microsoft Visual Studio .NET (libraries)7.0.9466
 MicroQuill Smartheap Library 6.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
 icl and ifl are the Intel C/C++ and Fortran compilers
 f90 is the Compaq Fortran compiler
 shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
 Portability:
 178.galgel: -FI -Fe\$@ -link -stack:32000000
 Baseline: C icl +FDO -O3 -QxW -Qipo
 Baseline: Fortran ifl +FDO -O3 -QxW -Qipo
 Peak tuning:
 168.wupwise: ifl +FDO -QxK -Qipo -Ow
 171.swim: f90 -Optimize:5 -alignment:dcommons -alignment:records
 -alignment:sequence -architecture:k7
 -assume:noaccuracy_sensitive -math_library:fast -tune:k7
 172.mgrid: ifl +FDO -O3 -QaxW -Qipo -Oa -Qprefetch-
 173.applu: ifl +FDO -O3 -QxK -Qipo -Qscalar_rep- -Zp8
 177.mesa: icl +FDO -O3 -QxW -Qipo -Oa -Qscalar_rep-
 178.galgel: f90 -Optimize:5 -fast



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp_rate2000 = 11.7
SPECfp_rate_base2000 = 10.8

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

179.art:      icl          -Qipo -Oa          -Qunroll14 -Zp4
183.quake:   icl          -O3 -QxK  -Qipo -Oa  shlw32M6.lib -Zp4
187.facerec: ifl +FD0 -O3 -QaxW -Qipo          -Qscalar_rep- -Qunroll11
188.ampp:    icl          -QxW          -Oa
189.lucas:   ifl +FD0 -O3 -QxW  -Qipo          -Qprefetch-
191.fma3d:   ifl basepeak=1
200.sixtrack: ifl          -Qipo -Oa          -Zp4
301.apsi:    f90 -Optimize:5 -fast
ONESTEP is used for all base and peak runs

```