



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E6900 (24 processor)

SPECfp\_rate2000 = 258  
SPECfp\_rate\_base2000 = 208

SPEC license #: 6 Tested by: Sun Microsystems Test date: Apr-2004 Hardware Avail: May-2004 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	48	505	176	48	484	184
171.swim	48	2474	69.8	48	268	644
172.mgrid	48	1432	70.0	48	1434	69.9
173.applu	48	582	201	48	529	221
177.mesa	48	245	318	48	236	331
178.galgel	48	241	671	48	193	836
179.art	48	61.1	2370	48	56.9	2546
183.equake	48	468	155	48	467	155
187.facerec	48	285	372	48	293	361
188.amp	48	488	251	48	440	278
189.lucas	48	1431	77.8	48	1431	77.8
191.fma3d	48	1417	82.5	48	1331	87.8
200.sixtrack	48	368	167	48	317	193
301.apsi	48	685	211	48	674	215

### Hardware

CPU: UltraSPARC s400  
CPU MHz: 1050  
FPU: Integrated  
CPU(s) enabled: 48 cores, 24 chips, 2 cores/chip  
CPU(s) orderable: 4, 8, 12, 16, 20, 24 (order by # chips)  
Parallel: No  
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)  
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)  
L3 Cache: None  
Other Cache: None  
Memory: 96GB 16-way interleaved  
Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)  
Sun StorEdge T3 Array for the Workgroup (9x36GB)  
Other Hardware: None

### Software

Operating System: Solaris 9 04/04  
Compiler: Sun ONE Studio 8  
Sun Performance Library 8  
File System: ufs with ufs logging  
System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC  
F90: f90  
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire E6900 (24 processor)

SPECfp\_rate2000 = 258  
SPECfp\_rate\_base2000 = 208

SPEC license #: 6 Tested by: Sun Microsystems Test date: Apr-2004 Hardware Avail: May-2004 Software Avail: Apr-2004

## Notes/Tuning Information (Continued)

```

171.swim:      -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
               -Qoption iropt -Atile:skewp,-Ainline:cs=700
               (no feedback)
172.mgrid:    -fast -xipo=2
173.applu:    -fast -xipo=2
               -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
               -Qoption iropt -Aujam:inner=g
177.mesa:     -fast -xipo=2 -xalias_level=strong -xrestrict
               -Wc,-Qms_pipe+unoovf
178.galgel:   -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
               RM_SOURCES=lapak.f90
179.art:      -fast -xipo=2 -xalias_level=std
               -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.equake:   -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec:  -fast -xipo=2
188.ammpp:    -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas:    basepeak=yes
191.fma3d:    -fast -xipo=2 -stackvar -xprefetch_level=3
               -Qoption iropt -Apf:pdl=1
200.sixtrack:-O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi:     -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:    rm -rf ./feedback.profile ./SunWS_cache
PASS1:       -xprofile=collect:./feedback
PASS2:       -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind

The system was configured with multiple file systems.

The O/S was installed on one disk of the Sun StorEdge S1 Disk Array (ufs, ufs w/logging). The benchmark was run on the Sun StorEdge T3 Array, using H/W Raid 5 and ufs with ufs logging file system.