



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3 (3.2GHz/2MB L3 cache, Intel Xeon)

SPECfp2000 = **1349**
SPECfp_base2000 = **1318**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Apr-2004 Hardware Avail: Feb-2004 Software Avail: Mar-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	106	1505	104	1535
171.swim	3100	185	1676	180	1719
172.mgrid	1800	156	1153	156	1157
173.applu	2100	187	1121	180	1169
177.mesa	1400	100	1394	100	1394
178.galgel	2900	109	2672	108	2682
179.art	2600	140	1860	118	2196
183.quake	1300	107	1220	106	1231
187.facerec	1900	130	1463	128	1488
188.ammmp	2200	195	1129	195	1129
189.lucas	2000	140	1433	136	1474
191.fma3d	2100	190	1104	190	1104
200.sixtrack	1100	178	619	177	623
301.apsi	2600	243	1068	243	1072

Hardware

CPU: Intel Xeon (3.2GHz, 533MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (HT Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 2048KB(I+D) on chip
Other Cache: N/A
Memory: 4x512MB PC2100
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Standard (Build 3790)
Compiler: Intel C++ Compiler 8.0 Build 20031211Z
Intel Fortran Compiler 8.0 build 20040125Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for all programs: -QxN -Qipo -O3 +FDO ONESTEP=yes
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxN +FDO ONESTEP=yes
171.swim: -Qipo -QxN -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxN -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxN -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxN -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxN -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxN -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxN -O3 -Qunroll11 -Qscalar_rep- +FDO ONESTEP=yes
188.ammmp: basepeak=1
189.lucas: -Qipo -QaxN
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3 (3.2GHz/2MB L3 cache, Intel Xeon)

SPECfp2000 =	1349
SPECfp_base2000 =	1318

SPEC license #:	3	Tested by:	Hewlett-Packard Company	Test date:	Apr-2004	Hardware Avail:	Feb-2004	Software Avail:	Mar-2004
-----------------	---	------------	-------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```
200.sixtrack:  -Qipo -QxN  +FDO ONESTEP=yes
301.apsi:      -Qipo -QxN  -O3  +FDO ONESTEP=yes
BIOS Configuration Notes
HT Technology disabled
```