



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6800 (3.66GHz Intel Xeon)

SPECint2000 = **1377**
SPECint_base2000 = **1317**

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Nov-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	116	1208	118	1190
175.vpr	1400	177	790	177	790
176.gcc	1100	67.3	1635	67.3	1635
181.mcf	1800	213	845	213	845
186.crafty	1000	75.8	1319	75.0	1334
197.parser	1800	146	1237	146	1237
252.eon	1300	56.4	2304	56.7	2292
253.perlbnk	1800	105	1712	91.8	1962
254.gap	1100	66.0	1666	66.0	1666
255.vortex	1900	95.2	1996	96.0	1978
256.bzip2	1500	180	833	180	832
300.twolf	3000	258	1161	171	1757

Hardware

CPU: Intel Xeon (3.66GHz, 1MB L2, 667MHz system bus)
 CPU MHz: 3660
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2,3,4
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2GB (dual-ranked) ECC DDR2-400 SDRAM
 Disk Subsystem: 1 x 36GB 15000RPM SCSI
 Other Hardware: None

Software

Operating System: Windows 2003 Server, Enterprise Edition
 Compiler: Intel C/C++ Compiler 8.1 (20041119Z)
 Microsoft Visual Studio .NET 2003(7.1.3088, for libraries)
 MicroQuill SmartHeap Library 7.1
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 252.eon: srcalt=stdcpp
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO
 C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -Qansi_alias -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: basepeak=yes
 186.crafty: -fast -Oa +FDO shlw32M.lib
 197.parser: basepeak=yes
 252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell	SPECint2000 =	1377
PowerEdge 6800 (3.66GHz Intel Xeon)	SPECint_base2000 =	1317

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Nov-2004

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap:      basepeak=yes
255.vortex   -fast +FDO
256.bzip2:   -fast -Qunroll11 -Oa +FDO
300.twolf:   -fast +FDO shlw32M.lib
```

This result was measured on the Dell PowerEdge 6850.
The PowerEdge 6800 and PowerEdge 6850 are electronically equivalent.