



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6800 (3.33GHz Intel Xeon)

SPECint2000 = **1479**
SPECint_base2000 = **1446**

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Nov-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	130	1076	131	1066	
175.vpr	1400	139	1007	139	1007	
176.gcc	1100	65.6	1677	65.6	1677	
181.mcf	1800	122	1471	122	1471	
186.crafty	1000	81.3	1230	80.3	1245	
197.parser	1800	136	1321	136	1321	
252.eon	1300	62.1	2094	62.4	2083	
253.perlbmk	1800	110	1634	94.6	1902	
254.gap	1100	74.9	1469	74.9	1469	
255.vortex	1900	82.0	2316	82.0	2317	
256.bzip2	1500	132	1134	132	1138	
300.twolf	3000	206	1453	182	1644	

Hardware

CPU: Intel Xeon (3.33GHz, 1MB L2, 8MB L3, 667MHz system bus)
CPU MHz: 3330
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,3,4
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: 8192KB(I+D) on chip
Other Cache: N/A
Memory: 8x2GB (dual-ranked) ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 36GB 15000RPM SCSI
Other Hardware: None

Software

Operating System: Windows 2003 Server, Enterprise Edition
Compiler: Intel C/C++ Compiler 8.1 (20041119Z)
Microsoft Visual Studio .NET 2003(7.1.3088, for libraries)
MicroQuill SmartHeap Library 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: srcalt=stdcpp
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: basepeak=yes
252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell	SPECint2000 =	1479
PowerEdge 6800 (3.33GHz Intel Xeon)	SPECint_base2000 =	1446

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Nov-2004

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap:      basepeak=yes
255.vortex   -fast +FDO
256.bzip2:   -fast -Qunroll11 -Oa +FDO
300.twolf:   -fast +FDO shlw32M.lib
```

This result was measured on the Dell PowerEdge 6850.
The PowerEdge 6800 and PowerEdge 6850 are electronically equivalent.