



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 336 (3.2 GHz Intel Xeon)

SPECfp2000 = 1672
SPECfp_base2000 = 1649

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	66.7	2398	66.7	2398	[Bar chart showing ratio 2398]			
171.swim	3100	138	2245	138	2246	[Bar chart showing ratio 2246]			
172.mgrid	1800	129	1393	129	1393	[Bar chart showing ratio 1393]			
173.applu	2100	153	1374	154	1366	[Bar chart showing ratio 1366]			
177.mesa	1400	99.7	1404	99.7	1404	[Bar chart showing ratio 1404]			
178.galgel	2900	90.9	3190	90.9	3190	[Bar chart showing ratio 3190]			
179.art	2600	69.3	3752	69.3	3752	[Bar chart showing ratio 3752]			
183.quake	1300	71.3	1822	59.9	2171	[Bar chart showing ratio 2171]			
187.facerec	1900	113	1686	113	1686	[Bar chart showing ratio 1686]			
188.amp	2200	194	1135	194	1135	[Bar chart showing ratio 1135]			
189.lucas	2000	102	1958	101	1981	[Bar chart showing ratio 1981]			
191.fma3d	2100	156	1348	156	1348	[Bar chart showing ratio 1348]			
200.sixtrack	1100	190	578	188	586	[Bar chart showing ratio 586]			
301.apsi	2600	219	1189	219	1189	[Bar chart showing ratio 1189]			

Hardware

CPU: Intel Xeon (3.2 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 512 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 8.1 (20050409)
Intel Fortran Compiler 8.1 (20050405Z)
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F32000000

BASE TUNING

C/F77/F90: -fast -QxP -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
171.swim: -fast -QxP -f77rtl +FDO
172.mgrid: basepeak=yes
173.applu: -fast -QxP -Qscalar_rep- -Qauto -f77rtl +FDO
177.mesa: basepeak=yes
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -QxP -Qansi_alias -Oa -Qrcd +FDO shlw32M.lib
187.facerec: basepeak=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 336 (3.2 GHz Intel Xeon)

SPECfp2000 = 1672

SPECfp_base2000 = 1649

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
188. ammp:      basepeak=yes
189. lucas:     -fast -QxP
191. fma3d:     basepeak=yes
200. sixtrack: -QxP -Qipo +FDO
301. apsi:     -fast -QxP -f77rtl +FDO
```