



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 336 (3.4 GHz Intel Xeon)

SPECint2000 = 1620
SPECint_base2000 = 1602

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	123	1136	124	1130	
175.vpr	1400	122	1146	122	1146	
176.gcc	1100	57.4	1917	57.4	1917	
181.mcf	1800	98.6	1826	98.6	1826	
186.crafty	1000	79.0	1266	78.8	1270	
197.parser	1800	129	1393	129	1393	
252.eon	1300	62.5	2079	61.9	2100	
253.perlbmk	1800	102	1771	91.0	1977	
254.gap	1100	60.4	1820	60.4	1820	
255.vortex	1900	72.8	2610	72.8	2612	
256.bzip2	1500	125	1203	123	1217	
300.twolf	3000	178	1688	177	1692	

Hardware

CPU: Intel Xeon (3.4 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 512 MB ECC PC2-3200 Single Rank
 Disk Subsystem: 73GB SCSI 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
 Compiler: Intel C/C++ Compiler 8.1 (20050409)
 Intel Fortran Compiler 8.1 (20050405Z)
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.30
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -QxP -Qansi_alias +FDO
 C++: -QxP -Qipo -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -QxP -Qansi_alias -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: basepeak=yes
 186.crafty: -fast -QxP -Oa +FDO shlW32M.lib
 197.parser: basepeak=yes
 252.eon: -fast -QxP +FDO
 253.perlbmk: -fast -QxP -Qansi_alias +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 336 (3.4 GHz Intel Xeon)

SPECint2000 = 1620

SPECint_base2000 = 1602

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    -fast -QxP +FDO
256.bzip2:    -fast -QxP -Qunroll1 -Oa +FDO
300.twolf:    -fast -QxP +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.3
              www.microquill.com
```