



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 525

SPECfp_rate_base2000 = 441

SPEC license #: 19 Tested by: Fujitsu Limited Test date: May-2005 Hardware Avail: Jun-2005 Software Avail: Sep-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	32	173	343	32	148	400
171.swim	32	645	178	32	123	939
172.mgrid	32	399	167	32	390	172
173.applu	32	179	434	32	159	491
177.mesa	32	137	380	32	115	452
178.galgel	32	64.9	1658	32	55.0	1958
179.art	32	13.2	7296	32	12.8	7519
183.quake	32	137	353	32	136	356
187.facerec	32	116	609	32	115	615
188.amp	32	166	493	32	155	526
189.lucas	32	382	194	32	377	197
191.fma3d	32	355	220	32	355	220
200.sixtrack	32	160	256	32	159	257
301.apsi	32	215	448	32	215	448

Hardware

CPU: SPARC64 V
CPU MHz: 2160
FPU: Integrated
CPU(s) enabled: 32 cores, 32 chips, 1 core/chip
CPU(s) orderable: 1 to 32 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 4MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 65536MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 9 9/04
Compiler: (Fortran)
Fujitsu Parallelnavi 2.3 with patch 913221-03
Sun Studio 9
Sun Performance Library 9
(C)
Sun Studio 9
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.3)
fdo_pre0=rm -rf `pwd`/*.f.d
PASS1=-Kpg
PASS2=-Kpu
FDO: (for Sun Studio 9)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Floating point base flags:
(using Fortran compiler of Sun Studio 9)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C compiler of Sun Studio 9)
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO
```

Floating point peak flags:



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 525
SPECfp_rate_base2000 = 441

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2005 | Hardware Avail: Jun-2005 | Software Avail: Sep-2004

Notes/Tuning Information (Continued)

(using Fortran compiler of Parallelnavi 2.3)

168.wupwise: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=1 -Qoption iropt -Ainline:inc=800:cp=1 ONESTEP=yes FDO
172.mgrid: -Kfast_GP2=3,GREG_SYSTEM -O3 -Kcommonpad=180,alignc=64
189.lucas: -Kfast_GP2=3 -O5 -x dir=./ -Kunroll=2 FDO

(using Fortran compiler of Sun Studio 9)

171.swim: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xpad=common:1700 -Qoption iropt -Ainline:cs=700,-Atile:skewp:b10
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -Qoption cg -Qlp=1-av=192-t=4-fa=1-fl=0
-Qoption iropt -Aujam:inner=g ONESTEP=yes FDO
178.galgel: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
RM_SOURCES=lapak.f90 ONESTEP=yes FDO
187.facerec: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xprefetch=latx:1.6 ONESTEP=yes FDO
191.fma3d: basepeak=yes
200.sixtrack: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=1 ONESTEP=yes FDO
301.apsi: basepeak=yes

(using C compiler of Sun Studio 9)

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xchip=ultra2 -xalias_level=strong -xipo=2 -xrestrict
ONESTEP=yes FDO
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 ONESTEP=yes FDO
183.quake: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -W2,-whole -Wc,-Qms_pipe-pref,
-Qlp=1-av=512-t=6-fa=1-fl=1 ONESTEP=yes FDO
188.ammp: -fast -xalias_level=std -xipo=2 ONESTEP=yes FDO

Portability:

178.galgel: -e -fixed

System Tunables:

(for /etc/system)
set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400
set memscrub_period_sec=172800

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

Processes were bound to CPUs using "submit=pbind".

Extended Interleave Mode enabled.

Sun Studio 9, posted at URL <http://www.sun.com/software/products/studio/previous/9/index.xml>
was used for this submission.