



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

PDSLA/E Motherboard(Intel Pentium D 3.2GHz)

SPECfp_rate2000 = 28.6

SPECfp_rate_base2000 = 28.5

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	75.2	49.4	2	74.7	49.7
171.swim	2	252	28.5	2	249	28.8
172.mgrid	2	160	26.2	2	158	26.4
173.applu	2	199	24.4	2	192	25.4
177.mesa	2	98.8	32.9	2	98.8	32.9
178.galgel	2	169	39.9	2	168	40.0
179.art	2	152	39.6	2	152	39.6
183.quake	2	105	28.6	2	108	27.9
187.facerec	2	128	34.3	2	129	34.1
188.amp	2	261	19.6	2	254	20.1
189.lucas	2	174	26.6	2	176	26.4
191.fma3d	2	175	27.8	2	175	27.8
200.sixtrack	2	193	13.2	2	191	13.3
301.apsi	2	230	26.2	2	230	26.2

Hardware

CPU: Intel Pentium D 3.2GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 X 1GB PC2 5300, Unbuffered, Non-ECC
 Disk Subsystem: 1 X 120GB IDE
 Other Hardware: N/A

Software

Operating System: Windows XP Professional SP2
 Compiler: Intel C++ and Fortran Compiler 8.1 Build 20040802Z
 Microsoft Visual Studio .Net 2003(for libraries)
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -fast -Qansi_alias +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

PDSLA/E Motherboard(Intel Pentium D 3.2GHz)

SPECfp_rate2000 = 28.6

SPECfp_rate_base2000 = 28.5

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

The system bus runs at 800 MHz

Tested system was built with SC733T-645 chassis and

a 420W (minimum) ATX power supply [4-pin +12V AND (20 or 24-pin)] is required.

See: <http://www.supermicro.com/products/motherboard/DualCore/945/PDSLA.cfm>