



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries HS20 (2.0 GHz Xeon LV, 2MB L2 Shared Cache)

SPECfp2000 = 1397

SPECfp_base2000 = 1370

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	97.6	1639	97.6	1639	
171.swim	3100	194	1597	194	1597	
172.mgrid	1800	163	1102	163	1102	
173.applu	2100	183	1145	185	1137	
177.mesa	1400	87.7	1596	87.6	1598	
178.galgel	2900	99.1	2926	99.1	2926	
179.art	2600	91.5	2843	91.5	2843	
183.quake	1300	84.7	1535	64.5	2015	
187.facerec	1900	126	1513	125	1517	
188.amp	2200	244	900	244	900	
189.lucas	2000	132	1519	131	1523	
191.fma3d	2100	193	1088	193	1088	
200.sixtrack	1100	217	507	217	507	
301.apsi	2600	243	1068	243	1068	

Hardware

CPU: Dual-Core Intel Processor Xeon LV 2.0GHz (667 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) shared by 2 cores
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 2048 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20051130Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20051120Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F32000000

BASE TUNING

C/F77/F90: -fast -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
171.swim: -fast -f77rtl +FDO
172.mgrid: basepeak=yes
173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO
177.mesa: -fast +FDO
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries HS20 (2.0 GHz Xeon LV, 2MB L2 Shared Cache)

SPECfp2000 = 1397

SPECfp_base2000 = 1370

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

Notes/Tuning Information (Continued)

188. ammp: basepeak=yes
189. lucas: -fast
191. fma3d: basepeak=yes
200. sixtrack: -Qipo +FDO
301. apsi: basepeak=yes