



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge SC430 (3.4GHz Intel Pentium D 950)

SPECfp_rate2000 = 36.4
SPECfp_rate_base2000 = 36.3

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Mar-2006 | Hardware Avail: Apr-2006 | Software Avail: Oct-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	67.2	55.2	2	67.2	55.2
171.swim	2	220	32.7	2	220	32.7
172.mgrid	2	142	29.5	2	142	29.5
173.applu	2	172	28.3	2	168	29.0
177.mesa	2	94.4	34.4	2	94.4	34.4
178.galgel	2	88.9	75.7	2	88.9	75.7
179.art	2	69.6	86.6	2	69.6	86.6
183.equake	2	69.0	43.7	2	69.1	43.7
187.facerec	2	104	42.4	2	104	42.4
188.amp	2	200	25.5	2	198	25.8
189.lucas	2	145	32.0	2	145	32.0
191.fma3d	2	169	28.9	2	169	28.9
200.sixtrack	2	162	15.7	2	162	15.7
301.apsi	2	207	29.2	2	207	29.2

Hardware

CPU: Intel Pentium D 950 (3.4GHz, 2x2M L2, 800MHz system bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 512MB (dual-ranked) ECC 533MHz DDR2 SDRAM
Disk Subsystem: 1 x 36GB SCSI 15000 RPM
Other Hardware: None

Software

Operating System: Windows 2003 Server, Standard Edition, Service Pack 1
Compiler: Intel C/C++ Compiler 9.0 for IA32(20051020Z)
Intel Fortran Compiler 9.0 for IA32(20051020Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F32000000

BASE TUNING

FORTRAN: -fast -Qansi_alias +FDO
177.mesa: -fast +FDO shlW32M.lib
179.art: -fast +FDO shlW32M.lib
183.equake: -fast +FDO shlW32M.lib
188.amp: -fast +FDO shlW32M.lib

PEAK TUNING

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: basepeak=yes
173.applu: -fast -Qansi_alias -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge SC430 (3.4GHz Intel Pentium D 950)

SPECfp_rate2000 = 36.4

SPECfp_rate_base2000 = 36.3

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Mar-2006 | Hardware Avail: Apr-2006 | Software Avail: Oct-2005

Notes/Tuning Information (Continued)

```
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlW32M.lib
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: -fast -Oa shlW32M.lib
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: -fast +FDO
301.apsi: basepeak=yes
```