



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECfp_rate2000 = 56.6

SPECfp_rate_base2000 = 50.9

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2006 Hardware Avail: May-2006 Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	52.8	70.3	2	50.1	74.1
171.swim	2	65.9	109	2	63.5	113
172.mgrid	2	93.3	44.8	2	87.4	47.8
173.applu	2	88.2	55.2	2	80.4	60.6
177.mesa	2	82.1	39.6	2	63.5	51.1
178.galgel	2	82.4	81.6	2	58.4	115
179.art	2	107	56.4	2	103	58.5
183.equake	2	68.3	44.1	2	63.3	47.7
187.facerec	2	60.8	72.5	2	42.7	103
188.amp	2	139	36.7	2	139	36.7
189.lucas	2	105	44.1	2	105	44.1
191.fma3d	2	109	44.7	2	106	46.1
200.sixtrack	2	141	18.1	2	137	18.6
301.apsi	2	111	54.5	2	100	60.1

Hardware

CPU: AMD Opteron (TM) 256
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2 (order by # of chips)
Parallel: No
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1024KB (I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16GB (8x2GB, PC3200 CL3 DDR ECC Registered SDRAM)
Disk Subsystem: SAS,36GB,10K RPM
Other Hardware: None

Software

Operating System: Solaris 10 1/06
Compiler: Sun Studio 11
File System: ufs
System State: Multi-user

Notes/Tuning Information

Compiler invocation:

C: cc
F90: f90
F77: f90

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile

Floating point base flags:

F90: -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 ONESTEP=yes
C: -fast -xcrossfile -xalias_level=std -xpagesize=2m ONESTEP=yes

Floating point peak flags:

ONESTEP=yes for all benchmarks

168.wupwise: -fast -xautopar -xpad=common:3969 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xpagesize_heap=2m
171.swim: -fast -xpad=common:3969 -xipo=2 -xvector=simd -xprefetch_level=3 -Qoption iropt



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECfp_rate2000 = 56.6

SPECfp_rate_base2000 = 50.9

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Mar-2006 | Hardware Avail: May-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

```

-Atile:skewp,-Ainline:cs=700 -xarch=amd64 -Qoption ube_ipa -inl_alt
-xpagesize_stack=2m
172.mgrid: -fast -xautopar -stackvar -xpad=common:900 -xipo=2 -xarch=amd64 -xprefetch_level=3
-xvector -xpagesize=2m -Qoption ld -M,/usr/lib/ld/map.bssalign
173.applu: -fast -xautopar -unroll=5 -stackvar -x04 -xipo=2 -xprefetch_level=3 -xarch=amd64a
-qoption iropt -Rloop_dist -xpagesize_heap=2m
177.mesa: -fast -xautopar -x04 -xipo=2 -Wd,-iropt-prof -xarch=amd64 -xalias_level=strong -xpagesize=2m +FDO
178.galgel: -fast -xcache=64/32/4:1024/64/4 -xcrossfile -xpagesize_heap=2m -xprefetch_level=3 -xvector=simd -xarch=amd64
RM_SOURCES=lapak.f90
EXTRALIBS=-xlic_lib=sunperf
179.art: -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m
183.quake: -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m -lmopt -lm +FDO
187.facerec: -fast -x04 -xipo=2 -xprefetch_level=3 -xpagesize=2m
RM_SOURCES=cfftb.f90 cffti.f90 cfftf.f90
EXTRALIBS=-xlic_lib=sunperf
188.amp: -fast -xcache=64/32/4:1024/64/4 -x04 -xipo=2 -xarch=amd64a -xalias_level=std -xpagesize_heap=2m -lmopt -lm
189.lucas: -fast -Qoption ube_ipa -inl_alt -xipo=2 -xarch=amd64 -xprefetch_level=3
191.fma3d: -fast -xcache=64/32/4:1024/64/4 -unroll=5 -fsimple=1 -xipo=2
-xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m +FDO
200.sixtrack: -fast -xipo=2 -O -xprefetch_level=3 -xarch=amd64
-xpagesize_heap=2m -Qoption ld -M,/usr/lib/ld/map.bssalign +FDO
301.apsi: -fast -x04 -xipo=2 -xprefetch_level=3 -xarch=amd64a -xpagesize=2m

```

Portability:
178.galgel: -fixed

Shell Environments:
Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):
autoup=900
tune_t_fsflushr=1

Processes were bound to CPUs using submit=pbind
Default BIOS setting was used

This result was measured on the Sun Fire X4200. In addition,
Sun has submitted the same result for the Sun Fire X4100, which is
electronically equivalent to the Sun Fire X4200.