



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5050 processor, 3.0 GHz

SPECint\_rate2000 = 32.9

SPECint\_rate\_base2000 = 32.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jun-2006 | Software Avail: Oct-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	217	29.9	4	217	29.9
175.vpr	4	311	20.9	4	311	20.9
176.gcc	4	113	45.1	4	113	45.1
181.mcf	4	466	17.9	4	466	17.9
186.crafy	4	180	25.8	4	180	25.8
197.parser	4	253	33.0	4	253	33.0
252.eon	4	138	43.7	4	138	43.7
253.perlbnk	4	218	38.3	4	218	38.3
254.gap	4	142	35.9	4	142	35.9
255.vortex	4	163	54.2	4	163	54.2
256.bzip2	4	256	27.2	4	256	27.2
300.twolf	4	335	41.5	4	335	41.5

### Hardware

CPU: Intel Xeon 5050 processor (3.0 GHz, 2x2MB L2, 667 MHz system bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip, per core  
Secondary Cache: 2048KB(I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)  
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1  
Compiler: Intel C++ Compiler 9.0  
Build 20051020Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafy: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 667 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon 5050 processor, 3.0 GHz

SPECint\_rate2000 = 32.9

SPECint\_rate\_base2000 = 32.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jun-2006 | Software Avail: Oct-2005

## Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>