



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp_rate2000 = **59.0**
SPECfp_rate_base2000 = **58.8**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	199	74.5	8	200	74.3
171.swim	8	802	35.9	8	802	35.9
172.mgrid	8	497	33.6	8	496	33.7
173.applu	8	549	35.5	8	549	35.5
177.mesa	8	118	110	8	116	112
178.galgel	8	145	186	8	145	186
179.art	8	259	93.2	8	259	93.2
183.quake	8	266	45.4	8	266	45.3
187.facerec	8	287	61.3	8	287	61.3
188.amp	8	359	56.8	8	351	58.1
189.lucas	8	512	36.2	8	512	36.3
191.fma3d	8	450	43.3	8	450	43.3
200.sixtrack	8	190	53.6	8	190	53.6
301.apsi	8	330	73.1	8	330	73.1

Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2048MB PC2-3200 dual-rank
Disk Subsystem: 1x36GB SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for Fortran programs: -fast -Qansi_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes

188.amp: -fast -Qansi_alias +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp_rate2000 = 59.0

SPECfp_rate_base2000 = 58.8

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled