



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Supermicro

Motherboard X7DA8 ( 3.00GHz, Intel Xeon 5160 processor)

SPECfp\_rate2000 = 78.9

SPECfp\_rate\_base2000 = 78.9

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

250      200      150      100      50					Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					168.wupwise	4	69.7	106	4	69.8	106
					171.swim	4	286	50.2	4	286	50.2
					172.mgrid	4	199	41.9	4	198	42.2
					173.applu	4	191	51.0	4	191	51.0
					177.mesa	4	49.7	131	4	49.7	131
					178.galgel	4	56.6	238	4	56.6	238
					179.art	4	53.0	228	4	53.0	228
					183.quake	4	95.0	63.5	4	95.1	63.5
					187.facerec	4	89.5	98.5	4	88.6	99.5
					188.amp	4	146	70.0	4	148	68.9
					189.lucas	4	167	55.4	4	168	55.4
					191.fma3d	4	170	57.3	4	170	57.3
					200.sixtrack	4	93.7	54.5	4	95.2	53.6
					301.apsi	4	203	59.4	4	201	60.0

### Hardware

CPU: Intel Xeon 5160 processor ( 3.00 GHz, 4MB L2 shared, 1333 MHz bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1, 2  
Parallel: No  
Primary Cache: 32KBI + 32KBD on chip per core  
Secondary Cache: 4MB(I+D) on chip shared  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x 2GB 667MHz CL5 DDR2 FB-DIMM  
Disk Subsystem: 1 X WD 2500 250GB SATA  
Other Hardware: N/A

### Software

Operating System: Windows server 2003 Enterprise Edition 32-bits W/ SP1  
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_FC\_P\_9.1.020  
Microsoft Visual Studio 2005 (for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast +FDO shlw32M.lib
Base tuning for 179.art: -fast +FDO shlw32M.lib
Base tuning for 183.quake: -fast +FDO shlw32M.lib
Base tuning for 188.amp: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlw32M.lib
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Supermicro**

Motherboard X7DA8 ( 3.00GHz, Intel Xeon 5160 processor)

SPECfp\_rate2000 = 78.9

SPECfp\_rate\_base2000 = 78.9

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO
```

Tested systems can be used with SC825S2-R700LPV case,  
To ensure system stability, a 500W (minimum) ATX power supply  
[4-pin (+12V), 8-pin (+12V) and 24-pin are required]

Product description located as of X7DA8:

<http://www.supermicro.com/products/motherboard/Xeon1333/5000X/X7DA8.cfm>

The system bus runs at 1333 MHz