



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp\_rate2000 = 30.8  
SPECfp\_rate\_base2000 = 29.3

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	78.1	47.5	2	78.1	47.5
171.swim	2	284	25.3	2	282	25.5
172.mgrid	2	183	22.9	2	183	22.8
173.applu	2	211	23.1	2	165	29.5
177.mesa	2	95.7	33.9	2	89.2	36.4
178.galgel	2	119	56.5	2	119	56.5
179.art	2	72.0	83.8	2	72.0	83.8
183.quake	2	135	22.3	2	106	28.6
187.facerec	2	157	28.2	2	135	32.6
188.amp	2	210	24.3	2	210	24.3
189.lucas	2	190	24.4	2	191	24.3
191.fma3d	2	189	25.8	2	189	25.8
200.sixtrack	2	189	13.5	2	189	13.5
301.apsi	2	235	25.7	2	239	25.2

### Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)  
CPU(s) orderable: 1,2,4  
Parallel: No  
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core  
Secondary Cache: 2048KB(I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16x2048MB PC2-3200 ECC Dual-rank  
Disk Subsystem: 1x36GB 10K SAS  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
SuSE kernel 2.6.5-7.244-smp  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch Ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp\_rate2000 = 30.8  
SPECfp\_rate\_base2000 = 29.3

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```

177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t
188.ammp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t

```

### BIOS Configuration Notes

Hyper-Threading Technology disabled  
Adjacent Sector Prefetch disabled