



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL480c (3.0GHz, Intel Xeon processor 5160)

SPECfp\_rate2000 = 82.3  
SPECfp\_rate\_base2000 = 81.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	68.1	109	4	68.1	109
171.swim	4	263	54.7	4	263	54.6
172.mgrid	4	166	50.4	4	166	50.4
173.applu	4	184	52.8	4	184	52.8
177.mesa	4	50.1	130	4	51.0	127
178.galgel	4	58.0	232	4	58.0	232
179.art	4	59.1	204	4	59.1	204
183.quake	4	84.8	71.1	4	85.0	71.0
187.facerec	4	89.8	98.2	4	90.9	97.0
188.amp	4	146	70.0	4	118	86.4
189.lucas	4	171	54.3	4	170	54.5
191.fma3d	4	159	61.4	4	159	61.4
200.sixtrack	4	94.4	54.1	4	94.3	54.1
301.apsi	4	191	63.2	4	191	63.2

### Hardware

CPU: Intel Xeon processor 5160 (3.0GHz, 4MB L2 shared, 1333MHz bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KBI + 32KBD (on chip) per core  
Secondary Cache: 4096KB(I+D) (on chip) shared  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1024MB PC2-5300F  
Disk Subsystem: 2x36GB 10K SAS  
Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)  
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

Base tuning for Fortran programs: -fast -Qansi\_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi\_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi\_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar\_rep- +FDO ONESTEP=yes



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL480c (3.0GHz, Intel Xeon processor 5160)

SPECfp\_rate2000 = 82.3

SPECfp\_rate\_base2000 = 81.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

188. ammp: -fast -Qansi\_alias +FDO  
189. lucas: -fast  
191. fma3d: basepeak=1  
200. sixtrack: -fast +FDO  
301. psi: basepeak=1

### BIOS Configuration Notes

Power Regulator set to Static High  
Adjacent Sector Prefetch disabled