



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec ZX440 (Intel Xeon 7110M processor)

SPECint_rate2000 = 107

SPECint_rate_base2000 = 107

SPEC license #: 9001 | Tested by: Itautec | Test date: Dec-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	259	100	16	259	100
175.vpr	16	381	68.1	16	381	68.1
176.gcc	16	143	143	16	143	143
181.mcf	16	592	56.4	16	592	56.4
186.crafy	16	213	87.0	16	213	87.0
197.parser	16	313	107	16	313	107
252.eon	16	139	174	16	139	174
253.perlbnk	16	271	123	16	271	123
254.gap	16	183	111	16	183	111
255.vortex	16	199	177	16	199	177
256.bzip2	16	319	87.3	16	319	87.3
300.twolf	16	480	116	16	480	116

Hardware

CPU: Intel Xeon 7110M processor (2.60 GHz, 2x1MB L2, 4MB L3, 800 MHz system bus)
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2,3,4
Parallel: No
Primary Cache: 12k(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: 4MB on chip, per chip
Other Cache: N/A
Memory: 16x1GB DDR2-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem: 1 x 36GB SCSI 10000RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
Microquill SmartHeap Library v.8.0 for SMP
File System: NTFS
System State: Default

Notes/Tuning Information

```
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

```
for C programs: -fast +FDO shlSMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO shlSMPMt.lib
```

EXTRA LIBRARIES

MicroQuill SmartHeap Library v.8.0 for SMP
<http://www.microquill.com>

Bios Settings:

Hardware Prefetch enabled:
prefetch data in order to shorten execution cycles and maximize
data processing efficiency.



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec ZX440 (Intel Xeon 7110M processor)

SPECint_rate2000 = 107

SPECint_rate_base2000 = 107

SPEC license #: 9001 | Tested by: Itautec | Test date: Dec-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

Snoop Filter enabled:

Preserves cache coherency while minimizing snoops to remote nodes.

Memory Array set to High-Performance Memory Array:

Memory is up to 4-way interleaved (Memory RAID disabled).