



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Bull

NovaScale B260 (Intel Xeon processor 5110, 1.60 GHz)

SPECfp_rate2000 = 51.9

SPECfp_rate_base2000 = 51.4

SPEC license #: 20 | Tested by: Bull | Test date: Dec-2006 | Hardware Avail: Dec-2006 | Software Avail: Dec-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	93.6	79.3	4	93.6	79.3
171.swim	4	387	37.2	4	387	37.2
172.mgrid	4	240	34.8	4	240	34.8
173.applu	4	298	32.7	4	298	32.7
177.mesa	4	97.4	66.7	4	97.3	66.7
178.galgel	4	102	132	4	102	132
179.art	4	89.1	135	4	89.1	135
183.equake	4	120	50.2	4	120	50.2
187.facerec	4	144	61.3	4	144	61.3
188.amp	4	238	42.9	4	207	49.4
189.lucas	4	259	35.8	4	259	35.8
191.fma3d	4	250	38.9	4	250	38.9
200.sixtrack	4	175	29.2	4	175	29.2
301.apsi	4	289	41.8	4	289	41.8

Hardware

CPU: Intel Xeon Processor 5110 (1.60 GHz, 4MB L2, 1066MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1 to 2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip per chip (shared by 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8GB (2GB DIMMx4, FB-DIMM PC2-5300F ECC CL5)
Disk Subsystem: 1x73GB SAS 10000 rpm
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits), Service Pack 1
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20061103Z Package ID: W_CC_C_9.1.033
Intel(R) Fortran Compiler for 32-bit app., Version 9.1, - Build 20061103Z Package ID: W_FC_C_9.1.033
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:

178.galgel: -FI /F32000000

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
-fast +FDO ONESTEP=yes shlW32M.lib
for Fortran programs:
-fast -Qansi_alias +FDO

Peak Tuning Flags:

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: basepeak=yes
173.applu: basepeak=yes



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Bull

NovaScale B260 (Intel Xeon processor 5110, 1.60 GHz)

SPECfp_rate2000 = 51.9

SPECfp_rate_base2000 = 51.4

SPEC license #: 20 | Tested by: Bull | Test date: Dec-2006 | Hardware Avail: Dec-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

```
177.mesa: -fast +FDO ONESTEP=yes
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: basepeak=yes
187.facerec: basepeak=yes
188.ammp: -fast +FDO ONESTEP=yes
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes
```

Other Configuration Notes

For information about Bull please see:
<http://www.bull.com>