



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3200 (2.4 GHz Xeon X3220, 8MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 64.2

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jan-2007 | Hardware Avail: Feb-2007 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	87.5	84.8			
171.swim	4	395	36.4			
172.mgrid	4	239	34.9			
173.applu	4	272	35.8			
177.mesa	4	61.1	106			
178.galgel	4	75.3	179			
179.art	4	68.0	177			
183.quake	4	114	53.0			
187.facerec	4	105	84.0			
188.amp	4	162	63.2			
189.lucas	4	236	39.3			
191.fma3d	4	206	47.4			
200.sixtrack	4	117	43.6			
301.apsi	4	177	68.3			

Hardware

CPU: Intel Xeon processor X3220 (2.4 GHz, 1066 MHz bus)
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 2048 MB ECC PC2-5300
 Disk Subsystem: 80GB SATA 7200 RPM
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005 (for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```