



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(3.4 GHz, Intel(R) Pentium(TM) D processor 950)

SPECfp2000 = 2055

SPECfp_base2000 = 2048

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	40.4	3963	40.4	3963	
171.swim	3100	108	2867	108	2867	
172.mgrid	1800	117	1539	117	1539	
173.applu	2100	114	1836	114	1836	
177.mesa	1400	95.4	1468	95.4	1468	
178.galgel	2900	80.1	3621	80.1	3621	
179.art	2600	51.7	5033	51.7	5033	
183.earthquake	1300	42.7	3044	41.3	3148	
187.facerec	1900	92.6	2052	92.5	2054	
188.ammmp	2200	177	1245	175	1256	
189.lucas	2000	87.9	2276	87.9	2276	
191.fma3d	2100	128	1635	128	1635	
200.sixtrack	1100	163	676	163	675	
301.apsi	2600	191	1364	191	1364	

Hardware

CPU: Intel(R) Pentium(TM) D processor 950(3.4 GHz, 800 MHz bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K micro-opsI + 16KBD per core, on chip
Secondary Cache: 2 MB(I+D) per core, on chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: SoundBlaster Live! PCI card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Package IDs: W_CC_P_9.1.020 and W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast +FDO shlw32M.lib
Base tuning for 179.art: -fast +FDO shlw32M.lib
Base tuning for 183.earthquake: -fast +FDO shlw32M.lib
Base tuning for 188.ammmp: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.earthquake: -QxP -Oa -Qrcd -Qipo +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(3.4 GHz, Intel(R) Pentium(TM) D processor 950)

SPECfp2000 = 2055

SPECfp_base2000 = 2048

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO
```

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 1/2007:

<http://www.intel.com/products/motherboard/DG965WH/index.htm>

The system bus runs at 1066 MHz