



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon processor E5345, 2.33 GHz)

SPECfp_rate2000 = 82.5

SPECfp_rate_base2000 = 82.5

SPEC license #: 9001 | Tested by: Itautec | Test date: Feb-2007 | Hardware Avail: Feb-2007 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	150	99.0	8	150	99.0
171.swim	8	692	41.6	8	692	41.6
172.mgrid	8	421	39.6	8	421	39.6
173.applu	8	519	37.6	8	519	37.6
177.mesa	8	67.8	192	8	67.8	192
178.galgel	8	102	263	8	102	263
179.art	8	116	209	8	116	209
183.equake	8	188	64.1	8	188	64.1
187.facerec	8	177	99.5	8	177	99.5
188.amp	8	209	97.9	8	209	97.9
189.lucas	8	442	42.0	8	442	42.0
191.fma3d	8	366	53.3	8	366	53.3
200.sixtrack	8	122	83.5	8	122	83.5
301.apsi	8	269	89.9	8	269	89.9

Hardware

CPU: Intel Xeon processor E5345 (2.33 GHz, 2x4MB L2, 1333 MHz system bus)
CPU MHz: 2330
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: 1 x 80GB SATA 7200RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries)
Microquill SmartHeap Library v.8.0 for SMP
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

Basepeak=yes is used for all programs
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

178.galgel: -FI /F32000000

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO
for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap Library v.8.0 for SMP
<http://www.microquill.com>