



SPEC® CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X


(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Oct-2016
Hardware Availability: Jun-2016
Software Availability: Sep-2016



Hardware

CPU Name: Intel Xeon E7-8890 v4
 Max MHz.: 3400
 Nominal: 2200
 Enabled: 384 cores, 16 chips, 2 threads/core
 Orderable: 2 to 16 chips
 Cache L1: 32 KB I + 32 KB D on chip per core
 L2: 256 KB I+D on chip per core
 L3: 60 MB I+D on chip per chip
 Other: None
 Memory: 4 TB (128 x 32 GB 2Rx4 PC4-2400T-L, running at 1600)
 Storage: 8 x C8S59A, 900 GB 10 K RPM SAS
 Other: None

Software

OS: SUSE Linux Enterprise Server 12 (x86_64) SP1
 Kernel 3.12.53-60.30-default
 Compiler: C/C++: Version 17.0.0.098 of Intel C/C++ Compiler for Linux;
 Fortran: Version 17.0.0.098 of Intel Fortran Compiler for Linux
 Parallel: No
 Firmware: HP Bundle: 008.004.084 SFW: 043.025.000 08/16/2016
 File System: xfs
 System State: Run level 5 (multi-user, w/GUI)
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other: Microquill SmartHeap V10.2



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Oct-2016
Hardware Availability: Jun-2016
Software Availability: Sep-2016

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
603.bwaves_s	384	2284	25.8	<u>2273</u>	<u>26.0</u>	2262	26.1	384	<u>2116</u>	<u>27.9</u>	2131	27.7	2102	28.1
607.cactuBSSN_s	384	4675	3.57	4682	3.56	<u>4678</u>	<u>3.56</u>	384	<u>4475</u>	<u>3.73</u>	4476	3.72	4474	3.73
619.lbm_s	384	2475	2.12	2486	2.11	<u>2482</u>	<u>2.11</u>	384	<u>920</u>	<u>5.70</u>	920	5.70	914	5.73
621.wrf_s	384	1557	8.50	1569	8.43	<u>1566</u>	<u>8.45</u>	384	<u>1370</u>	<u>9.65</u>	1370	9.66	1370	9.65
627.cam4_s	384	<u>2154</u>	<u>4.12</u>	2151	4.12	2158	4.11	384	2037	4.35	2045	4.33	<u>2039</u>	<u>4.35</u>
628.pop2_s	384	<u>2465</u>	<u>4.82</u>	2462	4.82	2465	4.82	384	1809	6.56	<u>1809</u>	<u>6.56</u>	1805	6.58
638.imagick_s	384	<u>7517</u>	<u>1.92</u>	7488	1.93	7534	1.91	384	6573	2.19	6640	2.17	<u>6609</u>	<u>2.18</u>
644.nab_s	384	<u>2061</u>	<u>8.48</u>	2060	8.48	2063	8.47	384	<u>1753</u>	<u>9.97</u>	1757	9.94	1752	9.97
649.fotonik3d_s	384	1416	6.44	<u>1450</u>	<u>6.29</u>	1495	6.10	384	<u>1383</u>	<u>6.59</u>	1384	6.59	1375	6.63
654.roms_s	384	2640	5.96	<u>2638</u>	<u>5.97</u>	2638	5.97	384	2155	7.30	<u>2150</u>	<u>7.32</u>	2146	7.34

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
intel_idle.max_cstate=3 appended in kernel command line
Power profile set with:
  cpupower -c all frequency-set -g performance
Setting the value of perf-bias:
  cpupower set -b 0
Tuned profile set with:
  tuned-adm profile throughput-performance
Transparent Huge Pages enabled by default
```

General Notes

```
Environment variables set by runcpu before the start of the run:
KMP_AFFINITY = "granularity=fine,compact,1,0"
LD_LIBRARY_PATH = "/spec/cpu2017/lib/ia32:/spec/cpu2017/lib/intel64:/spec/cpu2017/sh10.2"
OMP_NUM_THREADS = "%{cores}"
OMP_STACKSIZE = "192M"
```

Binaries compiled on a system with 1x Intel Core i7-4790K CPU + 32GB RAM memory using Redhat Enterprise Linux 7.2

Platform Notes

```
Firmware settings:
Memory RAS Configuration set to Maximum Performance
Sysinfo program /spec/cpu2017/Docs/sysinfo
r4696 of 2016-07-28 da95b61906f345a0d9942e915810c155
```

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Platform Notes (Continued)

running on hawk049os1 Sat Oct 15 01:24:42 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E7-8890 v4 @ 2.20GHz

16 "physical id"s (chips)

768 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 24

siblings : 48

physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 2: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 3: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 4: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 5: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 6: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 7: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 8: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 9: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 10: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 11: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 12: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 13: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 14: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

physical 15: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Platform Notes (Continued)

cache size : 61440 KB

From /proc/meminfo

MemTotal: 4235891396 kB

HugePages_Total: 0

Hugepagesize: 2048 kB

/usr/bin/lsb_release -d

SUSE Linux Enterprise Server 12 SP1

From /etc/*release* /etc/*version*

SuSE-release:

SUSE Linux Enterprise Server 12 (x86_64)

VERSION = 12

PATCHLEVEL = 1

This file is deprecated and will be removed in a future service pack or release.

Please check /etc/os-release for details about this release.

os-release:

NAME="SLES"

VERSION="12-SP1"

VERSION_ID="12.1"

PRETTY_NAME="SUSE Linux Enterprise Server 12 SP1"

ID="sles"

ANSI_COLOR="0;32"

CPE_NAME="cpe:/o:suse:sles:12:sp1"

uname -a:

Linux hawk049os1 3.12.53-60.30-default #1 SMP Wed Feb 10 14:41:46 UTC 2016 (e57129f) x86_64 x86_64 x86_64 GNU/Linux

run-level 5 Oct 14 14:07

SPEC is set to: /spec/cpu2017

Filesystem	Type	Size	Used	Avail
------------	------	------	------	-------

Use% Mounted on

/dev/mapper/3600c0ff0001e1834e672ee5701000000-part1	xfs	1.9T	64G	1.8T
---	-----	------	-----	------

4% /spec

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP Bundle: 008.004.084 SFW: 043.025.000 08/16/2016

Memory:

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Platform Notes (Continued)

128x HP HMA84GL7MFR4N-UH 32 GB 2 rank 1067 MHz, configured at 1600 MHz
256x not defined not defined

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 4 TB and the dmidecode description should have one line reading as:

128x HP HMA84GL7MFR4N-UH 32 GB 2 rank 1067 MHz, configured at 1600 MHz

Compiler Version Notes

```
=====  
CC 607.cactuBSSN_s(base, peak) 619.lbm_s(base, peak) 621.wrf_s(base, peak)  
627.cam4_s(base, peak) 628.pop2_s(base, peak) 638.imagick_s(base, peak)  
644.nab_s(base, peak)  
-----
```

icc (ICC) 17.0.0 20160721

Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

```
=====  
CXXC 607.cactuBSSN_s(base, peak)  
-----
```

icpc (ICC) 17.0.0 20160721

Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

```
=====  
FC 603.bwaves_s(base, peak) 607.cactuBSSN_s(base, peak) 621.wrf_s(base,  
peak) 627.cam4_s(base, peak) 628.pop2_s(base, peak)  
649.fotonik3d_s(base, peak) 654.roms_s(base, peak)  
-----
```

ifort (IFORT) 17.0.0 20160721

Copyright (C) 1985-2016 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

icc -m64 -std=c11

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

ifort -m64 icc -m64 -std=c11

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Base Compiler Invocation (Continued)

Benchmarks using Fortran, C, and C++:

```
icpc -m64 icc -m64 -std=c11 ifort -m64
```

Base Portability Flags

```
603.bwaves_s: -DSPEC_LP64
607.cactuBSSN_s: -DSPEC_LP64
619.lbm_s: -DSPEC_LP64
621.wrf_s: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
627.cam4_s: -DSPEC_LP64 -DSPEC_CASE_FLAG
628.pop2_s: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
-assume byterecl
638.imagick_s: -DSPEC_LP64
644.nab_s: -DSPEC_LP64
649.fotonik3d_s: -DSPEC_LP64
654.roms_s: -DSPEC_LP64
```

Base Optimization Flags

C benchmarks:

```
-qopt-prefetch -qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP
```

Fortran benchmarks:

```
-DSPEC_SUPPRESS_OPENMP -qopt-prefetch -qopt-mem-layout-trans=3
-nostandard-realloc-lhs
```

Benchmarks using both Fortran and C:

```
-qopt-prefetch -qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP
-nostandard-realloc-lhs
```

Benchmarks using Fortran, C, and C++:

```
-Wl,-z,muldefs -qopt-prefetch -qopt-mem-layout-trans=3
-DSPEC_SUPPRESS_OPENMP -nostandard-realloc-lhs -L/sh10.2 -lsmartheap64
```

Peak Compiler Invocation

C benchmarks:

```
icc -m64 -std=c11
```

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

Peak Compiler Invocation (Continued)

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
ifort -m64 icc -m64 -std=c11
```

Benchmarks using Fortran, C, and C++:

```
icpc -m64 icc -m64 -std=c11 ifort -m64
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
-prof-gen(pass 1) -prof-use(pass 2) -O2 -xCORE-AVX2 -auto-p32 -ipo  
-qopt-prefetch -O3 -no-prec-div -qopt-mem-layout-trans=3  
-DSPEC_SUPPRESS_OPENMP
```

Fortran benchmarks:

```
-prof-gen(pass 1) -prof-use(pass 2) -DSPEC_SUPPRESS_OPENMP -O2  
-xCORE-AVX2 -qopt-prefetch -ipo -O3 -qopt-mem-layout-trans=3  
-no-prec-div -nostandard-realloc-lhs
```

Benchmarks using both Fortran and C:

```
-prof-gen(pass 1) -prof-use(pass 2) -O2 -xCORE-AVX2 -auto-p32 -ipo  
-qopt-prefetch -O3 -no-prec-div -qopt-mem-layout-trans=3  
-DSPEC_SUPPRESS_OPENMP -nostandard-realloc-lhs
```

Benchmarks using Fortran, C, and C++:

```
-Wl,-z,muldefs -prof-gen(pass 1) -prof-use(pass 2) -O2 -xCORE-AVX2  
-auto-p32 -ipo -qopt-prefetch -O3 -no-prec-div  
-qopt-mem-layout-trans=3 -DSPEC_SUPPRESS_OPENMP -nostandard-realloc-lhs  
-L/sh10.2 -lsmartheap64
```



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2018 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Integrity Superdome X

(384 core, 2.20 GHz, Intel Xeon E7-8890 v4)

SPECspeed2017_fp_base = 5.37

SPECspeed2017_fp_peak = 6.66

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Sep-2016

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic17.0-official-linux64-revD.html>

<http://www.spec.org/cpu2017/flags/HP-Platform-Flags-Intel-V1.2-Integrity-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic17.0-official-linux64-revD.xml>

<http://www.spec.org/cpu2017/flags/HP-Platform-Flags-Intel-V1.2-Integrity-revC.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v0.902.0 on 2016-10-15 03:24:41-0400.

Report generated on 2018-10-31 12:40:54 by CPU2017 PDF formatter v6067.

Originally published on 2017-06-19.