



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Ranks
104.milc
107.leslie3d
113.GemsFDTD
115.fds4
121.pop2
122.tachyon
126.lammps
127.wrf2
128.GAPgeofem
129.tera_tf
132.zeus_np2
137.lu



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
104.milc	32	NC	NC	NC	NC	NC	NC									
107.leslie3d	32	NC	NC	NC	NC	NC	NC									
113.GemsFDTD	32	NC	NC	NC	NC	NC	NC									
115.fds4	32	NC	NC	NC	NC	NC	NC									
121.pop2	32	NC	NC	NC	NC	NC	NC									
122.tachyon	32	NC	NC	NC	NC	NC	NC									
126.lammgs	32	NC	NC	NC	NC	NC	NC									
127.wrf2	32	NC	NC	NC	NC	NC	NC									
128.GAPgeofem	32	NC	NC	NC	NC	NC	NC									
129.tera_tf	32	NC	NC	NC	NC	NC	NC									
130.socorro	32	NC	NC	NC	NC	NC	NC									
132.zeusmp2	32	NC	NC	NC	NC	NC	NC									
137.lu	32	NC	NC	NC	NC	NC	NC									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogenous
 Compute Node: HP XC Cluster
 Interconnect: DDR InfiniBand
 File Server Node: HP ProLiant DL380 G4 file server
 Total Compute Nodes: 8
 Total Chips: 16
 Total Cores: 32
 Total Threads: 32
 Total Memory: 64 GB
 Base Ranks Run: 32
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

C Compiler: Intel C 9.1.045
 C++ Compiler: Intel C++ 9.1.045
 Fortran Compiler: Intel Fortran 9.1.040
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 MPI Library: HP-MPI 2.2.5
 Other MPI Info: None
 Pre-processors: No
 Other Software: None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test date: May-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2007

Tested by: HPCD

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Node Description: HP XC Cluster

Hardware		Software	
Number of nodes:	8	Adapter:	PCI-Express DDR InfiniBand HCA
Uses of the node:	compute	Adapter Driver:	Voltaire GridStack 3.5.5_25
Vendor:	Hewlett-Packard Company	Adapter Firmware:	Hp 1.2
Model:	XC3000	Operating System:	Redhat 4 Update 4
CPU Name:	Intel Xeon 5160	Local File System:	VXFS
CPU(s) orderable:	1-2 chips	Shared File System:	NFS
Chips enabled:	2	System State:	Multi User
Cores enabled:	4	Other Software:	None
Cores per chip:	2		
Threads per core:	1		
CPU Characteristics:	1333 MHz FSB		
CPU MHz:	3000		
Primary Cache:	32 KB I-Cache, 32 KB D-Cache on chip per core		
Secondary Cache:	4 MB D-Cache on chip per chip		
L3 Cache:	None		
Other Cache:	None		
Memory:	8 GB		
Disk Subsystem:	Ext 3		
Other Hardware:	None		
Adapter:	PCI-Express DDR InfiniBand HCA		
Number of Adapters:	1		
Slot Type:	Mezzanine - PCIe x8		
Data Rate:	Infiniband 4x DDR		
Ports Used:	1		
Interconnect Type:	InfiniBand		



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Node Description: HP ProLiant DL380 G4 file server

Hardware		Software	
Number of nodes:	1	Adapter:	PCI-Express DDR InfiniBand HCA
Uses of the node:	file server	Adapter Driver:	Voltaire GridStack 3.5.5_25
Vendor:	Hewlett-Packard Company	Adapter Firmware:	Hp 1.2
Model:	DL380 G4	Operating System:	Redhat 4 Update 4
CPU Name:	Intel Xeon	Local File System:	2 x 146GB Ultra320 SCSI 10k RPM Disks RAID 0+1
CPU(s) orderable:	1-2 chips	Shared File System:	N/A
Chips enabled:	2	System State:	Multi User
Cores enabled:	2	Other Software:	None
Cores per chip:	1		
Threads per core:	1		
CPU Characteristics:	None		
CPU MHz:	3800		
Primary Cache:	32 KB I-Cache, 32 KB D-Cache on chip per core		
Secondary Cache:	2 MB L2-Cache on chip per chip		
L3 Cache:	None		
Other Cache:	None		
Memory:	8 GB		
Disk Subsystem:	SCSI		
Other Hardware:	None		
Adapter:	PCI-Express DDR InfiniBand HCA		
Number of Adapters:	1		
Slot Type:	PCIe x4		
Data Rate:	Infiniband 4x DDR		
Ports Used:	1		
Interconnect Type:	InfiniBand		



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Interconnect Description: DDR InfiniBand

	Hardware	Software
Vendor:	Voltaire	
Model:	ISR	
Switch Model:	HP 4X DDR IB Switch Module for HP BladeSystem, C-Class	
Number of Switches:	1	
Number of Ports:	16	
Data Rate:	Infiniband 4x DDR	
Firmware:	1.30	
Switch Model:	Voltaire 24 port External Switch for subnet management ISR 9024	
Number of Switches:	1	
Number of Ports:	24	
Data Rate:	Infiniband 4x DDR	
Firmware:	0.8.6	
Topology:	two levels for subnet manager, and 1 for leaf.	
Primary Use:	MPI and HPC system traffic	

General Notes

```

# MPI2007 on XC3000 cluster.
module load mpi
. ./shrc
. /opt/intel/fc/9.1.040/bin/ifortvars.sh
. /opt/intel/cc/9.1.045/bin/iccvars.sh
runspec -c linux_cmd_intel medium --reportable --ranks=NN --define CMD_PREFIX= --define MPIRUN_OPTIONS= --flagsurl=hpmmpi-intel.xml -o cfg.txt,html,check
cluster launch performed via slurm's srun
submit= \ $MPI_ROOT/bin/mpirun -srun $command

```



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test date: May-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2007

Tested by: HPCD

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Base Compiler Invocation

C benchmarks:

mpicc -mpicc icc

C++ benchmarks:

126.lammps: mpiCC -mpicxx icpc

Fortran benchmarks:

107.leslie3d: mpif90 -mpif90 ifort

113.GemsFDTD: mpif90 -mpif90 ifort

115.fds4: mpif90 -mpif90 ifort

129.tera_tf: mpif90 -mpif90 ifort

132.zeusmp2: mpif90 -mpif90 ifort

137.lu: mpif90 -mpif90 ifort

Benchmarks using both Fortran and C (except as noted below):

mpicc -mpicc icc mpif90 -mpif90 ifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG

127.wrf2: -DSPEC_MPI_LINUX -DSPEC_MPI_CASE_FLAG



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Base Optimization Flags

C benchmarks:

103.no-prec-div -ftz -fno-alias -xT

C++ benchmarks:

126.lammgs: -03 -no-prec-div -ftz -fno-alias -xT

Fortran benchmarks:

107.leslie3d: -03 -no-prec-div -ftz -fno-alias -xT

113.GemsFDTD: -03 -no-prec-div -ftz -fno-alias -xT

115.fds4: -03 -no-prec-div -ftz -fno-alias -xT

129.tera_tf: -03 -no-prec-div -ftz -fno-alias -xT

132.zeusmp2: -03 -no-prec-div -ftz -fno-alias -xT

137.lu: -03 -no-prec-div -ftz -fno-alias -xT

Benchmarks using both Fortran and C:

121.pop2: -03 -no-prec-div -ftz -fno-alias -xT

127.wrf2: Same as 121.pop2

128.GAPgem: Same as 121.pop2

130.socorro: Same as 121.pop2



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

SPECmpiM_peak2007 = Not Run

HP Proliant BL460c blade Cluster Platform 3000BL

SPECmpiM_base2007 = NC

MPI2007 license: 0001

Test date: May-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: May-2007

Tested by: HPCD

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

The flags file that was used to format this result can be browsed at http://www.spec.org/mpi2007/flags/MPI2007_flags.html.

You can also download the XML flags source by saving the following link: http://www.spec.org/mpi2007/flags/MPI2007_flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v59.
Report generated on Tue Jul 22 13:32:29 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 16 July 2007.